

Project Proposal

Spatiotemporal Graph Neural Networks for Real-Time Fault Localization in Smart Grids

Student Name	Student ID
Anik Kumar Basu	22234103041
Sabrina Shonda Snaha	22234103048
Md. Sadik Mahmud Adiva	22234103057

February 7, 2026

1 Introduction

The transition to “Smart Grids” is critical for integrating renewable energy sources and ensuring a sustainable future (Green AI). However, modern power grids are becoming increasingly complex due to the stochastic nature of renewable generation (e.g., solar and wind) and the bidirectional flow of power. In such dynamic environments, traditional fault detection methods—which often rely on manual rule-based thresholds or simple statistical models—are becoming insufficient. They frequently fail to capture the complex, non-linear spatial dependencies between grid nodes (buses) and the temporal dependencies of fluctuating sensor data.

This project proposes a deep learning approach using **Spatiotemporal Graph Neural Networks (ST-GNN)**. Unlike standard Convolutional Neural Networks (CNNs) that treat data as Euclidean grids (images), GNNs are designed to process data represented as graphs. Since a power grid is naturally a graph (where buses are nodes and transmission lines are edges), GNNs offer a theoretically superior method for modeling the system’s physical topology to detect and localize faults in real-time.

2 Problem Statement

Grid failures, if not detected and isolated within milliseconds, can lead to cascading blackouts, equipment damage, and significant economic loss. The core challenges are:

1. **Topological Complexity:** Faults at one node propagate effects across the network based on physical connections, which standard ML models often ignore.
2. **Data High-Dimensionality:** Smart meters generate massive streams of time-series data that are difficult to process in real-time.

3. **Localization Precision:** Detecting *that* a fault occurred is easier than pinpointing *exactly where* it happened (e.g., Bus 14 vs. Bus 15), which is crucial for maintenance crews.

3 Literature Review

3.1 Evolution of Fault Detection Techniques

Early approaches to fault detection in power systems relied heavily on model-based methods (using impedance calculations) and traditional signal processing. As noted by **Liao et al. (2021)** in their comprehensive survey of over 100 studies, these physics-based methods require precise knowledge of grid parameters (e.g., line resistance), which vary stochastically in renewable-integrated grids. Consequently, the industry shifted toward data-driven Machine Learning (ML). Support Vector Machines (SVM) and Artificial Neural Networks (ANN) became popular for classifying fault types. However, Liao et al. highlight a critical bottleneck: these “shallow” models suffer from the curse of dimensionality and rely on manual feature extraction, making them unscalable for high-speed, real-time monitoring.

3.2 Limitations of Standard Deep Learning (CNNs)

To automate feature extraction, Deep Learning models like Convolutional Neural Networks (CNNs) were adopted. These models treat power grid data as Euclidean grids (similar to pixels in an image). However, **Owerko et al. (2020)** challenged this paradigm in their work on Optimal Power Flow. They argued that standard CNNs are not *permutation invariant*—meaning the model’s output changes if the ordering of the buses changes, which is physically incorrect for power systems. By treating the grid as a regular lattice, CNNs ignore the irregular, non-Euclidean topology where a fault at one bus propagates instantaneously to distant but physically connected neighbors.

3.3 The Rise of Graph Neural Networks (GNNs)

To address these topological constraints, Graph Neural Networks (GNNs) have emerged as the state-of-the-art. **Chen et al. (2020)** proposed a Graph Convolutional Network (GCN) specifically for fault diagnosis. By inputting the grid’s Adjacency Matrix directly into the neural network, their model could aggregate features from connected neighbors, effectively mimicking the flow of electrical current. Their results demonstrated a significant accuracy improvement over CNNs in distinguishing fault types. Furthermore, **Donon et al. (2019)** introduced the “Graph Neural Solver,” which integrates physical constraints (Kirchhoff’s laws) into the loss function, validating that GNNs can learn to respect the underlying physics of the grid better than unstructured black-box models.

3.4 The Spatiotemporal Gap (Project Focus)

While spatial GNNs effectively model topology, grid faults are dynamic events that evolve over milliseconds. A purely spatial model captures the “where” but may miss the “when.” **Yu et al. (2018)** pioneered the Spatiotemporal Graph Convolutional Network (ST-GCN) for traffic forecasting. They proposed a novel “sandwich” architecture containing

a spatial GCN layer between two temporal gated convolution layers. This structure allows the model to extract spatial features (road connections) and temporal features (traffic flow over time) simultaneously.

Research Gap: While ST-GCNs are widely used for forecasting loads, there is limited literature applying hybrid **GCN-LSTM** architectures specifically for **fault localization** in renewable-heavy grids. Most existing studies focus on binary detection. This project aims to bridge this gap by adapting the ST-GCN framework to pinpoint exactly *which* bus is faulted in real-time, even under noisy sensor conditions.

4 References

1. W. Liao, B. Bak-Jensen, J. R. Pillai, et al., “Review of Graph Neural Networks for Smart Grids: An Overview,” *IEEE Power & Energy Society General Meeting (PESGM)*, 2021.
Available: <https://ieeexplore.ieee.org/document/9520300>
2. D. Owerko, F. Gama, and A. Ribeiro, “Optimal Power Flow using Graph Neural Networks,” *IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, 2020.
Available: <https://ieeexplore.ieee.org/document/9053140>
3. K. Chen, J. Hu, and Y. Zhang, “Power System Fault Diagnosis Based on Graph Convolutional Networks,” *IEEE International Conference on Energy Internet and Energy System Integration (EI2)*, 2020.
Available: <https://ieeexplore.ieee.org/document/9347148>
4. B. Donon, B. Donnot, I. Guyon, and M. Sebag, “Graph Neural Solver for Power Systems,” *International Joint Conference on Neural Networks (IJCNN)*, 2019.
Available: <https://ieeexplore.ieee.org/document/8851824>
5. B. Yu, H. Yin, and Z. Zhu, “Spatiotemporal Graph Convolutional Networks: A Deep Learning Framework for Traffic Forecasting,” *IJCAI*, 2018.
Available: <https://www.ijcai.org/proceedings/2018/505>