API DOCUMENTATION

Version 2.0

Contents

Base URL 3
Authentication 3
GET& POST Get All Cities 4
Description 4
API Request 4
API Response 5
GET& POST Track Booked Packet 8
Description 8
API Request 8
API Response 9
GET& POST Book a Packet 17
API Request 17
API Response 19
POST Batch Book Packet 21
API Request 21
API Response 26
POST Cancel Booked Packets 31
API Request 31
POST Generate Load Sheet 34
API Request 34
API Response 35
POST Download Load Sheet 37
API Request 37
API Response 38
GET Get Booked Packet Last Statuses By Date Range 41
API Request 41
POST Shipper Advice List 46
API Request 46
API Response 47
POST Get Shipment Details By Order ID(s) 49

API Response 50
GET Get All Banks 53
API Request 53
POST Create Shipper 56
API Request 56
API Response 57
GET Get Payment Details By CN Number(s) 62
API Request 62
API Response 62
GET Get Tariff Details 66
API Request 66
API Response 67
GET Get Shipping Charges 69
API Request 69
API Response 69
GET Get Shipper Details 73
API Request 73
API Response 73
GET Get Electronic Proof Of Delivery 77
API Request 77
API Response 77
POST Shipper Advice List 81
API Request 81
API Response 82
POST Activity Log 85
API Request 85
API Response 86
POST Add Shipper Advices 89
API Request 89
API Response 91

Base URL

Staging	https://merchantapistaging.leopardscourier.com/api/
Production	https://merchantapi.leopardscourier.com/api/

Authentication

For the Get requests we will send these keys as parameters and for the post Api's we will send these parameters in request body these keys merchant can get from his account.

These are test account API credentials, do not use it for live/production environment.

For live API Credentials, please log in to your account & see API management option under API settings tabs. There, key will be required to generated & password will be chosen.

api_key	c7ab1d5f6b35f23b496c9cc24d4715c1
api_password	123456

GET & POST Get All Cities

Description:

To get list of all cities along with their origin and destination checks.

Staging Link:

https://merchantapistaging.leopardscourier.com/api/getAllCities/format/xml/ For 'XML' format
https://merchantapistaging.leopardscourier.com/api/getAllCities/format/json/ For 'JSON' format

Production Link:

https://merchantapi.leopardscourier.com/api/getAllCities/format/xml/ For 'XML' format
https://merchantapi.leopardscourier.com/api/getAllCities/format/json/ For 'JSON' format

API Request

The following is a sample API request using cURL in PHP.

```
$curl_handle = curl_init();

curl_setopt($curl_handle, CURLOPT_URL,
'https://merchantapistaging.leopardscourier.com/api/getAllCities/format/json/'); // Write here  or
Production Link

curl_setopt($curl_handle,  CURLOPT_RETURNTRANSFER,  1);

curl_setopt($curl_handle, CURLOPT_POST, 1);

curl_setopt($curl_handle, CURLOPT_POSTFIELDS, json_encode(array(

    'api_key' => 'your_api_key'

    'api_password' => 'your_api_password'

)));


$buffer = curl_exec($curl_handle);

curl_close($curl_handle);
```

API Response

The following is a JSON response with Error(s).

```
{
   "status":0,
   "error":"string",
   "city_list":null
}
```

The following is a XML response with Error(s).

```
<?xml version="1.0" encoding="utf-8"?>
<xml>
   <status>0</status>
   <error>string</error>
   <city_list/>
</xml>
```

The following is a JSON response without Error(s).

```
{
   "status":1,
   "error":"0",
   "city_list": [
                {
                   "id" : int,
                   "name" : "string",
                   "shipment_type”: [
                      "string",
```

```
                "string"
            ],
            "allow_as_origin”: Boolean,
            "allow_as_destination”: Boolean
        },
        {
            "id" : int,
            "name" : "string",
            "shipment_type”: [
                "string",
                "string",
                "string"
            ],
            "allow_as_origin”: Boolean,
            "allow_as_destination”: Boolean
        }
    ]
}
```


The following is a XML response without Error(s).


```
<?xml version="1.0" encoding="utf-8"?>
<xml>
  <status>1</status>
  <error>0</error>
  <city_list>
    <item>
      <id>int</id>
```

```
        <name>string</name>
        <shipment_type>
            <item>string</item>
            <item>string</item>
        </shipment_type>
      </item>
      <item>
        <id>int</id>
         <name>string</name>
        <shipment_type>
            <item>string</item>
            <item>string</item>
            <item>string</item>
        </shipment_type>
      </item>
    </city_list>
</xml>
```

GET & POST Track Booked Packet

Description:

This resource will be used to track a single packet.

Staging Link:

https://merchantapistaging.leopardscourier.com/api/trackBookedPacket/format/xml/ For 'XML' format
https://merchantapistaging.leopardscourier.com/api/trackBookedPacket/format/json/ For 'JSON' format

Production Link:

https://merchantapi.leopardscourier.com/api/trackBookedPacket/format/xml/ For 'XML' format
https://merchantapi.leopardscourier.com/api/trackBookedPacket/format/json/ For 'JSON' format

API Request

The following is a sample API request using cURL in PHP.

```
$curl_handle = curl_init();


// For Direct Link Access use below commented link

//curl_setopt($curl_handle, CURLOPT_URL,
'https://merchantapistaging.leopardscourier.com/api/trackBookedPacket/?api_key=XXXX&api_passwor
d=XXXX&track_numbers=XXXXXXXX');  // For Get Mother/Direct Link


curl_setopt($curl_handle, CURLOPT_URL,
'https://merchantapistaging.leopardscourier.com/api/trackBookedPacket/format/json/');  // Write here
or Production Link

curl_setopt($curl_handle,  CURLOPT_RETURNTRANSFER,  1);

curl_setopt($curl_handle, CURLOPT_POST, 1);

curl_setopt($curl_handle, CURLOPT_POSTFIELDS, json_encode(array(

   'api_key' => 'your_api_key'

   'api_password' => 'your_api_password'
```

```
    'track_numbers' => 'string'                    // E.g. 'XXYYYYYYYY' OR 'XXYYYYYYYY,XXYYYYYYYY,XXYYYYYY' 10 Digits each number
)));


$buffer = curl_exec($curl_handle);
curl_close($curl_handle);
```

API Response

```
The following is a JSON response with Error(s).
{
    "status"        :0,
    "error"         :"string",
    "packet_list"   :null
}
```

```
The following is a XML response with Error(s).
<?xml version="1.0" encoding="utf-8"?>
<xml>
    <status>0</status>
    <error>string</error>
    <packet_list/>
</xml>
```

```
The following is a JSON response without Error(s).
{
    "status"        :1,
    "error"         :0,
    "packet_list"   : [
```

```
{
    "booking_date"                  :"dd/mm/YY",
    "track_number"                  :"string",
    "track_number_short"            :"int",
    "booked_packet_weight"          :"int",
    "booked_packet_vol_weight_w"    :"int",
    "booked_packet_vol_weight_h"    :"int",
    "booked_packet_vol_weight_l"    :"int",
    "booked_packet_no_piece"        :"int",
    "booked_packet_collect_amount"  :"int",
    "booked_packet_order_id"        :"string",
    "origin_city_name"              :"string",
    "destination_city_name"         :"string",
    "invoice_number"                :"string",
    "invoice_date"                  :"string",
    "shipment_name_eng"             :"string",
    "shipment_email"                :"string",
    "shipment_phone"                :"int",
    "shipment_address"              :"string",
    "consignment_name_eng"          :"string",
    "consignment_email"             :"string",
    "consignment_phone"             :"int",
    "consignment_phone_two"         :"int",
    "consignment_phone_three"       :"int",
    "consignment_address"           :"string",
    "special_instructions"          :"string",
    "booked_packet_status"          :"string",
```

```
            "activity_date"              :"string",
            "status_reamrks"             :"string", /* it will show the receiver name in case of packet delivery and reason if packet is pending/return with any reason*/
            "reverseCN":                 "string(KI000000001)", /* if the tracked numbers is VPC CN, else this will not appear */
            /* Tracking detail will be in loop */
            "Tracking Detail": [
              {
                "Staus";       : "string",
                "Reciever Name" : "string",
                "Activity Date" : "yyyy-mm-dd",
                "Reason"       : "string"
              }
                          ]
            }
          /* For more than One Track Numbers below section will repeated */
          ,{
            "booking_date"               :"dd/mm/YY",
            "track_number"               :"string",
            "track_number_short"         :"int",
            "booked_packet_weight"       :"int",
            "booked_packet_vol_weight_w"   :"int",
            "booked_packet_vol_weight_h"   :"int",
            "booked_packet_vol_weight_l"   :"int",
            "booked_packet_no_piece"       :"int",
            "booked_packet_collect_amount"  :"int",
            "booked_packet_order_id"       :"string",
            "origin_city_name"           :"string",
```

```
"destination_city_name"        :"string",
"invoice_number"               :"string",
"invoice_date"                 :"string",
"shipment_name_eng"            :"string",
"shipment_email"               :"string",
"shipment_phone"               :"int",
"shipment_address"             :"string",
"consignment_name_eng"         :"string",
"consignment_email"            :"string",
"consignment_phone"            :"int",
"consignment_phone_two"        :"int",
"consignment_phone_three"      :"int",
"consignment_address"          :"string",
"special_instructions"         :"string",
"booked_packet_status"         :"string",
"activity_date"                :"string",
"status_remarks"               :"string", /* it will show the receiver name in case of packet
delivery and reason, if packet is pending/return with any reason */
"reverseCN"                    :"string(KI000000001)", /* if the tracked numbers is VPC CN, else
this will not appear */
/* Tracking detail will be shown in loop */
"Tracking Detail": [
    {
      "Staus"        : "string",
      "Reciever Name" : "string",
      "Activity Date" : "yyyy-mm-dd",
      "Reason"       : "string"
    }
```

```
                                    ]


                    }

          ]

}
```

The following is a XML response without Error(s).

```
<?xml version="1.0" encoding="utf-8"?>

<xml>

   <status>1</status>

   <error>0</error>

   <packetList>

      <item>

         <booking_date>dd/mm/YY</booking_date>

         <track_number>int</track_number>

         <track_number_short>int</track_number_short>

         <booked_packet_weight>int</booked_packet_weight>

         <booked_packet_vol_weight_w>int</booked_packet_vol_weight_w>                    /* If no value found it will <booked_packet_vol_weight_w/> */

         <booked_packet_vol_weight_h>int</booked_packet_vol_weight_h>                    /* If no value found it will <booked_packet_vol_weight_h/> */

         <booked_packet_vol_weight_l>int</booked_packet_vol_weight_l>                    /* If no value found it will <booked_packet_vol_weight_l/> */

         <booked_packet_no_piece>int</booked_packet_no_piece>

         <booked_packet_collect_amount>int</booked_packet_collect_amount>

         <booked_packet_order_id>string</booked_packet_order_id>              /* Optional Field (You can keep it empty), If no value found it will <booked_packet_order_id/> */

         <origin_city_name>string</origin_city_name>
```

```
<destination_city_name>string</destination_city_name>
<invoice_number>string</invoice_number>
<invoice_date>string</invoice_date>
<shipment_name_eng>string</shipment_name_eng>
<shipment_email>string</shipment_email>
<shipment_phone>int</shipment_phone>
<shipment_address>string</shipment_address>
<consignment_name_eng>string</consignment_name_eng>
<consignment_email>string</consignment_email>
<consignment_phone>int</consignment_phone>
<consignment_phone_two>int</consignment_phone>
<consignment_phone_three>int</consignment_phone>
<consignment_address>string</consignment_address>
<special_instructions>string</special_instructions>
<booked_packet_status>string</booked_packet_status>
<acitivity_date>string</acitivity_date>
<status_remarks>string</status_remarks>   /* It will show the receiver name in case of packet delivery and reason if packet is pending/return with any reason */
<reverseCN>string(KI000000001)</reverseCN> /* if the tracked numbers is VPC CN, else this will not appear */
<TrackingDetail>          /* Tracking detail will be shown in loop   */
  Æ<item>
    <Status>string</Status>
    <Reciever_Name>string</Reciever_Name>
    <Activity_Date>Date</<Activity_Date>
    <Activity_Time>Time</Activity_Time>
    <Reason>string</Reason>
  </item>
```

```
        </TrackingDetail>
    </item>
    /* For more than One Track Numbers 'item' section will repeated */
    <item>
        <booking_date>dd/mm/YY</booking_date>
        <track_number>int</track_number>
        <track_number_short>int</track_number_short>
        <booked_packet_weight>int</booked_packet_weight>
        <booked_packet_vol_weight_w>int</booked_packet_vol_weight_w>          /* If no value
found it will <booked_packet_vol_weight_w/> */
        <booked_packet_vol_weight_h>int</booked_packet_vol_weight_h>          /* If no value
found it will <booked_packet_vol_weight_h/> */
        <booked_packet_vol_weight_l>int</booked_packet_vol_weight_l>          /* If no value found
it will <booked_packet_vol_weight_l/> */
        <booked_packet_no_piece>int</booked_packet_no_piece>
        <booked_packet_collect_amount>int</booked_packet_collect_amount>
        <booked_packet_order_id>string</booked_packet_order_id>
        <origin_city_name>string</origin_city_name>
        <destination_city_name>string</destination_city_name>
        <invoice_number>string</invoice_number>
        <invoice_date>string</invoice_date>
        <shipment_name_eng>string</shipment_name_eng>
        <shipment_email>string</shipment_email>
        <shipment_phone>int</shipment_phone>
        <shipment_address>string</shipment_address>
        <consignment_name_eng>string</consignment_name_eng>
        <consignment_email>string</consignment_email>
        <consignment_phone>int</consignment_phone>
```

```
        <consignment_phone_two>int</consignment_phone>
        <consignment_phone_three>int</consignment_phone>
        <consignment_address>string</consignment_address>
        <special_instructions>string</special_instructions>
        <booked_packet_status>string</booked_packet_status>
        <acitivity_date>string</acitivity_date>
        <stauts_remarks>string</stauts_remarks>   /* It will show the receiver name in case of packet
delivery and reason if packet is pending/return with any reason */
        <reverseCN>string(KI000000001)</reverseCN> /* if the tracked numbers is VPC CN, else this will
not appear */
        <TrackingDetail>                    /* Tracking detail will be shown in loop   */
          <item>
            <Status>string</Status>
            <Reciever_Name>string</Reciever_Name>
            <Activity_Date>Date</<Activity_Date>
            <Activity_Time>Time</Activity_Time>
            <Reason>string</Reason>
          </item>
        </TrackingDetail>
      </item>
   </packetList>
</xml>
```

GET & POST Book a Packet

Staging Link:

https://merchantapistaging.leopardscourier.com/api/bookPacket/format/xml/ For 'XML' format
https://merchantapistaging.leopardscourier.com/api/bookPacket/format/json/ For 'JSON' format

Production Link:

https://merchantapi.leopardscourier.com/api/bookPacket/format/xml/ For 'XML' format
https://merchantapi.leopardscourier.com/api/bookPacket/format/json/ For 'JSON' format

API Request

The following is a sample API request using cURL in PHP.

```
$curl_handle = curl_init();


curl_setopt($curl_handle, CURLOPT_URL, 'https://merchantapistaging.leopardscourier.com/api/bookPacket/format/json/');  // Write here or Production Link

curl_setopt($curl_handle, CURLOPT_RETURNTRANSFER, 1);

curl_setopt($curl_handle, CURLOPT_POST, 1);

curl_setopt($curl_handle, CURLOPT_POSTFIELDS, json_encode(array(

   'api_key'                    => 'your_api_key'

   'api_password'               => 'your_api_password'

   'booked_packet_weight'       => int,          // Weight should in 'Grams' e.g. '2000'

   'booked_packet_vol_weight_w'  => int,          // Optional Field (You can keep it empty), Volumetric Weight Width

   'booked_packet_vol_weight_h'  => int,          // Optional Field (You can keep it empty), Volumetric Weight Height

   'booked_packet_vol_weight_l'  => int,          // Optional Field (You can keep it empty), Volumetric Weight Length

   'booked_packet_no_piece'     => int,          // No. of Pieces should an Integer Value

   'booked_packet_collect_amount' => int,         // Collection Amount on Delivery

   'booked_packet_order_id'     => 'string',     // Optional Filed, (If any) Order ID of Given Product
```

```
    'origin_city'                => 'string',          /** Params: 'self' or 'integer_value' e.g. 'origin_city' => 'self' or 'origin_city' => 789 (where 789 is Lahore ID)
                                                        * If 'self' is used then Your City ID will be used.
                                                        * 'integer_value' provide integer value (for integer values read 'Get All Cities' api documentation)
                                                        */

    'destination_city'           => 'string',          /** Params: 'self' or 'integer_value' e.g. 'destination_city' => 'self' or 'destination_city' => 789 (where 789 is Lahore ID)
                                                        * If 'self' is used then Your City ID will be used.
                                                        * 'integer_value' provide integer value (for integer values read 'Get All Cities' api documentation)
                                                        */

    'shipment_id'                => 'int',
    'shipment_name_eng'          => 'string',          // Params: 'self' or 'Type any other Name here', If 'self' will used then Your Company's Name will be Used here
    'shipment_email'             => 'string',          // Params: 'self' or 'Type any other Email here', If 'self' will used then Your Company's Email will be Used here
    'shipment_phone'             => 'string',          // Params: 'self' or 'Type any other Phone Number here', If 'self' will used then Your Company's Phone Number will be Used here
    'shipment_address'           => 'string',          // Params: 'self' or 'Type any other Address here', If 'self' will used then Your Company's Address will be Used here
    'consignment_name_eng'       => 'string',          // Type Consignee Name here
    'consignment_email'          => 'string',          // Optional Field (You can keep it empty), Type Consignee Email here
    'consignment_phone'          => 'string',          // Type Consignee Phone Number here
    'consignment_phone_two'      => 'string',          // Optional Field (You can keep it empty), Type Consignee Second Phone Number here
```

```
    'consignment_phone_three'       => 'string',          // Optional Field (You can keep it empty), Type Consignee Third Phone Number here

    'consignment_address'           => 'string',          // Type Consignee Address here

    'special_instructions'          => 'string',          // Type any instruction here regarding booked packet

    'shipment_type'                 => 'string',          // Optional Field (You can keep it empty so It will pick default value i.e. "overnight"), Type Shipment type name here

    'custom_data'                   => 'json array',      // Optional Field (You can keep it empty), [{"key1":"value1","key2":value2,.....}]

    'return_address'                => 'string',          // Optional Field (You can keep it empty) - If 'return_address' is empty, then the address of shipper will be added as return address

    'return_city'                   => 'int',             // Optional Field (You can keep it empty) - If 'return_city' is empty, then shipper's origin city will ne return city

    'is_vpc'                        => 'int',             // Optional Field (You can keep it empty) If is_vpc =1 then booked_packet_order_id should be a CN number

)));


$buffer = curl_exec($curl_handle);

curl_close($curl_handle);
```

API Response

The following is a JSON response with Error(s).

```
{

    "status"       :   0,

    "error"        :   "string",

    "track_number"  :   null

    "slip_link"     :   null

}
```

The following is a XML response with Error(s).

```
<?xml version="1.0" encoding="utf-8"?>
<xml>
   <status>0</status>
   <error>string</error>
   <track_number/>
   <slip_link/>
</xml>
```

The following is a JSON response without Error(s).

```
{
   "status"       :   1,
   "error"        :   0,
   "track_number"  :   "string"
   "slip_link"     :   "string"                          // Copy this URL in Browser to Get Slip
}
```

The following is a XML response without Error(s).

```
<?xml version="1.0" encoding="utf-8"?>
<xml>
   <status>1</status>
   <error>0</error>
   <track_number>string</track_number>
   <slip_link>string</slip_link>                  /* Copy this URL in Browser to Get Slip */
</xml>
```

POST Batch Book Packet

Staging Link:

https://merchantapistaging.leopardscourier.com/api/batchBookPacketsv2/format/xml/ For 'XML' format
https://merchantapistaging.leopardscourier.com/api/batchBookPacketsv2/format/json/ For 'JSON' format

Production Link:

https://merchantapi.leopardscourier.com/api/batchBookPacketv2/format/xml/ For 'XML' format
https://merchantapi.leopardscourier.com/api/batchBookPacketv2/format/json/ For 'JSON' format

API Request

The following is a sample API request using cURL in PHP.

```
$curl_handle = curl_init();


curl_setopt($curl_handle, CURLOPT_URL,
'https://merchantapistaging.leopardscourier.com/api/batchBookPacket/format/json/'); // Write here
or Production Link

curl_setopt($curl_handle, CURLOPT_RETURNTRANSFER, 1);

curl_setopt($curl_handle, CURLOPT_POST, 1);

curl_setopt($curl_handle, CURLOPT_POSTFIELDS,

  json_encode(

    array(

      'api_key'      => 'your_api_key'

      'api_password' => 'your_api_password'

      'packets'      =>

        array(

          array(

            'booked_packet_weight'        => int,            // Weight should in 'Grams' e.g. '2000'

            'booked_packet_vol_weight_w'   => int,            // Optional Field (You can keep it empty),
Volumetric Weight Width

            'booked_packet_vol_weight_h'   => int,            // Optional Field (You can keep it empty),
Volumetric Weight Height
```

'booked_packet_vol_weight_l' => int, // Optional Field (You can keep it empty), Volumetric Weight Length

'booked_packet_no_piece' => int, // No. of Pieces should an Integer Value

'booked_packet_collect_amount' => int, // Collection Amount on Delivery

'booked_packet_order_id' => 'string', // Optional Filed, (If any) Order ID of Given Product

'origin_city' => 'string', /** Params: 'self' or 'integer_value' e.g. 'origin_city' => 'self' or 'origin_city' => 789 (where 789 is Lahore ID)

* If 'self' is used then Your City ID will be used.

* 'integer_value' provide integer value (for integer values read 'Get All Cities' api documentation)

*/

'destination_city' => 'string', /** Params: 'self' or 'integer_value' e.g. 'destination_city' => 'self' or 'destination_city' => 789 (where 789 is Lahore ID)

* If 'self' is used then Your City ID will be used.

* 'integer_value' provide integer value (for integer values read 'Get All Cities' api documentation)

*/

'shipment_id' => 'int',

'shipment_name_eng' => 'string', // Params: 'self' or 'Type any other Name here', If 'self' will used then Your Company's Name will be Used here

'shipment_email' => 'string', // Params: 'self' or 'Type any other Email here', If 'self' will used then Your Company's Email will be Used here

'shipment_phone' => 'string', // Params: 'self' or 'Type any other Phone Number here', If 'self' will used then Your Company's Phone Number will be Used here

'shipment_address' => 'string', // Params: 'self' or 'Type any other Address here', If 'self' will used then Your Company's Address will be Used here

'consignment_name_eng' => 'string', // Type Consignee Name here

'consignment_email' => 'string', // Optional Field (You can keep it empty), Type Consignee Email here

'consignment_phone' => 'string', // Type Consignee Phone Number here

'consignment_phone_two' => 'string', // Optional Field (You can keep it empty), Type Consignee Second Phone Number here

'consignment_phone_three' => 'string', // Optional Field (You can keep it empty), Type Consignee Third Phone Number here

'consignment_address' => 'string', // Type Consignee Address here

'special_instructions' => 'string', // Type any instruction here regarding booked packet

'shipment_type' => 'string', // Optional Field (You can keep it empty so It will pick default value i.e. "overnight"), Type Shipment type name here

'custom_data' => 'json array', // Optional Field (You can keep it empty), [{"key1":"value1","key2":value2,..... }]

'return_address' => 'string', // Optional Field (You can keep it empty) - If 'return_address' is empty, then the address of shipper will be added as return address

'return_city' => 'int', // Optional Field (You can keep it empty) - If 'return_city' is empty, then shipper's origin city will ne return city

'is_vpc' => 'int', // Optional Field (You can keep it empty) If is_vpc =1 then booked_packet_order_id should be a CN number

),

/* For more than One Booked Packet below section will repeated */

array(

'booked_packet_weight' => int, // Weight should in 'Grams' e.g. '2000'

'booked_packet_vol_weight_w' => int, // Optional Field (You can keep it empty), Volumetric Weight Width

'booked_packet_vol_weight_h' => int, // Optional Field (You can keep it empty), Volumetric Weight Height

'booked_packet_vol_weight_l' => int, // Optional Field (You can keep it empty), Volumetric Weight Length

'booked_packet_no_piece' => int, // No. of Pieces should an Integer Value

'booked_packet_collect_amount' => int, // Collection Amount on Delivery

'booked_packet_order_id' => 'string', // Optional Filed, (If any) Order ID of Given Product

'origin_city' => 'string', /** Params: 'self' or 'integer_value' e.g. 'origin_city' => 'self' or 'origin_city' => 789 (where 789 is Lahore ID)

* If 'self' is used then Your City ID will be used.

* 'integer_value' provide integer value (for integer values read 'Get All Cities' api documentation)

*/

'destination_city' => 'string', /** Params: 'self' or 'integer_value' e.g. 'destination_city' => 'self' or 'destination_city' => 789 (where 789 is Lahore ID)

* If 'self' is used then Your City ID will be used.

* 'integer_value' provide integer value (for integer values read 'Get All Cities' api documentation)

*/

'shipment_id' => 'int',

'shipment_name_eng' => 'string', // Params: 'self' or 'Type any other Name here', If 'self' will used then Your Company's Name will be Used here

'shipment_email' => 'string', // Params: 'self' or 'Type any other Email here', If 'self' will used then Your Company's Email will be Used here

'shipment_phone' => 'string', // Params: 'self' or 'Type any other Phone Number here', If 'self' will used then Your Company's Phone Number will be Used here

'shipment_address' => 'string', // Params: 'self' or 'Type any other Address here', If 'self' will used then Your Company's Address will be Used here

'consignment_name_eng' => 'string', // Type Consignee Name here

```
                'consignment_email'          => 'string',          // Optional Field (You can keep it empty),
Type Consignee Email here

                'consignment_phone'          => 'string',          // Type Consignee Phone Number here

                'consignment_phone_two'      => 'string',          // Optional Field (You can keep it empty),
Type Consignee Second Phone Number here

                'consignment_phone_three'    => 'string',          // Optional Field (You can keep it empty),
Type Consignee Third Phone Number here

                'consignment_address'        => 'string',          // Type Consignee Address here

                'special_instructions'       => 'string',          // Type any instruction here regarding booked
packet

                'shipment_type'              => 'string',          // Optional Field (You can keep it empty so It
will pick default value i.e. "overnight"), Type Shipment type name here

                'custom_data'                => 'json array',      // Optional Field (You can keep it empty),
[{"key1":"value1","key2":value2,..... }]

                'return_address'             => 'string',          // Optional Field (You can keep it empty) - If
'return_address' is empty, then the address of shipper will be added as return address

                'return_city'                => 'int',             // Optional Field (You can keep it empty) - If
'return_city' is empty, then shipper's origin city will ne return city

                'is_vpc'                     => 'int',             // Optional Field (You can keep it empty) If is_vpc =1
then booked_packet_order_id should be a CN number

            )


        )

    )

  )

);

curl_setopt($curl_handle, CURLOPT_HTTPHEADER, array(

  'Content-Type: application/json'

));
```

```
$response = curl_exec($curl_handle);
curl_close($curl_handle);
echo $response;
```

API Response

The following is a JSON response with Error(s).


```
{
   "status" : 0,
   "error"  : {

            "bookPacket - 0": {
              "booked_packet_weight": "Packet Weight is required",
              "booked_packet_no_piece": "No. of Pieces is required",
              "booked_packet_collect_amount": "COD Amount is required",
              "origin_city": "Origin City is required",
              "destination_city": "Destination City is required",
              "shipment_name_eng": "Shipper Name is required",
              "shipment_phone": "Shipper Phone is required",
              "shipment_address": "Shipper Address is required",
              "consignment_name_eng": "Consignee Name is required",
              "consignment_phone": "Consignee Phone is required",
              "consignment_address": "Consignee Address is required",
              "special_instructions": "Special Instructions are required"
            },

            /* For more than One Booked Packet above section will repeated */
```

```
            "bookPacket - 1": {
              "booked_packet_weight": "Packet Weight is required",
              "booked_packet_no_piece": "No. of Pieces is required",
              "booked_packet_collect_amount": "COD Amount is required",
              "origin_city": "Origin City is required",
              "destination_city": "Destination City is required",
              "shipment_name_eng": "Shipper Name is required",
              "shipment_phone": "Shipper Phone is required",
              "shipment_address": "Shipper Address is required",
              "consignment_name_eng": "Consignee Name is required",
              "consignment_phone": "Consignee Phone is required",
              "consignment_address": "Consignee Address is required",
              "special_instructions": "Special Instructions are required",
              "custom_data": "Invalid Custom Data / Custom Data must be Json Array"
            }
          }
          ,
}
```


The following is a XML response with Error(s).


```
<?xml version="1.0" encoding="utf-8"?>
<xml>
   <status>0</status>
   <error>
      <bookPacket-0>
         <booked_packet_weight>string</booked_packet_weight>
```

```
    <booked_packet_no_piece>string</booked_packet_no_piece>
    <booked_packet_collect_amount>string</booked_packet_collect_amount>
    <origin_city>string</origin_city>
    <destination_city>string</destination_city>
    <shipment_name_eng>string</shipment_name_eng>
    <shipment_phone>string</shipment_phone>
    <shipment_address>string</shipment_address>
    <consignment_name_eng>string</consignment_name_eng>
    <consignment_phone>string</consignment_phone>
    <consignment_address>string</consignment_address>
    <special_instructions>string</special_instructions>
</bookPacket-0>

/* For more than One Track Numbers 'item' section will repeated */

<bookPacket-1>
    <booked_packet_weight>string</booked_packet_weight>
    <booked_packet_no_piece>string</booked_packet_no_piece>
    <booked_packet_collect_amount>string</booked_packet_collect_amount>
    <origin_city>string</origin_city>
    <destination_city>string</destination_city>
    <shipment_name_eng>string</shipment_name_eng>
    <shipment_phone>string</shipment_phone>
    <shipment_address>string</shipment_address>
    <consignment_name_eng>string</consignment_name_eng>
    <consignment_phone>string</consignment_phone>
    <consignment_address>string</consignment_address>
```

```
        <special_instructions>string</special_instructions>
      </bookPacket-1>
   </error>
</xml>
```

The following is a JSON response without Error(s).

```
{
   "status" : 1,
   "error"  : 0,
   "data"   : [
              {
               "track_number"          : "string"
               "booked_packet_order_id" : "string"
               "slip_link"             : "string"   // Copy this URL in Browser to Get Slip
              },

              /* For more than One Booked Packet above section will repeated */

               {
               "track_number"          : "string"
               "booked_packet_order_id" : "string"
               "slip_link"             : "string"   // Copy this URL in Browser to Get Slip
              },
             ]
}
```

The following is a XML response without Error(s).

```
<?xml version="1.0" encoding="utf-8"?>
<xml>
  <status>1</status>
  <error>0</error>
  <data>
    <item>
      <track_number>string</track_number>
      <booked_packet_order_id>string</booked_packet_order_id>
      <slip_link>string</slip_link>
    </item>

    /* For more than One Track Numbers 'item' section will repeated */

    <item>
      <track_number>string</track_number>
      <booked_packet_order_id>string</booked_packet_order_id>
      <slip_link>string</slip_link>
    </item>
  </data>
</xml>
```

POST Cancel Booked Packets

Staging Link:

https://merchantapistaging.leopardscourier.com/api/cancelBookedPackets/format/xml/ For 'XML' format
https://merchantapistaging.leopardscourier.com/api/cancelBookedPackets/format/json/ For 'JSON' format

Production Link:

https://merchantapi.leopardscourier.com/api/cancelBookedPackets/format/xml/ For 'XML' format
https://merchantapi.leopardscourier.com/api/cancelBookedPackets/format/json/ For 'JSON' format

API Request

The following is a sample API request using cURL in PHP.

```
$curl_handle = curl_init();


curl_setopt($curl_handle, CURLOPT_URL, 'https://merchantapistaging.leopardscourier.com/api/cancelBookedPackets/format/json/'); // Write here or Production Link

curl_setopt($curl_handle, CURLOPT_RETURNTRANSFER, 1);

curl_setopt($curl_handle, CURLOPT_POST, 1);

curl_setopt($curl_handle, CURLOPT_POSTFIELDS, json_encode(array(

   'api_key'       => 'your_api_key',

   'api_password'  => 'your_api_password',

   'cn_numbers'    => 'string',                    // E.g. 'XXYYYYYYYY' OR 'XXYYYYYYYY,XXYYYYYYYY,XXYYYYYY' 10 Digits each number

)));


$buffer = curl_exec($curl_handle);

curl_close($curl_handle);
```

API Response

The following is a JSON response with Error(s).

```
{
   "status": 0,
   "error" :{
      "provided_cn"  :  "error_string",
      "provided_cn"  :  "error_string"
   }
}
```

The following is a XML response with Error(s).

```
<?xml version="1.0" encoding="utf-8"?>
<xml>
   <status>0</status>
   <error>
      <provided_cn>"error_string"</provided_cn>
      <provided_cn>"error_string"</provided_cn>
   </error>
</xml>
```

The following is a JSON response without Error(s).

```
{
   "status":  "1",
   "error" :  "null",
}
```

The following is a XML response without Error(s).

```
<?xml version="1.0" encoding="utf-8"?>
<xml>
   <status>1</status>
   <error>null</error>
</xml>
```

POST Generate Load Sheet

Staging Link:

https://merchantapistaging.leopardscourier.com/api/generateLoadSheet/format/xml/ For 'XML' format
https://merchantapistaging.leopardscourier.com/api/generateLoadSheet/format/json/ For 'JSON' format

Production Link:

https://merchantapi.leopardscourier.com/api/generateLoadSheet/format/xml/ For 'XML' format
https://merchantapi.leopardscourier.com/api/generateLoadSheet/format/json/ For 'JSON' format

API Request

The following is a sample API request using cURL in PHP.

```
$curl_handle = curl_init();

curl_setopt($curl_handle, CURLOPT_URL, 'https://merchantapistaging.leopardscourier.com/api/generateLoadSheet/format/json/');  // Write here or Production Link

curl_setopt($curl_handle,  CURLOPT_RETURNTRANSFER,  1);

curl_setopt($curl_handle, CURLOPT_POST, 1);

curl_setopt($curl_handle, CURLOPT_POSTFIELDS, json_encode(array(

   'api_key' => 'your_api_key',

   'api_password'  => 'your_api_password',

   'cn_numbers'    => array(),                    // E.g. array('XXYYYYYYYY') OR  array('XXYYYYYYY1', 'XXYYYYYYY2', 'XXYYYYYYY3') 10 Digits each number

   'courier_name'  => 'courier_name',

   'courier_code'  => 'courier_code'

)));


$buffer = curl_exec($curl_handle);

curl_close($curl_handle);
```

API Response

The following is a JSON response with Error(s).

```
{
   "status": 0,
   "error" :{
      "provided_cn"  :  "error_string",
      "provided_cn"  :  "error_string"
   }
}
```

The following is a XML response with Error(s).

```
<?xml version="1.0" encoding="utf-8"?>
<xml>
   <status>0</status>
   <error>
      <provided_cn>"error_string"</provided_cn>
      <provided_cn>"error_string"</provided_cn>
   </error>
</xml>
```

The following is a JSON response without Error(s).

```
{
   "status"       :  "1",
   "error"        :  "null",
   "load_sheet_id" :  "generated_loadsheet_id",
}
```

The following is a XML response without Error(s).


```
<?xml version="1.0" encoding="utf-8"?>
<xml>
   <status>1</status>
   <error>null</error>
   <load_sheet_id>generated_loadsheet_id</load_sheet_id>
</xml>
```

POST Download Load Sheet

Staging Link:

https://merchantapistaging.leopardscourier.com/api/downloadLoadSheet/format/json For 'JSON' format
https://merchantapistaging.leopardscourier.com/api/downloadLoadSheet/ For 'PDF' file format

Production Link:

https://merchantapi.leopardscourier.com/api/downloadLoadSheet/format/json For 'JSON' format
https://merchantapi.leopardscourier.com/api/downloadLoadSheet/ For 'PDF' file format

API Request

The following is a sample API request using cURL in PHP.

```
$curl_handle = curl_init();

curl_setopt($curl_handle, CURLOPT_URL,
'https://merchantapistaging.leopardscourier.com/api/downloadLoadSheet/');  // Write here Production
Link

curl_setopt($curl_handle,  CURLOPT_RETURNTRANSFER,  1);

curl_setopt($curl_handle, CURLOPT_POST, 1);

curl_setopt($curl_handle, CURLOPT_POSTFIELDS, json_encode(array(

   'api_key'       => 'your_api_key',

   'api_password'  => 'your_api_password',

   'load_sheet_id' => int,                    // E.g. 123456

   'response_type' => String                  // E.g. PDF or JSON

)));


$buffer = curl_exec($curl_handle);

curl_close($curl_handle);
```

API Response

The following is a JSON response with Error(s).

```
{
   "status":   "int",
   "error" :   "string"
}
```

The following is a XML response with Error(s).

```
<?xml version="1.0" encoding="utf-8"?>
<xml>
   <status>0</status>
   <error>string</error>
</xml>
```

The following is a PDF resonse without Error(s), it will return binary data of PDF file so you can parse it like:

```
   file_put_contents("loadsheet.pdf",  $response);              // You can change "loadsheet.pdf" to whatever you want.
                                                                 // $response is the API Response
   header('Content-Type:  application/pdf');
   header('Content-Disposition: attachment; filename="' . basename("loadsheet.pdf") . '"');
   readfile("loadsheet.pdf");
```

The following is a JSON response without Error(s).

```
{
   "status": 1,
   "error" : "",
```

```
"data" : [
  {
    "booking_date"              :  "YY/mm/dd",
    "track_number"              :  "string",
    "track_number_short"        :  "int",
    "booked_packet_weight"      :  "int",
    "booked_packet_no_piece"    :  "int",
    "booked_packet_collect_amount" :  "int",
    "booked_packet_order_id"    :  "string",
    "origin_city_id"            :  "int",
    "destination_city_id"       :  "int",
    "shipment_name_eng"         :  "string",
    "shipment_email"            :  "string",
    "shipment_phone"            :  "int",
    "shipment_address"          :  "string",
    "consignment_name_eng"      :  "string",
    "consignment_email"         :  "string",
    "consignment_phone"         :  "int",
    "consignment_phone_two"     :  "int",
    "consignment_phone_three"   :  "int",
    "consignment_address"       :  "string",
    "special_instructions"      :  "string",
    "shipment_type_id"          :  "int",
    "shipment_type_name"        :  "string"
  },
  /* For more than One Track Numbers below section will repeated */
  {
```

```
        "booking_date"              :   "YY/mm/dd",
        "track_number"              :   "string",
        "track_number_short"        :   "int",
        "booked_packet_weight"      :   "int",
        "booked_packet_no_piece"    :   "int",
        "booked_packet_collect_amount" :  "int",
        "booked_packet_order_id"    :  "string",
        "origin_city_id"            :   "int",
        "destination_city_id"       :   "int",
        "shipment_name_eng"         :   "string",
        "shipment_email"            :   "string",
        "shipment_phone"            :   "int",
        "shipment_address"          :   "string",
        "consignment_name_eng"      :   "string",
        "consignment_email"         :   "string",
        "consignment_phone"         :   "int",
        "consignment_phone_two"     :   "int",
        "consignment_phone_three"   :   "int",
        "consignment_address"       :   "string",
        "special_instructions"      :   "string",
        "shipment_type_id"          :   "int",
        "shipment_type_name"        :   "string"
      }
   ]
}
```

GET Get Booked Packet Last Statuses By Date Range

Staging Link:

https://merchantapistaging.leopardscourier.com/api/getBookedPacketLastStatus/format/xml/ For 'XML' format
https://merchantapistaging.leopardscourier.com/api/getBookedPacketLastStatus/format/json/ For 'JSON' format

Production Link:

https://merchantapi.leopardscourier.com/api/getBookedPacketLastStatus/format/xml/ For 'XML' format
https://merchantapi.leopardscourier.com/api/getBookedPacketLastStatus/format/json/ For 'JSON' format

API Request

The following is a sample API request using cURL in PHP.

```
$params = http_build_query (array(
   'api_key' => 'your_api_key',
   'api_password' => 'your_api_password',
   'from_date'    => 'string',                  // E.g. 2019-12-31
   'to_date'      => 'string'                   // E.g. 2019-12-31
));


$curl_handle = curl_init();
curl_setopt($curl_handle, CURLOPT_URL, "https://merchantapistaging.leopardscourier.com/api/getBookedPacketLastStatus/format/json/?{$params}");
curl_setopt($curl_handle, CURLOPT_RETURNTRANSFER, 1);


$buffer = curl_exec($curl_handle);
curl_close($curl_handle);
```

API Response

The following is a JSON response with Error(s).

```
{
   "status"       : 0,
   "error"        : "string",
   "packet_list"   : null
}
```

The following is a XML response with Error(s).

```
<?xml version="1.0" encoding="utf-8"?>
<xml>
   <status>0</status>
   <error>string</error>
   <packet_list/>
</xml>
```

The following is a JSON response without Error(s).

```
{
   "status"       :   1,
   "error"        :   0,
   "packet_list"   :   [
                        {
                           "booking_date":  "2020-01-01",
                           "delivery_date":  "2020-01-01",
                           "tracking_number": "KI123456789",
                           "booked_packet_weight": "250",
```

```
            "arival_dispatch_weight": "0",
            "booked_packet_order_id": "Order ID",
            "origin_city": "Karachi",
            "destination_city": "Lahore",
            "consignment_name_eng": "Jhon Doe",
            "consignment_phone": "03451234567",
            "consignment_address": "House no. 420, ABC street",
            "booked_packet_status": "Pickup Request not Send",
            "cod_value": "1.00"
        },
        {
            "booking_date": "2020-01-01",
            "delivery_date": "2020-01-01",
            "tracking_number": "KI123456789",
            "booked_packet_weight": "250",
            "arival_dispatch_weight": "0",
            "booked_packet_order_id": "Order ID",
            "origin_city": "Karachi",
            "destination_city": "Lahore",
            "consignment_name_eng": "Jhon Doe",
            "consignment_phone": "03451234567",
            "consignment_address": "House no. 420, ABC street",
            "booked_packet_status": "Pickup Request not Send",
            "cod_value": "1.00"
        }
    ]
}
```

The following is a XML response without Error(s).


```
<?xml version="1.0" encoding="utf-8"?>
<xml>
  <status>1</status>
  <error>null</error>
  <packet_list>
    <item>
      <booking_date>2020-01-01</booking_date>
      <delivery_date>2020-01-02</delivery_date>
      <tracking_number>KI123456789</tracking_number>
      <booked_packet_weight>250</booked_packet_weight>
      <arival_dispatch_weight>0</arival_dispatch_weight>
      <booked_packet_order_id>Order  ID</booked_packet_order_id>
      <origin_city>Karachi</origin_city>
      <destination_city>Lahore</destination_city>
      <consignment_name_eng>Jhon  Doe</consignment_name_eng>
      <consignment_phone>03451234567</consignment_phone>
      <consignment_address>House no. 420, ABC street</consignment_address>
      <booked_packet_status>Pickup Request not Send</booked_packet_status>
      <cod_value>1.00</cod_value>
    </item>
    <item>
      <booking_date>2020-01-01</booking_date>
      <delivery_date>2020-01-02</delivery_date>
      <tracking_number>KI123456789</tracking_number>
      <booked_packet_weight>250</booked_packet_weight>
```

```
        <arival_dispatch_weight>0</arival_dispatch_weight>
        <booked_packet_order_id>Order  ID</booked_packet_order_id>
        <origin_city>Karachi</origin_city>
        <destination_city>Lahore</destination_city>
        <consignment_name_eng>Jhon  Doe</consignment_name_eng>
        <consignment_phone>03451234567</consignment_phone>
        <consignment_address>House no. 420, ABC street</consignment_address>
        <booked_packet_status>Pickup Request not Send</booked_packet_status>
        <cod_value>1.00</cod_value>
      </item>
   </packet_list>
</xml>
```

POST Shipper Advice List

Staging Link:

https://merchantapistaging.leopardscourier.com/api/shipperAdviceList/format/xml/ For 'XML' format
https://merchantapistaging.leopardscourier.com/api/shipperAdviceList/format/json/ For 'JSON' format

Production Link:

https://merchantapi.leopardscourier.com/api/shipperAdviceList/format/xml/ For 'XML' format
https://merchantapi.leopardscourier.com/api/shipperAdviceList/format/json/ For 'JSON' format

API Request

The following is a sample API request using cURL in PHP.

```
$curl_handle = curl_init();

curl_setopt($curl_handle, CURLOPT_URL,
'https://merchantapistaging.leopardscourier.com/api/shipperAdviceList/format/json/');  // Write here
Production Link

curl_setopt($curl_handle,  CURLOPT_RETURNTRANSFER,  1);

curl_setopt($curl_handle, CURLOPT_POST, 1);

curl_setopt($curl_handle, CURLOPT_POSTFIELDS, json_encode(array(

   'api_key'       => 'your_api_key',

   'api_password'  => 'your_api_password',

   'from_date' => date,                    // E.g. 2019-12-24

   'to_date' => date,                      // E.g. 2020-01-24

   'origin_city' => int,                   // (Optional) E.g. Origin City ID 592

   'destination_city' => int               // (Optional) E.g. Destination City ID 592

)));


$buffer = curl_exec($curl_handle);

curl_close($curl_handle);
```

API Response

The following is a JSON response with Error(s).

```
{
   "status":   "int",
   "error" :   "string"
}
```

The following is a XML response with Error(s).

```
<?xml version="1.0" encoding="utf-8"?>
<xml>
   <status>0</status>
   <error>string</error>
</xml>
```

The following is a JSON response without Error(s).

```
{
   "status": 1,
   "error" : "",
   "packet_list"  : [
      {
         "track_number"                :    "string",
         "booked_packet_date"          :    "YY/mm/dd",
         "consignment_name_eng"        :    "string",
         "consignment_phone"           :    "string",
         "consignment_address"         :    "string",
         "booked_packet_collect_amount"  :    "string",
         "origin_city_id"              :    "int",
         "destination_city_id"         :    "int",
```

```
        "origin_city_name"          :   "string",
        "destination_city_name"       :   "string",
        "booked_packet_status"        :   "string",
        "pending_reason"            :   "string",
        "shipment_name_eng"           :   "string",
        "advice_text"               :   "int",
        "advice_date_created"         :   "int"
    },
    /* For more than One Track Numbers below section will repeated */
    {
        "track_number"              :   "string",
        "booked_packet_date"          :   "YY/mm/dd",
        "consignment_name_eng"        :   "string",
        "consignment_phone"           :   "string",
        "consignment_address"         :   "string",
        "booked_packet_collect_amount" :   "string",
        "origin_city_id"            :   "int",
        "destination_city_id"         :   "int",
        "origin_city_name"          :   "string",
        "destination_city_name"       :   "string",
        "booked_packet_status"        :   "string",
        "pending_reason"            :   "string",
        "shipment_name_eng"           :   "string",
        "advice_text"               :   "int",
        "advice_date_created"         :   "int"
    }  ]
}
```

POST Get Shipment Details By Order ID(s)

Staging Link:

https://merchantapistaging.leopardscourier.com/api/getShipmentDetailsByOrderID/format/xml/ For 'XML' format
https://merchantapistaging.leopardscourier.com/api/getShipmentDetailsByOrderID/format/json/ For 'JSON' format

Production Link:

https://merchantapi.leopardscourier.com/api/getShipmentDetailsByOrderID/format/xml/ For 'XML' format
https://merchantapi.leopardscourier.com/api/getShipmentDetailsByOrderID/format/json/ For 'JSON' format

API Request

The following is a sample API request using cURL in PHP.

```
$curl_handle = curl_init();

curl_setopt($curl_handle, CURLOPT_URL, 'https://merchantapistaging.leopardscourier.com/api/getShipmentDetailsByOrderID/format/json/'); // Write here Production Link

curl_setopt($curl_handle, CURLOPT_RETURNTRANSFER, 1);

curl_setopt($curl_handle, CURLOPT_HTTPHEADER, array('Content-Type: application/json'));

curl_setopt($curl_handle, CURLOPT_CUSTOMREQUEST, 'POST');

curl_setopt($curl_handle, CURLOPT_POSTFIELDS, json_encode(array(

   'api_key'       => 'your_api_key',

   'api_password'  => 'your_api_password',

   'shipment_order_id' => array(),                    // E.g. array('Order Id') OR array('Order Id-1', 'Order Id-2', 'Order Id-3')

)));


$buffer = curl_exec($curl_handle);

curl_close($curl_handle);
```

API Response

The following is a JSON response with Error(s).

```
{
   "status":   "int",
   "error" :   "string"
}
```

The following is a XML response with Error(s).

```
<?xml version="1.0" encoding="utf-8"?>
<xml>
   <status>0</status>
   <error>string</error>
</xml>
```

The following is a JSON response without Error(s).

```
{
   "status":  1,
   "error" : "",
   "data"  : [
      {
         "booking_date"                :    "YYYY/mm/dd",
         "track_number"                :    "string",
         "booked_packet_weight"        :    "string",
         "booked_packet_no_piece"      :    "string",
         "booked_packet_collect_amount"  :  "string",
         "booked_packet_order_id"      :  "string",
```

```
    "origin_city"                :   "string",
    "destination_city"           :   "string",
    "shipment_name_eng"          :   "string",
    "shipment_email"             :   "string",
    "shipment_phone"             :   "string",
    "shipment_address"           :   "string",
    "consignment_name_eng"       :   "string",
    "consignment_email"          :   "string",
    "consignment_phone"          :   "string",
    "consignment_phone_two"      :   "string",
    "consignment_phone_three"    :   "string",
    "consignment_address"        :   "string",
    "special_instructions"       :   "string",
    "shipment_type_name"         :   "string",
    "booked_packet_status"       :   "string",
    "delivery_date"              :   "string",
    "return_date"                :   "string",
    "invoice_number"             :   "string",
    "invoice_date"               :   "string",
  },
  /* For more than One Order Numbers, above section will repeated like this */
  {
    "booking_date"               :   "YYYY/mm/dd",
    "track_number"               :   "string",
    "booked_packet_weight"       :   "string",
    "booked_packet_no_piece"     :   "string",
    "booked_packet_collect_amount" :   "string",
```

```
        "booked_packet_order_id"        :   "string",
        "origin_city"                   :   "string",
        "destination_city"              :   "string",
        "shipment_name_eng"             :   "string",
        "shipment_email"                :   "string",
        "shipment_phone"                :   "string",
        "shipment_address"              :   "string",
        "consignment_name_eng"          :   "string",
        "consignment_email"             :   "string",
        "consignment_phone"             :   "string",
        "consignment_phone_two"         :   "string",
        "consignment_phone_three"       :   "string",
        "consignment_address"           :   "string",
        "special_instructions"          :   "string",
        "shipment_type_name"            :   "string",
        "booked_packet_status"          :   "string",
        "delivery_date"                 :   "string",
        "return_date"                   :   "string",
        "invoice_number"                :   "string",
        "invoice_date"                  :   "string",
      }
   ]
}
```

GET Get All Banks

Staging Link:

https://merchantapistaging.leopardscourier.com/api/getBankList/format/xml/ For 'XML' format
https://merchantapistaging.leopardscourier.com/api/getBankList/format/json/ For 'JSON' format

Production Link:

https://merchantapi.leopardscourier.com/api/getBankList/format/xml/ For 'XML' format
https://merchantapi.leopardscourier.com/api/getBankList/format/json/ For 'JSON' format

API Request

The following is a sample API request using cURL in PHP.

```
$curl_handle = curl_init();

curl_setopt($curl_handle, CURLOPT_URL,
'https://merchantapistaging.leopardscourier.com/api/getBankList/format/json/'); // Write here  or
Production Link

curl_setopt($curl_handle,  CURLOPT_RETURNTRANSFER,  1);

curl_setopt($curl_handle, CURLOPT_POST, 1);

curl_setopt($curl_handle, CURLOPT_POSTFIELDS, json_encode(array(

    'api_key' => 'your_api_key'

    'api_password' => 'your_api_password'

)));


$buffer = curl_exec($curl_handle);

curl_close($curl_handle);
```

API Response

The following is a JSON response with Error(s).

```
{

    "status":0,
```

```
   "error":"string",
   "bank_list":null
}
```

The following is a XML response with Error(s).

```
<?xml version="1.0" encoding="utf-8"?>
<xml>
   <status>0</status>
   <error>string</error>
   <bank_list/>
</xml>
```

The following is a JSON response without Error(s).

```
{
   "status":1,
   "error":"0",
   "bank_list":[
               {
                  "bank_id" : int,
                  "bank_name_eng" : "string",
               },
               {
                  "bank_id" : int,
                  "bank_name_eng" : "string",
               }
            ]
}
```

The following is a XML response without Error(s).

```
<?xml version="1.0" encoding="utf-8"?>
<xml>
  <status>1</status>
  <error>0</error>
  <bank_list>
    <item>
      <bank_id>int</bank_id>
      <bank_name_eng>string</bank_name_eng>
    </item>
    <item>
      <bank_id>int</bank_id>
      <bank_name_eng>string</bank_name_eng>
    </item>
  </bank_list>
</xml>
```

POST Create Shipper

Production Link:

https://merchantapiStaging.leopardscourier.com/api/createShipper/format/xml/ For 'XML' format
https://merchantapiStaging.leopardscourier.com/api/createShipper/format/json/ For 'JSON' format

Production Link:

https://merchantapi.leopardscourier.com/api/createShipper/format/xml/ For 'XML' format
https://merchantapi.leopardscourier.com/api/createShipper/format/json/ For 'JSON' format

API Request

The following is a sample API request using cURL in PHP.

```
$curl_handle = curl_init();

curl_setopt($curl_handle, CURLOPT_URL,
'https://merchantapistaging.leopardscourier.com/api/createShipper/format/json/');  // Write here
Production Link

'https://merchantapi.leopardscourier.com/api/createShipper/format/json/');

curl_setopt($curl_handle, CURLOPT_RETURNTRANSFER, 1);

curl_setopt($curl_handle, CURLOPT_POST, 1);

curl_setopt($curl_handle, CURLOPT_POSTFIELDS, json_encode(array(

   'api_key'       => 'your_api_key',

   'api_password'  => 'your_api_password',

   'shipment_name' => string,

   'shipment_email' => string,                // Optional Field (You can keep it empty)

   'shipment_phone' => string,

   'shipment_address' => string,

   'bank_id' => int,                          // Provide Bank ID integer value (for integer values read 'Get All Banks'
API documentation)

   'bank_account_no' => string,               // Optional Field (You can keep it empty)

   'bank_account_title' => string,            // Optional Field (You can keep it empty)

   'bank_branch' => string,                   // Optional Field (You can keep it empty)
```

```
   'bank_account_iban_no' => string,          // Optional Field (You can keep it empty)
   'city_id' => string                        // Provide City ID integer value (for integer values read 'Get All Cities'
API documentation)
   'cnic' => string                           // Optional Field (You can keep it empty)
   'return_address' => string                 // Optional Field (You can keep it empty) -
)));
curl_setopt($curl_handle, CURLOPT_HTTPHEADER, array(
   'Content-Type: application/json'
));


$response = curl_exec($curl_handle);
curl_close($curl_handle);
echo $response;
```

API Response

```
The following is a JSON response with Error(s).
{
   "status":   "int",
   "error" :   "string"
}


The following is a XML response with Error(s).
<?xml version="1.0" encoding="utf-8"?>
<xml>
   <status>0</status>
   <error>string</error>
</xml>
```

The following is a JSON response without Error(s). And in case of New User.


```
{
   "status": 1,
   "error" : "0",
   "message": "Shipper added successfully.",
   "data"  : [
      {
         "shipment_id"        :   "int",
         "shipment_name"      :   "string",
         "shipment_email"     :   "string",
         "shipment_phone"     :   "string",
         "shipment_address"   :   "string",
         "city_id"            :   "int",
         "bank_id"            :   "int",
         "bank_account_no"    :   "string",
         "bank_account_title" :   "string",
         "bank_branch"        :   "string",
         "bank_account_iban_no":   "string",
         "username"           :   "string",
         "user_password"      :   "string",
         "cnic"               :   "string",
         "return_address"     :   "string"
      }
   ]
}
```


The following is a JSON response without Error(s). And in case of User already exists.


```
{
```

```
  "status": 1,
  "error" : "0",
  "message": "Shipper already exists.",
  "data"  : [
    {
      "shipment_id"        :   "int",
      "shipment_name"      :   "string",
      "shipment_email"     :   "string",
      "shipment_phone"     :   "string",
      "shipment_address"   :   "string",
      "city_id"            :   "int",
      "bank_id"            :   "int",
      "bank_account_no"    :   "string",
      "bank_account_title" :   "string",
      "bank_branch"        :   "string",
      "bank_account_iban_no":   "string",
      "cnic"               :   "string",
      "return_address"     :   "string"
    }
  ]
}
```


The following is a XML response without Error(s). And in case of New User.


```
<?xml version="1.0" encoding="utf-8"?>
<xml>
  <status>1</status>
  <error>"0"</error>
  <message>"Shipper added successfully."</error>
```

```
  <data>
    <item>
      <shipment_id>string</shipment_id>
      <shipment_name>string</shipment_name>
      <shipment_email>string</shipment_email>
      <shipment_phone>string</shipment_phone>
      <shipment_address>string</shipment_address>
      <city_id>int</city_id>
      <bank_id>int</bank_id>
      <bank_account_no>string</bank_account_no>
      <bank_account_title>string</bank_account_title>
      <bank_branch>string</bank_branch>
      <bank_account_iban_no>string</bank_account_iban_no>
      <username>string</username>
      <user_password>string</user_password>
      <cnic>string</cnic>
      <return_address>string</return_address>
    </item>
  </data>
</xml>
```


The following is a XML response without Error(s). And in case of User already exists.


```
<?xml version="1.0" encoding="utf-8"?>
<xml>
  <status>1</status>
  <error>"0"</error>
  <message>"Shipper already exists."</error>
  <data>
```

```
    <item>
      <shipment_id>string</shipment_id>
      <shipment_name>string</shipment_name>
      <shipment_email>string</shipment_email>
      <shipment_phone>string</shipment_phone>
      <shipment_address>string</shipment_address>
      <city_id>int</city_id>
      <bank_id>int</bank_id>
      <bank_account_no>string</bank_account_no>
      <bank_account_title>string</bank_account_title>
      <bank_branch>string</bank_branch>
      <bank_account_iban_no>string</bank_account_iban_no>
      <cnic>string</cnic>
      <return_address>string</return_address>
    </item>
  </data>
</xml>
```

GET Get Payment Details By CN Number(s)

Staging Link:

https://merchantapistaging.leopardscourier.com/api/getPaymentDetails/format/xml/ For 'XML' format
https://merchantapistaging.leopardscourier.com/api/getPaymentDetails/format/json/ For 'JSON' format

Production Link:

https://merchantapi.leopardscourier.com/api/getPaymentDetails/format/xml/ For 'XML' format
https://merchantapi.leopardscourier.com/api/getPaymentDetails/format/json/ For 'JSON' format

API Request

The following is a sample API request using cURL in PHP.

```
$curl_handle = curl_init();

curl_setopt($curl_handle, CURLOPT_URL,
'https://merchantapistaging.leopardscourier.com/api/getPaymentDetails/format/json/?
                                 api_key=your_api_key
                                &api_password=your_api_password
                                &cn_numbers=CN number'); // Write Production Link here.
                                            // you can provide multiple comma separated cn numbers
                                            // 50 CN Numbers can be provided once
curl_setopt($curl_handle, CURLOPT_RETURNTRANSFER, 1);


$buffer = curl_exec($curl_handle);
curl_close($curl_handle);
```

API Response

The following is a JSON response with Error(s).

```
{
   "status":0,
   "error":"string",
```

```
   "payment_list":null
}
```

The following is a XML response with Error(s).

```
<?xml version="1.0" encoding="utf-8"?>
<xml>
   <status>0</status>
   <error>string</error>
   <payment_list/>
</xml>
```

The following is a JSON response without Error(s).

```
{
   "status":1,
   "error":"0",
   "payment_list":[
            {
               "booked_packet_cn" : int,
               "billing_method" : "string",
               "status" : "string",
               "invoice_cheque_no" : "string",
               "invoice_cheque_date" : "string",
               "payment_method" : "string",
               "message" : "string",
               "slip_link" : "string"
            },
         /* For more than One CN Numbers, above section will repeated like this */
            {
```

"booked_packet_cn" : int,
"billing_method" : "string",
"status" : "string",
"invoice_cheque_no" : "string",
"invoice_cheque_date" : "string",
"payment_method" : "string",
"message" : "string",
"slip_link" : "string"
}
]
}

The following is a XML response without Error(s).

<?xml version="1.0" encoding="utf-8"?>
<xml>
<status>1</status>
<error>0</error>
<payment_list>
<item>
<booked_packet_cn>int</booked_packet_cn>
<billing_method>string</billing_method>
<status>string</status>
<invoice_cheque_no>string</invoice_cheque_no>
<invoice_cheque_date>string</invoice_cheque_date>
<payment_method>string</payment_method>
<message>string</message>
<slip_link>string</slip_link>
</item>

```
  /* For more than One CN Numbers, above section will repeated like this */
    <item>
      <booked_packet_cn>int</booked_packet_cn>
      <billing_method>string</billing_method>
      <status>string</status>
      <invoice_cheque_no>string</invoice_cheque_no>
      <invoice_cheque_date>string</invoice_cheque_date>
      <payment_method>string</payment_method>
      <message>string</message>
      <slip_link>string</slip_link>
    </item>
  </payment_list>
</xml>
```

GET Get Tariff Details

Staging Link:

https://merchantapistaging.leopardscourier.com/api/getTariffDetails/format/xml/ For 'XML' format
https://merchantapistaging.leopardscourier.com/api/getTariffDetails/format/json/ For 'JSON' format

Production Link:

https://merchantapi.leopardscourier.com/api/getTariffDetails/format/xml/ For 'XML' format
https://merchantapi.leopardscourier.com/api/getTariffDetails/format/json/ For 'JSON' format

API Request

The following is a sample SOAP request using cURL in PHP.

```
$curl_handle = curl_init();

curl_setopt($curl_handle, CURLOPT_URL,
'https://merchantapistaging.leopardscourier.com/api/getTariffDetails/format/json/?              // Write
Production Link here.

                                 api_key=Your API Key

                                &api_password=Your API Password

                                &packet_weight=Your Weight

                                &shipment_type=Your Shipment Type ID

                                &origin_city=Your Origin City ID

                                &destination_city=Your Destination City ID');

                                &cod_amount=Your COD Amount              // If your shipment is prepaid, please
insert zero or in other case,

                                                        //please insert amount to get actual charges including
cash handling charges.

curl_setopt($curl_handle,  CURLOPT_RETURNTRANSFER,  1);


$buffer = curl_exec($curl_handle);

curl_close($curl_handle);
```

API Response

The following is a JSON response with Error(s).


```
{
   "status":0,
   "error":"string",
   "packet_charges":null
}
```


The following is a XML response with Error(s).


```
<?xml version="1.0" encoding="utf-8"?>
<xml>
   <status>0</status>
   <error>string</error>
   <packet_charges/>
</xml>
```


The following is a JSON response without Error(s).


```
{
   "status":1,
   "error":"0",
   "packet_charges": {
      "shipment_charges" : string,
      "cash_handling" : "string",
      "insurance_charges" : "string",
      "gst_percentage" : "string",
      "gst_amount" : "string",
      "fuel_surcharge_percentage" : "string",
      "fuel_surcharge_amount" : "string"
```

```
  }
}
```

The following is a XML response without Error(s).

```
<?xml version="1.0" encoding="utf-8"?>
<xml>
  <status>1</status>
  <error>0</error>
  <packet_charges>
    <item>
      <shipment_charges>string</shipment_charges>
      <cash_handling>string</cash_handling>
      <insurance_charges>string</insurance_charges>
      <gst_percentage>string</gst_percentage>
      <gst_amount>string</gst_amount>
      <fuel_surcharge_percentage>string</fuel_surcharge_percentage>
      <fuel_surcharge_amount>string</fuel_surcharge_amount>
    </item>
  </packet_charges>
</xml>
```

GET Get Shipping Charges

Staging Link:

https://merchantapistaging.leopardscourier.com/api/getShippingCharges/format/xml/ For 'XML' format
https://merchantapistaging.leopardscourier.com/api/getShippingCharges/format/json/ For 'JSON' format

Production Link:

https://merchantapi.leopardscourier.com/api/getShippingCharges/format/xml/ For 'XML' format
https://merchantapi.leopardscourier.com/api/getShippingCharges/format/json/ For 'JSON' format

API Request

The following is a sample API request using cURL in PHP.

```
$curl_handle = curl_init();

curl_setopt($curl_handle, CURLOPT_URL,
'https://merchantapistaging.leopardscourier.com/api/getShippingCharges/format/json/?

                                 api_key=your_api_key

                                &api_password=your_api_password

                                &cn_numbers=CN number'); // Write Production Link here.

                                          // you can provide multiple comma separated cn numbers

                                          // 50 CN Numbers can be provided once

curl_setopt($curl_handle, CURLOPT_RETURNTRANSFER, 1);


$buffer = curl_exec($curl_handle);

curl_close($curl_handle);
```

API Response

The following is a JSON response with Error(s).

```
{

   "status":   "int",
```

```
  "error" :   "string"
}
```

The following is a XML response with Error(s).

```
<?xml version="1.0" encoding="utf-8"?>
<xml>
  <status>0</status>
  <error>string</error>
</xml>
```

The following is a JSON response without Error(s).

```
{
  "status": 1,
  "error" : "0",
  "data"  : [
    {
      "cn_number"                : "string",
      "billing_method"           : "string",
      "invoice_cheque_no"        : "string",
      "invoice_cheque_date"      : "yyyy-mm-dd",
      "weight_charged"           : "int",
      "shipment_charges"         : "int",
      "cash_handling_charges"    : "int",
      "return_charges"           : "int",
      "insurance_charges"        : "int",
      "fuel_surcharge_percentage" : "int",
      "fuel_surcharge_amount"    : "int",
      "gst"                      : "int",
```

"gst_amount" : "int",

"booked_packet_collect_amount": "int",

"billed_charges": " int",

"old_invoice_no": "string",

"net_charges" : "int",

"gross_charges" : "int",
}

]

}

The following is a XML response without Error(s).

<?xml version="1.0" encoding="utf-8"?>

<xml>

<status>1</status>

<error>"0"</error>

<data>

<item>

<cn_number>string</cn_number>

<billing_method>string</billing_method>

<invoice_cheque_no>string</invoice_cheque_no>

<invoice_cheque_date>yyyy-mm-dd</invoice_cheque_date>

<weight_charged>int</weight_charged>

<shipment_charges>int</shipment_charges>

<cash_handling_charges>int</cash_handling_charges>

<return_charges>int</return_charges>

<insurance_charges>int</insurance_charges>

<fuel_surcharge_percentage>int</fuel_surcharge_percentage>

<fuel_surcharge_amount>int</fuel_surcharge_amount>

```
        <gst>int</gst>
        <gst_amount>int</gst_amount>

        < booked_packet_collect_amount >int</booked_packet_collect_amount >

        < billed_charges >int</billed_charges>

        < old_invoice_no >int</old_invoice_no>
        <net_charges>int</net_charges>
        <gross_charges>int</gross_charges>
      </item>
  </data>
</xml>
```

GET Invoices List

Staging Link:

https://merchantapistaging.leopardscourier.com/api/getInvoices/format/xml/ For 'XML' format
https://merchantapistaging.leopardscourier.com/api/getInvoices/format/json/ For 'JSON' format

Production Link:

https://merchantapi.leopardscourier.com/api/getInvoices /format/xml/ For 'XML' format
https://merchantapi.leopardscourier.com/api/getInvoices/format/json/ For 'JSON' format

API Request

The following is a sample API request using cURL in PHP.

```
$curl_handle = curl_init();

curl_setopt($curl_handle, CURLOPT_URL,
'https://merchantapistaging.leopardscourier.com/api/getInvoices/format/json/? api_key=your_api_key

&api_password=your_api_password); // Write Production Link here.

curl_setopt($curl_handle, CURLOPT_RETURNTRANSFER, 1);

$buffer = curl_exec($curl_handle);

curl_close($curl_handle);
```

API Response

The following is a JSON response.


```
{
status": 1,
   "error": "0",
   "data": [{
         "invoice_cheque_no": "string",
         "invoice_cheque_date": "date",
         "invoice_cheque_holder_name": "string",
         "invoice_cheque_amount": "int",
         "bank_name": "string",
         "payment_method_name": "string",
         "pay_status_name": "string"
           }]

}
```

GET Get Shipper Details

Staging Link:

https://merchantapistaging.leopardscourier.com/api/getShipperDetails/format/xml/ For 'XML' format
https://merchantapistaging.leopardscourier.com/api/getShipperDetails/format/json/ For 'JSON' format

Production Link:

https://merchantapi.leopardscourier.com/api/getShipperDetails/format/xml/ For 'XML' format
https://merchantapi.leopardscourier.com/api/getShipperDetails/format/json/ For 'JSON' format

API Request

The following is a sample API request using cURL in PHP.

```
$curl_handle = curl_init();

curl_setopt($curl_handle, CURLOPT_URL,
'https://merchantapistaging.leopardscourier.com/api/getShipperDetails/format/json/?
                    api_key=your_api_key
                    &api_password=your_api_password
                    &request_param=request_param
                    &request_value=request_value);
curl_setopt($curl_handle, CURLOPT_RETURNTRANSFER, 1);
curl_setopt($curl_handle, CURLOPT_HTTPHEADER, array(
   'Content-Type: application/json'
));


$response = curl_exec($curl_handle);
curl_close($curl_handle);
echo $response;
```

API Response

The following is a JSON response with Error(s).

{

```
  "status":   "int",
  "error" :   "string"
}
```

The following is a XML response with Error(s).

```
<?xml version="1.0" encoding="utf-8"?>
<xml>
  <status>0</status>
  <error>
    <request_param>string</request_param>
    <request_value>string</request_value>
  </error>

</xml>
```

The following is a JSON response without Error(s).

```
{
  "status": 1,
  "error" : "0",
  "data"  : [
    {
      "shipment_id"            : "int",
      "shipment_name_eng"       : "string",
      "shipment_contact_person" : "string",
      "shipment_email"          : "string",
      "shipment_phone"          : "int",
      "shipment_address"        : "string",
      "bank_id"                 : "int",
      "bank_name_eng"           : "string",
```

```
        "bank_account_no"        : "string",
        "bank_account_title"      : "string",
        "bank_branch"            : "string",
        "bank_account_iban_no"    : "string",
        "is_settlement"          : "int",
        "cnic"                   : "string",
        "return_address"         : "string",
        "shipper_city_id"        : "int",

      }
   ]
}
```


The following is a XML response without Error(s).


```
<?xml version="1.0" encoding="utf-8"?>
<xml>
   <status>1</status>
   <error>"0"</error>
   <data>
      <item>
         <shipment_id>int</shipment_id>
         <shipment_name_eng>string</shipment_name_eng>
         <shipment_contact_person>string</shipment_contact_person>
         <shipment_email>string</shipment_email>
         <shipment_phone>int</shipment_phone>
         <shipment_address>string</shipment_address>
         <bank_id>int</bank_id>
         <bank_name_eng>string</bank_name_eng>
```

```
        <bank_account_no>string</bank_account_no>
        <bank_account_title>string</bank_account_title>
        <bank_branch>string</bank_branch>
        <bank_account_iban_no>string</bank_account_iban_no>
        <is_settlement>int</is_settlement>
        <cnic>string</cnic>
        <return_address>string</return_address>
        <shipper_city_id>int</shipper_city_id>
      </item>
  </data>
</xml>
```

GET Get Electronic Proof Of Delivery

Staging Link:

https://merchantapistaging.leopardscourier.com/api/getElectronicProofOfDelivery/format/json For 'JSON' format
https://merchantapistaging.leopardscourier.com/api/getElectronicProofOfDelivery/format/xml For 'XML' format

Production Link:

https://merchantapi.leopardscourier.com/api/getElectronicProofOfDelivery/format/json For 'JSON' format
https://merchantapi.leopardscourier.com/api/getElectronicProofOfDelivery/format/xml For 'XML' format

API Request

The following is a sample API request using cURL in PHP.

```
$curl_handle = curl_init();

curl_setopt($curl_handle, CURLOPT_URL,
'https://merchantapistaging.leopardscourier.com/api/getElectronicProofOfDelivery/format/json/?
                    api_key=your_api_key
                    &api_password=your_api_password
                    &cn_number=cn_number); // Write Production Link here.
                              // you can provide multiple comma separated cn numbers
                              // 50 CN Numbers can be provided once
curl_setopt($curl_handle, CURLOPT_RETURNTRANSFER, 1);

$buffer = curl_exec($curl_handle);

curl_close($curl_handle);
```

API Response

The following is a JSON response with Error(s).

```
{
  "status":  "int",
```

```
  "error" :   "string"
}
```

The following is a XML response with Error(s).

```
<?xml version="1.0" encoding="utf-8"?>
<xml>
  <status>0</status>
  <error>
    <cn_number>string</cn_number>

  </error>

</xml>
```

The following is a JSON response without Error(s).

```
{
  "status": 1,
  "error" : "0",
  "data"  : [
    'cn_number':{
      "City_Name"     : "string",
      "CN_Number"     : "string",
      "Arrival_Date"  : "date",
      "Status"        : "string",
      "Status_Detail" : "string",
      "Cour_Code"     : "int",
```

```
        "Cour_Name"     : "string",
        "Receiver_Name" : "string",
        "Relation"      : "string",
        "Reason"        : "string",
        "Pcs"           : "string",
        "Weight"        : "int",
        "Latitude"      : "int",
        "Longitude"     : "int",
        "Sig_Url"       : "string",
        "Activity"      : "string",

      }
  ]
}
```


The following is a XML response without Error(s).


```
<?xml version="1.0" encoding="utf-8"?>
<xml>
  <status>1</status>
  <error>"0"</error>
  <data>
    <cn_number>
      <City_Name>string</City_Name>;
      <CN_Number>string</CN_Number>;
      <Arrival_Date>date</Arrival_Date>;
      <Status>string</Status>;
      <Status_Detail>string</Status_Detail>
```

```
        <Cour_Code>int</Cour_Code>
        <Cour_Name>string</Cour_Name>
        <Receiver_Name>string</Receiver_Name>
        <Relation>string</Relation>
        <Reason>string</Reason>
        <Pcs>string</Pcs>
        <Weight>int</Weight>
        <Latitude>int</Latitude>
        <Longitude>int</Longitude>
        <Sig_Url>string</Sig_Url>
        <Activity>string</Activity>
      </cn_number>
  </data>
</xml>
```

POST Shipper Advice List

Staging Link:

https://merchantapistaging.leopardscourier.com/api/shipperAdviceList/format/xml/ For 'XML' format
https://merchantapistaging.leopardscourier.com/api/shipperAdviceList/format/json/ For 'JSON' format

Production Link:

https://merchantapi.leopardscourier.com/api/shipperAdviceList/format/xml/ For 'XML' format
https://merchantapi.leopardscourier.com/api/shipperAdviceList/format/json/ For 'JSON' format

API Request

The following is a sample API request using cURL in PHP.

```
$curl = curl_init();
curl_setopt_array($curl, array(
  CURLOPT_URL =>
'https://merchantapistaging.leopardscourier.com/api/shipperAdviceList/format/json/',
  CURLOPT_RETURNTRANSFER => true,
  CURLOPT_ENCODING => '',
  CURLOPT_MAXREDIRS => 10,
  CURLOPT_TIMEOUT => 0,
  CURLOPT_FOLLOWLOCATION => true,
  CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
  CURLOPT_CUSTOMREQUEST => 'POST',
  CURLOPT_POSTFIELDS =>'{
    "api_key": "your_api_key",
    "api_password": "your_api_password",
    "product": "",
    "status": "",
    "origionID": "",
    "destinationID": "",
```

```
    "dateFrom": "",
    "toDate": "",
    "Cn_number": "",
    "start": 0,
    "length": 100
}',
  CURLOPT_HTTPHEADER => array(
    'Content-Type: application/json',
    'Accept: application/json',
    'Cookie: '
  ),
));

$response = curl_exec($curl);

curl_close($curl);
echo $response;
```

API Response

The following is a JSON response with Error(s).

```
{
    "status":   "int",
    "error" :   "string"
}
```

The following is a JSON response without Error(s).

```
{
    "status": "1",
```

```
"error": "0",
"totalrecords": 1,
"data": [
  {
    "id": int,
    "cn_number": "string",
    "origin_id": int,
    "courier_id": int,
    "cour_date": "string",
    "cour_time": null,
    "dest_id": int,
    "product": "string",
    "shipper_name": "string",
    "shipper_address": "string",
    "shipper_mobile": "string",
    "consignee_name": "string",
    "consignee_address": "string",
    "consignee_mobile": "string",
    "status": "string",
    "reason": "string",
    "client_id": null,
    "shipper_advice_status": "string",
    "shipper_remarks": "string",
    "created_date": "string",
    "created_time": null,
    "remarks": "",
    "delete_type": null,
```

```
            "attempt_counter": 0,
            "user_id": int,
            "station_id": int,
            "activity": "string,
            "orgncityid": string,
            "origin_name": string,
            "dstncityid": string,
            "dst_name": string,
            "status_description": string,
            "outcome_status": string,
            "oms_status": string"
        }
    ]
}
```

POST Activity Log

Staging Link:

https://merchantapistaging.leopardscourier.com/api/activityLog/format/xml/ For 'XML' format
https://merchantapistaging.leopardscourier.com/api/activityLog/format/json/ For 'JSON' format

Production Link:

https://merchantapi.leopardscourier.com/api/activityLog/format/xml/ For 'XML' format
https://merchantapi.leopardscourier.com/api/activityLog/format/json/ For 'JSON' format

API Request

The following is a sample API request using CURL in PHP.

```
$curl = curl_init();

curl_setopt_array($curl, array(
  CURLOPT_URL =>
'https://merchantapistaging.leopardscourier.com/api/activityLog/format/json/',
  CURLOPT_RETURNTRANSFER => true,
  CURLOPT_ENCODING => '',
  CURLOPT_MAXREDIRS => 10,
  CURLOPT_TIMEOUT => 0,
  CURLOPT_FOLLOWLOCATION => true,
  CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
  CURLOPT_CUSTOMREQUEST => 'POST',
  CURLOPT_POSTFIELDS =>'{
    "api_key": "your_api_key",
    "api_password": "your_api_password",
    "product": "",
    "status": "",
    "Cn_number": "",
```

```
    "start": 0,
    "length": 100
}',
  CURLOPT_HTTPHEADER => array(
    'Content-Type: application/json',
    'Cookie:
  ),
));

$response = curl_exec($curl);

curl_close($curl);
echo $response;
```

API Response

The following is a JSON response with Error(s).

```
{
    "status":   "int",
    "error" :   "string"
}
```

The following is a JSON response without Error(s).

```
{
    "status": "1",
    "error": "0",
    "totalrecords": 1,
    "data": [
```

```
{
    "id": int,
    "cn_number": "string",
    "origin_id": int,
    "courier_id": int,
    "cour_date": "string",
    "cour_time": null,
    "dest_id": int,
    "product": "string",
    "shipper_name": "string",
    "shipper_address": "string",
    "shipper_mobile": "string",
    "consignee_name": "string",
    "consignee_address": "string",
    "consignee_mobile": "string",
    "status": "string",
    "reason": "string",
    "client_id": null,
    "shipper_advice_status": "string",
    "shipper_remarks": "string",
    "created_date": "string",
    "created_time": null,
    "remarks": "",
    "delete_type": null,
    "attempt_counter": 0,
    "user_id": int,
    "station_id": int,
```

```
            "activity": "string,
            "orgncityid": string,
            "origin_name": string,
            "dstncityid": string,
            "dst_name": string,
            "status_description": string,
            "outcome_status": string,
            "oms_status": string"
        }
    ]
}
```

POST Add Shipper Advices

Staging Link:

https://merchantapistaging.leopardscourier.com/api/updateShipperAdvice/format/xml/ For 'XML' format
https://merchantapistaging.leopardscourier.com/api/updateShipperAdvice/format/json/ For 'JSON' format

Production Link:

https://merchantapi.leopardscourier.com/api/updateShipperAdvice/format/xml/ For 'XML' format
https://merchantapi.leopardscourier.com/api/updateShipperAdvice/format/json/ For 'JSON' format

API Request

The following is a sample API request using cURL in PHP.

```
$curl = curl_init();
curl_setopt_array($curl, array(
 CURLOPT_URL =>
'https://merchantapistaging.leopardscourier.com/api/updateShipperAdvice/format/json/',
 CURLOPT_RETURNTRANSFER => true,
 CURLOPT_ENCODING => '',
 CURLOPT_MAXREDIRS => 10,
 CURLOPT_TIMEOUT => 0,
 CURLOPT_FOLLOWLOCATION => true,
 CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
 CURLOPT_CUSTOMREQUEST => 'POST',
 CURLOPT_POSTFIELDS =>'{
 "api_key": "your_api_key",
 "api_password": "your_api_password",
 "data": [
    {
      "id": ,
```

```
            "cn_number": "",
            "shipper_advice_status": "", // allowed statuses are ('RA', 'RT')
            "shipper_remarks": ""
        },
        {
            "id": ,
            "cn_number": "",
            "shipper_advice_status": "", // allowed statuses are ('RA', 'RT')
            "shipper_remarks": ""
        },
        {
            "id": ,
            "cn_number": "",
            "shipper_advice_status": "", // allowed statuses are ('RA', 'RT')
            "shipper_remarks": ""
        }
    ]
}',
  CURLOPT_HTTPHEADER => array(
    'Content-Type: application/json',
    'Cookie:  '
  ),
));
$response = curl_exec($curl);


curl_close($curl);
echo $response;
```

API Response

The following is a JSON response with Error(s).

```
{
   "status":   "int",
   "error" :   "string"
}
```

The following is a JSON response without Error(s).

```
{
        "status": "1",
        "error": "0",
        "data": "Shipper Advice Updated successfully"
}
```