

Tabla de contenidos

```
using Pkg
pkg"activate ."
```

Activating environment at `~/courses/CURSO-ALGO-IR/U4/Project.toml`

```
using JSON3, Random, Printf
```

Lectura de la lista de posteo

```
function read_posting_lists(filename)
    T = String[]
    P = Vector{Int32}[]

    open(filename) do f
        for line in eachline(f)
            token, list = JSON3.read(line)
            push!(T, token)
            push!(P, list)
        end
    end

    T, P
end
```

read_posting_lists (generic function with 1 method)

Cada arreglo A se perturba con $\lfloor p \times n \rfloor$ intercambios de dos elementos aleatorios de cada lista

```
function perturbate_list(L_, prob)
    L = copy(L_)
    n = length(L)
    for c in 1:floor{Int, prob * length(L)}
        i = rand(1:n-1)
        L[i], L[i+1] = L[i+1], L[i]
    end

    L
end
```

perturbate_list (generic function with 1 method)

```

voc, lists = read_posting_lists("../datos/listas-posteo-100.json")

for p in [0.01, 0.03, 0.10, 0.30]
    outname = @sprintf "unsorted-list-p=%0.2f.json" p
    println(outname)
    open(outname, "w") do f
        for i in eachindex(voc)
            w = voc[i]
            L = lists[i]
            s = (w, perturbate_list(L, p))
            println(f, JSON3.write(s))
        end
    end
end

unsorted-list-p=0.01.json
unsorted-list-p=0.03.json
unsorted-list-p=0.10.json
unsorted-list-p=0.30.json

```