



APLICACIÓN Y SUMINISTROS TEXTILES, S.A.

Av. Camí Reial, 13-15
08184 PALAU-SOLITÀ I PLEGAMANS
BARCELONA (SPAIN)
Teléfono: 34 93 864 71 11 – Fax: 34 93 864 51 04
e-mail: chemicals@asutex.es
Website: www.asutex.es

TECHNICAL DATA SHEET

Updated: 08/11/13

Page: 1 of 1

ASUTOL FTT POLVO

Anti back-staining agent for increasing the contrast in the Stone Wash treatment of Jeans.

SCOPE OF APPLICATION

Once the stone treatment has been carried out with cellulase, **ASUTOL FTT POLVO** is applied in new bath to improve the blue/white contrast and modify the appearance of the Jeans.

PROPERTIES

Appearance:	White powder.
Composition:	A mixture of surfactants, oxidising and dispersing agents.
pH 10%:	10,5 ± 0,5.
Dissolution:	In water at any ratio. Sprinkle over the water.
Compatibility:	It is not compatible with the enzyme.

APPLICATION

De-sizing:

AMILASE AGO
PRODER SCPC/LF or JT-FL
ASULIT PA-NI

Stone Wash:

PUMICE STONE
STONE WASH GN 72, PN 10 or ASUCEL NE

Wash:

0,5 – 1,5 g/L

ASUTOL FTT POLVO

Heat to 60 – 70 °C quickly and maintain at 10 - 15 minutes.

Rinse or bleach with ClONa

Soften with ASUMIN C.

Dry.