According top 1907/2006 EEC

Rev No:01

Reviewed on 05.01.2016

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND COMPANY

• Product details:

• Trade name: TEXSTAIN RM

Code: DS525

- Anti-back staining agent
- Supplier details
 SETAŞ KİMYA A.Ş.
 Çerkezköy Organize Sanayi bölgesi 9.sokak 545500
 Tekirdağ –Turkey
 Santral@setas.com.tr
- Emergency telephone number:

+90 (0282) 7581832

2. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical characterization

100% Nonionic Polyester Polymer formulation

Dispersing & Antiredeposition Aid for Garment Wet Processing

It have been pre-registered under the REACH Regulation and this textile dye do not contain any of the REACH SVHC substances

Hazardous components

CAS No	percent	EINECS
37335-03-8		
	-	-

3 HAZARDS IDENTIFICATION

Hazard designation

This material has been classified as non-hazardous for supply

4. FIRST AID MEASURES

• Eves:

Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

• Skin:

Get medical aid. Flush skin with plenty of soap and water for at least 15 minutes while removing







According top 1907/2006 EEC

Rev No:01

Reviewed on 05.01.2016

contaminated clothing and shoes. Wash clothing before reuse.

Ingestion:

Never give anything by mouth to an unconscious person. Get medical aid. Do NOT induce vomiting. If conscious and alert, rinse mouth and drink 2-4 cupfuls of milk or water.

Inhalation:

Remove from exposure to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult, give oxygen .Get medical aid.

Notes to Physician:

Treat symptomatically and supportively.

5. FIRE-FIGHTING MEASURES

• General Fire Fighting

As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.

• Extinguishing Media:

Water spray, foam, and dry chemical, CO2.

Special Exposure Hazards:

May burn if involved in afire, releasing irritant/toxic fumes

• Protective Equipment

Under fire conditions the use of self-contained breathing apparatus is advised. Autoignition Temperature:Not available.

6. ACCIDENTAL RELEASE MEASURES:

- Personal protection: Contact with skin and eyes should be avoided. Wear eye protection and impervious gloves
- Environmental protection: Do not flush into surface water or sanitary sewer system
- **Methods for cleaning up** Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

7. HANDLING AND STORAGE

Handling

When handling all chemicals. Observe good standards of industrial hygiene to avoid swallowing. And eye and skin contact.

- Storage: Keep only the original container in a well-ventilated place away from excess heat and cool Keep container tightly closed. Storage life is 12 mounts in the original package from the production data
- Packing: 25 kg or 200Kg plastic drums





ETAD Page: 2/4

According top 1907/2006 EEC

Rev No:01

Reviewed on 05.01.2016

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation System:

A system of local and /or general exhaust is recommended to keep employee exposures as low as possible. Local exhaust is recommended to keep employee as low as possible. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area.

- Personal protection:
- **Eyes:** Wear appropriate protective eyeglasses or chemical safety goggles as described by European Standard EN166.
- Skin/ Wear appropriate protective gloves to prevent skin exposure
- Clothing: Wear appropriate protective clothing to prevent skin exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical State: viscose liquid
- Appearance: light brown to cream color liquid
- Odor: characteristic
- Solubility: Dispersible in Water

10.STABILITY AND REAKTIVITY

- Stable under normal conditions
- Conditions to Avoid

Incompatible materials,

Incompatibilities with other materials:

Strong oxidizing agents

Hazardous Decomposition

May produce ammonia, hydrogen chloride and oxides of nitrogen and carbon when heated to decomposition

Hazardous polymerization:

Will not occur

11.TOXICOLOGICAL INFORMATION

General Toxicology

This information has been determined by consideration of toxicological data for components and by animal testing

LD50 oral, rat :>2000 mg/kg

Cancerogenic effect:

Not listed by ACGIH, IARC, NIOSH or OSHA

12.ECOLOGICAL INFORMATION

• Aquatic toxicity:

LC50 fish ,96 hour: >100 ppm (OECD 203)







According top 1907/2006 EEC

Rev No:01

Reviewed on 05.01.2016

• General hints:

Do not introduce into water and soil It must be treated in a treatment plant before they are passed through a sewerage system or rivers

13.DISPOSAL CONSIDERATION

Recommendations: Recovered material and/or unwanted product should be disposed of by land-fill
or incineration at an authorized site in accordance with local regulations

14.TRANSPORT INFORMATION

Road transport

ADR Not classified

RID Not classified

Inland waterways transport

ADNR Not classified

Marine transport

IMDG-code Not classified

Air transport

ICAO/IATA-DGR Not classified

Further information

Dispatch by post permitted

15.REGULATORY INFORMATION

• European Labelling in accordance with GefStoffV/EC

This material has been classified as non hazardous			for supply

Hazard Symbols: Not available

16-OTHER INFORMATION

This information is based on our present state of knowledge. It should not therefore be construed as guaranteeing specific properties of the products described or their suitability for a particular application.





