



Technical Data Sheet

Texstain RM

Nonionic Polyester Polymer Formulation

Dispersing & Antiredeposition Aid for Garment Wet Processing

INTRODUCTION

Texstain RM is a state of the art dispersing & antiredeposition aid for garment wet processing.

Texstain RM provides maximum dye antiredeposition properties in garment wet processing.

BENIFITS

- ✓ Excellent whiter pockets, cleaner garment
- ✓ Superb overall garment contrast
- ✓ Potential for shorter abrasion cycles
- ✓ Less clean-up needed after processing
- ✓ Improved physical strength of garments after processing
- ✓ Exceptional Softness

DOSAGE RECOMMENDATIONS

0.5-1.0 g/l is recommended

TYPICAL PROPERTIES

Appearance	Dark cream color liquid
Solubility	Dispersible in Water

PACKAGING

Texstain RM is available in 25Kg or 200Kg open ended plastic drums.

STORAGE & HANDLING

Texstain RM must be kept in a cool, dry place. Follow good industrial hygiene. Please refer to the Material Safety Data Sheet for handling details.

CONTACT INFORMATION

**denimse**
A SETAS DIVISION

Product Development Center – Çerkezköy, Turkey.

t: +90 282 758 18 23 pbx

f: +90 282 758 18 32

denimse@denimse.com

www.denimse.com

Disclaimer: Information given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of the product for particular uses are beyond our control; the user therefore assumes all risks of the use of the product. Appropriate warnings and safe handling procedures should be provided to handlers and users. It is also the responsibility of the user to observe any and all the laws and regulations concerning the transportation, use, storage, and disposal of the product.

Created on 21/05/2011 by MW