

# Unified Type System

Lutz Wrage

Software Engineering Institute  
Carnegie Mellon University  
Pittsburgh, PA 15213

Copyright 2018 Carnegie Mellon University. All Rights Reserved.

This material is based upon work funded and supported by the Department of Defense under Contract No. FA8702-15-D-0002 with Carnegie Mellon University for the operation of the Software Engineering Institute, a federally funded research and development center.

The view, opinions, and/or findings contained in this material are those of the author(s) and should not be construed as an official Government position, policy, or decision, unless designated by other documentation.

NO WARRANTY. THIS CARNEGIE MELLON UNIVERSITY AND SOFTWARE ENGINEERING INSTITUTE MATERIAL IS FURNISHED ON AN "AS-IS" BASIS. CARNEGIE MELLON UNIVERSITY MAKES NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, AS TO ANY MATTER INCLUDING, BUT NOT LIMITED TO, WARRANTY OF FITNESS FOR PURPOSE OR MERCHANTABILITY, EXCLUSIVITY, OR RESULTS OBTAINED FROM USE OF THE MATERIAL. CARNEGIE MELLON UNIVERSITY DOES NOT MAKE ANY WARRANTY OF ANY KIND WITH RESPECT TO FREEDOM FROM PATENT, TRADEMARK, OR COPYRIGHT INFRINGEMENT.

[DISTRIBUTION STATEMENT A] This material has been approved for public release and unlimited distribution. Please see Copyright notice for non-US Government use and distribution.

This material may be reproduced in its entirety, without modification, and freely distributed in written or electronic form without requesting formal permission. Permission is required for any other use. Requests for permission should be directed to the Software Engineering Institute at [permission@sei.cmu.edu](mailto:permission@sei.cmu.edu).

Carnegie Mellon® is registered in the U.S. Patent and Trademark Office by Carnegie Mellon University.

DM18-1276

# Type System Unification

Unification of type systems and expression languages (Peter, Lutz\*, Alexey, Brian, Serban)

- Data Components
- Property Types
- Classifiers
- Annexes
  - Resolute, AGREE
  - Data Modeling
  - EMV2
  - BA, BLESS
- ReqSpec
- Scripting languages (Python)

# Current Usages of Types

Application data that occurs in the modeled system

- Data subcomponents
  - Shared data
  - Local variables in threads and subprograms
- Data communicated via data and event data ports

Information about the modeled system and individual components

- Properties

Mixture of models and properties

- Component classifiers and model elements as properties
  - Bindings
  - Specify constraints, e.g., `Required_Virtual_Bus_Class`

Additions in annexes

- Resolute: sets
- EMV2: error types and type sets, error types can have properties
- BLESS

# Current Composite Types

## AADL 2.2

### Property types

- range of
- list of
- record

### Data implementations

- Very similar to records

### No operations available except

- List append ( $+=>$ )
- Boolean operations

### Property expressions provide syntax for literals

### ReqSpec adds expressions, uses simple type inference

# Goals

Goal of the type system

Common type system available for use as data types, property types, annex sublanguage types

Goal for today

Discuss the scope of the type system

**What should be in AADL 3 and what is outside?**

# Type System Unification Approach

*Goal: Common type system available for use as data types, property types, annex sublanguage types*

## Base types

- Numeric, Boolean, String
- Enumeration, Unit
- Category (thread, processor, etc.), Classifier, Model Element
- Range of Numeric (Compute\_Execution\_Time => 10ms .. 15ms)

## Composite types

- Array (ordered sequence of fixed length)
- List (ordered sequence of arbitrary length)
- Record (named fields)
- Union (named alternatives)
- Tuples (unnamed fields)
- Set (unique elements)
- Map
  - Modal and binding specific property values in AADL 2.2 are (almost) maps
- Bag, Graph

*Which should be built-in?*

# Properties on Types

AADL2 core language, data modeling annex, and code generation annex use data classifiers to associate properties to data types for a variety of purposes

Meta data for use by model analyses

- `integer {data_size => 16bit}`

Restrictions on valid values

- `integer {range => 100 .. 1000}`

Information for code generation

- `string {encoding => UTF-16}`

Could be used for measurement units(?)

- `integer {unit => Time}`

What should a type checker do w.r.t. properties?

- *Interpret some pre-declared properties?*
  - Allows checking of assignments: -1 is not valid for `integer {signed => false}`
  - Details may become complicated
- *Ignore properties completely?*
  - No checking of assignments
  - Properties are then not part of a value of the type so no need to track them
  - Need syntax for measurement units
- *Add properties to ports directly, not as part of the data type?*



# User Defined Types

Users can create named types

- **type** byte **is** integer { range => 0 .. 255 }
- **type** otherByte **is** byte { data\_size => 16bit }
- **type** sensed **is** record  
    value: integer  
    timestamp: integer  
**end**
- **type** sensed2 **is** record  
    timestamp: integer  
    value: integer  
**end**

Is a type name just a shorthand, or is it a new type?

- In OSTATE we require that property types are identical for assigning one property to another
- AADL 2.2 standard:
  - property types must “be identical”, “match”
  - Classifier\_Matching\_Rule for port data types

*Properties not part of type => otherByte, byte, integer are the same type*

*No structural comparison => sensed, sensed2 are different types*

*These user defined types correspond to data components in AADL2*

# Subtypes

Subsets of numeric types (or enumerations?)

- Range constrained Numeric  
e.g., `integer [100 .. 120]`
- Could be considered special syntax for a property on a type  
e.g., `integer {range => 100 .. 200}`

Subset constraints are difficult to maintain for expressions

- Simple assignments are easy to check
- `2 * integer[100 .. 120]` results in `integer[200 .. 240]`
- `sin(integer[100 .. 120])` results in (not quite) `real[-1.0 .. 1.0]`

*Type checking should ignore range constraints, maybe except for simple assignments*

# Type Hierarchy

## Type extension

- Exists for classifiers (including data components in AADL 2)
- Records
  - Add fields
- Unions:
  - Add fields to one or more variants
  - Add variants
- Add properties to any type
  - byte is subtype of integer
  - Then: list of byte is subtype of list of integer
- Change property values?
- “refinement”?
- Should there be a complete type hierarchy with something like Object as the root?

*Do we really need type extension for data types?*

# Expression Language: Literals

Numbers, strings, boolean true/false as in AADL 2

- Automatic conversion from integer literal to real value

Range literals

Enumeration and unit literals

- Qualified name: <package>.<enum type>.<enum literal>  
e.g., `myenums.signaltype.RED`
- Need to import enumeration and unit literals in order to use them

# Expression Language: Operations 1

## Boolean

- And, or, not, ...

## Numeric values

- +, -, \*, /, div, mod

## Ranges

- Union, intersection, contains

## Enumerations

- Assign a numeric value to enumeration elements?
- Consider them ordered?

## Units

- Get conversion factor

## Strings, List

- Append, substring, ...

## Records

- Extract a field

## Union

- Access field depending on variant tag

# Expression Language: Operations 2

## Classifiers

- Extends, get extended, get all extending

## Named elements

- Get name, get classifier

## Set

- Union, intersection, contains

## Generic collection operations

- Forall, exists, filter

*Does it make sense to define our own set of collections and operations on them or should we just borrow from an existing standard?*

- OCL?, a programming language?

# Expression Language: Operations 3

Where should AADL end?

- Types
- Values: properties, ports, constants
- Literals
- Expressions
- Functions
- Recursive functions (to process lists)
  - Now we have a programming language!

# Measurement Units

Represent a (physical) quantity as a number with a dimension

- Length, Time, Mass, Force

Dimension has associated measurement units

- Length – **meter** (SI base unit)
- Time – **second** (SI base unit)
- Mass – **kilogram** (SI base unit)
- Force – **Newton** (Derived:  $1\ N = 1\ \frac{kg \cdot m}{s^2}$ )

Different unit systems

- SI vs. Imperial
- Non-physical quantities, e.g., bit
- Other: minute, day, year; rpm, angle, ...

*Users must be able to define new units*



# Standard Metric Prefixes

## Metric prefixes

- Base 10: **centi**, **milli**, micro  $\mu$ , **deka**, **kilo**, **Mega**
- Binary: **Ki** ( $2^{10}$ ), **Mi** ( $2^{20}$ ), **Gi** ( $2^{30}$ )
- These are case sensitive, one is a greek letter
- Not distinct from units: **meter** vs. **milli**

*Should metric prefixes be part of the unit literal as in AADL2 or separate entities?*

# Unit Definitions and Usage

Defining dimensions and units

- **type** LengthU **is** <cm, m = 100 \* cm, ...>
- **type** TimeU **is** <s, ms = s / 1000, ...>
- **type** USLengthU **is** <in, ft = 12 \* in, ...>

Type declarations with units

- **type** LengthType **is** real <LengthU>

Property definition

- Value is a unit
  - **property** lengthUnit: LengthU
  - lengthUnit => <m>
- Value is a physical quantity
  - **property** distance: real <USLengthU>
  - speed => 2.5 <in>

*Should one be able to convert between different unit systems?*

*E.g. USLength  $\Leftrightarrow$  SI Length, TempF  $\Leftrightarrow$  TempC*

# Unit Definitions and Usage

Derived units with unit expressions

- **type** Mass **is** <kg>
- **type** Speed **is** <Length / Time>
- **type** Force **is** <N = kg \* m / s<sup>2</sup>, ...>

Type declarations with units

- **type** SpeedT **is** real <Speed>
- **type** ForceT **is** real <Force>
- **type** OtherSpeedT **is** real <Length / Time>

Property definition

- **property** speedUnit: Speed
- speedUnit => <m/s>
- **property** force: ForceT
- speed => 2.5 <kg \* m / s<sup>2</sup>>

*Should unit expressions be part of AADL3?*

# Data Subcomponents 1

How to model shared data without data components

- `sharedData: data MyRecord`

Types alone are not sufficient because they don't have access features!

Option 1: Interface extends type

- `interface I extends MyRecord is`

`...`

`end`

- `sharedData: interface I`

# Data Subcomponents 2

Option 2: Generic component + data type as property

- **component C is**  
    ...  
  **end**
- **component implementation C.i is**  
    data\_type => MyRecord  
  **end**
- sharedData: **component C.i**

Issues

- No enforcement of consistent extension between implementation and data\_type property
- “Magic property”

Option 3: Interface + data type as property

- **interface I is**  
    ...  
  **end**
- sharedData: **interface I {data\_type => MyRecord}**

Issues

- Same extension consistency issue if property is included in interface

```
interface I is
  data_type => MyRecord
end
```

# Type System Usage

## Properties

- Property definitions reference types  
**property** temp: TemperatureT

## Port types

- Associate a data type directly with a port  
p: **in port** TemperatureT

## Data representation

- Data modeling annex
- Base\_Type property references a data classifier
- If we still need that, the type of Base\_Type must be “type” or “data”

# Representation of Transferred Data

## Example

- **type** BodyTemp **is** integer <TemperatureUnits>  
p1: **out port** BodyTemperature;

Is unit included in transferred data or is a unit assumed?

- p1: **out port** integer {unit => <degC>}

Non-zero reference point for transferred value

Transfer representation may be different from in memory representation

## Alternatives:

- Protocol specification
  - As virtual bus
  - Mapping into bit representation (see 429 protocol example in SAVI demo)

# Representation of Types

## Example

- BodyTemperature: **type** integer [30..50 C] **units** TemperatureUnits;
- P1: **out port** BodyTemperature;

## Digital representation

- Base\_Type property in Data\_Model
- Associated with type or with port

## Physical representation

- Dynamic behavior
- Specified as part of type or specific to each use site
  - Associated with feature