AADL Configuration Specification

Peter Feiler

Software Engineering Institute Carnegie Mellon University Pittsburgh, PA 15213



Copyright 2019 Carnegie Mellon University. All Rights Reserved.

This material is based upon work funded and supported by the Department of Defense under Contract No. FA8702-15-D-0002 with Carnegie Mellon University for the operation of the Software Engineering Institute, a federally funded research and development center.

The view, opinions, and/or findings contained in this material are those of the author(s) and should not be construed as an official Government position, policy, or decision, unless designated by other documentation.

NO WARRANTY. THIS CARNEGIE MELLON UNIVERSITY AND SOFTWARE ENGINEERING INSTITUTE MATERIAL IS FURNISHED ON AN "AS-IS" BASIS. CARNEGIE MELLON UNIVERSITY MAKES NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, AS TO ANY MATTER INCLUDING, BUT NOT LIMITED TO, WARRANTY OF FITNESS FOR PURPOSE OR MERCHANTABILITY, EXCLUSIVITY, OR RESULTS OBTAINED FROM USE OF THE MATERIAL. CARNEGIE MELLON UNIVERSITY DOES NOT MAKE ANY WARRANTY OF ANY KIND WITH RESPECT TO FREEDOM FROM PATENT, TRADEMARK, OR COPYRIGHT INFRINGEMENT.

[DISTRIBUTION STATEMENT A] This material has been approved for public release and unlimited distribution. Please see Copyright notice for non-US Government use and distribution.

This material may be reproduced in its entirety, without modification, and freely distributed in written or electronic form without requesting formal permission. Permission is required for any other use. Requests for permission should be directed to the Software Engineering Institute at permission@sei.cmu.edu.

Carnegie Mellon® is registered in the U.S. Patent and Trademark Office by Carnegie Mellon University.

Carnegie Mellon University

DM19-0625

Architecture Design & Configuration

Architecture design via extends, refines to evolve design space (V2)

- Revise and add to existing architecture design structure
- Add/revise annotation of property values, bindings, annexes

Configuration specification

- Elaborate but do not change architecture structure only expand leaf nodes
- Configuration assignments assign classifiers
 - To subcomponents and features
 - Assignments of classifiers are additive
 - Via configurations associate collections of property values, bindings, annexes to given architecture substructure

Composition of configuration specifications

Parameterized configuration specification

Subcomponent configuration assignment via parameter only



Evolution of System Design

Component Interface Extension

- Addition of features, flows, etc.
- Assignment of types/classifiers to existing features
 - Assign missing type
 - Override with any type
- Assignment of property values

Component Implementation Extension

- Addition of subcomponents, connections, etc.
- Refinement of existing subcomponents
 - Refine to implementation or configuration

Myport => MyDataType; Same as configuration assignment syntax

Configuration of a System Design

Configuration Specification elaborates and annotates component hierarchy

- Associated with an implementation/interface via extends
- Configuration assignment assigns
 - implementation or configuration to subcomponent
 - Data type or classifier to feature
- Assign property values within existing component hierarchy
- Specify bindings
- Add flow specification
- Add annex subclauses

Design Refinement

Configuration assignment in implementation extensions

- Effectively a refined to but with reach down
 - Assign implementation/configuration for specified interface
 - Override existing implementation with extension
 - Assign interface extensions and their implementations
 - Only for direct subcomponent as it may need to add connections

```
System Top.refined extends top.basic
is
Sub1 \Rightarrow x.i;
Sub2 \Rightarrow v.i;
end;
```

```
System top.basic is
Sub1: system x;
Sub2: system y;
End;
```

Configuration of a System Design

Configuration assignment in configuration

- Elaborate and annotate subcomponent substructure
 - Annotate substructure with property values, bindings, annex subclauses
 - Assign component implementation for subcomponent
 - Assigned classifier interface must not be an interface extension
 - Explicit implementation: it becomes the intended implementation that cannot be overwritten
 - If subcomponent was declared with implementation assignment cannot be of an implementation extension

```
configuration Top.config_L1 extends top.basic
is
Sub1 => x.i;
Sub2 => y.i;
end;
```

```
System top.basic is
Sub1: system x;
Sub2: system y;
End;
```

Explicit implementation: at least one configuration assignment must have an explicit implementation of the subcomponent only has a type. Otherwise additional configuration assignments can expand design with implementation extensions.

Configuration of a System Design

- Assign configurations for subcomponent with implementation
 - Configurations for ancestor implementation or interface are ok

```
configuration Top.config L1 extends top.L1impl
is
                                                       System top.L1impl is
Sub1 \Rightarrow x.i2;
                                                        Sub1: system x.i;
Sub2 => y.performance;
                                                        Sub2: system y;
end;
                                                       System x.i is
                                                        xsub1: process subsubsys;
                                                        xsub2: process subsubsys;
                                                       System x.i2 extends x.i is
                                                        xsub3: process subsubsys;
                                                       System y.i is
                                                        ysub1: process subsubsys;
                                                        ysub2: process subsubsys;
                                               configuration y.performance extends y.i is
                                                xsub1#Period => 20 ms;
```

Configuration Across Multiple Levels

- Reach down configuration assignments
 - Left hand side resolved relative to classifier being extended

```
configuration Top.config_Sub11 extends top.Llimpl
is
    Sub1.xsub1 => subsubsys.i;
    Sub1.xsub2 => subsubsys.i;
end;

System top.Llimpl is
    Sub1: system x.i;
Sub2: system y.i;

System x.i is
    xsub1: process subsubsys;
    xsub2: process subsubsys;
```

No ordering assumption in configuration assignments, i.e., second assignment cannot reach into the implementation assigned by the first. Handed by nested assignments (next slide)

Nested Configuration Assignment

- Nested configuration specification
 - Used to configure an assigned classifier
- System x.12 extends x.i is xsub1 => subsubsys.i; xsub2 => subsubsys.i;

- Left hand side resolved relative to enclosing extended or assigned classifier

```
configuration Top.config Sub1 extends top.basic
is
  Sub1 \Rightarrow x.i {
    xsub1 => subsubsys.i;
    xsub2 => subsubsys.i;
end;
Sub1 \Rightarrow x.12
```

```
System top.basic is
 Sub1: system x;
Sub2: system y;
```

```
System x.i is
xsub1: process subsubsys;
xsub2: process subsubsys;
```

Nested configuration for existing subcomponent classifier

```
configuration Top.config Sub11 extends top.Llimpl
Is
Sub2 => {
    ysub1 => subsubsys.i;
    ysub2 => subsubsys.i;
                              Shorter target paths
    @EM {* ... *};
    #Period => 20 ms
  };
end;
```

Annex assignment without explicit configuration specification

Property assignment without target path

Assignment of Configuration Specifications

Specification and use of separate subsystem configurations

Configuration of subsystems

```
Configuration x.config L1 extends x.i is
  xsub1 => subsubsys.i;
  xsub2 => subsubsys.i;
end;
Configuration y.config L1 extends y.i is
  ysub1 => subsubsys.i;
  ysub2 => subsubsys2.i;
end;
```

Use of configuration as assignment value

```
Configuration Top.config L2 extends top.basic is
  Sub1 => x.config L1;
                                Implementation associated with configuration is assigned to the
                                target subcomponent if the original assignment is an interface
  Sub2 => y.config L1;
end;
Configuration Top.config L1L2 extends top.L1impl is
  Sub1 => x.config L1;
                                Implementation associated with configuration must be the
                                same or an ancestor of the original implementation
  Sub2 => y.config L1;
end;
```

Configuration of Property Values

Specifying a set of property values

- Property value assignment to any component in the
 - subcomponent path resolvable via the classifier referenced by extends
 - Should property value assigned in configuration always be final or should users specify final assignment explicitly and we have a design rule?

```
Configuration Top.config Security extends Top.config L2
is
  #myps::Security Level = L1,
                                                              => is changeable
  Sub1#myps::Security Level = L2,
                                                              = is final
  Sub1.xsub1#myps::Security Level = L0,
  Sub2#myps::Security Level = L1
end;
Configuration Top.config Safety extends Top.config L1
is
  #myps::Safety Level = Critical,
  Sub1#myps::Safety Level = NonCritical,
  Sub2#myps::Safety Level = Critical
end;
Configuration x.config Performance extends x.i
is
  xsub1 => subsubsys.i {
                                            A configuration specification may only annotate property
   #Period = 10ms,
                                            values or it may also configure and annotate other items.
   #Deadline = 10ms }
```

end;

Composition of Configurations

Combine multiple configurations into new configuration specification

- Define configuration with multiple extends
- Multiple configuration assignments to same subcomponent

Rules

- Associated interfaces must be the same
- Associated implementations must have a single extends lineage
 - The implementation associated with the composite: most descendant
- Only one assigned property value is allowed for any assignment target
 - Two property associations with the same value ok?
 - Local assignment may override or should conflict be error?

```
Configuration Top.config L2 extends top.config L1, Top.config Sub1, Top.config Sub2 end;
Configuration Top.config L22 extends Top.config Sub1, Top.config Sub2 end;
Configuration Top.config SafeSecure extends Top.config L2, Top.config Safety,
  Top.config Security end;
Configuration Top.config SafetySecurity extends Top.config Security, Top.config Safety end;
```

Multiple Refinements

Multiple assignments as part of a subcomponent configuration

```
Configuration Top.config L2 extends top.basic is
  Sub1 => x.config L1;
                                                            Multiple assignments to same target within same
  Sub1 => x.security;
                                                            configuration or by separate configurations.
  -- shorthand: Sub1 => x.config L1, x.security;
  Sub2 => y.config L1;
end;
```

- Different assigned configurations may contain configuration assignment to same target component
- Associated interfaces must be the same
- Associated implementations must be same or ancestors of explicitly assigned implementation
 - Explicitly assigned in subcomponent declaration
 - Explicitly assigned by one of the configuration assignments
 - If derived from configuration users can add an implementation extension through a ocnfiguration
- Only one property value assignment is allowed for any assignment target
 - Property value assignments in configuration specifications are "final"

Multiple Configuration Assignments

Multiple assignments as part of a configuration

```
Configuration Top.config_L2 extends top.basic is
  Sub1 => x.config_L1;
  Sub1 => x.security;
  -- shorthand: Sub1 => x.config_L1, x.security;
  Sub2 => y.config_L1;
end;
```

- Different assigned configurations may contain configuration assignment to same target component and may do so at different levels of the hierarchy
- Associated interfaces must be the same
- Associated implementations must be same or ancestors of explicitly assigned implementation
 - Explicitly assigned in subcomponent declaration
 - Explicitly assigned by one of the configuration assignments
 - If implementation is derived from collection of configurations (deepest in extends lineage)
 users can add an implementation extension through a configuration
- Only one property value assignment is allowed for any assignment target
 - Property value assignments in configuration specifications are "final"
 - Alternative: Rules about override order as we have for implementations and implementation extensions

Composition of Flow Configurations

Adding in end to end flows

- End to end flows may be declared in a separate classifier extension
- No conflicting end to end flow declarations

```
System Top.flows extends top.basic
is
    Sensor_to_Actuator: end to end flow sensor1.reading -> ... -> actuator1.cmd;
End;

Configuration Top.config_full extends Top.config_L2, Top.flows end;
```

- Flow specs for end-to-end flow targets may be declared in separate configurations
- Flow implementations for intermediate flow targets may be declared in a separate configurations

```
configuration X.flowspec extends X
is
  outsource: flow source outp;
End;
configuration X.flowsequence extends x.i
is
  outsource => flow subsub1.flowsrc -> ... -> outp;
End;
```

Configuration/composition of Annex Subclauses

Adding in annex specifications

- Annex subclauses may be declared in a separate classifier extensions
- Different annex specifications may be added

```
System Top_emv2 extends top is

Annex EMV2 {**

use types ErrorLibrary;

End Top_emv2;

Use @ consisten

Vse {} instead of Alternative option
```

```
Configuration Top_emv2 extends top
@e { use types ErrorLibrary; };
End Top_emv2;
Use @ consistent with reference path usage
```

Use {} instead of {** **} with {} usage restriction within annex Alternative option: use another symbol pair e.g. <>

```
Configuration Top.config_full extends Top.config_L2, Top.flows, Top_emv2 end;
```

Inherited annex subclauses based on classifier extends

- Automatically included
- Extends override rules of annex apply

Separate extensions

No conflicting declarations

Parameterized Configuration

Explicit specification of all choice points

- Configuration of subcomponents via configuration parameters only
 - Assignment of formal parameter to one or more subcomponents
- No direct configuration assignment to subcomponents by user
- Substitute the type of the parameter specification

```
Configuration x.configurable dual (replicate: system subsubsys) extends x.i is
  xsub1 => replicate;
                                      Configuration parameter classifier must the same or an
  xsub2 => replicate;
                                      ancestor of the assignment target
end;
```

Usage

Similar to V2 prototype but we map parameter to targets instead of requiring all targets to reference prototype

Supply parameter values

```
Configuration Top.config sub1 sub2 extends top.i
is
  Sub1 => x.configurable dual( replicate => subsubsys.i );
end;
Configuration x.configured extends x.configurable dual ( replicate => subsubsys.i )
end:
```

Configuration parameter actual must match

- an implementation/configuration of the specified interface
- a configuration of the specified implementation or its ancestor or interface

18

Explicit Specification of Candidates

Explicit list of candidates

```
Configuration x.configurable dual (securityProperties: system {
subsubsys.sec1, subsubsys.sec2 } ) extends x.i is
  xsub1 => securityProperties;
  xsub2 => securityProperties;
end;
```

Property Values as Parameters

Explicit specification of all values that can be supplied to properties

- Values that can be used for different properties of the same type
- Values for specific properties

```
Configuration x.configurable dual (TaskPeriod : time ,
    TaskDeadline: #Deadline) extends x.i is
  xsub3.T1#Period = TaskPeriod;
                                          Xsub2.T1 must exist in x.i
  xsub3.T1#Deadline = TaskDeadline;
end;
```

Specify value time vs. property to be assigned

Usage: Supply parameter values

```
Configuration Top.config sub1 sub2 extends top.i is
  Sub1 => x.configurable dual(
    TaskPeriod = 20ms, TaskDeadline = 30 ms );
end;
```

Via configuration specification as parameter

- Collections of property value assignments
 - Consistent set of property values
- Explicitly specified collections to choose from

```
Configuration x.configurable dual1(securityProperties: system subsubsys.i ) extends x.i is
  xsub1 => securityProperties;
  xsub2 => securityProperties;
end;
Configuration x.configurable dual2(securityProperties: system { subsubsys.sec1, subsubsys.sec2 } )
extends x.i is
  xsub1 => securityProperties;
  xsub2 => securityProperties;
end;
```

Complete Configuration

 Finalizing choice points of an existing implementation or configuration

Configuration Top.config L0() extends top.basic end;

Annotating Parameterized Configurations

- Users should be able to add "missing annotations"
 - Additional flows, error model specification, property values
 - User can declare extensions of parameterized configuration that contain the annotations
 - Configuration assignments can reach into component with parameterized configuration but can only add missing property values, flows, EM
 - User can compose multiple such annotations into the configuration
 - As new configuration or as part of each usage

```
Configuration Top.LO Security extends Top.config LO
is <security properties> end;
Configuration Top.LO Safety extends Top.config LO
is <EMV2 subclause for Top> end;
```

Configuration Assignment Patterns

Assignment of configuration to classifiers (all instances of classifiers)

Match&replace classifier/data type within a scope

Match classifier in subcomponents and features, data types in features

```
Configuration FlightSystem.secure extends FlightSystem.TripleGPS is
                                                    Assign GPS.secure for all subcomponents with interface
 all(GPS) => GPS.secure;
                                                    GPS within scope of FlightSystem.TripleGPS
 all(Dlib::dt) => Secure.securesample;
                                               Assign type Secure.securesample for all features with
  \#Period *=> 20 ms;
                                               type dt within scope of FlightSystem.TripleGPS
```

Period for all elements within scope of associated implementation that require a Period

```
Package FS
Import mine::*;
System FlightSystem.TripleGPS
is
 gps1: device GPS;
 gps2: device GPS;
 gps3: device GPS;
End:
End;
```

```
Package mine
Device interface GPS
is
 inpl: in data port Dlib::dt;
  outp1: out data port Dlib::dt;
End;
Device GPS. secure is
```

23

end;

Reusable Configuration Patterns

Match&replace within the scope the configuration pattern is assigned to

- Match classifier or primitive type in subcomponents and features
- Configuration without extends can be

```
Configuration GenericPattern is
  all(Mine::Sensor) => Sensor.Settings;
  all(Dlib::dt) => Secure.securesample;
  all(Mine::GPS) => GPS.secure { #Period => 50 ms};
  all(Your::GPS) => { #Period => 50 ms};
end;
Configuration Sensor.Settings extends Sensor.impl is
  #Period => 50 ms;
  reading#Data_Size => 20 Bytes;
end;
```

Assign configuration pattern to subsystems

```
Configuration AvionicsSystem.Dual is
  FlightSystem1 => FlightSystem.primary, FlightSystem.secure;
  FlightSystem2 => FlightSystem.primary, GenericPattern;
  BackupFlightSystem => FlightSystem.backup, SimpleGPS.config;
```

Assignment of Configurations to All Instances

Configurations as annotations for all subcomponents of a given classifier

- Example: EMV2 configuration for a classifier
- Assign annotations individually

```
Configuration AvionicsSystem. Dual is
  FlightSystem2 => FlightSystem.primary;
  all(Mine::Sensor) => Sensor.emv2;
  all(Mine::GPS) => { @e { ... };};
```

Sensor @e { use types ErrorLibrary; }; End Top emv2;

Configuration Sensor.emv2 extends

Specify collection of EM annotations

Simplified syntax does not require @e{} inside {}

```
Configuration FlightSystemEMV2 is
  all(Mine::Sensor) => Sensor.emv2;
  all(Mine::GPS) => @e { ... };
end;
```

Assign configuration pattern to subsystems

```
Configuration AvionicsSystem. Dual is
  FlightSystem2 => FlightSystem.primary, FlightSystemEMV2;
```