

AADL 3 Type System and Expression Language

Lutz Wrage

Software Engineering Institute
Carnegie Mellon University
Pittsburgh, PA 15213

Copyright 2019 Carnegie Mellon University. All Rights Reserved.

This material is based upon work funded and supported by the Department of Defense under Contract No. FA8702-15-D-0002 with Carnegie Mellon University for the operation of the Software Engineering Institute, a federally funded research and development center.

The view, opinions, and/or findings contained in this material are those of the author(s) and should not be construed as an official Government position, policy, or decision, unless designated by other documentation.

NO WARRANTY. THIS CARNEGIE MELLON UNIVERSITY AND SOFTWARE ENGINEERING INSTITUTE MATERIAL IS FURNISHED ON AN "AS-IS" BASIS. CARNEGIE MELLON UNIVERSITY MAKES NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, AS TO ANY MATTER INCLUDING, BUT NOT LIMITED TO, WARRANTY OF FITNESS FOR PURPOSE OR MERCHANTABILITY, EXCLUSIVITY, OR RESULTS OBTAINED FROM USE OF THE MATERIAL. CARNEGIE MELLON UNIVERSITY DOES NOT MAKE ANY WARRANTY OF ANY KIND WITH RESPECT TO FREEDOM FROM PATENT, TRADEMARK, OR COPYRIGHT INFRINGEMENT.

[DISTRIBUTION STATEMENT A] This material has been approved for public release and unlimited distribution. Please see Copyright notice for non-US Government use and distribution.

This material may be reproduced in its entirety, without modification, and freely distributed in written or electronic form without requesting formal permission. Permission is required for any other use. Requests for permission should be directed to the Software Engineering Institute at permission@sei.cmu.edu.

Carnegie Mellon® is registered in the U.S. Patent and Trademark Office by Carnegie Mellon University.

DM19-0611

Type System Unification

Unification of type systems and expression languages (Peter, Lutz*, Alexey, Brian, Serban)

- Data Components
- Property Types
- Classifiers
- Annexes
 - Resolute, AGREE
 - Data Modeling
 - EMV2
 - BA, BLESS
- ReqSpec
- Scripting languages (Python)

Current Composite Types

AADL 2.2

Property types

- Range of
- List of
- Record

Data implementations

No operations available except

- List append ($+=>$)
- Boolean operations

Property expressions provide syntax for literals only

ReqSpec adds expressions, uses basic type inference

Current Usages of Types

Application data that occurs in the modeled system

- Data subcomponents
 - Shared data
 - Local variables in threads and subprograms
- Data communicated via data and event data ports

Information about the modeled system and individual components

- Properties

Mixture of models and properties

- Component classifiers and model elements as property values
 - Bindings
 - Specify constraints, e.g., `Required_Virtual_Bus_Class`

Additions in annexes

- Resolute: sets
- EMV2: error types and type sets, error types can have properties
- BLESS

Type System and Expression Language Goals

Provide types for

- Properties
- Features, e.g., data ports
- Data components
- Error types(?)

Support

- Specification of dependencies / constraints between properties
- Selecting model elements in configurations: Queries
- Structural analysis of instance models
 - Similar to Resolute
- Requirement specification
 - Similar to ReqSpec

Do we need structural analysis / constraints for declarative models?

Type System Unification Approach

Base types

- Integer, Real, Boolean, String
- Enumeration, Unit
- Category (thread, processor, etc.), Classifier, Model Element
- Range of Numeric (Compute_Execution_Time => 10ms .. 15ms)

Composite types

- List (ordered sequence of arbitrary length): `list of int`
- Set (unique elements): `set of classifier`
- Record (named fields) / Union (named alternatives)
- Tuples (unnamed fields)
 - Convenient for multiple return values from a function
- Map: `map mode -> Time`
 - Modal and binding specific property values in AADL 2.2 are (almost) maps
 - Error type specific property values
- Arrays: `array of int(10)`
- Bag (?)
- ~~Graph~~

Type System Unification Approach

Properties on types

Useful for code generation and analyses that looks at data size (in memory or on a bus)

- Information about representation
`int {data_size => 16bit}`
- Range of valid values
`int {range => 10 .. 20}`
- Size of a fixed size list (if we don't have arrays)
`list of int {size => 3}`

Properties are ignored for type checking purposes

User Defined Types

Users can create named types

- `type byte: int { range => 0 .. 255 }`
- `type otherByte: byte { data_size => 8bit }`
- `type sensed: record (value: int, timestamp: int)`
- `type sensed2: record (value: int, timestamp: int)`

Is a type name just a shorthand, or is it a new type?

- Structural equality is easily implemented, but we may want the same type **name** on connected ports
- Fully “opaque” types would complicate the expression language, i.e., how would we know that we can add 2 bytes?

Numeric Ranges

Subsets of numeric types (or enumerations?)

- Range constrained Numeric
e.g., `int [100 .. 120]`
- Could be considered special syntax for a property on a type
e.g., `int {range => 100 .. 200}`

Subset constraints are difficult to maintain for expressions

- Simple assignments are easy to check
- If `x` is an integer `[100 .. 120]`
- `2 * x` results in integer `[200 .. 240]`
- `sqrt(integer[100 .. 120])` results in (not quite) real `[10.0 .. 10.95]`

Type checking should ignore range constraints, maybe except for simple assignments

Expression Language: Literals

Numbers, strings, boolean true/false as in AADL 2

- Automatic conversion from integer literal to real value

Range literals

- AADL2: `2 .. 3` or interval notation `[2, 3]`

Enumeration and unit literals

- Qualified name: `<package>.<enum type>.<enum literal>`
e.g., `myenums.signaltype.RED`
- Need to import enumeration and unit literals in order to use their simple names

Collections

- To mirror declaration syntax
- **list** `(1,2,3)` is a **list of int**
- **record** `(intfield = 1, boolfield = true)` is a **record** `(intfield: int, boolfield: bool)`

Expression Language: Operations 1

Boolean

- and, or, not, ...

Numeric values

- +, -, *, /, div, mod

Ranges

- Union, intersection, contains

Enumerations

- Consider them ordered, comparison operations

Units

- Get conversion factor, conversions

Strings, List

- append, substring, ...

Records

- Access a field value

Union

- Access field depending on variant tag



Expression Language: Operations 2

Set

- union, intersection, contains

Generic collection operations

- forall, exists, filter, fold
- Look for inspiration in existing collection library and copy

Classifiers

- Extends, get extended, get all extending, ...
- → methods defined in the AADL meta-model

Named elements

- Get name, get classifier, get all subcomponents, ...
- → methods defined in the AADL meta-model

Variables

Need to be able to name results of expressions

- **val** $x = 2 * 5$

Variables or unmodifiable values?

- For constraints and structural analysis unmodifiable named values should be sufficient
- Variables require additional language constructs (loops) that can be avoided if only named values are allowed

Add vals in block expressions

- {
 val $x = 2$;
 $x + 1$
}

Function Definitions

Reusable expressions => Functions

Proposed syntax

- **def** double(x: int): int = 2 * x
- **def** triple(x: int): int = {
 val d = double(x);
 x * d
}
- **def** factorial(x: int): int = {
 def f(x: int, a: int): int =
 if x <= 1 **then** 1 **else** f(x-1, x * a);
 f(x, 1)
}

Prototype Implementation

Expression Annex for AADL2

Implemented

- Most types
- Some type checking
- Subset of expressions
- Initial expression evaluation

- No units yet



Type Extension

Type extension

- Exists for classifiers to add subcomponents, properties, ...
- Records
 - Add fields
- Unions:
 - Add fields to one or more variants(?)
 - Add variants
- Add properties to any type
 - byte is a subtype of integer
 - Not problematic as properties are ignored for type checking
- Assignment compatibility and type inference
 - list of byte is subtype of list of integer
 - Should be possible to define in a sound manner

Should there be configurations for types?

Measurement Units

Represent a (physical) quantity as a number with a dimension

- Length, Time, Mass, Force

Dimension has associated measurement units

- Length – **meter** (SI base unit)
- Time – **second** (SI base unit)
- Mass – **kilogram** (SI base unit)
- Force – **Newton** (Derived: $1\ N = 1\ \frac{kg \cdot m}{s^2}$)

Different unit systems

- SI vs. Imperial
- Non-physical quantities, e.g., bit, byte
- Other: minute, day, year; rpm, angle, ...

Users must be able to define new units

Unit Definition 1

Defining dimensions and corresponding measurement units

- Dimension as variation of enumeration types
 - **type** LengthU: **unit** (cm, m = 100 * cm, ...)
 - **type** TimeU: **unit** (s, ms = s / 1000, ...)
 - **type** USLengthU: **unit** (in, ft = 12 * in, ...)
- Similar to AADL2
- Similar to compound type declarations (records, lists, etc.)

Literals with units

- 100 ms
- 12 [ms]

Type declarations with units

- **type** LengthType: **real** [LengthU]
- **type** LengthType: **real** **unit** LengthU

Unit Definition 2

Property definition

- Value is a physical quantity
 - **property** distance: real **unit** USLengthU
 - **property** distance: real [USLengthU]

 - distance => 2.5 [in]

- Value is a unit, e.g., to document the unit of the data on a data port
 - **property** dataUnit: LengthU

 - dataUnit => [m]

Standard Metric Prefixes

Metric prefixes

- Base 10: **centi**, **milli**, micro μ , **deka**, **kilo**, **Mega**
- Binary: **Ki** (2^{10}), **Mi** (2^{20}), **Gi** (2^{30})
- These are case sensitive, one is a greek letter
- Not distinct from units: **meter** vs. **milli**

Convenient to use them with any unit without repeatedly defining the conversion factor.

Use syntax to separate metric prefix and unit name

- 1 [k'g], 12 [m's], 640 [Ki'byte]

Only with base units

- If ms is defined as derived ($ms = s/1000$) the 1 [k'ms] should not be valid

Unit Expressions 1

Avoid units names such as KBytesps (as we have in AADL 2)

Allow expressions for derived units

- $[k'g * m / s^2]$

Unit expressions are written in []

- `speed == 12 [m/s]`

Simple unit may be written with or without []

- `latency == 10 m's` or `latency == 10[m's]`

Allow only multiplication, division, and exponentiation

Defining a derived unit type

- **type** ForceU = **unit** (N = $[k'g * m / s^2]$)

Unit Expressions - 2

Convert between numbers and quantities

- `val x = 1` `x` is an integer
- `val y = (x + 1)[s]` `y` is an integer with a unit: 2s
- `val z = y in [ms]` `z` is an integer: 1000

Calculation with units

- `10 N / 2.5 k'g == 4.0 [m / s^2]`

Unit Definitions and Usage

Derived units with unit expressions

- **type** MassU: **unit** (g)
- **type** SpeedU: **unit** (LengthU / TimeU)
- **type** ForceU: **unit** ($N = k'g * m / s^2, \dots$)

Type declarations with units

- **type** SpeedT: **real** [SpeedU]
- **type** ForceT: **real** [ForceU]
- **type** OtherSpeedT: **real** [LengthU / TimeU]

Property definition

- **property** speedUnit: Speed
- speedUnit => [m/s]
- **property** force: ForceT
- speed => 2.5 [$k'g * m / s^2$]

Expressions and Classifiers

Add **vals** and **defs** to classifiers

Specify expressions that should be evaluated

```
system S.i
  -- subcomponents, etc
  prop => 1;
  val v = 1;
  def f(x: int): int = x;
  -- assertions or invariants
  assert test: #prop == f(v);
end S.i;
```

Definitions and assertions are inherited or can be configured in

For structural verification

- Add descriptive text to assertions (similar to Resolute claim functions)
- Analysis evaluates assertions (all, or just for a single component) on an instance model

Next Steps

Complete expression annex implementation

Work out details of type extension

Add types and expressions to AADL 3 prototype implementation

Draft document