

The slide features abstract geometric decorations. In the top-left corner, there are several overlapping triangles in shades of blue, green, and red. In the bottom-right corner, there are overlapping triangles in shades of light gray.

Naïve Bayes




Melika Zare

Naïve Bayes

- In statistics, naive Bayes classifiers are a family of simple "probabilistic classifiers" based on applying Bayes' theorem with strong (naïve) independence assumptions between the features.
- They are among the simplest Bayesian network models, but coupled with kernel density estimation, they can achieve higher accuracy levels.

Naive Bayes....



Example

\vec{X} = email

$\vec{X} = \{x_1, x_2, \dots, x_n\}$ = all words in emails
($w_1, w_2, \dots, w_{1000}$)

$$P(c_k | \vec{x}) = ?$$

$$P(c_k | \vec{x}) = \frac{P(c_k)P(\vec{x}|c_k)}{P(\vec{x})}$$

Bayesian Rule

Chain Rule

$$\begin{aligned} P(C_k, x_1, \dots, x_n) &= P(x_1, \dots, x_n, C_k) \\ &= P(x_1 | x_2, \dots, x_n, C_k) P(x_2, \dots, x_n, C_k) \\ &= P(x_1 | x_2, \dots, x_n, C_k) P(x_2 | x_3, \dots, x_n, C_k) P(x_3, \dots, x_n, C_k) \\ &= \dots \\ &= P(x_1 | x_2, \dots, x_n, C_k) P(x_2 | x_3, \dots, x_n, C_k) \dots P(x_{n-1} | C_k) P(x_n | C_k) P(C_k) \end{aligned}$$

Naïve Conditional Independence

$$P(x_i | x_{i+1}, \dots, x_n, C_k) = P(x_i | C_k)$$

$$P(x_1 | x_2, \dots, x_n, C_k) P(x_2 | x_3, \dots, x_n, C_k) \dots P(x_{n-1} | C_k) P(x_n | C_k)$$

Conditional Probability

$$P(\vec{x} | c_k) = P(x_1 | C_k) P(x_2 | C_k) \dots P(x_n | C_k) = \prod_{i=1}^n P(x_i | C_k)$$

$$P(c_k | \vec{x}) = \frac{P(c_k) P(\vec{x} | c_k)}{P(\vec{x})} = \frac{P(C_k) \prod_{i=1}^n P(x_i | C_k)}{P(\vec{x})}$$

Binary Classifier

$$P(\mathbf{S} | \vec{\mathbf{x}}) = \frac{P(\mathbf{S}) \prod_{i=1}^n P(x_i | \mathbf{S})}{P(\vec{\mathbf{x}})}$$



$$P(\mathbf{N} | \vec{\mathbf{x}}) = \frac{P(\mathbf{N}) \prod_{i=1}^n P(x_i | \mathbf{N})}{P(\vec{\mathbf{x}})}$$

$$P(\mathbf{S} | \vec{\mathbf{x}}) \cong P(\mathbf{S}) \prod_{i=1}^n P(x_i | \mathbf{S})$$

$$P(\mathbf{N} | \vec{\mathbf{x}}) \cong P(\mathbf{N}) \prod_{i=1}^n P(x_i | \mathbf{N})$$

Multi-class classifier

$$\hat{y} = \arg \max P(c_k) \prod_{i=1} P(x_i | c_k)$$

Example

Num	Words in Email	Type
1	Click on this link	Spam
2	Share your review	Not spam
3	Share your account number	Spam
4	Send us your review	Not spam
5	Send us your password	Spam

- 1) Remove Stopwords & commonly used words.
- 2) Create dictionary

Train Phase

Word	P(word spam)	P(word Not spam)
Click	1	0
Link	1	0
Share	$\frac{1}{2}$	$\frac{1}{2}$
Review	0	1
Account	1	0
Number	1	0
Send	$\frac{1}{2}$	$\frac{1}{2}$
Password	1	0

Words in Email	Type
Click on this link	Spam
Share your review	Not spam
Share your account number	Spam
Send us your review	Not spam
Send us your password	Spam

$$P(\text{send} \mid \text{spam}) = \frac{1}{2}$$

$$P(\text{send} \mid \text{Not spam}) = \frac{1}{2}$$

$$P(\vec{X} = \text{spam}) = \frac{3}{5}$$

$$P(\vec{X} = \text{Not spam}) = \frac{2}{5}$$

Test Phase

Word	P(word spam)	P(word Not spam)
Click	1	0
Link	1	0
Share	$\frac{1}{2}$	$\frac{1}{2}$
Review	0	1
Account	1	0
Number	1	0
Send	$\frac{1}{2}$	$\frac{1}{2}$
Password	1	0

$\vec{X}_{new} = \{\text{send your review to me}\}$

$\vec{X}_{new} = \{\text{send, review}\}$

$$\hat{y} = \arg \max P(c_k) \prod_{i=1} P(x_i | c_k)$$

$$\begin{cases} \text{spam: } \frac{3}{5} * \frac{1}{2} * 0 = 0 \\ \text{Not spam: } \frac{2}{5} * \frac{1}{2} * 1 = 0.2 \end{cases}$$



argmax

$\hat{y} = \text{Not Spam}$



Total emails: 72

Prob. Ham
= 72/100
= 0.72



Total emails : 28

Prob. Spam
= 28/100
= 0.28

HAM Total Words 717

Word	Count	Prob of Word if mail is <i>Ham</i>
Friend	86	0.238227
Rich	41	0.113573
Money	79	0.218837
Beach	80	0.221607
Office	75	0.207756

SPAM Total Words 741

Word	Count	Prob of Word if mail is <i>Spam</i>
Friend	63	0.184751
Rich	36	0.105572
Money	97	0.284457
Beach	53	0.155425
Office	92	0.269795

$\vec{X}_{new} = \{\text{you have rich friend}\} = \{\text{rich, friend}\}$

$$\begin{cases} \text{spam: } 0.28 * 0.105572 * 0.18475 = 0.0054612 \\ \text{Not spam: } 0.72 * 0.11357 * 0.23822 = 0.0194804 \end{cases}$$

- log()

$$\begin{cases} \text{spam: } 0.54 + (3.144 + 2.1363) = 5.8303 \\ \text{Not spam: } 0.14 + (3.238 + 2.996) = 6.3476 \end{cases}$$



Total emails: 72

Prob. Ham
= 72/100
= 0.72



Total emails : 28

Prob. Spam
= 28/100
= 0.28

HAM Total Words 717

Word	Count	Prob of Word if mail is Ham
Friend	86	0.238227
Rich	41	0.113573
Money	79	0.218837
Beach	80	0.221607
Office	75	0.207756

SPAM Total Words 741

Word	Count	Prob of Word if mail is Spam
Friend	63	0.184751
Rich	36	0.105572
Money	97	0.284457
Beach	53	0.155425
Office	92	0.269795

- log()

$$\left\{ \begin{array}{l} \text{spam: } 0.54 + (3.144 + 2.1363) = 5.8303 \\ \text{Not spam: } 0.14 + (3.238 + 2.996) = 6.3476 \end{array} \right.$$

$$P(\text{class}) * P(x_1|\text{class}) * \dots * P(x_n|\text{class}) \rightarrow$$

$$\log(P(\text{class})) + \log(P(x_1|\text{class})) + \dots + \log(P(x_n|\text{class}))$$

$\vec{X}_{new} = \{\text{send your review to me}\}$

$\vec{X}_{new} = \{\text{send, review}\}$

$$\hat{y} = \arg \max P(c_k) \prod_{i=1} P(x_i | c_k)$$

$$\begin{cases} \text{spam: } \frac{3}{5} * \frac{1}{2} * 0 = 0 \\ \text{Not spam: } \frac{2}{5} * \frac{1}{2} * 1 = 0.2 \end{cases} \xrightarrow{-\log()} \begin{cases} \text{spam: } 0.73 + (1 + \text{Undefiend}) \\ \text{Not spam: } 1.32 + (1 + 0) \end{cases}$$

Laplace Smoothing



Thank you

Train:

$$P(F_{i,j} = f | class = c) = \frac{\# \text{ of times } F_{i,j} = f \text{ when } class = c}{\text{Total number of training examples where } class = c}$$

$$P(class = c) = \frac{\# \text{ of training examples where } class = c}{\# \text{ of training examples}}$$

Test:

$$\log(P(class)) + \log(P(f_{1,1}|class)) + \log(P(f_{1,2}|class)) + \dots + \log(P(f_{28,28}|class))$$

class	posterior probability
0	.3141
1	.432
2	0
3	0
4	.4
5	.004
6	.1
7	.2
8	.7
9	.5