Private Tutor + StudyFeed

Git split, version 2 — who uploads what to GitHub

What changed since the first PDF

- **Two new features** were added: the **AI Studies** tab and the **saved-chats sidebar** (with material deletion). Every new file is listed below under its owner and marked NEW / UPDATED.
- **The split was fixed.** In the first version some shared files (server helpers, OpenAI/embeddings, utils) sat in one person's list while other people's code imported them, so those branches would not have compiled on their own. Now anything used by more than one person lives in **Saeed's base**. I checked it by building three combinations: base alone, base + Mohammed, base + Arkan — all three print `Compiled successfully`, and no feature imports another feature's files.
- It uses **your existing GitHub branches**: `saeed`, `mohammed`, `devolp` (all currently empty, pointing at the README commit), plus a new `arkan`.

The split

Person	Area	GitHub branch	Files
Saeed	Base: auth, navigation, shared state, shared libraries, deployment	saeed	31
Mohammed	Smart Tutor: upload, RAG chat, saved chats sidebar, exam, hints, summary, gap map, delete material	mohammed	34
Arkan	StudyFeed, Explore, AI Studies, XP, database SQL & seeding	arkan (new)	27

Each person's list has no overlap with the others, so the merges cannot conflict.

The order (4 steps)

1. **Saeed** pushes his `saeed` branch and merges it into `devolp` (a Pull Request on GitHub). This is the base everyone else builds on.
2. **Saeed** sends `mohammed-files.zip` to Mohammed and `arkan-files.zip` to Arkan, plus the `.env.local` keys (privately — never through GitHub).
3. **Mohammed and Arkan** each bring the base into their own branch, unzip their files, check that it builds, commit **under their own name** and push. That is what puts their name on the work in GitHub.
4. **Everyone** opens a Pull Request into `devolp`. When all three are merged, `devolp` goes into `main`.

Assumption: `devolp` is your integration branch. If you'd rather merge straight into `main`, replace `devolp` with `main` everywhere below.

Saeed — Base, auth, navigation, deployment

GitHub branch: `saeed`

What to do

The branch `saeed` is already prepared on your computer: one commit with the files below, on top of the README commit that is on GitHub. Pushing does **not** touch your working folder, so your `npm run dev` keeps running.

```
cd C:\Users\saied\Desktop\private-tutor
git push -u origin saeed
```

Then on GitHub: **Pull requests** → **New pull request**, base = `devolp`, compare = `saeed` → Create → **Merge**. Do this first — Mohammed and Arkan wait for it.
Then send the two zips (they are in `C:\Users\saied\Desktop\private-tutor-handoff\`) and the `.env.local` keys.

Careful: your folder is on the branch `main` and holds the whole app. Don't `git checkout` another branch while the dev server is running — the files on disk change and the server crashes (that already happened once).

Files this person uploads

31 files. NEW / UPDATED = compared with the first split.

File	Since the last PDF
`.env.example`	**UPDATED**
`.eslintrc.json`	unchanged
`.gitignore`	unchanged
`DEMO.md`	unchanged
`DEPLOY.md`	**UPDATED**
`README.md`	**UPDATED**
`app/(auth)/login/page.js`	unchanged
`app/(auth)/register/page.js`	unchanged
`app/(main)/layout.js`	unchanged
`app/favicon.ico`	unchanged
`app/fonts/GeistMonoVF.woff`	unchanged
`app/fonts/GeistVF.woff`	unchanged
`app/globals.css`	unchanged
`app/layout.js`	unchanged
`app/page.js`	unchanged
`components/AuthForm.js`	unchanged
`components/layout/TabBar.js`	**UPDATED**
`components/layout/TopNav.js`	unchanged
`jsconfig.json`	unchanged
`lib/embeddings.js`	unchanged
`lib/openai.js`	unchanged
`lib/server.js`	**UPDATED**
`lib/supabase.js`	unchanged
`lib/utils.js`	unchanged
`next.config.mjs`	unchanged
`package-lock.json`	unchanged
`package.json`	unchanged

File	Since the last PDF
postcss.config.mjs	unchanged
scripts/vercel-env.ps1	**UPDATED**
store/useStore.js	unchanged
tailwind.config.js	unchanged

Mohammed — Smart Tutor

GitHub branch: `mohammed`

What to do (after Saeed merged the base into devolp)

```
git clone https://github.com/saeedabuhani/private-tutor.git
cd private-tutor
git config user.name "Mohammed <your full name>"
git config user.email "<the email linked to your GitHub account>"
git checkout mohammed
git merge origin/devolp # brings in Saeed's base
```

Unzip `mohammed-files.zip` **into the project folder** (keep the folders; say yes if asked to overwrite). Create `.env.local` from `.env.example` with the keys Saeed sent — never commit it.

```
npm install
npm run build # must end with: Compiled successfully
git status # must list ONLY the files in the table below
git add .
git commit -m "Smart Tutor: upload, RAG chat, saved chats, exam, hints, summary, gap map"
git push -u origin mohammed
```

Then on GitHub: New pull request, base = `devolp`, compare = `mohammed`. Don't merge it alone — merge all together.

Try it: `npm run dev` → /tutor → upload a file → ask a question → the chat appears in the left sidebar → reopen it → Test me → Gap map.

This branch has no SQL file. The two tables for saved chats (`chat_sessions`, `chat_messages`) are created by `supabase/add-chat-history.sql`, which is in Arkan's list (the database owner).

Files this person uploads

34 files. NEW / UPDATED = compared with the first split.

File	Since the last PDF
app/(main)/tutor/[materialId]/exam/page.js	unchanged
app/(main)/tutor/[materialId]/page.js	**UPDATED**
app/(main)/tutor/[materialId]/report/page.js	unchanged
app/(main)/tutor/layout.js	**NEW**
app/(main)/tutor/page.js	**UPDATED**
app/api/exam/route.js	unchanged
app/api/gap-map/route.js	unchanged
app/api/hint/route.js	unchanged
app/api/materials/[materialId]/route.js	**NEW**
app/api/materials/route.js	unchanged
app/api/sessions/[sessionId]/messages/route.js	**NEW**
app/api/sessions/[sessionId]/route.js	**NEW**
app/api/sessions/route.js	**NEW**
app/api/stuck/route.js	unchanged
app/api/summary/route.js	unchanged
components/tutor/AIResponse.js	unchanged
components/tutor/ActiveRecallHint.js	unchanged
components/tutor/ChatSidebar.js	**NEW**
components/tutor/ExamCard.js	unchanged
components/tutor/GapMap.js	unchanged

File	Since the last PDF
components/tutor/LanguageBridge.js	unchanged
components/tutor/MaterialCard.js	unchanged
components/tutor/MaterialUpload.js	unchanged
components/tutor/MaterialsGrid.js	NEW
components/tutor/MessageContent.js	unchanged
components/tutor/StuckInput.js	UPDATED
components/tutor/SummaryButton.js	unchanged
hooks/useGapMap.js	unchanged
lib/authFetch.js	NEW
lib/chatSessions.js	NEW
lib/dates.js	NEW
lib/extract.js	unchanged
lib/stuckTypes.js	unchanged
supabase/add-chat-history.sql	NEW

Arkan — StudyFeed, Explore, AI Studies, database

GitHub branch: `arkan (new)`

What to do (after Saeed merged the base into devolp)

```
git clone https://github.com/saeedabuhani/private-tutor.git
cd private-tutor
git config user.name "Arkan <your full name>"
git config user.email "<the email linked to your GitHub account>"
git checkout -b arkan origin/devolp # the branch does not exist yet
```

Unzip `arkan-files.zip` **into the project folder** (keep the folders). Create `.env.local` from `.env.example` with the keys Saeed sent — never commit it.

```
npm install
npm run build # must end with: Compiled successfully
git status # must list ONLY the files in the table below
git add .
git commit -m "StudyFeed, Explore, AI Studies and database SQL"
git push -u origin arkan
```

Then on GitHub: New pull request, base = `devolp`, compare = `arkan`.

The SQL is run by hand in the Supabase SQL Editor (once): `add-explore.sql`, `add-ai-videos.sql`, `add-chat-history.sql` — or just `schema.sql` on a fresh project. Explore videos: `node scripts/seed-explore.js`. Try it: `npm run dev` → /feed, /explore, /ai-studies (add a video with the admin route `POST /api/ai-videos/add`, header `x-admin-key`).

Files this person uploads

27 files. NEW / UPDATED = compared with the first split.

File	Since the last PDF
app/(main)/ai-studies/page.js	**NEW**
app/(main)/explore/page.js	unchanged
app/(main)/feed/page.js	unchanged
app/api/ai-videos/add/route.js	**NEW**
app/api/ai-videos/route.js	**NEW**
app/api/explore/answer/route.js	unchanged
app/api/explore/question/route.js	unchanged
app/api/explore/videos/route.js	unchanged
app/api/feed/question/route.js	unchanged
app/api/feed/route.js	unchanged
app/api/xp/route.js	unchanged
components/ai-studies/AiVideoPlayer.js	**NEW**
components/explore/ExploreExplain.js	unchanged
components/explore/ExploreQuestion.js	unchanged
components/explore/ExploreVideo.js	unchanged
components/feed/FeedSyncBanner.js	unchanged
components/feed/QuickQuestion.js	unchanged
components/feed/VideoControls.js	unchanged
components/feed/VideoFeed.js	unchanged
components/feed/VideoSidebar.js	unchanged
hooks/useFeed.js	unchanged

File	Since the last PDF
lib/youtube.js	unchanged
lib/youtubePlayer.js	unchanged
scripts/seed-explore.js	unchanged
supabase/add-ai-videos.sql	**NEW**
supabase/add-explore.sql	unchanged
supabase/schema.sql	**UPDATED**

When all three are merged

- On `devolp` run `npm install` and `npm run build` once — it must end with `Compiled successfully`.
- Open a Pull Request `devolp` → `main` and merge it.
- GitHub → **Insights** → **Contributors** now shows the three names, each with their own commits.

Rules

- `.env.local` holds real API keys. It is git-ignored — never add it, never send it in a chat you don't control.
- Each person changes only the files in their own table. If you need to change someone else's file, tell them.
- Never `git push --force` on a shared branch.
- Before every push: `git status` lists only your files, and `npm run build` passes.

Notes on Saeed's computer

The two old local branches from the first split were renamed to `old/smart-tutor-v1` and `old/studyfeed-explore-db-v1` so nobody pushes them by mistake. The zips are in `C:\Users\saied\Desktop\private-tutor-handoff\`.