

Trustsignal (Sigmo) integration: what Relay needs

Checklist for the Trustsignal call, 2 October 2026

How to use this document

Relay is our multi-tenant messaging platform (API at <https://sms-api.saqibsaheed.cloud>). We want to send **RCS, SMS, WhatsApp and Email** for our customers through Trustsignal (sold to us as Sigmo).

Each section lists **what we need from Trustsignal** (credentials, settings, approvals) and **the questions to ask on the call**. Tick items off as they arrive.

Where each channel stands on our side today:

Channel	Relay today	What going live needs
RCS	Built, tested and deployed for Trustsignal (1 Oct). The API key works	Credits, an approved bot, the webhook set in Sigmo, one approved template
SMS	Built over SMPP : live today on another operator (VIDEOCON)	An SMPP account from Trustsignal means no code; we add a bind in our console. An HTTP-only account means building a small HTTP SMS connector (~1–2 days)
WhatsApp	Channel exists in the product; no WhatsApp provider connected yet (messages are simulated)	A WhatsApp connector to Trustsignal's API (~3–5 days) plus the WABA/number details below
Email (campaigns)	Channel exists; no email provider connected for campaigns . Our own account emails (login, reset) go through Resend	An email connector to Trustsignal's API or SMTP (~2–3 days) plus the domain/DNS details below
Voice	Channel exists, simulated	Trustsignal's API collection has no voice; ask if they offer it
OTP (Otify)	Relay has its own OTP/verify service	Not needed; price comparison only

1. Account, commercial and security (all channels)

1.1 We need

- ☐ **Account id** and account name exactly as Trustsignal has it
- ☐ **API keys**: one per environment (**live** and **test/sandbox**) if they offer a test environment. We already have one key; confirm it is the live one

- **Sub-accounts.** Their API has `POST /register-subaccount`. We need to know whether each of **our customers** should get their own Trustsignal sub-account (separate bots, senders, WABAs and billing) or all traffic runs under one account
- **Price list per channel** (India): RCS (basic / rich / per-message vs per-conversation), SMS (transactional / promotional / service), WhatsApp (marketing / utility / authentication / service), Email (per 1,000)
- **Billing model:** prepaid credits or postpaid; how to top up; minimum top-up; invoice with GST; payment terms
- **Credit alerts:** can they warn us at a low balance? Is there a balance API? (`/v1/accounts/credits` exists for SMS; ask for RCS/WhatsApp/Email)
- **Support and escalation:** named account manager, technical contact, WhatsApp/email for incidents, response times, uptime SLA
- **Rate limits:** requests per second per API (RCS send, bulk send, template, WhatsApp, email) and what happens above them (HTTP 429?)

1.2 Security: we give them, and we need from them

- **Our server's fixed IP** for their allowlist: `3.111.226.170` (all our outbound traffic, AWS Mumbai)
- **Their webhook source IPs**, so our webhook endpoints accept only them
- **Webhook signing:** do they sign webhook requests (HMAC header)? If not, we protect each URL with a secret token in the path (done for RCS)
- **Webhook retries:** on a non-200 answer, how often and for how long they retry, and whether an event can arrive twice
- **API key rotation:** how to rotate a key without downtime; can two keys be active during a switch?
- **API key in the URL** (`?api_key=`): can it be sent as a **header** instead? A key in the URL ends up in proxy logs. Our code keeps it out of our own logs

1.3 Questions

1. Is there a **sandbox/test environment** with a separate base URL and key, or a test mode on the live account?
2. Which **Indian operators** does each channel reach (Jio, Airtel, Vi, BSNL)? International?
3. Is there a **status page** or incident notification?
4. Where is data stored, and for how long do they keep message content and phone numbers (DPDP Act)?

2. RCS

Status: our side is done. We send by approved template, submit templates from our dashboard (text and rich card with buttons), and read delivery, read, “not RCS”, template-approval and customer-reply webhooks.

2.1 We need

- **Credits** for RCS on the account. The balance is **0** today, so every send would be refused

- **An RCS bot, created and approved** (Sigo → RCS → RCS Settings → Bots), with:
 - Bot name: what the user sees, **max 40 characters**
 - Brand name
 - Short description: **max 100 characters**
 - Logo: **224 × 224 px**, JPG/PNG, **max 90 KB**
 - Banner: **1440 × 448 px**, JPG/PNG, **max 360 KB** (the logo is overlaid bottom-centre)
 - Brand colour: hex, at least **4.5 : 1 contrast** against white
 - Phone number(s), email(s), website(s), each with a label
 - Terms of service URL and privacy policy URL (public)
 - Message type: **promotional / transactional / OTP**. Every template must match the bot's type
 - Languages (e.g. English)
- **The bot's** `bot_id` once it is **active**. We link it to the customer's agent in Relay
- **Webhook configured** (Sigo → RCS → Webhooks → Add Event Webhook):
 - URL: `https://sms-api.saqibsaheed.cloud/v1/carrier-webhooks/rcs/trustsignal/<token>`. The token is shared separately and is secret
 - Events: **Delivery Status, Template, User Response**; Agent Delivery Status optional
- **One or two test phones**: Android, Google Messages, RCS chats turned on

2.2 Questions (answers change our code or our pricing)

1. `sms_fallback` **on the send API**. Their docs mark it required. We run our own SMS fallback and **do not want theirs**, or the SMS goes out twice. Can we send **without** `sms_fallback`? If not, can we disable it?
 2. **Carrying our message id**. Their webhook includes `pr1-pr5`, "custom parameters passed while sending". **How do we pass them on the send?** We would put our own message id in `pr1`; it makes matching reports safer than their `transaction_id` alone.
 3. **Idempotency**. If we retry a send after a timeout, is it sent twice? Is there a client reference that makes a retry safe?
 4. **Charging for** `nonrccs` (the phone can't take RCS): are we charged? Relay does not charge the customer for these.
 5. **Capability check**. Is there an API to ask whether a number can receive RCS before sending? Their public docs have none; the direct Airtel and Vi APIs do.
 6. **Template rules**: allowed characters and length for the **template name**; variable naming (`[custom_param0]` or any `[name]` ?); maximum number of variables; maximum buttons; text length limit.
 7. **Media for rich cards**: must images/videos be hosted by them (upload API) or can we pass our own https URL? Size and format limits? Is a thumbnail needed for video?
 8. **Carousels**: supported through the API (we saw `s=3`)? We will add carousels to our product if yes.
 9. **Approval times**: typical time to approve a bot, and a template.
 10. **TTL**: what `ttl: "30s"` does. Is it the time RCS is attempted before giving up?
 11. **Error codes**: the full list behind the "ERROR Codes" button in the portal, with meanings.
 12. **Bulk send**: maximum recipients per `bulk_with_fallback` call.
 13. **Per-customer bots**: can one account hold many bots (one per customer brand)? Any limit?
-

3. SMS

Status: our SMS engine speaks **SMPP** and is live today with another operator. With an **SMPP account** from Trustsignal we add a bind in our operator console, with no code change. An **HTTP-only** account needs a new connector (~1–2 days).

3.1 We need: SMPP account (preferred)

- **Host** and **port**, live, plus a test bind if they have one
- **system_id** (username) and **password**
- **system_type**, if they require one
- **Bind type**: transceiver (preferred), or separate transmitter and receiver
- **Number of simultaneous binds (sessions)** allowed
- **TPS** (messages per second) per bind and per account
- **Window size**: submits in flight before a response
- **enquire_link** interval they expect
- **TLS or plain TCP?** Our SMPP client uses **plain TCP** today. If they require TLS or a VPN, tell us early
- **Our IP to allowlist** on their side: `3.111.226.170`
- **TON/NPI** for source (alphanumeric header: we send 5/0) and destination (we send 1/1, international)
- **DLT TLV tags**: which tags carry the **Principal Entity ID** and **Content Template ID** (we default to **0x1400 / 0x1401**), and whether they need the **PE-TM chain hash** on **0x1402**
- **Their Telemarketer (TM) DLT ID**, for the PE→TM chain
- **Delivery receipt format**: standard `id:... sub:... dlvr:... submit date:... done date:... stat:... err:... ?` Is the message id hex or decimal (it must match what `submit_sm_resp` returns)?
- **Long SMS**: UDH concatenation, or `sar_* / message_payload` TLVs?
- **Unicode**: `data_coding` 8 (UCS2) supported for Hindi and other Indian scripts?
- **Error code list** for `err:` in receipts, and for `submit_sm_resp` command statuses
- **Routes**: transactional, promotional and service (implicit/explicit). Is it one bind for all, or a bind per route?

3.2 If they only offer HTTP

- The same commercial and DLT details, plus: which endpoint (`/v1/sms`, `/v1/sms/multi`, `/v1/sms/params`), maximum numbers per bulk call, and the **SMS delivery webhook** payload (their docs show `POST /v1/SMSsavewebhook` to set the URL, but not the payload)

3.3 DLT (India): from each of our customers, with Trustsignal's help

- **Principal Entity (PE) ID** of the customer
- **Sender IDs (headers)** registered on DLT under that PE (e.g. `ACMERT`)
- **Content templates** registered on DLT, each with its **DLT template ID**, category (transactional / service / promotional) and exact approved text. Our templates store the DLT template ID and check every message against the text
- **Trustsignal added as telemarketer** on each customer's DLT account (the PE→TM chain binding), or the messages fail scrubbing
- Question: **does Trustsignal handle DLT registration** for customers who don't have it yet?

3.4 Questions

1. Promotional window (9 am–9 pm): enforced by them, us, or both? (We already enforce it.)
 2. DND scrubbing: done by them? Do they return a DND error per message?
 3. Sender ID for international traffic, if needed.
-

4. WhatsApp

Status: WhatsApp is in our product (templates, campaigns, contacts) but **not connected to any provider**, so messages are simulated. We build a **Trustsignal WhatsApp connector** (~3–5 days) once the details below are known.

4.1 We need

- **Onboarding model.** Does each customer get their **own WABA** (WhatsApp Business Account) and number under our Trustsignal account, via **embedded signup** or via Trustsignal? This decides how we design it
- Per WABA: **WABA id**, **phone number id**, the **phone number**, **display name** (Meta-approved), and **Meta Business Manager verification** status
- **Messaging tier** per number (1K / 10K / 100K unique users per day) and how it is raised
- **Webhook:** the payloads for status (sent / delivered / read / failed), inbound replies, template status, and phone quality. Their docs list these; confirm they apply to our account. Our URL will be `https://sms-api.saqibsaheed.cloud/v1/carrier-webhooks/whatsapp/trustsignal/<token>` once built
- **Template API** access: create / list / get / delete templates (their docs show all four), categories **marketing / utility / authentication**, and the approval time
- **Media:** upload by URL or form-data returns a media id (their docs show both). Size limits per type?
- **Pricing** per conversation category in India, and who pays Meta's fee

4.2 Questions

1. Can one Trustsignal account hold **many WABAs** (one per customer)? Is there a limit?
 2. Do they support **Meta's embedded signup** so a customer can connect their own number from our dashboard?
 3. **24-hour service window:** can we send free-form replies (the “agent-reply” API) inside the window?
 4. Opt-in: do they require proof of consent, or is that our responsibility? (We record consent per contact per channel.)
 5. What happens to a WhatsApp message that fails: any automatic SMS fallback? We would turn it **off**, as with RCS.
 6. **Authentication (OTP) templates** with copy-code buttons: supported through the send API?
-

5. Email

Status: campaign email is in our product but **not connected to a provider**. We build a **Trustsignal email connector**, API or SMTP (~2–3 days). Our own account emails (verification, password reset) stay on Resend.

5.1 We need

- **API** (their docs: `/v1/otp-email`, `/v1/transactional-email`, `/v1/promotional-email`) or **SMTP relay details**:
 - SMTP **host**, **port** (587 STARTTLS / 465 TLS), **username**, **password**
 - Sending limits per second and per day
- **Sending domains**: for each domain we (or a customer) send from, the **DNS records** to add:
 - SPF** (include), **DKIM** (CNAME/TXT), **DMARC** policy, **return-path / bounce** domain
 - Verification steps and how long they take
- **From / reply-to** rules: any address on a verified domain?
- **Dedicated or shared IP**; if dedicated, the **IP warm-up** plan
- **Webhooks** for delivered, bounced (hard/soft), complaint (spam), opened, clicked, unsubscribed, with example payloads
- **Suppression list**: do they keep one, and can we read and sync it?
- **Unsubscribe**: do they add `List-Unsubscribe` headers for promotional mail, or do we?
- **Content**: raw HTML accepted, or only their templates? Attachments? Maximum size?
- **Price** per 1,000 emails; separate for transactional and promotional?

5.2 Questions

1. One account with many customer domains: supported? Is each domain verified separately?
 2. Open/click tracking: can it be turned off per message?
 3. Do bounces and complaints auto-suppress on their side?
-

6. What we give Trustsignal

Item	Value
Company	Textify Digitals (account <code>afzal+1@textifydigitals.in</code>)
Our outbound IP (allowlist)	<code>3.111.226.170</code>
RCS webhook	<code>https://sms-api.saqibsaheed.cloud/v1/carrier-webhooks/rcs/trustsignal/<token></code> (token shared privately)
SMS delivery receipts	over the SMPP bind itself, so no URL is needed
WhatsApp / Email webhooks	issued once those connectors are built
Technical contact	(fill in)

7. After the call: our order of work

1. **RCS first send:** needs credits, bot, webhook and test phones (§2). About 1 hour on our side once they exist.
2. **SMS through Trustsignal:** SMPP details (§3.1) mean a same-day bind in our console. DLT per customer (§3.3).
3. **WhatsApp connector:** build once §4.1 is answered, then onboard the first customer WABA.
4. **Email connector:** build once §5.1 is answered, then verify the first domain.