CIP — Technical Specification

Data Automation · Coresight Research

October 13, 2026

CONTENTS

0. Overview

- 0.1 Scope
- 0.2 Document map
- 0.3 Architecture
- 0.4 Components

1. Connection and API

- 1.1 Systems involved
- 1.2 Forsta API
- Endpoints used (all GET)
- Response shapes
- Status codes and what the pipeline does
- 1.3 Warehouse connection
- 1.4 Configuration (.env)

2. Extract

- 2.1 Discovery (every run)
- 2.2 Choosing what to load
- 2.3 Fetching a wave
- 2.4 Wave identity
- 2.5 Legacy extraction (history)

3. Transform

- 3.1 Datamap → questions (one ParsedQuestion per Forsta question)
- 3.2 Records → respondent rows
- 3.3 Records → answer rows
- 3.4 Derived transformations (after load)

4. Load and verify

- 4.1 Order of writes
- 4.2 Verification (before anything is visible)
- 4.3 Visibility and status
- 4.4 Idempotency
- 4.5 Reconciliation (independent check)

5. Derived data, storage design and performance

- 5.1 Design principles
- 5.2 Cube — cip_agg_cell

CONFIDENTIAL

5.3 Search — cip_search

5.4 Line-by-line — cip_tracker_line

5.5 Concepts — harmonisation

5.6 Survey calendar — cip_wave_module

5.7 Indexes

5.8 Partitioning decision

5.9 Measured performance (over the VPN, P95)

6. Data dictionary — cip_ tables and views in dwh_stg

cip_agg_cell

cip_answer

cip_auth_session

cip_banner

cip_cohort_def

cip_concept

cip_concept_map

cip_concept_option

cip_crosstab

cip_crosstab_run

cip_field

cip_forsta_survey

cip_item

cip_load_error

cip_load_log

cip_load_state

cip_option

cip_profile

cip_profile_map

cip_publication

cip_publication_cell

cip_question

cip_respondent

cip_respondent_cohort

cip_saved_view

cip_search

cip_segment

cip_survey

cip_topic

cip_tracker_line

cip_wave_module

cip_weight

cip_weight_scheme

v_cip_answers

v_cip_crosstab

v_cip_grid

v_cip_item_incidence

v_cip_mapping_queue

v_cip_question_base

v_cip_single_distribution

v_cip_survey_health

v_cip_trend

7. Survey patterns — measured, stored and applied

7.1 Cadence

7.2 Title grammar

7.3 Rotation evidence (weeks between appearances of each lead sector)

7.4 Module question codes

7.5 Known scheme changes

7.6 Applying the patterns

8. Operations runbook

8.1 Schedule

8.2 What one run does

8.3 Exit codes

8.4 Commands

8.5 Monitoring queries

8.6 Common situations

8.7 Change management

8.8 Security

CONFIDENTIAL

Forsta ETL, data storage and operations for the Consumer Insight Portal. Version 1.0 · 13 October 2026 · Owner: Data Automation (Coresight Research)

Built from the section files in `docs/technical/` (00–08); the data dictionary is generated from the live database.

0. Overview

Consumer Insight Portal (CIP) — Technical Specification. How survey data is retrieved from Forsta, transformed, loaded into `dwh_stg`, verified and prepared for reporting. Version 1.0 · 13 October 2026.

0.1 Scope


In scope	Out of scope (for now)
Forsta API extraction, every survey the key can see	Reactivating hibernated surveys (manual in Forsta)
Transformation, loading, verification, derived tables	The new portal UI (designs only)
History from Qualtrics and SurveyMonkey (`dwh_sm*`)	Azure Blob archive of raw payloads (deferred)
Scheduling, monitoring, reconciliation	Weighting (columns reserved; waves are unweighted)

0.2 Document map


Section	Content
1	Connection and API: endpoints, authentication, responses, status codes, configuration
2	Extract: discovery, due selection, fetching, wave identity, legacy sources
3	Transform: question shapes, labels, bipolar grids, other-specify, flags, personal data, profiles, concepts
4	Load and verify: write order, transactions, verification, visibility, idempotency, reconciliation
5	Derived data, storage design, indexes, partitioning, performance
6	Data dictionary: every table, view and column
7	Survey patterns: cadence, rotation, modules, codes, how to apply
8	Operations runbook: schedule, exit codes, commands, monitoring, incidents, security

CONFIDENTIAL


0.3 Architecture




CONFIDENTIAL



CONFIDENTIAL




CONFIDENTIAL



CONFIDENTIAL

CIP Database Design (dwh_stg, cip_ tables)

Classic · Export



Long, not wide

- One row per respondent × variable in cip_answer, so the schema never changes when weekly modules rotate (BT, TF, HX, IN …)
- Definitions (question, item, option,

Serving layer — nothing left for the UI

- cip_agg_cell: every answer × standard cut (gender, age band, generation, income, region, urbanicity) × cohort, counted once

Indexes

- cip_answer (survey_id, field_id, value_code, respondent_id) covering, plus unique (respondent_id, field_id) for upserts; the duplicate

Partitioning — decided by measurement

- Applied: logical partitioning by wave. survey_id leads every hot index, a wave loads and verifies as one unit, and reads hit the pre-

Privacy

- No browser string, link, session, fingerprint or IP is stored; the panel RID only as sha256 respondent_key
- The portal connects with a read-

CONFIDENTIAL


0.4 Components

Component	File	Responsibility
Scheduled run	`scripts/weekly_forsta.py`	health, key and schema checks; discover; load due; drift; exit code
Forsta client	`etl/forsta_client.py`	authenticated GET with retries
Datamap adapter	`etl/forsta_api.py`	Forsta JSON → questions (shapes, labels, bipolar, other-specify, flags, personal-field denylist)
Pipeline	`etl/forsta_etl.py`	register, load, verify, reconcile, reindex
Loaders	`etl/loaders.py`	survey and definition upserts, load log, search index
Shared loader steps	`etl/run_pipeline.py`	profiles, question bases, wave label
Demographics	`etl/survey_map.py` + `config/survey_map.yml`	topics, profile mapping, age/income bands, regions
Harmoniser	`app/data/harmonise.py`	concepts across waves and platforms
Cohorts and cube	`app/data/cohorts.py`, `app/data/cube.py`	segment membership, pre-computed cells
Line-by-line	`etl/tracker_line.py` + `config/tracker_line.yml`	the data team's weekly table
Survey calendar	`etl/survey_calendar.py` + `config/survey_calendar.yml`	cadence, modules, season wave numbers
History	`etl/legacy_dwh.py`, `etl/qualtrics_export.py`	Qualtrics and SurveyMonkey
Schema	`sql/001_schema.sql`, `sql/002_views.sql`, `app/core/schema_upgrade.py`, `scripts/init_db.py`	DDL, views, upgrades
Checks	`scripts/reconcile.py`, `scripts/perf_check.py`, `tests/`	correctness, speed, 227 tests

1. Connection and API

1.1 Systems involved

CONFIDENTIAL



CONFIDENTIAL

System	Role	Access
Forsta Surveys (Decipher) `se1.decipherinc.com`	Live survey source	HTTPS REST API v1, **GET only**
Azure Database for MySQL 8.0 `csr-mysql8-flex-stg.mysql.database.azure.com`, schema `dwh_stg`	Warehouse	TLS 1.2+, PyMySQL via SQLAlchemy 2
`dwh_sm*` tables in `dwh_stg`	Qualtrics + SurveyMonkey history (read)	same connection
macOS launchd (`com.coresight.cip-forsta-etl`)	Scheduler	user agent on the ETL host

1.2 Forsta API

Setting	Value
Base URL	`https://se1.decipherinc.com/api/v1/`
Authentication	header `x-apikey: <64-character key>`; key in `.env` as `FORSTA_API_KEY` (never logged or printed)
Other headers	`Accept: application/json`, `User-Agent: coresight-cip/1.0`
Account	user 879, company 86, directory “Coresight Research” (`58f`)
Timeout	120 s per request (`FORSTA_TIMEOUT_SECONDS`)
Retries	up to 4 attempts, exponential back-off 2 → 60 s, on connection errors, timeouts, **429** and **5xx**
Usage header	`x-usage-today` logged at debug level
Client	`etl/forsta_client.py` (`ForstaClient`)

ENDPOINTS USED (ALL GET)

Endpoint	Purpose	Called
`rh/users/self`	Proves the key works	Start of every scheduled run
`rh/companies/all/surveys`	Every survey the key can see: `path`, `title`, `state`, `hibernated`, `tags`, `createdOn`, `dateLaunched`, `closedDate`, `qualified`, `total`, `sampleSources`	Once per run (discovery) and reused for the run’s loads
`surveys/{path}/datamap?format=json`	Questionnaire definition	Once per wave loaded
`surveys/{path}/data?format=json`	Every respondent record; **no `cond` filter**, so terminates, over-quota and partials are included	Once per wave loaded and per reconciliation

Nothing else is called. `data/edit`, reactivation, survey edits and datafeed acknowledgements are not used; the client has no POST/PUT/DELETE method.

RESPONSE SHAPES

Survey list item

```
{"path": "selfserve/58f/260908", "title": "Shopping and Spending – inc Home Furnishings + Holiday Tracker + GenAI",
 "state": "closed", "hibernated": false, "tags": ["Coresight Research", "Weekly consumer tracker"],
 "createdOn": "2026-09-22T15:57:00Z", "dateLaunched": "2026-10-05T12:22:25Z", "closedDate": "2026-10-06T14:19:55Z",
 "qualified": 401, "total": 823, "sampleSources": ["114"]}
```


Datamap — `questions[]`, each with `qlabel`, `qtitle`, `type` (single / multiple / float / number / text), `grouping` (rows / cols), optional `flags` (`t` technical, `v` virtual), `values[]` (`value`, `title`) on the question *or* on each variable, and `variables[]` (`label`, `row`, `rowTitle`, `colTitle`, `type`, `values`).

Data — a JSON array, one object per respondent, **every value a string**: `"status": "3"`, checkbox `"0"` / `"1"`, single choice `"1"`…`"n"`, numbers as text, verbatims as text, `"date": "09/28/2026 10:56"`, plus `record`, `uuid`, `RID`, `markers`, `userAgent`, `url`, `session`, `dcua`.

STATUS CODES AND WHAT THE PIPELINE DOES

Code	Meaning	Handling
200	OK	continue
401	Key missing, wrong, revoked or user disabled	run stops, exit 2
403	Key valid, no rights on the survey	wave fails, recorded
428	Survey hibernated	never loaded; reconciliation skips it with a warning
429 / 5xx	Busy / server error	retried (4 attempts) then the wave fails and is retried next run

1.3 Warehouse connection

Setting	Value
Driver	`mysql+pymysql`, SQLAlchemy 2 engine, pooled (`DB_POOL_SIZE`, `DB_MAX_OVERFLOW`)
ETL account	`STG_DB_USER` — ALL PRIVILEGES on `dwh_stg`
Portal account	read-only grants (`sql/004_grants.sql`, applied by the DBA)
TLS	required; CA bundle `STG_DB_SSL_CA` (DigiCert Global Root G2)
Latency	≈250 ms round trip from the India office — every loader step is batched to a constant number of statements per wave
Health check	`SELECT VERSION()`; the scheduled run tries 4 times, 5 minutes apart, before exiting 4


1.4 Configuration (`.env`)

Variable	Use
`APP_ENV`	`LOCAL` / `STAGING` / `PRODUCTION`
`STG_DB_HOST`, `STG_DB_PORT`, `STG_DB_NAME`, `STG_DB_USER`, `STG_DB_PASSWORD`, `STG_DB_SSL_CA`	Warehouse
`FORSTA_HOST` (default `se1.decipherinc.com`), `FORSTA_API_KEY`	Forsta
`FORSTA_TIMEOUT_SECONDS` (120), `FORSTA_MAX_RETRIES` (4)	Client
`LOCAL_SQLITE_PATH`	Offline SQLite copy for development

2. Extract

Code: `etl/forsta_etl.py` (`discover`, `run_due`, `load_survey`), `etl/forsta_client.py`.

CONFIDENTIAL



2.1 Discovery (every run)

`discover(client)` calls `rh/companies/all/surveys` once and upserts one row per survey into `cip_forsta_survey` (key `forsta_path`). The **load state** is decided as follows:

CONFIDENTIAL

Condition (in order)	`load_state`
previously `loaded` and neither `closedDate` nor `total` changed	`loaded`
Forsta `state` ≠ `closed` (testing, live)	`testing`
closed and `hibernated = true`	`hibernated`
closed, readable, previously `failed`	`failed` (retried)
closed, readable, otherwise	`due`

A loaded survey whose close date or total respondents changed (reopened in Forsta) becomes `due` again. The same transaction rebuilds the survey calendar (`cip_wave_module` , section 5.6).

Columns written: `title` , `state` , `hibernated` , `tags` (comma list), `study_type` (`tracker` if tagged “Weekly consumer tracker” or titled “Shopping and spending…”, `annual` if tagged “annual tracker”, else `adhoc`), `created_on` , `launched_at` , `closed_at` , `qualified_n` , `total_n` , `last_seen` (UTC), `load_state` .

2.2 Choosing what to load

`run_due(client)` selects `load_state IN ('due','failed')` ordered by `closed_at, forsta_path` (oldest first) and loads them one at a time. The survey list from discovery is reused, so a run makes **one** list call however many waves it loads. A failure is recorded (`load_state = failed` , `last_error`) and the run continues with the next wave.

2.3 Fetching a wave

For each due survey:

1. `GET surveys/{path}/datamap?format=json` — the questionnaire (≈0.5 MB).
2. `GET surveys/{path}/data?format=json` — all records (≈2 MB for 500 respondents), **without** `cond` , so every status is present: 1 terminated · 2 over quota · 3 qualified · 4 partial.
3. Records without a `uuid` are discarded (Forsta system rows).

2.4 Wave identity

Field	Rule
Forsta path	`selfserve/58f/YYMMNN` — one survey = one wave
`wave_label` / `wave_date`	Monday of the earliest completion date among **qualified** records (all records if none qualified)
Reload	A survey already loaded by this pipeline (load log `source_ref = forsta:{path}`) keeps its wave label and `survey_id` , even if its first date moves
Family	`CSI-US` for the weekly tracker; for other studies the title without the year, upper-cased (`HOLIDAY_SHOPPING`)

CONFIDENTIAL


2.5 Legacy extraction (history)

Source	Module	Notes
Qualtrics 2022–2025 in `dwh_sm*`	`python -m etl.legacy_dwh --all`	142 waves, completes only, matched to the original responses
SurveyMonkey 2018–2022 in `dwh_sm*`	`python -m etl.legacy_dwh --all --era surveymonkey`	145 waves; matrix questions as grids; SurveyMonkey Audience demographics fill profiles
Qualtrics Excel export, May 2025	`python -m etl.qualtrics_export --wave 2025-05-12 --file …`	The only wave missing from `dwh_sm*`

3. Transform

Code: `etl/forsta_api.py` (`questions_from_datamap`), `etl/forsta_etl.py` (`_answer` , `_respondent`), `etl/records.py` (`ParsedQuestion` , `clean_text`), `etl/survey_map.py` (profiles), `etl/loaders.py` (topics, short labels).

CONFIDENTIAL



CONFIDENTIAL

3.1 Datamap → questions (one `ParsedQuestion` per Forsta question)

Forsta shape	Measured frequency (1,416 questions)	Stored as `qtype`	Fields created
`single`, 1 variable	693	`single`	one field = the question code
`multiple`, many variables	491	`multi` (0/1 per item)	one field per item (`q1r1` , `q1r2` …)
`single` , `rows` , many variables	73	`grid_single`	one field per row
`single` , `cols` , + a text variable	53	`single` + separate `text` question for the "Other (specify)" variable	
`single` , `rows` , 1 variable	43	`single` (or `grid_single` when the variable is named apart)	
`float` / `number`	32	`numeric`	
`text` / `textarea`	23	`text`	
`date`	—	`datetime`	

Rules, in order:

1. **Text** — titles are HTML-unescaped and whitespace-normalised (`clean_text`); `qtext_short` is a ≤ 80-character label.
2. **Answer labels** — taken from the question's `values[]` ; when empty (about a third of datamaps) from the first variable that has `values[]` . Only integer codes are kept.
3. **Grid** — a single-choice question whose variables are "named apart" (more than one row, or the one row's code differs from the question code). Row label = `rowTitle – colTitle` .
4. **Bipolar grid** — a grid whose answer titles are all blank (e.g. HX6): options become `1 = Left statement` , `2 = Right statement` ; each row stores its left statement (its own title) and its right statement (the `{question}_norm{row}_r` variable of Forsta's NORMALIZED copy) in `cip_item.left_label / right_label` .
5. **Other (specify)** — a `text` variable inside a non-text question becomes its own `text` question, code = the variable label (`vosr15oe` , `q1r2oe`), wording " — (please specify)".
6. **Flags** — `t` → `is_technical = 1` (conditions, qtime, start_date, status…); `v` → `is_virtual = 1` (vlist, vos, vbrowser…); a title ending "- NORMALIZED" is virtual. Technical and virtual questions are stored but never reported, harmonised or cubed.
7. **Personal variables** — `RID` , `userAgent` , `url` , `session` , `dcua` , `ipAddress` never become questions or fields, even if a datamap lists them.
8. **Topic** — each question is placed in an editorial topic (`cip_topic`) from its code and wording (`config/survey_map.yml`); technical topics also set `is_technical` .
9. **Answer attributes** — an option whose label contains "don't know", "not sure" or "prefer not to say" is `is_nonresponse` ; an item starting "None of these" is `is_exclusive` ; an item code ending `oe` is `is_other` .

CONFIDENTIAL

3.2 Records → respondent rows

Column	Source	Rule
`record_no`	`record`	integer
`forsta_uuid`	`uuid`	≤ 64 chars, the upsert key with `survey_id`
`status_code` / `status_label`	`status`	1 Terminated · 2 Overquota · 3 Qualified · 4 Partial
`is_qualified`		`status = 3`
`completed_at`	`date`	`MM/DD/YYYY HH:MM` → datetime
`interview_secs`	`qtime`	integer seconds
`markers`	`markers`	≤ 1,000 chars
`device`, `os`, `browser`, `dropout_qcode`	`vmobiledevice`, `vos`, `vbrowser`, `vdropout`	≤ 50 chars
`panel_source`	`vlist` / `list`	≤ 100 chars
`respondent_key`	`RID`	**sha256 hex** — the panel id itself is never stored
`sample_rid`		always NULL

3.3 Records → answer rows

Each `(record, field)` with a non-empty value becomes one `cip_answer` row:

Field kind	Stored
`code` (single, grid row, checkbox item)	`value_code` integer (`"3"`, `"3.0"` → 3); `value_label` = the option label (single/grid) or the item label (checkbox)
`code` but not a whole number	`value_label` = the raw text, no code invented
`numeric`	`value_number`, only if finite and $\lvert x \rvert < 10^{14}$ (column is DECIMAL(18,4)); otherwise not stored
`text`	`value_text` verbatim

Empty strings and nulls are not stored, so “no answer” is the absence of a row. Checkbox `0` **is** stored (item shown, not chosen), which gives every multi-select question its “answered” base.

CONFIDENTIAL


3.4 Derived transformations (after load)

Output	Rule	Code
Profile per respondent (`cip_profile`)	Demographic questions found per wave from `config/survey_map.yml` (CSI-US: D1 gender, D2 age, D3 relationship, D4 ethnicity, D5 income, D6 urbanicity, D7 political, D8 state, CS1/CS2 outlook) or by wording; mapping recorded in `cip_profile_map`	`run_pipeline._rebuild_profiles`
Age band	18-29 · 30-44 · 45-60 · Over 60 (from a single year, or a band that fits one band); “Under 18” unbanded	`survey_map.classify_age`
Generation	GenZ 18-28 · Millennial 29-44 · GenX 45-60 · Boomer 61+	same
Age midpoint	the year itself; bands: the analysts’ midpoints (over 60 = 67)	same
Income midpoint ($000)	under $25k = 13 · $25-49.9k = 37.4995 · $50-99.9k = 74.9995 · $100-149.9k = 124.9995 · $150-199.9k = 174.9995 · $200k+ = 225	`survey_map.income_mid_k`
Census region	State → Northeast / Midwest / South / West (SurveyMonkey: Census division → region)	`survey_map.census_region`
Question base	qualified respondents who reached the question	`_rebuild_question_bases`
Concepts	exact (same normalised wording and options) → confirmed; changed options → proposed; wording ≥ 0.85 similar → proposed; else new concept	`app/data/harmonise.py`
Line-by-line row	the data team’s format, see 5.4	`etl/tracker_line.py`
Calendar	lead sector, topics, seasonal tracker, events; season wave numbers	`etl/survey_calendar.py`

4. Load and verify

Code: `etl/forsta_etl.py` (`load_survey` , `_write` , `verify`), `etl/loaders.py` (`upsert_survey` , `load_definitions` , `start_run` , `finish_run`).

CONFIDENTIAL



CONFIDENTIAL

4.1 Order of writes

Step	Table(s)	Statement	Transaction
1	`cip_survey`	`INSERT … ON DUPLICATE KEY UPDATE` keyed `(platform, source_ref, wave_label)`; then `load_status = 'loading'`, `sample_source`, `total_n`, `tags`, `field_start`, `field_end`	own
2	`cip_load_log`	new run row: `source_type = api`, `object_type = data`, `source_ref = forsta:{path}`	own
3	`cip_topic`, `cip_question`, `cip_option`, `cip_item`, `cip_field`	batched upserts (one statement per table), `INSERT IGNORE` for fields	own
4	`cip_respondent`	one batched upsert keyed `(survey_id, record_no)`	**A**
4b	`cip_answer`, `cip_respondent_cohort`, `cip_profile`, `cip_respondent`	respondents no longer in Forsta's payload are deleted	**A**
4c	`cip_answer`	`DELETE … WHERE survey_id`, then inserts in batches of 5,000 rows (all placeholders, so PyMySQL batches them)	**A**
5	—	verify (reads only)	
6	`cip_profile_map`, `cip_profile`	profiles rebuilt	own
7	`cip_question.base_n`	question bases	own
8	`cip_concept*`, `cip_concept_map`	harmonise	own
9	`cip_respondent_cohort`, `cip_agg_cell`	cohorts derived, cube rebuilt (old cells removed first)	own
10	`cip_search`	the wave's survey + question rows; concept rows	own
11	`cip_tracker_line`	the wave's lines (tracker family only)	own
12	`cip_load_log`	run finished: rows read / loaded, status	own
13	`cip_survey`, `cip_forsta_survey`	`load_status = 'verified'`; register `loaded`, `survey_id`, `loaded_at`	own
14	`cip_wave_module`	calendar rebuilt (questions now known)	own

Transaction **A** is all-or-nothing: if it fails, the previous answers are untouched.

4.2 Verification (before anything is visible)

`verify(survey_id, datamap, records)` must return no problems:

1. **Respondents** — stored respondents for the wave = records sent.
2. **Fields** — every datamap variable (except personal ones) has a `cip_field`.
3. **Answers** — for every field, stored answer count = the number of records with a non-empty value.

Any mismatch raises `"{path} does not match its payload"`, the wave is marked `failed`, and its error is kept in `cip_load_log.error_text` and `cip_forsta_survey.last_error`.

CONFIDENTIAL

4.3 Visibility and status

`cip_survey.load_status`	Meaning	Visible in reports
`loading`	being written	no
`verified`	proven equal to Forsta and derived	**yes**
`failed`	did not match, or a later step failed	no

If a reload fails **before** transaction A commits, a previously verified wave keeps `verified` (its data did not change). If it fails after, the wave becomes `failed` and the next run retries it.

4.4 Idempotency


- Every write is an upsert or a replace keyed on Forsta's own identifiers (`forsta_path`, `uuid`, `record`, variable label), so re-running a load never duplicates anything.
- A reload of the same Forsta survey reuses its `survey_id` and wave label — but only a wave that this pipeline loaded from the API (load log `forsta:{path}`); a wave loaded another way on the same path is never overwritten.

4.5 Reconciliation (independent check)

`python scripts/reconcile.py` (or `python -m etl.forsta_etl --reconcile`) re-reads every loaded wave from Forsta and compares **every stored answer**: codes exactly, numbers at the stored 4-decimal precision, texts exactly. Hibernated surveys are skipped with a warning. Last run (8 Oct 2026): **31 waves, 4,476,153 answers, 0 differences**. Legacy waves are compared with their `dwh_sm*` source the same way.

5. Derived data, storage design and performance

Everything a report needs is computed in the warehouse when a wave loads, so the portal and exports only read pre-computed rows.



5.1 Design principles

- **Long, not wide.** `cip_answer` holds one row per respondent × variable, so the schema never changes when weekly modules rotate. (A wide table — one column per variable — would break every week.)
- **Definitions per wave.** Forsta codes are not stable (`D2` , `BT14` , `DS1` – `DS7` changed meaning across waves), so questions are linked across waves by wording through **concepts**, never by code.
- **Conformed dimensions.** Concept + concept option are the shared “question” dimension across Forsta, Qualtrics and SurveyMonkey.
- **Pre-aggregated cube.** `cip_agg_cell` counts every answer once per standard cut and cohort.
- **Prefix** `cip_` (views `v_cip_`) so nothing collides with other `dwh_stg` tables.

CONFIDENTIAL

5.2 Cube — `cip_agg_cell`

Aspect	Rule
Rows	every answer of every reportable question (single, grid row, checkbox item) × cut × cohort, **qualified respondents only**
Cuts (`dim`)	total, gender, age_band, generation, income_band, census_region, urbanicity
Cohorts	everyone (`cohort_id NULL`) and each current cohort (`config/cohorts.yml` , e.g. Beauty shoppers)
Measures	`n` , `base_n` , `sum_age_mid` , `n_age_mid` , `sum_income_mid_k` , `n_income_mid` (averages without raw rows)
Bases	single/grid: who answered that row; checkbox: everyone who answered the question (“Total answering”)
Concept link	`map_key = question:item:option` , joined to `cip_concept_map` at read time, so confirming a mapping needs no rebuild
Build	answers read once into a temporary table with every cut; each cut × cohort is an aggregate over it

5.3 Search — `cip_search`

One row per wave (title, family, tags, path), per non-technical question (wording, code) and per concept (name, code, number of waves). MySQL FULLTEXT on `(title, body)` ; queries use boolean mode with required, prefix-matched words, skipping InnoDB stop-words; LIKE fallback for words under 3 characters (e.g. “D5”). Only verified waves are returned.

5.4 Line-by-line — `cip_tracker_line`

The data team’s “Weekly Line-By-Line Survey Data” rebuilt per tracker wave (`config/tracker_line.yml`): one JSON row per **qualified** respondent, keys in the team’s column order.

Column(s)	Rule
Month	first day of the wave’s month
date	completion `MM/DD/YYYY HH:MM`
Activities: … / Purchased In-store: … / Purchased Online: … / Food: … / Non-food: …	q1–q5, one column per item: the label when chosen, blank when not
Household Situation, Economic Situation	CS1, CS2
Gender, Age, Relationship Status, Ethnicity, Household Income, Primary Residence, State	D1–D6, D8 (Age a number when a single year)
start_date	survey start time
Age Range, Generation	profile bands in the team’s spelling (“over 60”, “Millenial”)

Not carried: D7 (the team omits it) and the panel `session` id (personal data). Check against the team’s file: `python -m etl.tracker_line --compare "Weekly Line-By-Line Survey Data.xlsx"` .

5.5 Concepts — harmonisation

Decision	Condition	Status
exact	same normalised wording and type; every answer already a concept option	confirmed
changed	same wording, new answers	proposed
similar	wording ≥ 0.85 alike (the highest unrelated pair measured 0.796)	proposed
new	nothing close	new concept, confirmed

A grid is harmonised row by row. Proposals wait on the Mappings page; answers trend only once confirmed.

5.6 Survey calendar — `cip_wave_module`

Rebuilt after every discovery and load from `config/survey_calendar.yml`: each Forsta survey × module with `kind` (sector · topic · seasonal · event · annual · adhoc), `is_lead`, `launched_on`, `season` (July–June), `series_wave_no`, `detected_by` (title or questions). A seasonal tracker is detected from its own question (XM3 “current status of your holiday shopping”) once loaded. `python -m etl.survey_calendar` prints the calendar and the next 12 expected lead sectors.

5.7 Indexes

Index	Serves
`cip_answer (survey_id, field_id, value_code, respondent_id)` covering	item incidence, cube build
`cip_answer (respondent_id, field_id)` unique	upserts, cohort rules
`cip_agg_cell (survey_id, map_key, cohort_id, dim)`, `(survey_id, question_id, dim)`	concept trends, standard views
`cip_survey (load_status, study_type, wave_date)`	wave pickers
`cip_forsta_survey (load_state, closed_at)`	the due list
`cip_search` FULLTEXT `(title, body)`	search
`cip_wave_module (module_code, season, series_wave_no)`	”wave N vs last year’s wave N”
`cip_tracker_line (wave_date, survey_id)`	line-by-line exports

5.8 Partitioning decision

Measured 8 Oct 2026: `cip_answer` 14.3 M rows, 1.3 GB data + 2.9 GB index (≈23 M rows after the SurveyMonkey reload). It is **not** physically partitioned:

- InnoDB cannot partition a table that has foreign keys or a FULLTEXT index; `cip_answer` has both (referential integrity and verbatim search).
- Every hot read already starts with `survey_id` on a covering index; reports read the cube, not raw answers.

Applied instead: **logical partitioning by wave** — `survey_id` leads every hot index, a wave loads, verifies and is replaced as one unit, and reads go to the pre-computed cube and line tables. Trigger to revisit: `cip_answer` above 100 M rows → `PARTITION BY HASH(survey_id)` with integrity moved to the loader’s verify step and verbatim search to `cip_search`.

5.9 Measured performance (over the VPN, P95)

Read	P95
Search (FULLTEXT)	0.26 s
Whole wave report (catalogue + cube + numbers + verbatims)	1.05 s
Standard view (cube, one cut)	0.25 s
Ad-hoc cohort, one wave	0.76 s
Five-wave pooled concept	0.27 s

Load time: 1.5–3 minutes per weekly wave (dominated by ~250 ms round trips; every step is batched).

6. Data dictionary — `cip_` tables and views in `dwh_stg`

Generated from the live database by `scripts/data_dictionary.py`; row counts are InnoDB estimates.

CONFIDENTIAL

Object	Kind	Rows (approx.)	Purpose
cip_agg_cell	table	1,796,799	Pre-computed counts per wave x answer x cut x cohort.
cip_answer	table	22,959,662	Every answer, long format. ~151k rows per wave.
cip_auth_session	table	2	Sign-in audit and revocation.
cip_banner	table	0	Cross-tab column groups.
cip_cohort_def	table	2	Named, versioned respondent rules.
cip_concept	table	1,558	Canonical questions, stable across waves and platforms.
cip_concept_map	table	63,375	Wave question/item/option -> canonical concept, proposed or confirmed.
cip_concept_option	table	12,708	Canonical answers, with band midpoints.
cip_crosstab	table	0	Cross-tab cells: percentage, count, true base, significance.
cip_crosstab_run	table	0	One row per cross-tab export, with its base and filter settings.
cip_field	table	51,932	Export column -> question/item map.
cip_forsta_survey	table	90	Register of every Forsta survey the key can see, and what the ETL did with it.
cip_item	table	45,281	List items and grid rows.
cip_load_error	table	0	Rows that failed validation, kept for review.
cip_load_log	table	393	Audit trail. Nothing enters CSI without a row here.
cip_load_state	table	0	Watermarks so incremental pulls never re-read a whole survey.
cip_option	table	28,832	Answer codes and their labels.
cip_profile	table	166,393	Demographic cuts, one row per respondent.
cip_profile_map	table	1,184	Which question feeds each demographic cut, per wave. Auditable and editable.
cip_publication	table	2	A delivered chart or table, frozen at a version.
cip_publication_cell	table	196	The frozen numbers of a publication.
cip_question	table	8,218	Questions, with their own answering base.
cip_respondent	table	165,948	One row per interview.
cip_respondent_cohort	table	6,215	Materialised cohort membership.
cip_saved_view	table	0	Saved filter + question sets, re-run against current data.
cip_search	table	10,034	Search index: one row per wave, question and concept (FULLTEXT).
cip_segment	table	0	Cross-tab columns with their Forsta definitions.
cip_survey	table	301	Survey waves.
cip_topic	table	15	Editorial grouping of questions.
cip_tracker_line	table	4,223	The data team's line-by-line rows: one per qualified tracker respondent, JSON in their column order.
cip_wave_module	table	242	Survey calendar: every Forsta survey x module (lead sector, topic, seasonal, event, annual, ad hoc).

CONFIDENTIAL

Object	Kind	Rows (approx.)	Purpose
cip_weight	table	0	One weight per respondent per scheme.
cip_weight_scheme	table	0	Named weighting schemes, per wave.
v_cip_answers	view		VIEW
v_cip_crosstab	view		VIEW
v_cip_grid	view		VIEW
v_cip_item_incidence	view		VIEW
v_cip_mapping_queue	view		VIEW
v_cip_question_base	view		VIEW
v_cip_single_distribution	view		VIEW
v_cip_survey_health	view		VIEW
v_cip_trend	view		VIEW

cip_agg_cell

Table — Pre-computed counts per wave x answer x cut x cohort.

CONFIDENTIAL

Column	Type	Null	Key	Default	Meaning
cell_id	bigint unsigned	NO	PRI		
survey_id	int unsigned	NO	MUL		→ cip_survey.survey_id (cascade)
cell_key	varchar(200)	NO			question:item:option:cohort:scheme:dim:value
question_id	int unsigned	NO	MUL		→ cip_question.question_id (cascade)
item_id	int unsigned	YES			
option_id	int unsigned	YES			
concept_option_id	int unsigned	YES	MUL		
cohort_id	int unsigned	YES			NULL = all qualified respondents
scheme_id	int unsigned	YES			NULL = unweighted
dim	varchar(30)	NO			total, gender, age_band, …
dim_value	varchar(120)	NO			
n	int	NO			
base_n	int	NO			
n_weighted	decimal(14,4)	YES			
base_weighted	decimal(14,4)	YES			
sum_age_mid	decimal(14,4)	YES			
sum_income_mid_k	decimal(16,4)	YES			
built_at	timestamp	NO		CURRENT_TIMESTAMP	
map_key	varchar(40)	YES			
n_age_mid	int	YES			
n_income_mid	int	YES			

Indexes: fk_agg_question (btree: question_id); ix_agg_concept (btree: concept_option_id, cohort_id, dim, survey_id); ix_agg_map (btree: survey_id, map_key, cohort_id, dim); ix_agg_question (btree: survey_id, question_id, dim); PRIMARY (btree: cell_id); uq_agg_cell (unique btree: survey_id, cell_key)

cip_answer

Table — Every answer, long format. ~151k rows per wave.

CONFIDENTIAL

Column	Type	Null	Key	Default	Meaning
`answer_id`	bigint unsigned	NO	PRI		
`respondent_id`	bigint unsigned	NO	MUL		→ cip_respondent.respondent_id (cascade)
`survey_id`	int unsigned	NO	MUL		denormalised for filter speed
`field_id`	int unsigned	NO	MUL		→ cip_field.field_id (cascade)
`value_code`	int	YES			0/1, 1-5, 1-54
`value_label`	varchar(500)	YES			resolved label, denormalised for display
`value_number`	decimal(18,4)	YES			open numeric
`value_text`	text	YES	MUL		open-ended verbatim

Indexes: `fk_answer_field` (btree: field_id); `ft_answer_text` (fulltext: value_text); `ix_answer_cover` (btree: survey_id, field_id, value_code, respondent_id); `ix_answer_respondent` (btree: respondent_id); `PRIMARY` (btree: answer_id); `uq_answer` (unique btree: respondent_id, field_id)

cip_auth_session

Table — Sign-in audit and revocation.

Column	Type	Null	Key	Default	Meaning
`session_id`	varchar(64)	NO	PRI		
`user_email`	varchar(200)	NO	MUL		
`user_name`	varchar(200)	YES			
`provider`	varchar(20)	NO		local	
`created_at`	timestamp	NO		CURRENT_TIMESTAMP	
`expires_at`	datetime	YES			
`revoked_at`	datetime	YES			
`request_meta`	varchar(500)	YES			host and user agent at sign-in

Indexes: `ix_auth_user` (btree: user_email, created_at); `PRIMARY` (btree: session_id)

cip_banner

Table — Cross-tab column groups.

Column	Type	Null	Key	Default	Meaning
`banner_id`	int unsigned	NO	PRI		
`survey_id`	int unsigned	NO	MUL		→ cip_survey.survey_id (cascade)
`banner_code`	varchar(50)	NO			AGE, GENDER, INCOME
`banner_name`	varchar(500)	NO			header text as printed
`source_q`	varchar(50)	YES			question the banner is built from
`sort_order`	smallint	NO		0	

Indexes: `PRIMARY` (btree: banner_id); `uq_banner` (unique btree: survey_id, banner_code)

cip_cohort_def

Table — Named, versioned respondent rules.

Column	Type	Null	Key	Default	Meaning
`cohort_id`	int unsigned	NO	PRI		
`cohort_code`	varchar(60)	NO	MUL		BEAUTY_SHOPPER
`version`	smallint unsigned	NO		1	
`cohort_name`	varchar(200)	NO			
`rule_json`	json	NO			any/all over concepts; see the spec §5.4
`base_note`	varchar(500)	YES			
`owner_email`	varchar(200)	YES			
`is_current`	tinyint(1)	NO		1	
`created_at`	timestamp	NO		CURRENT_TIMESTAMP	

Indexes: `PRIMARY` (btree: cohort_id); `uq_cohort_def` (unique btree: cohort_code, version)

cip_concept

Table — Canonical questions, stable across waves and platforms.

Column	Type	Null	Key	Default	Mea
`concept_id`	int unsigned	NO	PRI		
`concept_code`	varchar(80)	NO	UNI		BE/
`concept_name`	varchar(255)	NO			
`concept_group`	varchar(80)	YES	MUL		row gro
`topic_id`	smallint unsigned	YES	MUL		→ c null
`qtype`	enum('single','multi','grid_single','grid_multi','numeric','text','datetime')	NO			
`description`	varchar(1000)	YES			
`created_at`	timestamp	NO		CURRENT_TIMESTAMP	
`match_text`	varchar(2000)	YES			

Indexes: `fk_concept_topic` (btree: topic_id); `ix_concept_group` (btree: concept_group); `PRIMARY` (btree: concept_id); `uq_concept` (unique btree: concept_code)

cip_concept_map

Table — Wave question/item/option -> canonical concept, proposed or confirmed.

Column	Type	Null	Key	Default	Meaning
map_id	bigint unsigned	NO	PRI		
survey_id	int unsigned	NO	MUL		→ cip_survey.survey_id (ca
map_key	varchar(80)	NO			question_id:item_id:option_ absent
question_id	int unsigned	NO	MUL		→ cip_question.question_id
item_id	int unsigned	YES	MUL		→ cip_item.item_id (cascad
option_id	int unsigned	YES	MUL		→ cip_option.option_id (cas
concept_id	int unsigned	NO	MUL		→ cip_concept.concept_id (
concept_option_id	int unsigned	YES	MUL		→ cip_concept_option.concep (cascade)
status	enum('proposed','confirmed','rejected')	NO	MUL	proposed	
method	enum('exact_text','similar_text','manual')	NO			
confidence	decimal(5,4)	YES			
evidence	varchar(1000)	YES			why the harmoniser propos
reviewed_by	varchar(200)	YES			
reviewed_at	datetime	YES			
created_at	timestamp	NO		CURRENT_TIMESTAMP	

Indexes: fk_map_concept (btree: concept_id); fk_map_item (btree: item_id); fk_map_option (btree: option_id); fk_map_question (btree: question_id); ix_map_concept_option (btree: concept_option_id); ix_map_question (btree: survey_id, question_id); ix_map_status (btree: status); PRIMARY (btree: map_id); uq_concept_map (unique btree: survey_id, map_key)

cip_concept_option

Table — Canonical answers, with band midpoints.

Column	Type	Null	Key	Default	Meaning
concept_option_id	int unsigned	NO	PRI		
concept_id	int unsigned	NO	MUL		→ cip_concept.concept_id (cascade)
option_code	varchar(80)	NO			amazon
option_label	varchar(500)	NO			Amazon.com
sort_order	smallint	NO		0	
midpoint	decimal(12,4)	YES			numeric midpoint of a band: 23.5, 74.9995
net_group	varchar(50)	YES			TOP2, ANY_DRUGSTORE
is_nonresponse	tinyint(1)	NO		0	

Indexes: PRIMARY (btree: concept_option_id); uq_concept_option (unique btree: concept_id, option_code)

cip_crosstab

Table — Cross-tab cells: percentage, count, true base, significance.

Column	Type	Null	Key	Default	Meaning
`crosstab_id`	bigint unsigned	NO	PRI		
`run_id`	int unsigned	NO	MUL		→ cip_crosstab_run.run_id (cascade)
`survey_id`	int unsigned	NO	MUL		
`question_id`	int unsigned	NO	MUL		→ cip_question.question_id (cascade)
`item_id`	int unsigned	YES	MUL		
`option_id`	int unsigned	YES			
`segment_id`	int unsigned	NO	MUL		→ cip_segment.segment_id (cascade)
`item_label`	varchar(500)	YES			grid sub-item, e.g. the retailer being rated in DP7
`stub_label`	varchar(1000)	NO			row label as printed
`stub_key`	varchar(600)	NO			item_label
`stub_type`	enum('item','net','mean','count','base')	NO		item	
`pct`	decimal(9,6)	YES			0.527228 = 52.7%
`count_n`	int	YES			
`answer_base_n`	int	YES			the true denominator: count_n / pct
`sig_letters`	varchar(40)	YES			segments this cell significantly beats

Indexes: `fk_crosstab_question` (btree: question_id); `fk_crosstab_segment` (btree: segment_id); `ix_crosstab_item` (btree: item_id); `ix_crosstab_lookup` (btree: survey_id, question_id, segment_id); `PRIMARY` (btree: crosstab_id); `uq_crosstab` (unique btree: run_id, question_id, stub_key, segment_id)

cip_crosstab_run

Table — One row per cross-tab export, with its base and filter settings.

Column	Type	Null	Key	Default	Meaning
run_id	int unsigned	NO	PRI		
survey_id	int unsigned	NO	MUL		→ cip_survey.survey_id (cascade)
run_label	varchar(255)	NO			
respondent_base	varchar(100)	YES			”Qualified Only”
extra_filter	varchar(500)	YES			
table_set	varchar(100)	YES			
pct_base	varchar(100)	YES			”Total Answering” — see csi_crosstab.answer_base_n
stat_test	varchar(100)	YES			
date_from	date	YES			
date_to	date	YES			
source_type	enum(‘api’,’excel’)	NO		excel	
source_file	varchar(255)	YES			
is_current	tinyint(1)	NO		1	
created_at	timestamp	NO		CURRENT_TIMESTAMP	

Indexes: ix_run_survey (btree: survey_id, is_current); PRIMARY (btree: run_id)

cip_field

Table — Export column -> question/item map.

Column	Type	Null	Key	Default	Meaning
field_id	int unsigned	NO	PRI		
survey_id	int unsigned	NO	MUL		→ cip_survey.survey_id (cascade)
question_id	int unsigned	YES	MUL		→ cip_question.question_id (cascade)
item_id	int unsigned	YES	MUL		set when the column is one row of a list/grid → cip_item.item_id (cascade)
field_name	varchar(100)	NO			exact export header: q1r1, D2, uuid
value_type	enum(‘code’,’numeric’,’text’,’datetime’)	NO			
col_position	smallint	YES			

Indexes: ix_field_item (btree: item_id); ix_field_question (btree: question_id); PRIMARY (btree: field_id); uq_field (unique btree: survey_id, field_name)

cip_forsta_survey

Table — Register of every Forsta survey the key can see, and what the ETL did with it.

Column	Type	Null	Key	Default	Meaning
forsta_path	varchar(255)	NO	PRI		selfserve/58f/260907
title	varchar(500)	NO			
state	varchar(30)	NO			Forsta state: testing, live, closed
hibernated	tinyint(1)	NO		0	1 = Forsta answers 428 until reactivated
tags	varchar(500)	YES			
study_type	enum('tracker','annual','adhoc')	NO		adhoc	
created_on	datetime	YES			
launched_at	datetime	YES			
closed_at	datetime	YES			
qualified_n	int	YES			
total_n	int	YES			
last_seen	datetime	NO			
load_state	enum('new','due','loaded','failed','hibernated','testing')	NO	MUL	new	
survey_id	int unsigned	YES			cip_survey row once loaded
loaded_at	datetime	YES			
last_error	varchar(1000)	YES			

Indexes: ix_forsta_due (btree: load_state, closed_at); PRIMARY (btree: forsta_path)

cip_item

Table — List items and grid rows.

Column	Type	Null	Key	Default	Meaning
item_id	int unsigned	NO	PRI		
question_id	int unsigned	NO	MUL		→ cip_question.question_id (cascade)
item_code	varchar(50)	NO			q1r1, DP7r3
item_label	varchar(1000)	NO			
item_short	varchar(255)	YES			trimmed for axis ticks
is_exclusive	tinyint(1)	NO		0	1 = "None of these" — drop from rankings
is_other	tinyint(1)	NO		0	1 = Other (please specify)
sort_order	smallint	NO		0	
left_label	varchar(500)	YES			
right_label	varchar(500)	YES			

Indexes: PRIMARY (btree: item_id); uq_item (unique btree: question_id, item_code)

cip_load_error

Table — Rows that failed validation, kept for review.

Column	Type	Null	Key	Default	Meaning
`error_id`	bigint unsigned	NO	PRI		
`load_id`	bigint unsigned	NO	MUL		→ cip_load_log.load_id (cascade)
`record_ref`	varchar(200)	YES			record number or sheet!cell
`reason`	varchar(500)	NO			
`payload`	json	YES			

Indexes: `ix_error_load` (btree: load_id); `PRIMARY` (btree: error_id)

cip_load_log

Table — Audit trail. Nothing enters CSI without a row here.

Column	Type	Null	Key	Default	Meaning
`load_id`	bigint unsigned	NO	PRI		
`survey_id`	int unsigned	YES	MUL		
`source_type`	enum('api','excel','manual')	NO			
`object_type`	enum('datamap','data','crosstab','profile')	NO			
`source_ref`	varchar(500)	YES			endpoint URL or file name
`rows_read`	int	NO		0	
`rows_loaded`	int	NO		0	
`rows_bad`	int	NO		0	
`status`	enum('running','success','partial','failed')	NO		running	
`error_text`	text	YES			
`started_at`	datetime	NO		CURRENT_TIMESTAMP	
`finished_at`	datetime	YES			
`archive_uri`	varchar(1000)	YES			
`archive_sha256`	char(64)	YES			

Indexes: `ix_load_survey` (btree: survey_id, object_type, started_at); `PRIMARY` (btree: load_id)

cip_load_state

Table — Watermarks so incremental pulls never re-read a whole survey.

CONFIDENTIAL

Column	Type	Null	Key	Default	Meaning
`feed_name`	varchar(100)	NO	PRI		
`survey_id`	int unsigned	YES			
`last_record`	int unsigned	YES			
`last_completed`	datetime	YES			watermark for incremental pulls
`last_ack_at`	datetime	YES			
`last_status`	varchar(50)	YES			
`updated_at`	timestamp	NO		CURRENT_TIMESTAMP	

Indexes: `PRIMARY` (btree: feed_name)

cip_option

Table — Answer codes and their labels.

Column	Type	Null	Key	Default	Meaning
`option_id`	int unsigned	NO	PRI		
`question_id`	int unsigned	NO	MUL		→ cip_question.question_id (cascade)
`value_code`	int	NO			
`value_label`	varchar(500)	NO			
`is_nonresponse`	tinyint(1)	NO		0	Don’t know / Prefer not to say — excluded from Top-2-Box
`net_group`	varchar(50)	YES			TOP2 / BOT2 for net calculations
`sort_order`	smallint	NO		0	

Indexes: `PRIMARY` (btree: option_id); `uq_option` (unique btree: question_id, value_code)

cip_profile

Table — Demographic cuts, one row per respondent.

CONFIDENTIAL

Column	Type	Null	Key	Default	Meaning
respondent_id	bigint unsigned	NO	PRI		→ cip_respondent.respondent_id (cascade)
survey_id	int unsigned	NO	MUL		→ cip_survey.survey_id (cascade)
gender	varchar(40)	YES			D1
age_years	smallint	YES			D2 resolved to a number
age_band	varchar(20)	YES			18-29 / 30-44 / 45-60 / Over 60
generation	varchar(20)	YES			GenZ / Millennial / GenX / Boomer
relationship	varchar(60)	YES			D3
ethnicity	varchar(60)	YES			D4
income_band	varchar(40)	YES			D5
urbanicity	varchar(20)	YES			D6
political	varchar(120)	YES			D7
state_name	varchar(60)	YES			D8
census_region	varchar(20)	YES			derived from D8
outlook_income	varchar(40)	YES			CS1
outlook_economy	varchar(40)	YES			CS2
weight	decimal(10,6)	NO		1.000000	reserved; these waves are unweighted
age_mid	decimal(6,2)	YES			
income_mid_k	decimal(10,4)	YES			

Indexes: ix_profile_cuts (btree: survey_id, generation, gender, income_band); ix_profile_region (btree: survey_id, census_region); PRIMARY (btree: respondent_id)

cip_profile_map

Table — Which question feeds each demographic cut, per wave. Auditable and editable.

Column	Type	Null	Key	Default	Meaning
survey_id	int unsigned	NO	PRI		→ cip_survey.survey_id (cascade)
dimension	varchar(40)	NO	PRI		gender, age, income_band, …
qcode	varchar(50)	NO			the question that supplies it
resolved_by	enum('config','detected','manual')	NO		detected	
updated_at	timestamp	NO		CURRENT_TIMESTAMP	

Indexes: PRIMARY (btree: survey_id, dimension)

cip_publication

Table — A delivered chart or table, frozen at a version.

Column	Type	Null	Key	Default	Meaning
publication_id	int unsigned	NO	PRI		
pub_code	varchar(80)	NO	MUL		BEAUTY_RETAILER_PROFILE
version	smallint unsigned	NO		1	
pub_name	varchar(255)	NO			
owner_email	varchar(200)	YES			
definition	json	NO			waves, concepts, cohort, break, scheme, min base
footnote	varchar(2000)	YES			
destination	varchar(1000)	YES			where it was delivered, e.g. SharePoint URL
status	enum('draft','published','withdrawn')	NO		draft	
published_at	datetime	YES			
created_at	timestamp	NO		CURRENT_TIMESTAMP	

Indexes: PRIMARY (btree: publication_id); uq_publication (unique btree: pub_code, version)

cip_publication_cell

Table — The frozen numbers of a publication.

Column	Type	Null	Key	Default	Meaning
cell_id	bigint unsigned	NO	PRI		
publication_id	int unsigned	NO	MUL		→ cip_publication.publication_id (cascade)
row_key	varchar(250)	NO			
col_key	varchar(250)	NO			
n	int	YES			
base_n	int	YES			
value	decimal(18,6)	YES			

Indexes: PRIMARY (btree: cell_id); uq_publication_cell (unique btree: publication_id, row_key, col_key)

cip_question

Table — Questions, with their own answering base.

Column	Type	Null	Key	Default	Meaning
`question_id`	int unsigned	NO	PRI		
`survey_id`	int unsigned	NO	MUL		→ cip_survey.survey_id (cascade)
`topic_id`	smallint unsigned	YES	MUL		→ cip_topic.topic_id (set null)
`qcode`	varchar(50)	NO			q1, DP7, BN3
`qtext`	text	NO			
`qtext_short`	varchar(255)	YES			chart title
`qtype`	enum('single','multi','grid_single','grid_multi','numeric','text','datetime')	NO			
`value_min`	int	YES			
`value_max`	int	YES			
`is_technical`	tinyint(1)	NO		0	
`is_multi`	tinyint(1)	NO		0	1 = respondent may pick several
`base_n`	int	YES			respondents who reached this question
`base_desc`	varchar(255)	YES			e.g. "Bought from a department store in past 3 months"
`asked_if`	varchar(500)	YES			routing condition, when known
`sort_order`	smallint	NO		0	
`is_virtual`	tinyint(1)	NO		0	

Indexes: `ix_question_topic` (btree: topic_id); `PRIMARY` (btree: question_id); `uq_question` (unique btree: survey_id, qcode)

cip_respondent

Table — One row per interview.

Column	Type	Null	Key	Default	Meaning
respondent_id	bigint unsigned	NO	PRI		
survey_id	int unsigned	NO	MUL		→ cip_survey.survey_id (cascade)
record_no	int unsigned	NO			Forsta [record]
forsta_uuid	varchar(64)	YES			
status_code	tinyint	YES			1 Terminated 2 Overquota 3 Qualified 4 Partial
status_label	varchar(30)	YES			
is_qualified	tinyint(1)	NO		0	default analysis base
started_at	datetime	YES			
completed_at	datetime	YES			
interview_secs	int	YES			
panel_source	varchar(100)	YES			
sample_rid	varchar(100)	YES			
markers	varchar(1000)	YES			quota buckets as Forsta records them
device	varchar(50)	YES			
os	varchar(100)	YES			
browser	varchar(100)	YES			
dropout_qcode	varchar(50)	YES			
load_id	bigint unsigned	YES			
loaded_at	timestamp	NO		CURRENT_TIMESTAMP	
respondent_key	char(64)	YES			
quality_flag	varchar(40)	YES			

Indexes: ix_respondent_completed (btree: survey_id, completed_at); ix_respondent_key (btree: survey_id, respondent_key); ix_respondent_qualified (btree: survey_id, is_qualified); PRIMARY (btree: respondent_id); uq_respondent (unique btree: survey_id, record_no)

cip_respondent_cohort

Table — Materialised cohort membership.

Column	Type	Null	Key	Default	Meaning
cohort_id	int unsigned	NO	PRI		→ cip_cohort_def.cohort_id (cascade)
respondent_id	bigint unsigned	NO	PRI		→ cip_respondent.respondent_id (cascade)
survey_id	int unsigned	NO	MUL		→ cip_survey.survey_id (cascade)

Indexes: fk_rcohort_survey (btree: survey_id); ix_rcohort_respondent (btree: respondent_id); ix_rcohort_survey (btree: cohort_id, survey_id); PRIMARY (btree: cohort_id, respondent_id)

cip_saved_view

Table — Saved filter + question sets, re-run against current data.

Column	Type	Null	Key	Default	Meaning
`view_id`	int unsigned	NO	PRI		
`survey_id`	int unsigned	NO	MUL		→ cip_survey.survey_id (cascade)
`view_name`	varchar(160)	NO			
`owner_email`	varchar(200)	NO	MUL		
`is_shared`	tinyint(1)	NO		0	1 = visible to the whole team
`definition`	text	NO			JSON: criteria, question ids, break
`description`	varchar(500)	YES			
`created_at`	timestamp	NO		CURRENT_TIMESTAMP	
`updated_at`	timestamp	NO		CURRENT_TIMESTAMP	

Indexes: `ix_saved_view_survey` (btree: survey_id, is_shared); `PRIMARY` (btree: view_id); `uq_saved_view` (unique btree: owner_email, view_name)

cip_search

Table — Search index: one row per wave, question and concept (FULLTEXT).

Column	Type	Null	Key	Default	Meaning
`search_id`	int unsigned	NO	PRI		
`kind`	enum('survey','question','concept')	NO	MUL		
`survey_id`	int unsigned	YES			
`question_id`	int unsigned	YES			
`concept_id`	int unsigned	YES			
`wave_label`	varchar(50)	YES			
`waves`	int	YES			concept: waves it appears in
`title`	varchar(500)	NO	MUL		
`body`	text	YES			

Indexes: `ft_search` (fulltext: title, body); `ix_search_kind` (btree: kind, wave_label); `PRIMARY` (btree: search_id)

cip_segment

Table — Cross-tab columns with their Forsta definitions.

Column	Type	Null	Key	Default	Meaning
`segment_id`	int unsigned	NO	PRI		
`banner_id`	int unsigned	NO	MUL		→ cip_banner.banner_id (cascade)
`survey_id`	int unsigned	NO	MUL		→ cip_survey.survey_id (cascade)
`seg_letter`	varchar(4)	YES			stat-test letter A..N1
`seg_label`	varchar(255)	NO			Male, GenZ, $50,000 - $99,999
`seg_definition`	varchar(2000)	YES			Forsta expression, kept verbatim so a wave is auditable
`seg_base_n`	int	YES			segment size — NOT the denominator of a routed question
`is_total`	tinyint(1)	NO		0	
`low_base`	enum('','*','**')	NO			* caution, ** too small to report
`sort_order`	smallint	NO		0	

Indexes: `ix_segment_survey` (btree: survey_id); `PRIMARY` (btree: segment_id); `uq_segment` (unique btree: banner_id, seg_label)

cip_survey

Table — Survey waves.

CONFIDENTIAL

Column	Type	Null	Key	Default	Meaning
survey_id	int unsigned	NO	PRI		
forsta_host	varchar(100)	NO	MUL		se1.decipherinc.com
forsta_path	varchar(255)	NO			selfserve/58f/260908
title	varchar(500)	NO			
survey_family	varchar(100)	YES	MUL		CSI-US — groups waves for trending
wave_label	varchar(50)	NO			fielding week, 2026-09-28
wave_date	date	YES			
field_start	datetime	YES			
field_end	datetime	YES			
country	char(2)	YES		US	
status	enum('draft','fielding','closed','archived')	NO		closed	
datamap_hash	char(64)	YES			sha256 of the datamap; detects questionnaire change
created_at	timestamp	NO		CURRENT_TIMESTAMP	
updated_at	timestamp	NO		CURRENT_TIMESTAMP	
platform	enum('forsta','qualtrics','surveymonkey')	NO	MUL	forsta	
source_ref	varchar(255)	NO			
study_type	enum('tracker','annual','adhoc')	NO		tracker	
load_status	enum('loading','verified','failed','superseded')	NO	MUL	verified	
language	varchar(10)	NO		en	
sample_source	varchar(50)	YES			
total_n	int	YES			
tags	varchar(500)	YES			

Indexes: `ix_survey_family` (btree: survey_family, wave_date); `ix_survey_pick` (btree: load_status, study_type, wave_date); `PRIMARY` (btree: survey_id); `uq_survey` (unique btree: forsta_host, forsta_path, wave_label); `uq_survey_source` (unique btree: platform, source_ref, wave_label)

cip_topic

Table — Editorial grouping of questions.

Column	Type	Null	Key	Default	Meaning
topic_id	smallint unsigned	NO	PRI		
topic_code	varchar(40)	NO	UNI		DEPT_STORES
topic_name	varchar(150)	NO			Department Stores
is_technical	tinyint(1)	NO		0	1 = paradata/quota, hidden by default
sort_order	smallint	NO		0	

Indexes: PRIMARY (btree: topic_id); uq_topic (unique btree: topic_code)

cip_tracker_line

Table — The data team's line-by-line rows: one per qualified tracker respondent, JSON in their column order.

Column	Type	Null	Key	Default	Meaning
respondent_id	bigint unsigned	NO	PRI		
survey_id	int unsigned	NO			
wave_date	date	NO	MUL		
line	json	NO			header -> value, config/tracker_line.yml order

Indexes: ix_line_wave (btree: wave_date, survey_id); PRIMARY (btree: respondent_id)

cip_wave_module

Table — Survey calendar: every Forsta survey x module (lead sector, topic, seasonal, event, annual, ad hoc).

Column	Type	Null	Key	Default	Meaning
forsta_path	varchar(255)	NO	PRI		
module_code	varchar(40)	NO	PRI		
module_name	varchar(120)	NO			
kind	enum('sector','topic','seasonal','event','annual','adhoc')	NO			
is_lead	tinyint(1)	NO		0	the tracker week's lead sector
launched_on	date	YES	MUL		
season	smallint	YES			seasonal / annual: Jul-Jun season year
series_wave_no	smallint	YES			nth wave of this module (in its season)
survey_id	int unsigned	YES			set once loaded
detected_by	enum('title','questions')	NO		title	

Indexes: ix_module_day (btree: launched_on); ix_module_series (btree: module_code, season, series_wave_no); PRIMARY (btree: forsta_path, module_code)

cip_weight

Table — One weight per respondent per scheme.

Column	Type	Null	Key	Default	Meaning
`respondent_id`	bigint unsigned	NO	PRI		→ cip_respondent.respondent_id (cascade)
`scheme_id`	int unsigned	NO	PRI		→ cip_weight_scheme.scheme_id (cascade)
`weight`	decimal(12,6)	NO			

Indexes: `ix_weight_scheme` (btree: scheme_id); `PRIMARY` (btree: respondent_id, scheme_id)

cip_weight_scheme

Table — Named weighting schemes, per wave.

Column	Type	Null	Key	Default	Meaning
`scheme_id`	int unsigned	NO	PRI		
`survey_id`	int unsigned	NO	MUL		→ cip_survey.survey_id (cascade)
`scheme_code`	varchar(60)	NO			CENSUS_AGE_GENDER_REGION
`method`	varchar(100)	YES			raking, cell, …
`targets`	json	YES			
`description`	varchar(500)	YES			
`created_at`	timestamp	NO		CURRENT_TIMESTAMP	

Indexes: `PRIMARY` (btree: scheme_id); `uq_weight_scheme` (unique btree: survey_id, scheme_code)

v_cip_answers

View — VIEW

CONFIDENTIAL

Column	Type	Null	Key	Default	Meaning
survey_id	int unsigned	NO			
survey_family	varchar(100)	YES			CSI-US — groups waves for trending
wave_label	varchar(50)	NO			fielding week, 2026-09-28
wave_date	date	YES			
respondent_id	bigint unsigned	NO		0	
is_qualified	tinyint(1)	NO		0	default analysis base
gender	varchar(40)	YES			D1
age_band	varchar(20)	YES			18-29 / 30-44 / 45-60 / Over 60
generation	varchar(20)	YES			GenZ / Millennial / GenX / Boomer
ethnicity	varchar(60)	YES			D4
income_band	varchar(40)	YES			D5
urbanicity	varchar(20)	YES			D6
census_region	varchar(20)	YES			derived from D8
political	varchar(120)	YES			D7
topic_name	varchar(150)	YES			Department Stores
qcode	varchar(50)	YES			q1, DP7, BN3
qtext	text	YES			
qtext_short	varchar(255)	YES			chart title
qtype	enum('single','multi','grid_single','grid_multi','numeric','text','datetime')	YES			
question_base_n	int	YES			respondents who reached this question
item_code	varchar(50)	YES			q1r1, DP7r3
item_label	varchar(1000)	YES			
field_name	varchar(100)	NO			exact export header: q1r1, D2, uuid
value_code	int	YES			0/1, 1-5, 1-54
value_label	varchar(500)	YES			resolved label, denormalised for display

CONFIDENTIAL

Column	Type	Null	Key	Default	Meaning
value_number	decimal(18,4)	YES			open numeric
weight	decimal(10,6)	YES		1.000000	reserved; these waves are unweighted

v_cip_crosstab

View — VIEW

Column	Type	Null	Key	Default	Meaning
survey_id	int unsigned	NO			
wave_label	varchar(50)	NO			fielding week, 2026-09-28
qcode	varchar(50)	NO			q1, DP7, BN3
qtext	text	NO			
item_label	varchar(500)	YES			grid sub-item, e.g. the retailer being rated in DP7
stub_label	varchar(1000)	NO			row label as printed
stub_type	enum('item','net','mean','count','base')	NO		item	
banner_name	varchar(500)	NO			header text as printed
seg_letter	varchar(4)	YES			stat-test letter A..N1
seg_label	varchar(255)	NO			Male, GenZ, $50,000 - $99,999
segment_size_n	int	YES			segment size — NOT the denominator of a routed question
denominator_n	int	YES			the true denominator: count_n / pct
low_base	enum('','*','**')	NO			* caution, ** too small to report
pct	decimal(9,6)	YES			0.527228 = 52.7%
count_n	int	YES			
sig_letters	varchar(40)	YES			segments this cell significantly beats
pct_base	varchar(100)	YES			"Total Answering" — see csi_crosstab.answer_base_n
respondent_base	varchar(100)	YES			"Qualified Only"

v_cip_grid

View — VIEW

CONFIDENTIAL

Column	Type	Null	Key	Default	Meaning
survey_id	int unsigned	NO			
qcode	varchar(50)	NO			q1, DP7, BN3
qtext_short	varchar(255)	YES			chart title
item_label	varchar(1000)	NO			
value_code	int	YES			0/1, 1-5, 1-54
scale_label	varchar(500)	YES			
scale_order	smallint	YES		0	
n	bigint	NO		0	
pct	decimal(26,5)	YES			

v_cip_item_incidence

View — VIEW

Column	Type	Null	Key	Default	Meaning
survey_id	int unsigned	NO			denormalised for filter speed
question_id	int unsigned	NO		0	
qcode	varchar(50)	NO			q1, DP7, BN3
qtext_short	varchar(255)	YES			chart title
item_id	int unsigned	NO		0	
item_label	varchar(1000)	NO			
is_exclusive	tinyint(1)	NO		0	1 = “None of these” — drop from rankings
base_n	bigint	YES			
selected_n	decimal(23,0)	YES			
pct	decimal(29,5)	YES			

v_cip_mapping_queue

View — VIEW

CONFIDENTIAL

Column	Type	Null	Key	Default	Mean
survey_id	int unsigned	NO			
wave_label	varchar(50)	NO			fieldir 28
survey_title	varchar(500)	NO			
question_id	int unsigned	NO			
item_id	int unsigned	YES			
qcode	varchar(50)	NO			q1, D
qtext	text	NO			
qtype	enum('single','multi','grid_single','grid_multi','numeric','text','datetime')	NO			
item_label	varchar(1000)	YES			
concept_id	int unsigned	NO			
concept_code	varchar(80)	NO			BEAU
concept_name	varchar(255)	NO			
method	enum('exact_text','similar_text','manual')	NO			
confidence	decimal(5,4)	YES			
evidence	varchar(1000)	YES			why t propc
created_at	timestamp	NO		CURRENT_TIMESTAMP	

v_cip_question_base

View — VIEW

Column	Type	Null	Key	Default	Meaning
survey_id	int unsigned	NO			
topic_name	varchar(150)	YES			Department Stores
qcode	varchar(50)	NO			q1, DP7, BN3
qtext_short	varchar(255)	YES			chart title
qtype	enum('single','multi','grid_single','grid_multi','numeric','text','datetime')	NO			
is_multi	tinyint(1)	NO		0	1 = respondent may pick several
base_n	int	YES			respondents who reached this question
base_desc	varchar(255)	YES			e.g. "Bought from a department store in past 3 months"
pct_of_wave	decimal(15,1)	YES			

v_cip_single_distribution

View — VIEW

Column	Type	Null	Key	Default	Meaning
survey_id	int unsigned	NO			
question_id	int unsigned	NO		0	
qcode	varchar(50)	NO			q1, DP7, BN3
qtext_short	varchar(255)	YES			chart title
value_code	int	YES			0/1, 1-5, 1-54
answer_label	varchar(500)	YES			
is_nonresponse	tinyint(1)	YES		0	Don’t know / Prefer not to say — excluded from Top-2-Box
net_group	varchar(50)	YES			TOP2 / BOT2 for net calculations
n	bigint	NO		0	
pct	decimal(26,5)	YES			
base_n	decimal(42,0)	YES			

v_cip_survey_health

View — VIEW

Column	Type	Null	Key	Default	Meaning
survey_id	int unsigned	NO		0	
title	varchar(500)	NO			
wave_label	varchar(50)	NO			fielding week, 2026-09-28
total_records	bigint	NO		0	
qualified_n	decimal(25,0)	YES			
terminated_n	decimal(23,0)	YES			
overquota_n	decimal(23,0)	YES			
partial_n	decimal(23,0)	YES			
avg_loi_minutes	decimal(12,1)	YES			
first_complete	datetime	YES			
last_complete	datetime	YES			

v_cip_trend


View — VIEW

Column	Type	Null	Key	Default	Meaning
`survey_family`	varchar(100)	YES			CSI-US — groups waves for trending
`wave_label`	varchar(50)	NO			fielding week, 2026-09-28
`wave_date`	date	YES			
`qcode`	varchar(50)	NO			q1, DP7, BN3
`item_label`	varchar(1000)	NO			
`pct`	decimal(29,5)	YES			
`base_n`	bigint	YES			

7. Survey patterns — measured, stored and applied

Source of every number below: the 90 surveys in `cip_forsta_survey` (Jul 2025 – Oct 2026) and the 23 loaded weekly waves. Rules live in `config/survey_calendar.yml`; results in `cip_wave_module`.

CONFIDENTIAL



CONFIDENTIAL

7.1 Cadence

Measure	Value
Tracker launches (UTC)	Monday 12–13 in 56 of 66 waves; Monday 14–16 in 7; Friday 2; Tuesday 1
Close (IST)	Monday 20:00 → Wednesday 23:00
Fielding time	median 13.1 h, 90th percentile 49 h, range 2.4 h – 6 days
Qualified	400–414 per tracker wave (fixed quota ≈400)
Total started	403 – 887
Gender quota	exactly balanced (7,000 / 7,000 in the team's Feb–Sep file)
Hibernation	≈3–4 months after close (`428`); deletion 365 days after creation

7.2 Title grammar

`Shopping and Spending – inc <part> + <part> + …` — the first part is the **lead sector**; each further part is a recurring topic, a seasonal tracker, or a one-off event. Matching (case-insensitive regex, first part only for the lead):

Kind	Codes (config)
sector	DRUGSTORE, ECOMMERCE, LUXURY, DEPT_STORES, BEAUTY, HOME_FURNISHINGS, HOME_IMPROVEMENT, SOCIAL_COMMERCE, OFF_PRICE, APPAREL, MASS_WAREHOUSE, FOOTWEAR
topic	TARIFFS_INFLATION, GLP1, GENAI, FINANCIAL_HEALTH, MIDEAST_GAS
seasonal	HOLIDAY_TRACKER (title "holiday track…" or question "current status of your holiday shopping")
event	any other part, slugged (PRIME_DAY, LABOR_DAY, BLACK_FRIDAY …)
annual	HOLIDAY_SHOPPING, AMAZON_APPAREL, ONLINE_GROCERY, BACK_TO_SCHOOL (not "inc" titles)
adhoc	everything else, slug of the title

7.3 Rotation evidence (weeks between appearances of each lead sector)

Sector	Gaps (weeks)
Drugstore	12, 12, 12, 12, 12
eCommerce	12, 12, 12, 12, 12
Luxury	12, 12, 11, 12, 12
Department stores	12, 12, 12, 12, 12
Beauty	12, 12, 12, 12, 12
Home furnishings	13, 11, 12, 12, 12
Home improvement	13, 11, 12, 12
Social commerce	24 (replaced by a Holiday week, Nov 3 2025), 12, 12
Off-price / dollar, Apparel, Mass / warehouse, Footwear	12, 12, 12, 12

Prediction check: after Home furnishings (Oct 5 2026) the rotation gives Home improvement for Oct 12 — the Forsta survey `261000` is “Home Improvement/DIY + Holiday Tracker + …”.

7.4 Module question codes

Prefix	Module	Example
q1–q5, CS1–CS2, D1–D8	Core (every wave)	see the business description, section 4.1
CS3+, D9+ , q6+	Topical extensions of the core (tax filing, government shutdown, expenses)	CS3 “Have you filed your 2026 income tax return, yet?”
BT	Beauty	BT1 “Have you purchased any beauty products … in the past three months?”
XM	Holiday tracker	XM3 status · XM1 bought in last 7 days · XM1A categories · XM2 retailers
HX	Holiday outlook	HX1 spend vs last year · HX6 bipolar preferences
TF / T	Tariffs	TF1 “What impact, if any, do you think tariffs have on you personally?”
IN	Inflation	IN1 “Have you noticed any recent price changes in retail?”
GP	GLP-1	GP1 “Are you currently using a GLP-1 drug like Ozempic?”
G, GU	GenAI	GU1 “Which, if any, of the following AI tools have you used …?”
F	Financial health	F1 “How long could you cover all of your bills … using just your personal savings?”
AP, DNM, R	Apparel, denim, returns	
HF, HI	Home furnishings, home improvement	
DP, LX, FW, EC, SC, O, DS, M	Dept stores, luxury, footwear, eCommerce, social commerce, off-price, dollar stores, mass	
PB, BF, APR, PDR, BD, JP, SD	Holiday purchases, Black Friday, Prime Day, Big Deal Days, Singles Day	
E, ID/IDR, FDR, LDR, HW, FWC/FWCR	Easter, July 4th, Father’s Day, Labor Day, Halloween, FIFA World Cup	
EAT, CPG, SHRNK, BN, DJ, BST, EH, PF	Restaurants, packaged goods, shrink, BNPL, diamonds, store tech, experience, preferences	

Codes are **not** stable across waves (the same code can carry different wording), which is why the harmoniser matches on wording.

CONFIDENTIAL

7.5 Known scheme changes

Change	Effect	Handling
D2 age: bands (to Oct 2025) → single years (2026)	Age band / generation derivation differs	`classify_age` derives bands from either
XM1 (bought in last 7 days): asked of everyone in 2025, only of those who started shopping in 2026	Not comparable year on year	flagged in outputs
HX6 bipolar grid: blank answer titles	Excel route lost ~3,300 answers	API route stores left/right statements

7.6 Applying the patterns

- **Expect the next wave** — `python -m etl.survey_calendar` lists the next 12 lead sectors.
- **Trend a sector** — read waves where `cip_wave_module.module_code = 'BEAUTY' AND is_lead = 1` (every 12 weeks).
- **Year-on-year holiday** — join this season's `HOLIDAY_TRACKER` wave N to last season's wave N on `series_wave_no`.
- **New module or sector** — add a line to `config/survey_calendar.yml`; the next run re-labels every survey.

8. Operations runbook

8.1 Schedule

Scheduler	launchd user agent `com.coresight.cip-forsta-etl` (plist in `scripts/launchd/`, installed in `~/Library/LaunchAgents/`)
Command	`.venv/bin/python scripts/weekly_forsta.py` in the repository
Times (IST)	daily **09:00**; Tuesday and Wednesday **14:00** and **23:30**
Why these times	waves launch Monday 12–13 UTC and close Monday 20:00 – Wednesday 23:00 IST; a missed slot runs when the Mac wakes
Log	`logs/forsta-etl.log` (appended)
Server equivalent	cron `0 9 * * *`, `0 14 * * 2,3`, `30 23 * * 2,3` with `APP_ENV=staging`

8.2 What one run does

1. Database health check — 4 tries, 5 minutes apart.
2. Forsta key check — `GET rh/users/self`.
3. Schema check — `cip_forsta_survey`, `cip_search`, `cip_tracker_line` must exist.
4. Discover → load every due wave → verify → derive (see sections 2–5).
5. Re-check every frozen publication for drift.

8.3 Exit codes

Code	Meaning	Action
0	Everything due loaded and verified (or nothing due)	none
1	A wave failed to load or verify	read `cip_forsta_survey.last_error`; the next run retries
2	Forsta rejected the key, it is not configured, or the schema is behind the code	renew the key / run `python scripts/init_db.py`
3	Loaded, but a published number moved	review on the Publications page
4	Database unreachable after 4 tries	check VPN / Azure firewall; the next slot retries

8.4 Commands

```
python scripts/test_connection.py                 # database + Forsta check (never prints the key)
python scripts/init_db.py                         # create / upgrade the schema (refuses while a load runs)
python scripts/weekly_forsta.py                   # the scheduled run, by hand
python -m etl.forsta_etl --discover               # refresh the register only
python -m etl.forsta_etl --due                    # discover + load everything due
python -m etl.forsta_etl --survey selfserve/58f/260908   # load or reload one wave
python -m etl.forsta_etl --reconcile              # every loaded Forsta wave vs Forsta
python -m etl.forsta_etl --reindex                # rebuild search for every verified wave
python -m etl.tracker_line --rebuild              # rebuild line-by-line rows
python -m etl.tracker_line --compare "<team file>.xlsx"  # compare with the data team's file (reads only)
python -m etl.survey_calendar                     # calendar + next 12 lead sectors
python -m etl.legacy_dwh --all [--era surveymonkey]      # history from dwh_sm*
python scripts/reconcile.py                       # every wave vs its source
python scripts/perf_check.py                      # P95 timings
python scripts/data_dictionary.py > docs/technical/06-data-dictionary.md
```

8.5 Monitoring queries

```
-- what the pipeline knows about Forsta
SELECT load_state, COUNT(*) FROM cip_forsta_survey GROUP BY load_state;

-- anything waiting or failed
SELECT forsta_path, state, load_state, qualified_n, total_n, closed_at, last_error
  FROM cip_forsta_survey WHERE load_state IN ('due', 'failed');

-- last runs
SELECT load_id, survey_id, source_type, status, rows_read, rows_loaded, started_at, finished_at, error_text
  FROM cip_load_log ORDER BY load_id DESC LIMIT 20;

-- nothing should be stuck
SELECT survey_id, wave_label, load_status FROM cip_survey WHERE load_status <> 'verified';
```


CONFIDENTIAL

8.6 Common situations

Situation	Cause	Fix
Runs log “Loaded 0” for days	No survey has closed in Forsta	Expected; the wave loads at the first run after it is closed
Exit 4 / “Can’t connect to MySQL … timed out”	VPN down or office IP not allowed by the Azure firewall	Reconnect; the next slot retries
A wave `failed` with “does not match its payload”	Forsta changed data mid-load, or a load step broke	`python -m etl.forsta_etl --survey <path>`; investigate `last_error`
Survey `hibernated` and history needed	Forsta hibernated it before it was loaded	A Forsta owner reactivates it; the next run loads it
Survey reopened and closed again	New respondents	Discovery marks it due; it is reloaded in place
Exit 2 “schema is behind the code”	New code deployed	`python scripts/init_db.py`

8.7 Change management

- Code: Python 3.13, SQLAlchemy 2, PyMySQL, tenacity, pandas; tests `pytest` (227 passing, SQLite).
- Schema: `sql/001_schema.sql` is the single source (MySQL DDL, converted to SQLite for tests); `app/core/schema_upgrade.py` adds new columns and indexes to an existing database.
- Rules without code changes: `config/survey_map.yml` (topics, demographics, bands), `config/cohorts.yml`, `config/tracker_line.yml`, `config/survey_calendar.yml`.

8.8 Security

- Forsta: GET only; no write method exists in the client. Key in `.env`, git-ignored, never printed.
- Warehouse: TLS; the portal uses a read-only account; only the ETL writes.
- Personal data: never stored (browser string, link, session, fingerprint, IP); panel id only as sha256.

CONFIDENTIAL