



Logout Bridge Page — Technical Documentation

Coresight Research Portal — Technical Documentation

Document version: 1.0

Generated: June 29, 2026

Classification: Internal — Engineering Reference

CONFIDENTIAL — INTERNAL USE ONLY — DO NOT DISTRIBUTE

This document contains proprietary information belonging to Coresight Research. Unauthorized disclosure, copying, or distribution is strictly prohibited.

Table of Contents

Logout Bridge Page — Technical Documentation	1
Overview	3
URL / Route	3
Dependencies	4
UI Components	5
Session State Keys	6
Data Layer	6
Business Logic	7
Error Handling	11
Access Control List (ACL) / Permissions	11
Flowcharts	11

Source: `app/pages/logout_bridge.py`

URL: `/logout_bridge`

Purpose: Invisible backend handler that performs **RP-initiated OpenID Connect (OIDC) logout** — recovers `id_token`, clears local auth state and cookies, then redirects the browser to the Coresight Identity Provider (IdP) logout endpoint.

Important: This page intentionally has **minimal visible User Interface (UI)** ("Logging out..."). Do not add interactive Streamlit widgets here.

Overview

When a user clicks **Logout** in the navigation header (`?action=logout`), `main.py` calls `stash_logout_context()` and routes to this page. `logout_bridge.py` then:

1. **Recovers** `id_token_hint` from multiple sources (before any clearing).
2. **Clears** server-side session state and sets `__just_logged_out`.
3. **Injects** parent-frame JavaScript to atomically clear browser cookies and navigate to either:
 - IdP logout URL (with `id_token_hint` + `post_logout_redirect_uri`), or
 - Login page (local-only fallback when no `id_token`).

The page exists because Streamlit 1.54+ strips `<script>` via DOMPurify in `st.html()`, and `components.html()` iframes cannot top-navigate reliably. The solution uses **parent-document script injection** (same pattern as login Single Sign-On (SSO) button and auth cookie handoff).

URL / Route

Route	Access
<code>/logout_bridge</code>	Via <code>st.switch_page</code> from <code>main.py</code> (<code>?action=logout</code>) or <code>auth_manager.logout()</code>

Not linked in navigation — `st.navigation` registers it with `position="hidden"`.

Query parameters: None required; all context comes from session state and cookies.

Dependencies

Python modules

Import	Role
<code>core.auth_environment.is_production_deploy</code>	Chooses <code>OIDC_REDIRECT_URI</code> host
<code>core.auth_manager.build_cookie_clear_js_lines</code>	JS lines to expire cookies (host + <code>.coresight.com</code>)
<code>streamlit</code> / <code>streamlit.components.v1</code>	Minimal UI + iframe script injection
<code>utils.server_logger</code>	<code>log_warning</code> , <code>log_error</code> , <code>log_timing</code>
<code>dotenv.load_dotenv</code>	Environment loading

Constants (must match `login.py`)

Constant	Value
<code>IDP_BASE_URL</code>	<code>https://coresight.com</code>
<code>OIDC_REDIRECT_URI</code>	<code>https://marketdata.coresight.com</code> (prod) or <code>https://marketdata-stg.coresight.com</code> (non-prod)
<code>OIDC_CLIENT_ID</code>	<code>market-data</code>
<code>COOKIE_NAME</code>	<code>auth_session</code>
<code>LOGOUT_BRIDGE_COOKIE_NAME</code>	<code>auth_logout_bridge</code>
<code>OIDC_RETURN_CONTEXT_MAX_AGE_SECONDS</code>	900 (default)
<code>LOGOUT_COOKIE_SYNC_WAIT_MS</code>	250 (defined, legacy)
<code>LOGOUT_COOKIE_SYNC_POLL_MS</code>	50 (defined, legacy)

External integrations

Integration	Usage
Coresight IdP logout	<code>GET https://coresight.com/csr-idp/logout/?id_token_hint=...&post_logout_redirect_uri=...</code>
Browser cookies	Read then clear <code>auth_session</code> , <code>auth_logout_bridge</code>
<code>/tmp</code> <code>id_token</code> files	<code>_oidc_idtok_{hash}.json</code> fallback when slim cookie has no <code>id_token</code>

UI Components

Visible UI (intentionally minimal)

Element	Description
Inline CSS	Hides <code>stHeader</code> , footer, <code>#MainMenu</code> , sidebar
Centered text	"Logging out..." — full viewport flex center
Background	White <code>#fff</code>

No Streamlit buttons, forms, or sidebar. The page should appear as a brief transitional screen before browser navigation.

Invisible machinery

Element	Purpose
<code>streamlit.components.v1.html</code>	Zero-height iframe injecting parent-frame script
Parent script	Cookie clear lines + <code>window.location.href = dest</code>

Session State Keys

Read

Key	Purpose
<code>__logout_bridge_data</code>	Primary source: <code>{id_token, user_email, created_at}</code> from <code>stash_logout_context</code>
<code>auth_data</code>	Fallback <code>id_token</code> / <code>session_id</code>
<code>__logout_oidc_redirect_started</code>	Guard against duplicate renders

Written / cleared

Key	Action
<code>__just_logged_out</code>	Set <code>True</code> — login page sets <code>__logout_guard</code>
<code>__logout_oidc_redirect_started</code>	Set when IdP redirect path taken
Cleared:	<code>auth_data</code> , <code>authenticated</code> , <code>__auth_invalidated</code> , <code>__completed_oidc_code</code> , <code>__completed_oidc_token_data</code> , <code>__oidc_cb_*</code> , <code>__oidc_exchange_result</code> , <code>__logout_bridge_data</code> , handoff keys, <code>__completed_oidc_post_logout_key</code>

Data Layer

No database queries

This page performs **zero** MySQL operations. Session invalidation happens earlier in `stash_logout_context()` via temp-file blacklist (`invalidate_session` in `auth_manager.py`).

Ephemeral files

Operation	File	Purpose
Write	<code>_oidc_logout_return_{hash}.json</code>	Stores origin for cross-host post-logout return
Read	<code>_oidc_idtok_{hash}.json</code>	Recover <code>id_token</code> from <code>session_id</code> (slim cookie deployments)

`_build_post_logout_redirect_uri` logic:

- If current origin is allowed and differs from canonical `OIDC_REDIRECT_URI`, append `oidc_post_logout={return_key}` to redirect URI
- `login.py` `_process_post_logout_return()` consumes this and meta-refreshes browser back to original host

Business Logic

Step 1 — Recover `id_token` (priority order)

Logout bridge walks a fixed priority list of session, cookie, and temp-file sources to recover `id_token_hint`.

Figure 1 Part A — Priority sources 1–3 (session & cookies)

Figure 1 Part A — Priority sources 1–3 (session & cookies)





Figure 1 Part B — Priority sources 4–6 (fallbacks)

Figure 1 Part B — Priority sources 4–6 (fallbacks)



Logs `OIDC_LOGOUT_BRIDGE_RECOVER` timing with `source` and `has_id_token`.


Step 2 — Clear session state

Sets `__just_logged_out` and pops all auth/OIDC keys (see table above).

Step 3 — Atomic JS clear + redirect

Parent-frame JavaScript clears cookies atomically, then navigates to IdP logout or login fallback.

Parent-frame JavaScript clears cookies atomically, then navigates to IdP logout or login fallback.



IdP logout URL shape:

```
https://coresight.com/csr-idp/logout/?id_token_hint={jwt}&post_logout_redirect_uri={encoded}
```

Duplicate render guard: If `__logout_oidc_redirect_started` already set at page entry → log and `st.stop()`.

Fallback: On JS injection exception → `st.switch_page("pages/login.py")`.

Error Handling

Scenario	Behavior
Duplicate page render	<code>st.stop()</code> immediately
<code>id_token</code> not found in any source	Local-only logout to login URL; warning logged
JS injection fails	<code>switch_page(login.py)</code>
Bridge cookie parse error	Log warning; try next source
Temp file read error	Log warning; continue to local-only
Unsafe post-logout origin	Ignored in <code>login.py</code> handler

Local-only logout implication: Without `id_token_hint`, the IdP WordPress session is **not** destroyed. User may be silently re-authenticated on next SSO attempt. This is the documented safe fallback.

Access Control List (ACL) / Permissions


No ACL check — any authenticated user reaching this page via `?action=logout` may log out. The page is not directly bookmarkable for harm: without prior `stash_logout_context`, `id_token` recovery may fail (local-only logout).

Flowcharts

Entry from navigation

User logout starts in navigation, stashes OIDC context in `main.py`, then routes to the invisible logout bridge page.


User logout starts in navigation, stashes OIDC context in main.py, then routes to the invisible logout bridge page.



Cookie clearing (JS)

Both auth cookies are expired on host-only and `.coresight.com` paths before redirect.


Both auth cookies are expired on host-only and `.coresight.com` paths before redirect.



Cross-host post-logout return

Cross-host logout stores return origin in a temp file; login page meta-refreshes the browser back to the original host.

Cross-host logout stores return origin in a temp file; login page meta-refreshes the browser back to the original host.



Key code references

Section	Lines (approx.)
Module docstring / design rationale	1–20
Ephemeral cache helpers	58–74
Origin helpers	77–149
<code>_build_post_logout_redirect_uri</code>	152–177
Minimal UI CSS	180–191
Duplicate guard	198–200
Step 1 id_token recovery	203–333
Step 2 session clear	347–359
Step 3 JS clear + redirect	361–422

Related documentation

- [App Bootstrap and Auth](#) — `stash_logout_context`, logout routing in `main.py`
- [Login Page](#) — `_process_post_logout_return`, OIDC callback

Generated from source analysis of `app/pages/logout_bridge.py` .