


5th Edition

Elmasri / Navathe

## Chapter 3

Data Modeling Using the Entity-Relationship (ER) Model






#### **Chapter Outline**

- Overview of Database Design Process
- Example Database Application (COMPANY)
- ER Model Concepts
  - Entities and Attributes
  - Entity Types, Value Sets, and Key Attributes
  - Relationships and Relationship Types
  - Weak Entity Types
  - Roles and Attributes in Relationship Types
- ER Diagrams Notation
- ER Diagram for COMPANY Schema
- Alternative Notations UML class diagrams, others

- Two main activities:
  - Database design
  - Applications design
- Focus in this chapter on database design
  - To design the conceptual schema for a database application
- Applications design focuses on the programs and interfaces that access the database
  - Generally considered part of software engineering



1- Requirements collection and analysis

During this step, the database designers interview prospective database users to understand and document their data requirements. The result of this step is a concisely written set of users' requirements.

- functional requirements
- operations (or transactions)

2- Create a conceptual schema, (conceptual design)

The conceptual schema is a concise description of the data requirements of the users and includes detailed descriptions of the entity types, relationships, and constraints; these are expressed using the concepts provided by the high-level data model.

3- Logical design or data model mapping

Most current commercial DBMSs use an implementation data model—such as the relational (SQL) model—so the conceptual schema is transformed from the high-level data model into the implementation data model.

4- Physical design

The last step is the physical design phase, during which the internal storage structures, file organizations, indexes, access paths, and physical design parameters for the database files are specified.

### **Example COMPANY Database**

#### Example COMPANY Database

- The COMPANY database keeps track of a company's employees, departments, and projects.
- Suppose that after the requirements collection and analysis phase, the database designers provide the following description of the miniworld—the part of the company that will be represented in the database.

#### Example COMPANY Database

- We need to create a database schema design based on the following (simplified) requirements of the COMPANY Database:
  - The company is organized into DEPARTMENTs. Each department has a name, number and an employee who manages the department.
  - We keep track of the start date of the department manager.
  - A department may have several locations.
  - Each department controls a number of PROJECTs.
  - Each project has a unique name, unique number and is located at a single location.

# Example COMPANY Database (Contd.)

- We store each EMPLOYEE's social security number, address, salary, gender, and birthdate.
  - Each employee works for one department but may work on several projects.
  - We keep track of the number of hours per week that an employee currently works on each project.
  - We also keep track of the direct supervisor of each employee.
- Each employee may have a number of DEPENDENTs.
  - For each dependent, we keep track of their name, gender, birthdate, and relationship to the employee.

#### **ER Model Concepts**

- Entities and Attributes
  - Entities are specific objects or things in the mini-world that are represented in the database.
    - For example the EMPLOYEE John Smith, the Research DEPARTMENT, the ProductX PROJECT
  - Attributes are properties used to describe an entity.
    - For example an EMPLOYEE entity may have the attributes Name, SSN, Address, Gender, BirthDate

#### **ER Model Concepts**

- Entities and Attributes
  - A specific entity will have a value for each of its attributes.
    - For example a specific employee entity may have Name='John Smith', SSN='123456789', Address ='731, Fondren, Houston, TX', Gender='M', BirthDate='09-JAN-55'
  - Each attribute has a value set (or data type) associated with it – e.g. integer, string, subrange, enumerated type, ...

### Types of Attributes (1)

#### Simple

Each entity has a single atomic value for the attribute.
 For example, SSN or Gender.

#### Composite

- The attribute may be composed of several components. For example:
  - Address(Apt#, House#, Street, City, State, ZipCode, Country),
  - Name(FirstName, MiddleName, LastName).
  - Composition may form a hierarchy where some components are themselves composite.

#### Multi-valued

- An entity may have multiple values for that attribute. For example, Color of a CAR or PreviousDegrees of a STUDENT.
  - Denoted as {Color} or {PreviousDegrees}.

### Types of Attributes (2)

- In general, composite and multi-valued attributes may be nested arbitrarily to any number of levels, although this is rare.
  - For example, PreviousDegrees of a STUDENT is a composite multi-valued attribute denoted by {PreviousDegrees (College, Year, Degree, Field)}
  - Multiple PreviousDegrees values can exist
  - Each has four subcomponent attributes:
    - College, Year, Degree, Field

### Example of a composite attribute




Figure 3.4
A hierarchy of composite attributes.

#### Entity Types and Key Attributes (1)

- Entities with the same basic attributes are grouped or typed into an entity type.
  - For example, the entity type EMPLOYEE and PROJECT.
- An attribute of an entity type for which each entity must have a unique value is called a key attribute of the entity type.
  - For example, SSN of EMPLOYEE.

#### Entity Types and Key Attributes (2)


- A key attribute may be composite.
  - VehicleTagNumber is a key of the CAR entity type with components (Number, State).
- An entity type may have more than one key.
  - The CAR entity type may have two keys:
    - VehicleIdentificationNumber (popularly called VIN)
    - VehicleTagNumber (Number, State), aka license plate number.
- Each key is <u>underlined</u>

#### Displaying an Entity type

- In ER diagrams, an entity type is displayed in a rectangular box
- Attributes are displayed in ovals
  - Each attribute is connected to its entity type
  - Components of a composite attribute are connected to the oval representing the composite attribute
  - Each key attribute is underlined
  - Multivalued attributes displayed in double ovals
- See CAR example on next slide

# Entity Type CAR with two keys and a corresponding Entity Set

(a)



#### Figure 3.7

The CAR entity type with two key attributes, Registration and Vehicle\_id. (a) ER diagram notation. (b) Entity set with three entities.

(b) CAR
Registration (Number, State), Vehicle\_id, Make, Model, Year, {Color}

CAR<sub>1</sub>
((ABC 123, TEXAS), TK629, Ford Mustang, convertible, 2004 {red, black})

CAR<sub>2</sub>
((ABC 123, NEW YORK), WP9872, Nissan Maxima, 4-door, 2005, {blue})

CAR<sub>3</sub>
((VSY 720, TEXAS), TD729, Chrysler LeBaron, 4-door, 2002, {white, blue})


#### **Entity Set**


- Each entity type will have a collection of entities stored in the database
  - Called the entity set
- Previous slide shows three CAR entity instances in the entity set for CAR
- Same name (CAR) used to refer to both the entity type and the entity set
- Entity set is the current state of the entities of that type that are stored in the database


# Initial Design of Entity Types for the COMPANY Database Schema

- Based on the requirements, we can identify four initial entity types in the COMPANY database:
  - DEPARTMENT
  - PROJECT
  - EMPLOYEE
  - DEPENDENT
- Their initial design is shown on the following slide
- The initial attributes shown are derived from the requirements description

## Initial Design of Entity Types: EMPLOYEE, DEPARTMENT, PROJECT, DEPENDENT










Figure 3.8

Preliminary design of entity types for the COMPANY database. Some of the shown attributes will be refined into relationships.


# Refining the initial design by introducing relationships

- The initial design is typically not complete
- Some aspects in the requirements will be represented as relationships
- ER model has three main concepts:
  - Entities (and their entity types and entity sets)
  - Attributes (simple, composite, multivalued)
  - Relationships (and their relationship types and relationship sets)
- We introduce relationship concepts next


#### Relationships and Relationship Types (1)

- A relationship relates two or more distinct entities with a specific meaning.
  - For example, EMPLOYEE John Smith works on the ProductX PROJECT, or EMPLOYEE Franklin Wong manages the Research DEPARTMENT.
- Relationships of the same type are grouped or typed into a relationship type.
  - For example, the WORKS\_ON relationship type in which EMPLOYEEs and PROJECTs participate, or the MANAGES relationship type in which EMPLOYEEs and DEPARTMENTs participate.
- The degree of a relationship type is the number of participating entity types.
  - Both MANAGES and WORKS\_ON are binary relationships.

## Relationship instances of the WORKS\_FOR N:1 relationship between EMPLOYEE and DEPARTMENT



## Relationship instances of the M:N WORKS\_ON relationship between EMPLOYEE and PROJECT



#### Relationship type vs. relationship set (1)

- Relationship Type:
  - Is the schema description of a relationship
  - Identifies the relationship name and the participating entity types
  - Also identifies certain relationship constraints
- Relationship Set:
  - The current set of relationship instances represented in the database
  - The current state of a relationship type

#### Relationship type vs. relationship set (2)


- Previous figures displayed the relationship sets
- Each instance in the set relates individual participating entities – one from each participating entity type
- In ER diagrams, we represent the relationship type as follows:
  - Diamond-shaped box is used to display a relationship type
  - Connected to the participating entity types via straight lines

# Refining the COMPANY database schema by introducing relationships

- By examining the requirements, six relationship types are identified
- All are binary relationships (degree 2)
- Listed below with their participating entity types:
  - WORKS FOR (between EMPLOYEE, DEPARTMENT)
  - MANAGES (also between EMPLOYEE, DEPARTMENT)
  - CONTROLS (between DEPARTMENT, PROJECT)
  - WORKS\_ON (between EMPLOYEE, PROJECT)
  - SUPERVISION (between EMPLOYEE (as subordinate), EMPLOYEE (as supervisor))
  - DEPENDENTS\_OF (between EMPLOYEE, DEPENDENT)

#### ER DIAGRAM – Relationship Types are:

WORKS\_FOR, MANAGES, WORKS\_ON, CONTROLS, SUPERVISION, DEPENDENTS\_OF



**Figure 3.2**An ER schema diagram for the COMPANY database. The diagrammatic notation is introduced gradually throughout this chapter.

#### Discussion on Relationship Types

- In the refined design, some attributes from the initial entity types are refined into relationships:
  - Manager of DEPARTMENT -> MANAGES
  - Works\_on of EMPLOYEE -> WORKS\_ON
  - Department of EMPLOYEE -> WORKS\_FOR
  - etc
- In general, more than one relationship type can exist between the same participating entity types
  - MANAGES and WORKS\_FOR are distinct relationship types between EMPLOYEE and DEPARTMENT
  - Different meanings and different relationship instances.

#### Recursive Relationship Type

- An relationship type whose with the same participating entity type in distinct roles
- Example: the SUPERVISION relationship
- EMPLOYEE participates twice in two distinct roles:
  - supervisor (or boss) role
  - supervisee (or subordinate) role
- Each relationship instance relates two distinct EMPLOYEE entities:
  - One employee in supervisor role
  - One employee in supervisee role

### Weak Entity Types

- An entity that does not have a key attribute
- A weak entity must participate in an identifying relationship type with an owner or identifying entity type
- Entities are identified by the combination of:
  - A partial key of the weak entity type
  - The particular entity they are related to in the identifying entity type


#### Example:

- A DEPENDENT entity is identified by the dependent's first name, and the specific EMPLOYEE with whom the dependent is related
- Name of DEPENDENT is the partial key
- DEPENDENT is a weak entity type
- EMPLOYEE is its identifying entity type via the identifying relationship type DEPENDENT\_OF


### Constraints on Relationships

- Constraints on Relationship Types
  - (Also known as ratio constraints)
  - Cardinality Ratio (specifies maximum participation)
    - One-to-one (1:1)
    - One-to-many (1:N) or Many-to-one (N:1)
    - Many-to-many (M:N)
  - Existence Dependency Constraint (specifies minimum participation) (also called participation constraint)
    - zero (optional participation, not existence-dependent)
    - one or more (mandatory participation, existence-dependent)

### Many-to-one (N:1) Relationship



### Many-to-many (M:N) Relationship



# Displaying a recursive relationship

- In a recursive relationship type.
  - Both participations are same entity type in different roles.
  - For example, SUPERVISION relationships between EMPLOYEE (in role of supervisor or boss) and (another) EMPLOYEE (in role of subordinate or worker).
- In following figure, first role participation labeled with 1 and second role participation labeled with 2.
- In ER diagram, need to display role names to distinguish participations.

### A Recursive Relationship Supervision`





Figure 3.11

A recursive relationship SUPERVISION between EMPLOYEE in the *supervisor* role (1) and EMPLOYEE in the *subordinate* role (2).

### Recursive Relationship Type is: SUPERVISION (participation role names are shown)




**Figure 3.2**An ER schema diagram for the COMPANY database. The diagrammatic notation is introduced gradually throughout this chapter.

### Attributes of Relationship types

- A relationship type can have attributes:
  - For example, HoursPerWeek of WORKS\_ON
  - Its value for each relationship instance describes the number of hours per week that an EMPLOYEE works on a PROJECT.
    - A value of HoursPerWeek depends on a particular (employee, project) combination
  - Most relationship attributes are used with M:N relationships
    - In 1:N relationships, they can be transferred to the entity type on the N-side of the relationship

## Example Attribute of a Relationship Type: Hours of WORKS\_ON



**Figure 3.2**An ER schema diagram for the COMPANY database. The diagrammatic notation is introduced gradually throughout this chapter.


## Notation for Constraints on Relationships

- Cardinality ratio (of a binary relationship): 1:1, 1:N, N:1, or M:N
  - Shown by placing appropriate numbers on the relationship edges.
- Participation constraint (on each participating entity type): total (called existence dependency) or partial.
  - Total shown by double line, partial by single line.
- NOTE: These are easy to specify for Binary Relationship Types.

## Alternative (min, max) notation for relationship structural constraints:


- Specified on each participation of an entity type E in a relationship type R
- Specifies that each entity e in E participates in at least min and at most max relationship instances in R
- Default(no constraint): min=0, max=n (signifying no limit)
- Must have min≤max, min≥0, max ≥1
- Derived from the knowledge of mini-world constraints
- Examples:
  - A department has exactly one manager and an employee can manage at most one department.
    - Specify (0,1) for participation of EMPLOYEE in MANAGES
    - Specify (1,1) for participation of DEPARTMENT in MANAGES
  - An employee can work for exactly one department but a department can have any number of employees.
    - Specify (1,1) for participation of EMPLOYEE in WORKS\_FOR
    - Specify (0,n) for participation of DEPARTMENT in WORKS\_FOR

## The (min,max) notation for relationship constraints



Read the min, max numbers next to the entity type and looking **away from** the entity type


## COMPANY ER Schema Diagram using (min, max) notation



### Alternative diagrammatic notation

- ER diagrams is one popular example for displaying database schemas
- Many other notations exist in the literature and in various database design and modeling tools
- Appendix A illustrates some of the alternative notations that have been used
- UML class diagrams is representative of another way of displaying ER concepts that is used in several commercial design tools

### Summary of notation for ER diagrams




### UML class diagrams

- Represent classes (similar to entity types) as large rounded boxes with three sections:
  - Top section includes entity type (class) name
  - Second section includes attributes
  - Third section includes class operations (operations are not in basic ER model)
- Relationships (called associations) represented as lines connecting the classes
  - Other UML terminology also differs from ER terminology
- Used in database design and object-oriented software design
- UML has many other types of diagrams for software design (see Chapter 12)

## UML class diagram for COMPANY database schema

Figure 3.16
The COMPANY conceptual schema in UML class diagram notation.



### Other alternative diagrammatic notations




Figure A.1

Alternative notations. (a) Symbols for entity type/class, attribute, and relationship. (b) Displaying attributes. (c) Displaying cardinality ratios. (d) Various (min, max) notations. (e) Notations for displaying specialization/generalization.


### Relationships of Higher Degree

- Relationship types of degree 2 are called binary
- Relationship types of degree 3 are called ternary and of degree n are called n-ary
- In general, an n-ary relationship is not equivalent to n binary relationships
- Constraints are harder to specify for higherdegree relationships (n > 2) than for binary relationships

### Discussion of n-ary relationships (n > 2)

- In general, 3 binary relationships can represent different information than a single ternary relationship (see Figure 3.17a and b on next slide)
- If needed, the binary and n-ary relationships can all be included in the schema design (see Figure 3.17a and b, where all relationships convey different meanings)
- In some cases, a ternary relationship can be represented as a weak entity if the data model allows a weak entity type to have multiple identifying relationships (and hence multiple owner entity types) (see Figure 3.17c)

### Example of a ternary relationship




**Figure 3.17**Ternary relationship types. (a) The SUPPLY relationship. (b) Three binary relationships not equivalent to SUPPLY. (c) SUPPLY represented as a weak entity type.

### Discussion of n-ary relationships (n > 2)

- If a particular binary relationship can be derived from a higher-degree relationship at all times, then it is redundant
- For example, the TAUGHT\_DURING binary relationship in Figure 3.18 (see next slide) can be derived from the ternary relationship OFFERS (based on the meaning of the relationships)

### Another example of a ternary relationship



## Displaying constraints on higher-degree relationships

- The (min, max) constraints can be displayed on the edges
   however, they do not fully describe the constraints
- Displaying a 1, M, or N indicates additional constraints
  - An M or N indicates no constraint
  - A 1 indicates that an entity can participate in at most one relationship instance that has a particular combination of the other participating entities
- In general, both (min, max) and 1, M, or N are needed to describe fully the constraints

### **Data Modeling Tools**

- A number of popular tools that cover conceptual modeling and mapping into relational schema design.
  - Examples: ERWin, S- Designer (Enterprise Application Suite), ER- Studio, etc.

#### POSITIVES:

 Serves as documentation of application requirements, easy user interface - mostly graphics editor support

#### NEGATIVES:

- Most tools lack a proper distinct notation for relationships with relationship attributes
- Mostly represent a relational design in a diagrammatic form rather than a conceptual ER-based design

(See Chapter 12 for details)

# Some of the Currently Available Automated Database Design Tools

COMPANY	TOOL	FUNCTIONALITY
Embarcadero Technologies	ER Studio	Database Modeling in ER and IDEF1X
	DB Artisan	Database administration, space and security management
Oracle	Developer 2000/Designer 2000	Database modeling, application development
Popkin Software	System Architect 2001	Data modeling, object modeling, process modeling, structured analysis/design
Platinum (Computer Associates)	Enterprise Modeling Suite: Erwin, BPWin, Paradigm Plus	Data, process, and business component modeling
Persistence Inc.	Pwertier	Mapping from O-O to relational model
Rational (IBM)	Rational Rose	UML Modeling & application generation in C++/JAVA
Resolution Ltd.	Xcase	Conceptual modeling up to code maintenance
Sybase	Enterprise Application Suite	Data modeling, business logic modeling
Visio	Visio Enterprise	Data modeling, design/reengineering Visual Basic/C++

# Extended Entity-Relationship (EER) Model (in next chapter)

- The entity relationship model in its original form did not support the specialization and generalization abstractions
- Next chapter illustrates how the ER model can be extended with
  - Type-subtype and set-subset relationships
  - Specialization/Generalization Hierarchies
  - Notation to display them in EER diagrams

### **Chapter Summary**

- ER Model Concepts: Entities, attributes, relationships
- Constraints in the ER model
- Using ER in step-by-step conceptual schema design for the COMPANY database
- ER Diagrams Notation
- Alternative Notations UML class diagrams, others