

Track ABC External Data References

This file lists external, non-code artifacts (JSON/JSONL/CSV/etc.) referenced across Track A/B/C Python scripts, with brief notes on where and why they are used.

Track A

- `local_extraction/trackA/trackA_stageA/trackA_stageA.py`
 - `candidates.jsonl` (run output): proposals per image `{uid, frame, boxes}`.
 - `summary.json` (run output): counts/settings summary for Stage A.
- `local_extraction/trackA/trackA_stageA/oracle_k_sweep.py`
 - `summary.json` in Stage A run dirs: parsed to aggregate recall-by-K.
 - `oracle_k_sweep_*.json` (output): sweep results.
- `local_extraction/trackA/trackA_stageA/sweep_k_metrics.py`
 - `summary.json` (output): aggregated metrics per K.
 - `samples.jsonl` (optional output): per-image diagnostic samples.
- `local_extraction/trackA/trackA_stageB/trackA_stageB.py`
 - `candidates.jsonl` (input): Stage A proposals.
 - `head_train.jsonl` / `head_val.jsonl` (input/output): semantic head manifests; merged/write if available.
 - `head_train_clip.json` / `head_val_clip.json` (input): preferred CLIP manifests.
 - `head_train_video.json` / `head_val_video.json` (input): video manifests alternative.
 - `manifest.jsonl` / `manifest.csv` (output): per-crop metadata.
 - `summary.json` (output): Stage B run summary; may be patched with recall stats.
 - Reads sibling Stage A `summary.json` (if present) to propagate detector config.
- `local_extraction/trackA/trackA_stageB/san_stageB.py`
 - `head_train.jsonl` / `head_val.jsonl` (input): stats/overlays.
 - `summary.json` (input): recall metrics extraction.
 - `manifest.jsonl` (input): overlay preview.

Track B

- `local_extraction/trackB/trackB_dataset.py`
 - Manifest discovery inputs: `head_train*.json[1]`, `head_val*.json[1]`, `head_train_clip.json[1]`, `head_train_video.json[1]`, `head_val_clip.json[1]`, `head_val_video.json[1]`, `val.json[1]`.
 - Invalid log output: `runs/Track_B/cache/invalid_records.csv`.
- `local_extraction/trackB/trackB_train_loader.py`
 - Same manifest discovery list as dataset.
 - Best checkpoint summaries: `trackB_best_*_summary.json`, `trackB_best_summary.json`.
 - Val manifest fallback: `val.jsonl` under manifests root.
- `local_extraction/trackB/trackB_train_demo.py`
 - Manifest discovery: `head_train_video.json`, `head_train_clip.json`, `.jsonl` variants.
- `local_extraction/trackB/trackB_eval.py`
 - Val manifest discovery: `head_val*.json[1]`, `val.json[1]`.

- Hotspot priors: `local_extraction/v2/hotspot_priors_train_logodds_min10.json` .
- CLIP noun labels: `local_extraction/v2/org_annotations/fho_sta_val_height-540.json` .
- Outputs: `metrics/metrics_val_<ts>.json` , `metrics_val_<ts>_summary.json` , `predictions/predictions_val_<ts>.jsonl` , and CSV counterpart.
- `local_extraction/trackB/trackB_plots.py`
 - Inputs: `metrics/metrics_val_*.json` under Track B runs.
- `local_extraction/trackB/trackB_show_samples.py`
 - Stage B manifests: `head_train.jsonl` / `head_val.jsonl` (`.json` alternates).
 - Optional STA label JSONs: `fho_sta_val_height-540.json` , `fho_sta_train_height-540.json` .
- `local_extraction/trackB/trackB_manifest_validator.py`
 - Outputs: `ttc_stats.json` , `key_coverage.json` in cache directory for a manifest.
- `local_extraction/trackB/build_hotspot_priors.py`
 - Inputs: Stage B manifests (`head_train.jsonl` , `head_val.jsonl`).
 - Output: hotspot priors JSON (default `local_extraction/v2/hotspot_priors_{source}_{method}_min{min_total}.json`).

Track C

- `local_extraction/trackC/trackC_pruning.py`
 - Val manifest discovery: `head_val.jsonl/json` , `head_val_clip.jsonl` , `head_val_video.jsonl` .
 - Outputs: `metrics/trackC_val_rateXX_<ts>.json` and `trackC_val_rateXX_<ts>_summary.json` .
- `local_extraction/trackC/trackC_plots.py`
 - Inputs: `metrics/trackC_val_rate*.json` under Track C runs; outputs plots/TSV.
- `local_extraction/trackC/trackC_compare_metrics.py`
 - Inputs: Track B `metrics_val_*.json` and Track C `trackC_val_rate*.json` for comparison.

General Metrics/Artifacts Mentioned in Code

- Metrics/plots directories:
 - `runs/Track_B/metrics/metrics_val_*.json`
 - `runs/Track_C/metrics/trackC_val_rate*.json`
 - `runs/Track_B/plots/trackB_metrics_summary.tsv` , `trackB_metrics_over_time.png`
 - `runs/Track_C/plots/trackC_metrics_summary.tsv` , `trackC_metrics_over_time.png`
- Predictions/overlays:
 - `runs/Track_B/predictions/predictions_val_*.jsonl` / CSV
 - `runs/Track_B/overlays/val/*.jpg`
- Checkpoints:
 - `runs/Track_B/checkpoints/trackB_epoch*.pt` , `trackB_final*.pt` , `trackB_best*.pt`
 - Track B best summaries: `trackB_best*_summary.json` , `trackB_best_summary.json`
- Hotspot/annotation assets:
 - `local_extraction/v2/hotspot_priors_*.json`
 - `local_extraction/v2/org_annotations/fho_sta_val_height-540.json`

Notes:

- This list is derived from string references inside Track A/B/C Python files. It focuses on external data files (JSON/JSONL/CSV/etc.) that scripts read or write, and where they are used.