Studied C* Programming Guide_ from Thinking Machines Corporation*, including its architecture, shapes/parallel variables, execution model, context selection, communication, reductions/scans, general communication, and CM-5 layout/performance material. The manual is 312 pages in the uploaded copy.

There are also two important corrections to the interpretation you supplied:

The manual itself uses scalar variables vs. parallel variables, not “Mono vs. Poly” terminology. Its CM-200/CM-5 implementations explicitly separate serial instructions from parallel instructions.

C* does not give us a magic “virtual processor” abstraction in the modern AI sense. What it gives COS is something more precise and more valuable: a logical data space whose positions can be distributed over a variable amount of physical hardware, while the programming model remains mostly independent of that physical layout.

Here is the COS extraction.

COS AI

Book 3 Architectural Extraction

Thinking Machines Corporation — C* Programming Guide, May 1993

---

1. The Central Lesson

Books 1 and 2 gave COS:

Book 1
physical machine
storage
timing
I/O
reliability
diagnostics
hardware/software co-design

Book 2
abstraction
data
state
languages
interpreters
compilers
register machines

Book 3 adds something extremely important:

«A computational system can expose a logical computational space that is larger and more abstract than its physical processors, while allowing the runtime to map that logical space onto available hardware.»

This gives COS a missing architectural concept:

LOGICAL COMPUTATIONAL SPACE

The physical machine should not be the unit of cognition.

---

2. C*'s Shape Is More Important Than Its Syntax

C* defines a shape as a template for parallel data.

A shape specifies:

rank
dimensions
positions
logical organization

For example:

[256][256]

represents a two-dimensional logical computational/data space.

The important idea is not the syntax.

The important idea is:

LOGICAL SPACE
↓
DATA POSITIONS
↓
OPERATIONS OVER POSITIONS
↓
RUNTIME MAPPING
↓
PHYSICAL HARDWARE

This is directly relevant to COS.

---

3. COS Needs a Shape-Like Abstraction

COS should introduce:

Cognitive Shape

A Cognitive Shape describes the logical organization of a computational population.

Examples:

sensor_grid[1024][1024]

embedding_space[1000000][768]

knowledge_batch[65536]

robot_joint_state[32]

agent_population[10000]

token_batch[4096][2048]

matrix[4096][4096]

simulation_grid[512][512][512]

But COS must not define a Cognitive Shape as “a group of CPUs.”

It is:

«A logical indexed space over which an operation can be expressed independently of its physical execution placement.»

---

4. Logical Positions

Every Cognitive Shape contains logical positions.

For example:

Shape:
[4][4]

creates:

(0,0) (0,1) (0,2) (0,3)
(1,0) (1,1) (1,2) (1,3)
(2,0) (2,1) (2,2) (2,3)
(3,0) (3,1) (3,2) (3,3)

These positions are not necessarily physical processors.

They are logical locations in a computation.

This distinction is essential.

---

5. Physical Hardware Becomes a Mapping Problem

COS therefore needs:

LOGICAL SHAPE
↓
PLACEMENT / DISTRIBUTION
↓
PHYSICAL RESOURCES

Example:

Logical shape:
[1,000,000]

Available hardware:
8 CPU cores

COS could partition the logical positions:

CPU0 → positions 0...124999
CPU1 → positions 125000...249999
...

With another machine:

Logical shape:
[1,000,000]

Hardware:
GPU

the same logical computation may become:

GPU blocks / warps / vector lanes

With an NPU:

NPU tiles

With an FPGA:

dataflow pipelines


The logical operation remains unchanged.

---

6. This Becomes COS's Virtual Execution Space

The modern COS concept should therefore be:

Virtual Cognitive Execution Space — VCES



This is the correct modern interpretation of the C* lesson.

It is more general than “virtual processors.”

---

7. Do Not Tie Shapes to Neural Networks

The supplied proposal suggested mapping C* shapes directly to:

neural weights
context windows
multi-agent swarms

COS should not hard-code this.

A Cognitive Shape must be general enough to represent:

numbers
vectors
matrices
tensors
knowledge atoms
sensor samples
events
agents
tasks
particles
robot states
simulation cells
memory objects
communication endpoints

Neural computation becomes one application of the abstraction.

---

8. Scalar vs Parallel Is a Fundamental COS Distinction

The C* manual distinguishes:

SCALAR

from:

PARALLEL

The distinction should enter COS architecture.

But we should generalize it.

COS needs:

SINGLE-CONTROL / GLOBAL STATE

and:

DISTRIBUTED / ELEMENTAL STATE

For example:

GLOBAL:
task identity
authorization
scheduler state
global configuration
machine inventory

DISTRIBUTED:
sensor values
embeddings
matrix elements
agent states
simulation particles
parallel knowledge operations

---

9. But COS Should Not Create Only Two Worlds

C* gives us a scalar/parallel distinction.

COS needs a richer hierarchy:

GLOBAL
  ↓
PARTITION
  ↓
DISTRIBUTED
  ↓
ELEMENT

Potentially:

GLOBAL
 ├── system-wide
 │
 ├── partition-wide
 │
 ├── device-local
 │
 ├── worker-group
 │
 └── element-local

This is much better suited to modern heterogeneous machines.

---


10. Control/Data Separation

C* demonstrates a useful pattern:

serial/control execution
+
parallel/data execution

COS should preserve this concept.

But the modern implementation should become:



The control plane decides:

what
why
when
authorization
dependencies
resource requirements

The parallel execution layer performs:

elementwise operations
tensor operations
search
simulation
signal processing
batch inference

---

11. Cognitive OS Control Plane

The COS control plane should eventually manage:

intent

authorization
knowledge dependencies
task creation
resource selection
placement
scheduling
verification
recovery
provenance

It should not perform every numerical operation itself.

---

12. Cognitive Data Plane

The data plane executes operations across the logical computational space.

Examples:

MAP
REDUCE
SCAN
GATHER
SCATTER
BROADCAST
PERMUTE
SHIFT
NEIGHBOR_EXCHANGE
JOIN
FILTER

This is a major new COS concept.

---

13. MAP

C* makes elemental operations natural.

COS should explicitly define:

MAP(shape, operation)

Example:

```
MAP
   shape = [1,000,000]
```

```
    operation = normalize
```

meaning:

```
for every logical position:
    normalize(element)
```

The runtime determines how this is physically executed.

---

14. REDUCE

C* provides reduction operations.

COS needs the abstraction:

REDUCE

Examples:

sum
minimum
maximum
logical AND
logical OR
product

But COS should extend this to cognitive computation:

REDUCE confidence
REDUCE evidence
REDUCE error
REDUCE probability
REDUCE resource cost
REDUCE sensor observations

where mathematically valid.

---

15. SCAN

C* has scan operations that compute cumulative results across structured positions.

COS should preserve:

SCAN

because it is useful for:

prefix sums
cumulative probabilities
sequence processing
event accumulation
stream processing
dependency propagation

This is not merely a numerical primitive.

It is a general computational pattern.

---

16. SPREAD / BROADCAST

C* also provides operations analogous to spreading one result across a structured parallel population.

COS should formalize:

BROADCAST

Example:

GLOBAL SYSTEM STATE
↓
all workers

or:

model parameters
↓
worker population

or:

authorization token
↓
authorized execution group

---

17. Gather

C*'s parallel indexing gives COS an important primitive:

GATHER

Meaning:

destination[i] = source[index[i]]

This is fundamental for:

lookup
embedding access
knowledge retrieval
routing
graph traversal
attention
indirect addressing

---

18. Scatter

The reverse operation:

SCATTER

means:

destination[index[i]] = source[i]

This is equally important.

But COS must explicitly handle:

collision

when multiple sources target the same destination.

Possible policies:

reject
overwrite
sum
max
min
combine
queue
custom reducer

This is a direct architectural lesson from C* communication semantics.

---

19. Communication Is an Operation, Not an Accident

C* treats communication as an explicit computational concept.

COS should do the same.

A computation should be able to declare:

COMPUTE
COMMUNICATE
SYNCHRONIZE
REDUCE

rather than hiding communication inside arbitrary code.

---

20. Two Communication Classes

C* distinguishes:

GRID COMMUNICATION

and:

GENERAL COMMUNICATION

COS should preserve this distinction.

Structured communication

Neighbor-based:

left
right
up
down
previous
next
adjacent

Useful for:

grids

simulations
images
robot maps
spatial sensing
cellular systems

General communication

Arbitrary:

position A → position B
agent A → agent B
knowledge node → knowledge node
device A → device B

These have different performance characteristics.

---

21. Cognitive Topology

This leads to a new COS concept:

Cognitive Topology

A Cognitive Shape tells us:

WHAT POSITIONS EXIST

A Cognitive Topology tells us:

HOW POSITIONS CAN COMMUNICATE

Examples:

LINE
GRID
TORUS
TREE
GRAPH
MESH
STAR
RING
FULL
SPARSE GRAPH
DYNAMIC GRAPH

This is highly valuable for:

multi-agent systems
knowledge graphs
robot swarms
distributed inference
sensor networks

---

22. Shape + Topology

COS should therefore distinguish:

SHAPE
=
logical population/data organization

TOPOLOGY
=
communication relationships

PLACEMENT
=
mapping onto physical resources

This is one of the strongest architectural additions from Book 3.

---

23. Current Shape → Current Execution Domain

C* has a “current shape” concept.

COS should generalize this to:

Current Execution Domain

A task executes within a declared domain:

```
with ShapeA
   operation()
```

COS equivalent conceptually:

```
WITH DOMAIN D
   EXECUTE operation
```

The domain defines:

active positions
available data
communication topology
execution scope

---

24. Active and Inactive Positions

C*'s "where" mechanism allows only selected positions to participate.

COS should preserve this concept.

Example:

```
WHERE temperature > threshold
   activate cooling
```

Only matching positions execute the operation.

This gives COS a native:

MASK

abstraction.

mask = condition(data)

MAP(mask, operation)

Masks are important for:

conditional cognition
sparse computation
image processing
attention
robot sensing
knowledge filtering
event processing

---

25. Masked Cognition

This is particularly useful for COS.

Instead of:

if every element...

COS can express:

ACTIVE SET =
    all elements satisfying condition

Then:

reason over active set

This can reduce unnecessary computation.

---

26. Context Must Be Explicit

C* shows that context changes which positions are active.

COS should make context explicit in its IR.

For example:

```
ExecutionDomain
{
    shape
    topology
    mask
    permissions
    resources
    synchronization
}
```

This belongs in the Execution IR / Machine Planning layer.

---

27. Shape Is Also a Memory Contract

C*'s CM-5 implementation shows that shape is not merely mathematical.

Its physical layout affects:

locality
communication
stride
processor placement

performance

Therefore COS should not treat shape as merely:

array dimensions

It should eventually contain:

logical dimensions
layout constraints
placement hints
communication weights
locality requirements
alignment requirements

---

28. Logical Layout vs Physical Layout

COS must preserve:

LOGICAL LAYOUT

separately from:

PHYSICAL LAYOUT

Example:

Logical:

[1024][1024]

Physical:

CPU/GPU/NPU
partitioning
tile size
memory locality
network topology

Changing the physical layout must not change the logical semantics.

---

29. But Physical Layout Must Be Visible to the Optimizer

C* teaches something subtle:

«Physical layout can be hidden from the programmer while still being exposed to the performance system.»

COS should therefore have:

SEMANTIC LAYOUT

and:

EXECUTION LAYOUT

The user/cognitive layer sees:

matrix[1024][1024]

The optimizer sees:

tile = 32×32
GPU residency
memory locality
communication cost

---

30. Layout Becomes Part of Machine IR

This connects directly to the architecture from Books 1–2:

Semantic IR
↓
Execution IR
↓
Machine IR

Book 3 tells us Machine IR needs:

placement
partitioning
layout
communication routes
locality
synchronization

---

31. Physical Shape

C* exposes a "physical" shape representing the available physical processors.

COS should generalize this into:

Physical Resource Domain

Example:

```
PhysicalDomain
{
   CPU cores
   GPU units
   NPU units
   FPGA regions
   memory nodes
   network links
   robot controllers
}
```

The logical domain is then mapped onto the physical domain.

---

32. Capability-Based Placement

COS should never assume:

"there are exactly 8192 processors."

Instead:

```
DISCOVER CAPABILITIES
      ↓
CREATE PHYSICAL DOMAIN
      ↓
MAP LOGICAL DOMAIN
```

This directly supports the long-term COS requirement of working across heterogeneous systems.

---

33. Same Program, Different Machines

The C* architecture demonstrates the principle:

```
same logical program
      ↓
```

different implementation
↓
different physical machine

COS should make this a central property.

Example:

COS task:

MAP embeddings normalize

could become:

CPU:
SIMD loops

GPU:
CUDA-like kernel

NPU:
tensor operation

FPGA:
pipeline

distributed:
partitioned execution

The Semantic IR remains unchanged.

---

34. Communication Cost Must Enter Planning

C* performance material makes a crucial point:

Not all communication is equally expensive.

COS therefore needs a cost model:

COMPUTE COST
MEMORY COST
COMMUNICATION COST
SYNCHRONIZATION COST
ENERGY COST
LATENCY
THROUGHPUT

The planner can then choose between:

move computation to data

and:

move data to computation

This is foundational for future heterogeneous COS.

---

35. Locality

COS should understand:

LOCAL
REMOTE
NEAR
FAR

at multiple levels:

register
cache
local memory
device memory
host memory
neighbor device
network node
remote machine

This follows both Book 1 and Book 3.

---

36. Shape Aliasing

C* even permits advanced shape aliasing: the same physical data can be viewed under another logical shape when the layout permits it.

COS should extract the principle, not copy the dangerous implementation technique.

Principle:

«A data object may admit multiple valid logical views without physically copying the data.»

COS calls this:

Logical View

Example:

same tensor
↓
matrix view
↓
vector view
↓
tile view
↓
batch view

This can eliminate unnecessary data movement.

---

37. But Views Need Verification

Because physical layout matters, COS views must carry:

base object
shape
stride
offset
layout
bounds
aliasing information
permissions

This is directly compatible with the machine-independent data model developed from SICP.

---

38. Parallel Pointer → COS Data View

C* demonstrates that a parallel pointer contains more than a raw address.

COS should therefore avoid representing all distributed data as:

void*

A COS distributed data reference should conceptually contain:

DataRef

{
  object_id
  logical_shape
  layout
  placement
  stride/view
  memory_domain
  permissions
  version
}

This is much safer and more powerful.

---

39. Versioned Distributed Data

For cognitive systems, data may change while multiple workers operate.

Therefore COS should eventually add:

data version

to distributed objects.

Example:

KnowledgeState v41
KnowledgeState v42

Workers can declare which version they used.

This improves:

reproducibility
debugging
provenance
concurrency
rollback

---

40. Communication Collision Semantics

C* explicitly deals with collisions during communication.

COS should make collision behavior part of the IR.

Example:

```
SCATTER
   source = S
   index = I
   collision = SUM
```

or:

collision = REJECT

or:

collision = LAST_WRITE

Never leave this behavior undefined.

---

41. Synchronization

Parallel operations implicitly raise ordering questions.

COS should distinguish:

ASYNC

from:

SYNCHRONIZED

and eventually:

BARRIER

FENCE

DEPENDENCY

EVENT

This connects directly to the time/concurrency lessons from SICP.

---

42. Cognitive Event Streams + Parallel Shapes

Now Books 2 and 3 combine beautifully.

A COS stream can have a shape:

```
sensor_stream
   shape = [1024]
   time = continuous
```

or:

```
robot_sensor_stream
   shape = [128][128]
   time = continuous
```

The execution system can process each incoming event across the logical domain.

---

43. Knowledge Graph + Parallel Domain

The Knowledge Graph need not always be processed node-by-node.

COS can create:

KnowledgeDomain

where positions represent:

knowledge atoms

Then:

MAP
FILTER
GATHER
SCATTER
REDUCE

can operate over candidate knowledge.

This provides a path toward parallel symbolic reasoning without abandoning the symbolic architecture.

---

44. Multi-Agent Systems

C* does not give us “AI agents.”

But its architecture gives COS a useful primitive:

logical population
+
communication topology
+
parallel execution

Therefore a future agent population can be represented as:

```
AgentDomain
{
   shape
   topology
   agent_state
   capabilities
   communication_policy
}
```

But an agent is still a COS cognitive entity—not simply a processor.

---

45. Semantic Bus

The supplied proposal of an “inter-agent semantic bus” is directionally useful, but COS should make it broader.

Instead of:

tensor backplane

use:

Cognitive Communication Fabric

It should support:

data
events
messages
beliefs
observations
requests
results
knowledge references
proof references
control signals

with typed semantics.

---

46. Communication Has Semantics

A COS message should eventually contain something like:

```
Message
{
   sender
   receiver / group
   type
   payload
   timestamp
   causal_parent
   provenance
   authorization
   priority
   delivery_requirement
}
```

This is far more powerful than merely moving tensors.

---

47. C* Left Indexing → COS Indexed Routing

C*'s parallel left indexing is one of the most interesting ideas in the book.

Conceptually:

```
destination = source[index]
```

or:

```
destination[index] = source
```

allows an entire routing operation to be expressed as data.

COS should generalize this to:

Indexed Routing

```
ROUTE
   payload
   using index
```

collision policy

This can support:

embedding lookup
memory lookup
graph edges
agent routing
sensor routing
task routing
distributed gather/scatter

---

48. Routing as Data

A profound lesson is:

«The routing pattern itself can be represented as data.»

Instead of hard-coding:

send A to B
send C to D
...

COS can construct:

routing_map

and execute it.

This allows the cognitive system to reason about communication itself.

---

49. Communication Becomes Programmable Cognition

COS can therefore reason:

I need these observations
↓
construct routing map
↓
execute gather
↓
combine observations
↓

reason

The network becomes part of the computation graph.

---

50. Grid Communication → Spatial Cognition

C*'s grid communication is particularly useful for:

computer vision
robotics
physics simulation
maps
fluid dynamics
cellular models
distributed sensors

Example:

```
each cell
    reads neighbors
    computes local state
    writes next state
```

This is a natural COS primitive.

---

51. General Communication → Cognitive Graphs

General communication is more appropriate for:

knowledge graphs
agent networks
irregular meshes
sparse attention
event routing
dependency graphs

COS should therefore choose communication mechanisms based on topology.

---

52. Topology-Aware Scheduler

The scheduler eventually needs to know:

TASK
DATA
TOPOLOGY
HARDWARE

and choose:


placement
communication method
partitioning
synchronization


This becomes a major part of the future Machine IR planner.

---

53. New COS Architecture

After Books 1–3, the architecture becomes:





---

54. The New Four-Way Separation

COS now needs four distinct concepts:

SHAPE
What logical positions exist?

TOPOLOGY
How can they communicate?

PLACEMENT
Where are they physically executed?

VIEW
How is the underlying data represented?

These must not be collapsed into one object.

---

55. Cognitive Domain

The resulting abstraction should be:

```
CognitiveDomain
{
   shape
   topology
   active_mask
   data_views
   communication_rules
   synchronization
   placement_constraints
   authorization
}
```

This is one of the most important architectural additions from Book 3.

---

56. Example: Vision

A camera image might become:

Shape:
[4096][4096][3]

Topology:
2D grid

Mask:
valid pixels

Data view:
uint8 / normalized float

Operation:
feature extraction

Placement:
GPU

Communication:
neighbor tiles

COS does not need to know the physical GPU layout at the semantic level.

---

57. Example: Robot

Robot sensor state:

Shape:
[128]

Topology:
graph

Positions:
sensor / actuator / joint states

Mask:
active sensors

Operation:
state estimation

Placement:

CPU + NPU

Communication:
sensor → estimator → controller

---

58. Example: Knowledge Search

Shape:
[10,000,000 knowledge atoms]

Topology:
knowledge graph

Mask:
atoms satisfying domain constraints

Operation:
retrieve / compare / infer

Gather:
candidate dependencies

Reduce:
evidence aggregation

Placement:
CPU + accelerator

This is much closer to a true Cognitive OS than treating everything as neural tensors.

---

59. Example: Multi-Agent Cognition

Shape:
[10,000 agents]

Topology:
dynamic sparse graph

Mask:
agents participating in task

Operation:
reason / communicate / vote / specialize

Gather:
observations

Reduce:
aggregate results

Scatter:
assign subtasks

The same execution model applies without defining agents as processors.

---

60. Virtualization Principle

The correct COS principle derived from C* is:

«Logical computational scale must be independent of instantaneous physical computational scale.»

Therefore:

COS task size
≠
number of physical processors

A task may logically contain:

1,000,000 positions

while physically using:

4 CPU cores

or:

1 GPU

or:

100 GPUs

subject to resource and performance constraints.

---

61. But Virtualization Must Not Hide Reality

Book 1 prevents us from making the opposite mistake.

COS must know:

physical memory
latency
bandwidth
processor count
communication topology
energy
failure

Therefore:

LOGICAL ABSTRACTION
+
PHYSICAL MODEL

must coexist.

---

62. This Is the Missing Bridge

Books 1–3 now converge:

SICP:
abstraction

Book 1:
physical reality

C*:
logical parallelism mapped onto physical reality

Therefore:

SEMANTIC IR
↓
COGNITIVE DOMAIN
↓
EXECUTION PLAN
↓
PHYSICAL PLACEMENT
↓
MACHINE IR

This is the architecture we were missing.

---

63. New Machine IR Requirements

Machine IR should eventually contain:

```
MachineIR
{
   target_devices
   partitioning
   placement
   memory_spaces
   data_layout
   communication_routes
   synchronization
   kernel_operations
   resource_limits
   estimated_cost
   failure_policy
}
```

---

64. New Execution IR Requirements

Execution IR should eventually contain:

```
ExecutionPlan
{
   domain
   operations
   dependencies
   maps
   reductions
   scans
   gathers
   scatters
   broadcasts
   communication
   synchronization
   verification
}
```

This is more expressive than today's CIR.

---

65. New Domain IR

COS should eventually introduce:

```
DomainIR
{
   shape
   topology
   active_mask
   placement_constraints
}
```

This can sit between Semantic IR and Execution IR.

Potential pipeline:

```
SIR
↓
Domain IR
↓
Execution IR
↓
Machine IR
↓
Hardware
```

---

66. Performance Principle

COS should optimize:

```
TOTAL COST
=
COMPUTE
+
MEMORY MOVEMENT
+
COMMUNICATION
+
SYNCHRONIZATION
+
I/O
+
ENERGY
```

The cheapest arithmetic operation is irrelevant if its data movement is enormously expensive.

This connects directly to Book 1's storage/timing lesson.

---

67. Important Rejection

COS should not copy C* literally.

We should not create:

C* syntax inside COS

nor assume:

all computation = arrays

nor assume:

all parallelism = processors in a grid

nor assume:

all cognitive workers = neural networks

Instead we extract the underlying architecture.

---

68. What COS Takes from C*

Adopt

✓ logical shapes
✓ logical positions
✓ current execution domain
✓ scalar/global vs distributed data
✓ masks / active positions
✓ map-like elemental operations
✓ reductions
✓ scans
✓ broadcast/spread
✓ gather
✓ scatter
✓ collision semantics
✓ structured communication
✓ general communication
✓ topology

✓ data views
✓ shape-aware references
✓ logical/physical layout separation
✓ runtime hardware mapping
✓ topology-aware optimization
✓ communication-aware performance

Adapt

C* shape
→ COS Cognitive Shape

C* current shape
→ COS Execution Domain

C* parallel variable
→ COS Distributed Object

C* left indexing
→ COS Indexed Routing

C* grid communication
→ COS Topology Communication

C* physical shape
→ COS Physical Resource Domain

Do not copy

✗ C* syntax wholesale
✗ CM-specific processor assumptions
✗ CM-5 memory layout
✗ historical instruction mechanisms
✗ fixed-dimensional hardware assumptions
✗ treating all cognition as array computation

---

69. New Architectural Laws

Book 3 adds these laws:

P13 Logical computational space must be independent of physical processor count.

P14 Shape and topology are different concepts.

P15 Logical layout and physical layout must be separable.

P16 Communication is part of computation.

P17 Communication patterns must be representable as data.

P18 Collision behavior must be explicit.

P19 Active/inactive execution must be representable as a mask.

P20 Physical placement belongs to execution planning, not semantic meaning.

P21 Data views should permit multiple logical representations without unnecessary copying.


P22 The scheduler must be topology- and locality-aware.


P23 Distributed computation must preserve semantic traceability.

---

70. Updated COS Architecture

The architecture after Book 3 is now:





---

71. The Deeper COS Idea

After three books, COS is becoming something different from a conventional operating system.

A conventional OS primarily manages:

processes
memory
files
devices

COS must additionally manage:

meaning
knowledge
reasoning
computational domains
data topology
cognitive resources
provenance
verification

Therefore:

«COS is an operating system for computational processes whose primary abstraction is not merely the process, but the verified cognitive task.»

---

72. Current Implementation Consequence

Do not rewrite COS v2.1.

It remains valuable.

Instead, place it underneath the new architecture:

CURRENT COS v2.1

COS-B
↓
Bytecode
↓
CIR
↓
SIR
↓
Knowledge
↓
Reasoning
↓
Mathematics

Future:

SIR
↓
Domain IR
↓
Execution Planner
↓
CIR extension
↓
Machine IR
↓
backend

So the existing implementation becomes the foundation rather than a discarded prototype.

---

73. What Should Be Built Eventually

The first implementation target inspired by Book 3 should be very small.

Not GPU support.

Not multi-agent AI.

Not distributed cloud infrastructure.

First build:

COS DOMAIN MODEL

with:

Shape
Position
Mask
Topology
DataView
Placement

and then implement a tiny simulator.

---

74. Minimal Domain Example

Something like:

```
shape S = [8];

mask M = [1,1,0,1,1,0,0,1];

topology T = LINE;

operation:
    x = x + 1;
```

The simulator should produce:

logical execution trace

without requiring any GPU.

Then:

shape S = [4][4];
topology T = GRID;
operation = neighbor_sum;

Again:

software simulator first

---

75. Why Simulator First?

Book 2 teaches:

machine can be represented as data

Book 1 teaches:

machine behavior must be observable

Book 3 teaches:

logical computation can be mapped onto physical resources

Therefore COS should first create:

Cognitive Domain Simulator

before connecting it to physical accelerators.

---

76. Final Book 3 Principle

The deepest lesson from C* for COS is not:

«“Use parallel arrays.”»

It is:

«Separate the logical organization of computation from its physical realization, while making data movement, topology, locality, and synchronization explicit enough for the system to optimize and verify them.»

That is exactly the bridge COS needs between:

COGNITION

and:

HARDWARE.

---

77. Book 1 + Book 2 + Book 3

The three books now form a coherent progression:

BOOK 1
How does a physical computer actually work?

↓

BOOK 2
How can computation be represented through abstraction, data, languages and machines?

↓

BOOK 3
How can one logical computation operate across a distributed parallel machine without being tied to its physical organization?

↓

COS
How can a cognitive task operate across heterogeneous computational systems while preserving meaning, provenance, authorization, verification and physical efficiency?

This is the architectural direction we should carry into Book 4.One especially important takeaway: your original intuition about a “virtual cognitive engine” was close, but C* gives us a cleaner foundation: Shape + Topology + Placement + View. That four-part abstraction should become a first-class part of COS rather than building an AI-specific “parallel worker” system around GPUs/SLMs.