

Procedural Generation Using Noise

Michael Li

DRAFT 1

Dr.Dianne Hansford

Director

Dr.Yoshihiro Kobayashi

Second Committee Member



Ira A. Fulton Schools of Engineering
School of Computing, Informatics, and Decision Systems Engineering
Spring 2021

Abstract

Procedural Content Generation is a method of creating data algorithmically, often using stochastic models. These methods can be used to generate complex environments as opposed to manually creating environments by hand or by using photogrammetric techniques. Procedural generation can use a variety of techniques to achieve a stochastic or partially stochastic goal, including methods such as fractals, noise, deep learning as examples.

Contents

Abstract	1
1 Introduction	3
1.1 Overview	3
2 Mapping	4
3 Height Maps	5
4 Polygons	6
4.1 Rendering Differences	6
4.2	6
5 Voxels	7
6 Development	8
6.1 Areas of Research	8
6.2 Algorithm Advancements	8
6.3 Summary	8
6.4 Appendix	8
6.5 References	8

1. Introduction

This paper surveys various methods of procedural generation and their applications in generating geological formations. While procedural generated content can vary in task from generating terrain to creatures and stories, the focus of this paper is primarily on terrain and more specifically geological formations. While procedural generation is often described as being stochastic, in reality it is not entirely so. The majority of the techniques used for procedural generation include some level of user control, as well as a specified input to use as a starting point for the equation. This input, known as a seed is transformed through code to create the output, in this case geological formations.

1.1 Overview

2. Mapping

Before the development of more advanced noise generation techniques, some basic procedural generation techniques were used as early as the 1980s. One of the earliest usages of procedural generation was in *Rogue* which used a three by three grid in order to generate the layout of the level, with hallways randomly connecting the rooms. Some of these techniques were developed in order to bypass the computational restraints of the time.

Perlin noise was developed for use in the movie industry, although it later became a foundation for many other procedural generation algorithms as it provided a lot of control as well as randomness to be used. It was developed in 1983 for use in the sci-fi movie *Tron*, to map textures onto computer generated surfaces for visual effects. Perlin noise has been used for many different visual elements, ranging from the texture creation it was created for to particle effects such as fire, smoke and clouds, as well as landscapes and geological features. It has a variety of uses due to its ability to create a naturalistic appearance.

3. Height Maps

As mentioned previously, Perlin noise can be used to generate height maps in order to pseudo-randomly create geological formations. While heightmaps have the advantage of being two-dimensional and less complicated to run, they have difficulty in rendering a variety of geological formations. Due to the two-dimensional nature of a height map, they are unable to render more complex features such as alcoves, arches, and any other three-dimensional feature. In terms of randomness, this can create a sort of uniformity in geometry, where the only features are hills and valleys. This can be mitigated to some extent by the use of layering Perlin noise.

Implementation and how perlin noise works

While Perlin noise saw great success, it was succeeded by algorithms such as Simplex noise, designed to alleviate some of the problems with Perlin noise. This included the computational complexity and the artifacting in the noise created.

Some of the other uses of height maps include the voxel space rendering system, using voxel raster graphics to display three-dimensional geometry with low memory and processing requirements. This was developed in the early 90's, involving a height and color map to position the pixels on the screen. While this technique was not historically used with noise generating algorithms, the rendering system fits the requirements for the use of techniques such as two-dimensional Perlin noise. At the time, displaying complex heightmaps in three-dimensions was difficult computationally, and the voxel space technique allowed this to happen.

Talk about usage of heightmaps, weaknesses

some weakness include - only 2 dimensional geological formations, so archways and caves are not possible

might be mitigatable by layering multiple different height maps, but increases computation time

example of practical application in rendering or pre generating voxel space heightmaps

4. Polygons

4.1 Rendering Differences

Constructing polygons from height maps, similar problem

4.2

5. Voxels

Voxels can be used in a lot of ways to render maps
Talk about minecraft's storage of voxel terrain data
Contrast with vooxel rendering techniques

6. Development

6.1 Areas of Research

Possible areas of research?

There is deep learning for procedural generation, but it appears to not be very sophisticated - I cant tell any differences between the deep learning application of noise and just normal perlin noise

6.2 Algorithm Advancements

Talk about areas that have been advanced; i.e perlin noise vs simplex noise

6.3 Summary

6.4 Appendix

6.5 References

L^AT_EX [1] is a set of macros built atop T_EX [1].

Bibliography

- [1] N. Mikuličić and Ž. Mihajlović. Procedural generation of mediterranean environments. In *2016 39th International Convention on Information and Communication Technology, Electronics and Microelectronics (MIPRO)*, pages 261–266, 2016.