Item	Drawing	Part	Source	Qty	Mass kg
1	NS6-100	Blade, glass/epoxy, glass UD caps	new	3	20.6
2	NS6-200	Fixed hub weldment S355NL + shims ±2°	new	1	87
3	NS6-210	Spinner (GRP)	new	1	6
4	Rev C gen.	G6 generator: Rev C stator, drum, magnets, no fins/ribs	doc 23/29	1	263
5	NS6-610	Plain rear cover (replaces the bladed Rev C cover)	new	1	7
6	NP1-100/101	Spindle 42CrMo4 Ø140/90 + spacer	12 kW	1	58
7	NP1-230	Brake disc 16 mm	12 kW	1	34.5
8	NP1-310	Brake caliper bracket (one of two positions used)	12 kW	1	–
9	bought	Spring caliper, 1.5 kNm spring pack	doc 29	1	≈ 9
10	NP1-320	Rotor lock pin and holder	12 kW	1	4
11	NS6-300	Bedplate weldment, 6 kW (lighter)	new (doc 32)	1	127
12	NY-400…460	Yaw ring, adapter, 2 gearmotors, pads, lock, encoder, hanger	12 kW doc 25	1 set	≈ 275
13	NS6-400	Tower 18 m, 2 sections, base hinge	new size	1	1824
14	NS6-500	Foundation: spread footing or rock plinth	new size	1	concrete
15	NS6-600	Braking resistor box + K1 + safety chain	new (doc 29)	1	≈ 18
16	doc 12	Converter, dump chopper, 48 V module (6 kW firmware)	12 kW	1	–

NOTES

1. The 12 kW drawings named here (cad/nacelle_p1 NP1-xxx, cad/yaw NY-4xx, generator Rev C sheets in project files generator/revC) are used unchanged.
2. G6 differences from Rev C (doc 29): inner fins, outer ribs and cover blades left off; one caliper with a lighter spring pack; braking resistor and contactor added.
3. NS6-300 replaces the 12 kW bedplate NP1-300 (doc 32). Same interfaces: spindle flange, yaw inner ring, gearmotor brackets NP1-420, pad units NY-410, lock pin holder, cable hanger.
4. Masses: calculated. Head mass above the tower flange in doc 32 §2.

Dimensions mm · ISO 2768-mK · ISO 8015 · first angle projection · edges broken 0.5 unless stated · NOT CHECKED: prototype release only after review

6 kW WIND TURBINE S6 (ICELAND) · FIXED PITCH, STALL CONTROL

PARTS LIST AND REUSED 12 kW DRAWINGS

DRAWING NO.	REV / DATE	SCALE (A3)
NS6-001	A · 2026-11-06	–
MATERIAL	MASS (CALC.)	DRAWN / CHECKED
–	–	Claude / not checked