Drawing	Title	Source
NM8-000	GENERAL ARRANGEMENT · 12 kW M8 ON 8 m TOWER	M8 rev A
NM8-001	DRAWING INDEX	M8 rev A
NM8-002	BILL OF MATERIALS (1/2)	M8 rev A
NM8-003	BILL OF MATERIALS (2/2)	M8 rev A
NM8-010	GENERAL ARRANGEMENT · NACELLE AND DRIVETRAIN	M8 rev A
NM8-020	ROTOR ASSEMBLY · HUB, PITCH SYSTEM, BLADES, SPINNER	M8 rev A
NM8-100	BLADE Ø8.0 m · PLANFORM, TWIST AND ROOT	M8 rev A
NM8-105	BLADE ROOT INSERT M16 (BONDED)	M8 rev A
NM8-110	BLADE MOULD SET (PLUG, TWO HALVES, FRAME)	M8 rev A
NM8-200	HUB WELDMENT (COLLECTIVE PITCH)	M8 rev A
NM8-210	SPINNER (GRP) WITH BLADE BOOTS	M8 rev A
NM8-215	GENERATOR REV D · CHANGE SHEET (STACK 74 → 104 mm)	M8 rev A
NM8-250	COLLECTIVE PITCH · BEARINGS, CRANKS, LINKS, YOKE, CYLINDER	M8 rev A
NP8-300	BEDPLATE WELDMENT 12 kW NP8 (LIGHT)	M8 rev A
NM8-311	ROTOR BRAKE · THREE CALIPERS AND THIRD CALIPER BRACKET	M8 rev A
NM8-911	YAW SYSTEM LAYOUT · SLEWING RING Dpw 410	M8 rev A
NM8-400	TOWER 8 m · ONE-PIECE TILT-UP MONOPOLE	M8 rev A
NM8-410	BASE HINGE, GIN POLE INTERFACE AND ERECTION	M8 rev A
NM8-500	FOUNDATION · SPREAD FOOTING (8 m TOWER, M8)	M8 rev A
NM8-900	FASTENER AND TORQUE SCHEDULE	M8 rev A
NM8-910	BOUGHT PARTS SPECIFICATION (ENVELOPES AND INTERFACES)	M8 rev A
NP1-101/102	Front spacer, rear seal sleeve (Rev B)	12 kW P1 rev B
NP1-202	Stator front clamp ring	12 kW P1 rev B
NP1-211	Bearing seal covers front / rear	12 kW P1 rev B
NP1-212C	Drum rear cover with 24 fan blades	Rev C (doc 23)
NP1-230	Brake disc 16 mm Ø880 / Ø652	12 kW P1 rev B
NP1-310	Brake caliper brackets 3 and 9 o'clock	12 kW P1 rev B
NP1-320/321	Rotor lock pin and holder	12 kW P1 rev B
NP1-420	Yaw drive brackets (radius +30)	12 kW doc 25
NY-400…460	Adapter, pad units, lock, encoder, cable hanger (radii +25, see NM8-410)	12 kW doc 25
NM8-700/710/720/730	Nacelle cover, frame, met mast, junction box (S6 parts, cover front 15 mm longer	S6 rev B
NM8-420	Gin pole and tilt-up rigging (S6 tool, line pull see NM8-400)	S6 rev B
NM8-600/620/800	Resistor box, base cabinet, cabling routes (S6)	S6 rev B

NOTES

1. Rev A (2026-11-06): first issue for the 12 kW M8 on the 8 m tower (doc 37). Every new or changed part has an axonometric view from the 3D model (cad/turbine_m8/model8.py).
2. Reused drawings are used unchanged except where this index says otherwise. Their PDFs are in the earlier sets (cad/nacelle_p1, cad/yaw, cad/turbine_6kw).
3. All sheets NOT CHECKED: prototype release only after review, the open checks of doc 37 §9 and the supplier drawings of the bought parts.

Dimensions mm · ISO 2768-mK · ISO 8015 · first angle projection · edges broken 0.5 unless stated · NOT CHECKED: prototype release only after review

12 kW WIND TURBINE M8 (ICELAND) · Ø8.0 m, COLLECTIVE PITCH · 8 m TOWER

DRAWING INDEX (NM8 SET REV A + REUSED DRAWINGS)

DRAWING NO.	REV / DATE	SCALE (A3)
NM8-001	A · 2026-11-06	–
MATERIAL	MASS (CALC.)	DRAWN / CHECKED
–	–	Claude / not checked