Part	Specification	Interface	Qty
Pitch bearing (NM8-250)	4-point, Dpw 300, balls 30, Z 28, s0 ≥ 1.25 under SLM H	outer 20 holes PCD 360, inner 12 × M16 PCD 245	3
Pitch cylinder + motor (NM8-270)	≥ 28.5 kN rated, 37 kN static, 204 mm stroke, motor brake ≥ 14.2 Nm	trunnion in the nose frame	1
Supercap module (NM8-280)	≥ 4.1 kJ per stroke × 3.6 at EOL, −30 °C heater	nose frame tray	1
Main bearings (NM8-913)	32028 X tapered roller, C 280 kN, C0 430 kN	Ø140 j6 / f6, Ø210 P7	2
Brake calipers (NM8-915)	spring-applied, 4.8 kNm each on the Ø880 × 16 disc, ≥ 16.2 kN clamp	4 × M16 axial	3
Yaw slewing ring (NM8-911)	Dpw 410, external gear z165 m4, face 60, s0 ≥ 1.25	PCD 350 / 490, 16 × M16 each	1
Yaw gearmotor (NM8-912)	≥ 2.3 kNm static output, pinion z14 m4, motor brake	NP1-420 bracket	2
Magnets (NP1-220F)	N45SH 30 × 15 × 12, NiCuNi, 280 + spares	comb + sleeve	280
Slip ring	6 power + 6 signal, IP65, −30 °C	spindle nose Ø120	1
Overspeed sensors	M18 inductive PNP, 2 channels	NP1-321 seats	2
Converter + controller	12 kW, doc 12 / doc 35 §8	base cabinet	1

NOTES

1. Replace the 3D envelopes with the supplier models before release and rerun cad/turbine_m8/clash8.py.
2. Low-temperature grades (−30 °C operation, −40 °C storage) for all lubricants, seals and electronics.

Dimensions mm · ISO 2768-mK · ISO 8015 · first angle projection · edges broken 0.5 unless stated · NOT CHECKED: prototype release only after review

12 kW WIND TURBINE M8 (ICELAND) · Ø8.0 m, COLLECTIVE PITCH · 8 m TOWER

BOUGHT PARTS SPECIFICATION (ENVELOPES AND INTERFACES)

DRAWING NO.	REV / DATE	SCALE (A3)
NM8-910	A · 2026-11-06	–
MATERIAL	MASS (CALC.)	DRAWN / CHECKED
see lines	see lines	Claude / not checked