

```
AYOO@DESKTOP-UKN0IF6 MINGW64 ~/Desktop/learn_git
$ touch third.txt

AYOO@DESKTOP-UKN0IF6 MINGW64 ~/Desktop/learn_git
$ git init
Initialized empty Git repository in C:/Users/AYOO/Desktop/learn_git/.git/

AYOO@DESKTOP-UKN0IF6 MINGW64 ~/Desktop/learn_git (master)
$ git add .

AYOO@DESKTOP-UKN0IF6 MINGW64 ~/Desktop/learn_git (master)
$ git status
On branch master

No commits yet

Changes to be committed:
  (use "git rm --cached <file>..." to unstage)
    new file:   third.txt

AYOO@DESKTOP-UKN0IF6 MINGW64 ~/Desktop/learn_git (master)
$ git commit -m "adding third.txt"
[master (root-commit) 09026aa] adding third.txt
 1 file changed, 0 insertions(+), 0 deletions(-)
 create mode 100644 third.txt

AYOO@DESKTOP-UKN0IF6 MINGW64 ~/Desktop/learn_git (master)
$ git status
On branch master
nothing to commit, working tree clean

AYOO@DESKTOP-UKN0IF6 MINGW64 ~/Desktop/learn_git (master)
$ git log
commit 09026aa15ce4b1c4a53a164d952dbb7196b26e3a (HEAD -> master)
Author: SAIDJ Safa <sf3025349@gmail.com>
Date:   Fri Jul 14 14:30:11 2023 +0200

    adding third.txt

AYOO@DESKTOP-UKN0IF6 MINGW64 ~/Desktop/learn_git (master)
$ touch fourth.txt

AYOO@DESKTOP-UKN0IF6 MINGW64 ~/Desktop/learn_git (master)
$ git add fourth.txt

AYOO@DESKTOP-UKN0IF6 MINGW64 ~/Desktop/learn_git (master)
$ git status
```

```

AYOO@DESKTOP-UKN0IF6 MINGW64 ~/Desktop/learn_git (master)
$ git status
On branch master
Changes to be committed:
  (use "git restore --staged <file>..." to unstage)
    new file:   fourth.txt

AYOO@DESKTOP-UKN0IF6 MINGW64 ~/Desktop/learn_git (master)
$ git commit -m "adding fourth.txt"
[master faf2553] adding fourth.txt
 1 file changed, 0 insertions(+), 0 deletions(-)
 create mode 100644 fourth.txt

AYOO@DESKTOP-UKN0IF6 MINGW64 ~/Desktop/learn_git (master)
$ git rm third.txt
rm 'third.txt'

AYOO@DESKTOP-UKN0IF6 MINGW64 ~/Desktop/learn_git (master)
$ git add .

AYOO@DESKTOP-UKN0IF6 MINGW64 ~/Desktop/learn_git (master)
$ git status
On branch master
Changes to be committed:
  (use "git restore --staged <file>..." to unstage)
    deleted:   third.txt

AYOO@DESKTOP-UKN0IF6 MINGW64 ~/Desktop/learn_git (master)
$ git commit -m "removing third.txt"
[master 1bf4ee5] removing third.txt
 1 file changed, 0 insertions(+), 0 deletions(-)
 delete mode 100644 third.txt

```

```

AYOO@DESKTOP-UKN0IF6 MINGW64 ~/Desktop/learn_git (master)
$ git log
commit 1bf4ee5eaa667aecef2440e45cac13f3eefb3bee (HEAD -> master)
Author: SAIDJ Safa <sf3025349@gmail.com>
Date:   Fri Jul 14 14:40:14 2023 +0200

    removing third.txt

commit faf2553cc64692942ce716923d27b0320fffd255
Author: SAIDJ Safa <sf3025349@gmail.com>
Date:   Fri Jul 14 14:33:16 2023 +0200

    adding fourth.txt

commit 09026aa15ce4b1c4a53a164d952dbb7196b26e3a
Author: SAIDJ Safa <sf3025349@gmail.com>
Date:   Fri Jul 14 14:30:11 2023 +0200

    adding third.txt

AYOO@DESKTOP-UKN0IF6 MINGW64 ~/Desktop/learn_git (master)
$

```

```
AYOO@DESKTOP-UKN0IF6 MINGW64 ~/Desktop/learn_git (master)
$ git config --global user.name "SAIDJSAFA"
```

```
AYOO@DESKTOP-UKN0IF6 MINGW64 ~/Desktop/learn_git (master)
$ git config --global user.email sf3025349@gmail.com
```

```
AYOO@DESKTOP-UKN0IF6 MINGW64 ~/Desktop/learn_git (master)
$ git config --global
usage: git config [<options>]
```

Config file location

--global	use global config file
--system	use system config file
--local	use repository config file
--worktree	use per-worktree config file
-f, --file <file>	use given config file
--blob <blob-id>	read config from given blob object

Action

--get	get value: name [value-pattern]
--get-all	get all values: key [value-pattern]
--get-regexp	get values for regexp: name-regex [value-pattern]
--get-urlmatch	get value specific for the URL: section[.var] URL
--replace-all	replace all matching variables: name value [value-pattern]

ern]

--add	add a new variable: name value
--unset	remove a variable: name [value-pattern]
--unset-all	remove all matches: name [value-pattern]
--rename-section	rename section: old-name new-name
--remove-section	remove a section: name
-l, --list	list all
--fixed-value	use string equality when comparing values to 'value-pattern'

tttern'

-e, --edit	open an editor
--get-color	find the color configured: slot [default]
--get-colorbool	find the color setting: slot [stdout-is-tty]

Type

-t, --type <type>	value is given this type
--bool	value is "true" or "false"
--int	value is decimal number
--bool-or-int	value is --bool or --int
--bool-or-str	value is --bool or string
--path	value is a path (file or directory name)
--expiry-date	value is an expiry date

Other

-z, --null	terminate values with NUL byte
------------	--------------------------------