AquaPearl Installation Guide

1. Before You Install

Check that your site meets these conditions before you start. Inlet water pressure must be between 10 and 60 psi (0.7 to 4.1 bar). Above 60 psi you must fit a pressure regulator; below 10 psi you need a booster pump. Feed water TDS must be below 2,000 ppm.

You need a grounded 220–240 V socket within 1.5 metres of the unit, a cold-water supply line, and a drain pipe for the reject water. Leave at least 10 cm of clearance on each side of the unit and 15 cm above it for filter changes.

2. Tools Required

Drill with 6 mm masonry bit and 12 mm bit (for the faucet hole if your sink has none), screwdriver, adjustable spanner, PTFE thread tape, a tube cutter or sharp blade, a spirit level and a towel. A pencil and measuring tape are useful for marking the bracket position.

3. Wall-Mount Installation

Step 1: Mark the bracket position at least 30 cm above the counter, using the spirit level. Step 2: Drill four 6 mm holes, insert the wall plugs and fix the bracket with the supplied screws. Step 3: Hang the unit on the bracket and check that it sits level.

Step 4: Close the main cold-water supply. Fit the 3-way inlet valve to the cold-water line using PTFE tape. Step 5: Connect the white inlet tube from the valve to the IN port. Step 6: Fit the drain saddle clamp to the drain pipe above the trap and connect the red drain tube. Step 7: Connect the faucet to the OUT port and mount the faucet on the sink.

4. Under-Sink Installation

Place the unit upright on the cabinet floor on a drip tray. Follow steps 4 to 7 of the wall-mount procedure. Make sure no tube is kinked behind the unit and that the drain tube runs downhill without loops.

Under-sink installation is not suitable if the cabinet floor is regularly damp. In that case use the wall-mount method.

5. First-Run Flushing Procedure

Every new purifier and every new filter must be flushed before you drink the water. New carbon and RO cartridges release fine carbon particles and a food-grade preservative. Until these are rinsed out, the water can taste bitter, flat or unusual and may look slightly grey.

To flush: open the inlet valve, switch the unit on, let the tank fill completely (about 50 minutes for a new unit) and then empty it through the faucet. Repeat once, so that you discard the first two full tanks — about 20 minutes of running water after the tank is full each time. After a single filter change, discarding one full tank is usually enough, but discard two if the taste is still unusual.

Skipping this procedure is the most common cause of complaints about taste after installation or after a filter change.

6. Professional Installation

A Pearlz technician can install the unit for PKR 1,500 in Karachi, Lahore, Islamabad and Rawalpindi, and PKR 2,500 in other cities. Book through the Pearlz app or the helpline 0800-PEARLZ. Visits are scheduled within 3 working days in metro cities.

The technician brings a pressure gauge and will fit a regulator or booster pump if needed, which are charged separately.

7. Self-Installation and Your Warranty

You may install the unit yourself without affecting the warranty, provided you follow this guide. The warranty is void if, during self-installation, you drill into or open the purifier body, use fittings or tubes that are not supplied by Pearlz, or connect the unit to inlet pressure above 60 psi without a regulator.

Keep the photos of your installation; support may ask for them if you make a claim.