AquaPearl 500 Pro — User Manual

1. Box Contents

Thank you for choosing the AquaPearl 500 Pro. Before you begin, check that the carton contains everything listed below. If any item is missing or damaged, contact support within 7 days of delivery.

The box contains: the AquaPearl 500 Pro purifier unit with the four filter cartridges and UV lamp pre-installed; one 12-volt power adapter; a wall-mounting bracket with four screws and four wall plugs; a 3-way inlet valve (1/2 inch); 3 metres of 1/4 inch white inlet tubing; 2 metres of red drain tubing; a drain saddle clamp; a chrome faucet with its mounting nut; this user manual; and the Quick Installation Card.

The box does not include a pressure regulator, a booster pump or a pre-filter housing for very muddy water. These are sold separately if your water supply needs them.

2. Technical Specifications

Parameter	Value
Purification	5 stages: sediment, carbon block, RO membrane, UV-C, mineral
Pure water output	up to 15 litres per hour
Storage tank	12 litres
Operating inlet pressure	10–60 psi (0.7–4.1 bar)
Maximum feed water TDS	2,000 ppm
Feed water temperature	5–38 °C
Power supply	220–240 V AC, 50 Hz via 12 V adapter
Power consumption	36 W while purifying
Dimensions	38 × 26 × 47 cm (W × D × H)
Weight	9.2 kg empty

Using the purifier outside these limits may damage it and is not covered by the warranty. If your mains pressure exceeds 60 psi, fit a pressure regulator before the inlet valve.

3. Control Panel and Indicator Lights

The front control panel has a display and three touch buttons: POWER, RESET and WIFI.

The display shows the output TDS in ppm and the remaining life of the filter that is due soonest. A blue LED ring means the UV lamp is working. A steady green LED means the unit is purifying. A blinking red LED means a filter needs attention; the display shows which one. An amber LED indicates a sensor fault.

Press and hold POWER for 3 seconds to switch the unit on or off. Press and hold RESET for 5 seconds to clear a filter alert after replacing the filter. Press and hold WIFI for 3 seconds to enter app pairing mode.

4. Operating Instructions

Open the inlet valve fully and switch on the unit. The pump starts and the tank begins to fill. The first fill takes about 50 minutes.

Before first use you must complete the first-run flushing procedure described in the Installation Guide. Do not drink the water from the first two tanks.

The unit stops automatically when the tank is full and signals with one long beep. In normal use you do not need to switch the unit off. If you will be away for more than 7 days, close the inlet valve and switch the unit off; on return, discard the first full tank.

5. Filter Replacement Intervals

Filter	Replace every	SKU
Sediment pre-filter	6 months	AP5-SED
Carbon block	12 months	AP5-CB
RO membrane	24 months	AP5-RO
UV lamp	12 months	AP5-UV
Mineral cartridge	12 months	AP5-MIN

Intervals assume a household of four and feed water below 500 ppm TDS. Harder or muddier water shortens filter life. The app shows the remaining life of each filter in days.

6. Filter Maintenance

To replace the sediment pre-filter: switch off the unit and close the inlet valve. Open the front service door. Rotate the pre-filter cartridge a quarter turn anticlockwise and pull it straight out. Push the new cartridge in until it clicks and rotate it a quarter turn clockwise.

Close the service door, open the inlet valve and switch the unit on. Then press and hold the RESET button for five seconds until the red LED stops blinking. This resets the filter alert and the filter-life counter.

After replacing any filter, flush the system by discarding the first full tank of water, as explained in the Installation Guide. Unusual taste after a filter change is almost always caused by skipping this step.

7. Cleaning and Descaling

Wipe the outside of the unit weekly with a soft damp cloth. Do not use solvents or abrasive cleaners.

Sanitise the storage tank every 3 months: empty the tank, add one sachet of the Pearlz descaling kit (SKU AP5-DESC) dissolved in 1 litre of water, let the unit fill, wait 30 minutes and then discard two full tanks.

Descale the faucet aerator every 6 months by soaking it in white vinegar for 20 minutes. In areas with very hard water, descale every 3 months.

8. Safety Warnings

Do not open the purifier body. There are no user-serviceable parts inside except the filters behind the service door. Opening the body exposes live electrical parts and voids the warranty.

Never look directly at the UV lamp while it is on. Use only the supplied 12 V adapter. Keep the adapter away from water. Do not install the unit outdoors, in direct sunlight, or where it may freeze.

If you notice an electrical smell or water near the power adapter, unplug the unit immediately and contact support.

9. Audible Alert Codes

This table applies to firmware 2.3, which was installed when this manual was printed. Later firmware may change some codes; check the release notes.

Sound	Code	Meaning
One long beep	E-01	Tank full (normal)
Two short beeps	E-02	Low inlet pressure
Three short beeps	E-03	Sediment pre-filter saturated
Four short beeps	E-04	RO membrane efficiency low
Continuous beeping	E-05	UV lamp fault
Beep every 10 seconds	E-06	Pump overheating
Rapid beeping	E-07	TDS sensor fault
Two long beeps	E-08	Service mode (technicians only)

E-03 is raised when the sediment pre-filter reaches saturation. The red LED blinks together with three short beeps. Replace the pre-filter and hold RESET for five seconds.

10. Connecting the Pearlz App

Install the Pearlz Home app (Android 9 or later, iOS 15 or later). Turn on Bluetooth and location on your phone. Press and hold WIFI on the purifier for 3 seconds until the display shows PAIR, then follow the steps in the app.

The app shows water usage, filter life, TDS and alerts, and lets you order filters and book service visits. The app is optional; the purifier works fully without it.

11. Storage and Transport

If the unit must be moved, close the inlet valve, empty the tank through the faucet, disconnect the tubes and transport it upright. Do not lay the unit on its side, as water remaining in the RO membrane housing can reach the electronics.

For storage longer than one month, remove the RO membrane, seal it in a clean bag with its preservative and store it in a refrigerator.

12. Warranty and Service

The AquaPearl 500 Pro is covered by the Pearlz Warranty Policy. Filter cartridges and the UV lamp are consumables. For the full terms, exclusions and how to claim, see the Warranty Policy and the Service & Maintenance Agreement.

Record your serial number here for reference. The serial number label is inside the front service door.