

DEMOLITION AND DISMANTLING TOOLBOX TALK

Removing one component can change the behaviour of everything connected to it.

PURPOSE AND SCOPE

Prevent unexpected collapse, falling objects, stored-energy release and line-of-fire exposure during demolition and dismantling.

KEY HAZARDS

1  Uncontrolled structural movement.	2  Falling components.	3  Hidden energy sources.	4  Sharp edges.
5  Work at height.	6  Unstable heavy components.	7  Incorrect dismantling sequence.	8  Unauthorised access.

CRITICAL POINTS TO VERIFY IN THE FIELD

01 Uncontrolled structural movement.	02 Falling components.	03 Hidden energy sources.
---	---	--



REMEMBER — SERSEM

S

Stop and think

E

Evaluate the risk

R

Remove or reduce

N

Never assume

E

Ensure protection

M

Monitor and communicate

DEMOLITION AND DISMANTLING TOOLBOX TALK

Removing one component can change the behaviour of everything connected to it.

FIELD REQUIREMENTS AND VERIFICATION

Prevent unexpected collapse, falling objects, stored-energy release and line-of-fire exposure during demolition and dismantling.

SERNEM FIELD 01
FIELD VERIFICATION 1
Sequence approved

SERNEM FIELD 02
FIELD VERIFICATION 2
Energy isolated

SERNEM FIELD 03
FIELD VERIFICATION 3
Support assessed

SERNEM FIELD 04
FIELD VERIFICATION 4
Area barricaded

VERIFICATION BEFORE START

- | | |
|---|--|
| ☐ Sequence approved | ☐ Energy isolated |
| ☐ Support assessed | ☐ Area barricaded |
| ☐ Component weight known | ☐ Lift plan ready |

SUPERVISOR DISCUSSION POINTS

- Is the dismantling sequence defined?
- Is energy isolated?
- Is temporary support required?

FIELD APPLICATION



Removing one component can change the behaviour of everything connected to it.

DEMOLITION AND DISMANTLING TOOLBOX TALK

Removing one component can change the behaviour of everything connected to it.

CRITICAL CONTROL MEASURES

1. ELIMINATE / REDUCE THE RISK

Plan the dismantling sequence. • Determine component weights. • Apply work-at-height controls.

2. ENGINEERING & PHYSICAL CONTROLS

Isolate energy sources. • Plan lifting methods. • Stop and reassess if the plan changes.

3. WORK METHOD & FIELD CONTROLS

Assess temporary-support requirements. • Check connected members before cutting.

4. PPE, VERIFICATION & SUPERVISION

Establish exclusion zones. • Control sharp edges.

CRITICAL WARNING



Team, no dismantling component will be treated as independent. Before cutting we must understand what it supports, what it is connected to and how the system will react; any sequence change requires stop-work and reassessment.

SITE CHECKLIST — BEFORE STARTING WORK

- | | |
|---|---|
| ☐ Sequence approved | ☐ Energy isolated |
| ☐ Support assessed | ☐ Area barricaded |
| ☐ Component weight known | ☐ Lift plan ready |
| ☐ Connections checked | ☐ Sharp edges controlled |
| ☐ WAH controls in place | ☐ Crew briefed |



DEMOLITION AND DISMANTLING TOOLBOX TALK

Removing one component can change the behaviour of everything connected to it.

ATTENDANCE AND APPROVAL

Project / Site: _____ Date: _____

Presented by: _____ Work area: _____

No	Full Name	Company / Role	Signature
1			
2			
3			
4			
5			
6			
7			
8			
9			
10			
11			
12			