

HOSE AND COUPLING SAFETY TOOLBOX TALK

A pressurised hose failure can release uncontrolled energy within seconds.

PURPOSE AND SCOPE

Prevent hose whipping, coupling separation, leaks and failures involving compressed air, water, chemicals and process fluids.

KEY HAZARDS

1  Hose whipping after rupture.	2  Coupling separation under pressure.	3  Chemical or hot-fluid leakage.	4  Cut, crushed or abraded hose bodies.
5  Use of hoses with incorrect pressure	6  Missing whip-checks or locking pins.	7  Hoses routed through traffic or across sharp	8  Disconnecting fittings before pressure is

CRITICAL POINTS TO VERIFY IN THE FIELD

01 Hose whipping after rupture.	02 Coupling separation under pressure.	03 Chemical or hot-fluid leakage.
--	---	--



REMEMBER — SERSEM

S

Stop and think

E

Evaluate the risk

R

Remove or reduce

N

Never assume

E

Ensure protection

M

Monitor and communicate

HOSE AND COUPLING SAFETY TOOLBOX TALK

A pressurised hose failure can release uncontrolled energy within seconds.

FIELD REQUIREMENTS AND VERIFICATION

Prevent hose whipping, coupling separation, leaks and failures involving compressed air, water, chemicals and process fluids.

SERNEM FIELD 01 FIELD VERIFICATION 1

Pressure rating suitable

SERNEM FIELD 02 FIELD VERIFICATION 2

Hose undamaged

SERNEM FIELD 03 FIELD VERIFICATION 3

Coupling suitable

SERNEM FIELD 04 FIELD VERIFICATION 4

Whip-check installed

VERIFICATION BEFORE START

- | | |
|---|---|
| ☐ Pressure rating suitable | ☐ Hose undamaged |
| ☐ Coupling suitable | ☐ Whip-check installed |
| ☐ Safety pin installed | ☐ Routing safe |

SUPERVISOR DISCUSSION POINTS

- Is the hose correctly rated?
- Is a whip-check required?
- Is the coupling locked?

FIELD APPLICATION



A pressurised hose failure can release uncontrolled energy within seconds.

HOSE AND COUPLING SAFETY TOOLBOX TALK

A pressurised hose failure can release uncontrolled energy within seconds.

CRITICAL CONTROL MEASURES

1. ELIMINATE / REDUCE THE RISK

Confirm hose pressure and fluid compatibility. • Protect hoses from sharp edges, hot surfaces and vehicle traffic. • Do not continue using damaged hoses with temporary tape repairs.

2. ENGINEERING & PHYSICAL CONTROLS

Inspect hose bodies and couplings before every use. • Route long hoses to minimise trip hazards. • Establish an exclusion zone for pressure testing or high-energy service.

3. WORK METHOD & FIELD CONTROLS

Use suitable whip-checks on compressed-air connections. • Use a safe leak-detection method rather than hands.

4. PPE, VERIFICATION & SUPERVISION

Install locking pins and coupling restraints. • Isolate and depressurise before disconnecting.

CRITICAL WARNING



Team, hoses may look simple but they can contain significant stored energy. We will inspect the hose, coupling and restraints before applying pressure.

SITE CHECKLIST — BEFORE STARTING WORK

- | | |
|---|--|
| ☐ Pressure rating suitable | ☐ Hose undamaged |
| ☐ Coupling suitable | ☐ Whip-check installed |
| ☐ Safety pin installed | ☐ Routing safe |
| ☐ No leaks | ☐ Sharp edges protected |
| ☐ Isolation method clear | ☐ Crew briefed |



HOSE AND COUPLING SAFETY TOOLBOX TALK

A pressurised hose failure can release uncontrolled energy within seconds.

ATTENDANCE AND APPROVAL

Project / Site: _____ Date: _____

Presented by: _____ Work area: _____

No	Full Name	Company / Role	Signature
1			
2			
3			
4			
5			
6			
7			
8			
9			
10			
11			
12			