

PAINTING AND COATING SAFETY TOOLBOX TALK

Painting involves chemical, respiratory and fire hazards that must be managed together.

PURPOSE AND SCOPE

Control respiratory, skin-contact, fire and explosion risks during the use of paints, solvents, thinners, epoxies and coating products.

KEY HAZARDS

1  Inhalation of solvent and VOC vapours.	2  Ignition of flammable vapours.	3  Skin contact with epoxy or hardener.	4  Aerosol exposure during spray painting.
5  Atmospheric changes inside enclosed areas.	6  Incorrect respirator cartridge selection.	7  Open paint and solvent containers.	8  Spills creating environmental and slip

CRITICAL POINTS TO VERIFY IN THE FIELD

01 Inhalation of solvent and VOC vapours.	02 Ignition of flammable vapours.	03 Skin contact with epoxy or hardener.
--	--	--



REMEMBER — SERNEM

S

Stop and think

E

Evaluate the risk

R

Remove or reduce

N

Never assume

E

Ensure protection

M

Monitor and communicate

PAINTING AND COATING SAFETY TOOLBOX TALK

Painting involves chemical, respiratory and fire hazards that must be managed together.

FIELD REQUIREMENTS AND VERIFICATION

Control respiratory, skin-contact, fire and explosion risks during the use of paints, solvents, thinners, epoxies and coating products.

SERNEM FIELD 01 FIELD VERIFICATION 1

SDS available

SERNEM FIELD 02 FIELD VERIFICATION 2

Product identified

SERNEM FIELD 03 FIELD VERIFICATION 3

Ventilation adequate

SERNEM FIELD 04 FIELD VERIFICATION 4

RPE suitable

VERIFICATION BEFORE START

- | | |
|---|--|
| ☐ SDS available | ☐ Product identified |
| ☐ Ventilation adequate | ☐ RPE suitable |
| ☐ Gloves suitable | ☐ Eye protection suitable |

SUPERVISOR DISCUSSION POINTS

- What is the main hazard of today's product?
- Is the SDS available?
- Is ventilation adequate?

FIELD APPLICATION



Painting involves chemical, respiratory and fire hazards that must be managed together.

PAINTING AND COATING SAFETY TOOLBOX TALK

Painting involves chemical, respiratory and fire hazards that must be managed together.

CRITICAL CONTROL MEASURES

1. ELIMINATE / REDUCE THE RISK

Review the product SDS before starting work. • Wear chemical-resistant gloves, eye protection and protective clothing. • Keep spill-response equipment available and control waste disposal.

2. ENGINEERING & PHYSICAL CONTROLS

Provide sufficient ventilation in enclosed and semi-enclosed areas. • Remove flames, sparks and smoking from the work area. • Keep nearby workers outside spray and overspray zones.

3. WORK METHOD & FIELD CONTROLS

Perform VOC or atmospheric monitoring where required. • Keep paint and solvent containers closed when not in use.

4. PPE, VERIFICATION & SUPERVISION

Select the correct respirator and cartridge for the product. • Store flammable products in approved storage facilities.

CRITICAL WARNING



Team, simply wearing a mask is not enough. We will understand the SDS, provide ventilation, remove ignition sources and use the correct respiratory filters.

SITE CHECKLIST — BEFORE STARTING WORK

- | | |
|---|--|
| ☐ SDS available | ☐ Product identified |
| ☐ Ventilation adequate | ☐ RPE suitable |
| ☐ Gloves suitable | ☐ Eye protection suitable |
| ☐ No ignition source | ☐ Containers closed |
| ☐ Spill kit available | ☐ Crew briefed |



PAINTING AND COATING SAFETY TOOLBOX TALK

Painting involves chemical, respiratory and fire hazards that must be managed together.

ATTENDANCE AND APPROVAL

Project / Site: _____ Date: _____

Presented by: _____ Work area: _____

No	Full Name	Company / Role	Signature
1			
2			
3			
4			
5			
6			
7			
8			
9			
10			
11			
12			