

## HSE TOOLBOX TALK

# SAFETY HARNESS USE TOOLBOX TALK

## PURPOSE AND SCOPE

Ensure that full-body harnesses, lanyards, energy absorbers and connectors are correctly selected, inspected and used, and prevent unsafe anchorage, disconnection and suspension-related risks.

## KEY HAZARDS

|                                                                                                                                                    |                                                                                                                                                            |                                                                                                                                                     |                                                                                                                                                           |
|----------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
|  <p><b>1</b></p> <p>Cut, burned, chemically damaged or worn</p>   |  <p><b>2</b></p> <p>Missing, loose or incorrectly fastened</p>            |  <p><b>3</b></p> <p>Connection to an unsuitable anchor point.</p> |  <p><b>4</b></p> <p>Complete disconnection while moving or</p>         |
|  <p><b>5</b></p> <p>Connecting a snap hook back onto its own</p> |  <p><b>6</b></p> <p>Insufficient fall clearance above a lower level.</p> |  <p><b>7</b></p> <p>Swing-fall exposure caused by poor</p>       |  <p><b>8</b></p> <p>Prolonged suspension and delayed rescue after</p> |

## CRITICAL POINTS TO VERIFY IN THE FIELD

|                                                                          |                                                                         |                                                                   |
|--------------------------------------------------------------------------|-------------------------------------------------------------------------|-------------------------------------------------------------------|
| <p><b>01</b></p> <p>Cut, burned, chemically damaged or worn webbing.</p> | <p><b>02</b></p> <p>Missing, loose or incorrectly fastened buckles.</p> | <p><b>03</b></p> <p>Connection to an unsuitable anchor point.</p> |
|--------------------------------------------------------------------------|-------------------------------------------------------------------------|-------------------------------------------------------------------|



### REMEMBER — SERNEM

**S**

Stop and think

**E**

Evaluate the risk

**R**

Remove or reduce

**N**

Never assume

**E**

Ensure protection

**M**

Monitor and communicate

HSE TOOLBOX TALK

# SAFETY HARNESS USE TOOLBOX TALK

## FIELD REQUIREMENTS AND VERIFICATION

Ensure that full-body harnesses, lanyards, energy absorbers and connectors are correctly selected, inspected and used, and prevent unsafe anchorage, disconnection and suspension-related risks.

**SERNEM FIELD 01**  
**FIELD VERIFICATION 1**  
Harness inspected

**SERNEM FIELD 02**  
**FIELD VERIFICATION 2**  
Label readable

**SERNEM FIELD 03**  
**FIELD VERIFICATION 3**  
Buckles secure

**SERNEM FIELD 04**  
**FIELD VERIFICATION 4**  
Stitching intact

## VERIFICATION BEFORE START

- |                                            |                                                 |
|--------------------------------------------|-------------------------------------------------|
| <input type="checkbox"/> Harness inspected | <input type="checkbox"/> Label readable         |
| <input type="checkbox"/> Buckles secure    | <input type="checkbox"/> Stitching intact       |
| <input type="checkbox"/> Lanyard suitable  | <input type="checkbox"/> Energy absorber intact |

## SUPERVISOR DISCUSSION POINTS

- Is there any damage, cutting or burning on the harness or lanyard?
- Who approved the anchor point to be used today?
- How will continuous attachment be maintained while moving?

## FIELD APPLICATION



Prevent falls through correct selection, inspection, connection and rescue.

HSE TOOLBOX TALK

# SAFETY HARNESS USE TOOLBOX TALK

## CRITICAL CONTROL MEASURES

### 1. ELIMINATE / REDUCE THE RISK

Use only an approved full-body harness. • Connect only to approved and adequately rated anchor points.  
• Protect equipment from sharp-edge contact.

### 2. ENGINEERING & PHYSICAL CONTROLS

Inspect webbing, stitching, buckles, D-rings and labels before every use. • Select an anchor as high as reasonably practicable. • Confirm the rescue plan, rescue team and equipment before starting.

### 3. WORK METHOD & FIELD CONTROLS

Verify periodic inspection status and records. • Maintain continuous attachment with a twin-leg lanyard where required.

### 4. PPE, VERIFICATION & SUPERVISION

Adjust the harness correctly and evenly to the body. • Check available fall clearance and swing-fall exposure.

### CRITICAL WARNING



**Team, today we will not wear a harness simply to meet a rule. We will inspect the webbing, buckles, D-rings, lanyard and hooks together. Connection will be made only to an approved anchor and continuous attachment will be maintained while moving. We will not start if fall clearance is inadequate, an edge is unprotected or the anchor is unsuitable. Everyone must understand the rescue arrangement.**

## SITE CHECKLIST — BEFORE STARTING WORK

- |                                                  |                                                         |
|--------------------------------------------------|---------------------------------------------------------|
| <input type="checkbox"/> Harness inspected       | <input type="checkbox"/> Label readable                 |
| <input type="checkbox"/> Buckles secure          | <input type="checkbox"/> Stitching intact               |
| <input type="checkbox"/> Lanyard suitable        | <input type="checkbox"/> Energy absorber intact         |
| <input type="checkbox"/> Anchor approved         | <input type="checkbox"/> Continuous attachment possible |
| <input type="checkbox"/> Fall clearance adequate | <input type="checkbox"/> Rescue plan ready              |

HSE TOOLBOX TALK

SAFETY HARNESS USE TOOLBOX TALK

ATTENDANCE AND APPROVAL

Project / Site:

Date:

Presented by:

Work area:

| No | Full Name | Company / Role | Signature |
|----|-----------|----------------|-----------|
| 1  |           |                |           |
| 2  |           |                |           |
| 3  |           |                |           |
| 4  |           |                |           |
| 5  |           |                |           |
| 6  |           |                |           |
| 7  |           |                |           |
| 8  |           |                |           |
| 9  |           |                |           |
| 10 |           |                |           |
| 11 |           |                |           |
| 12 |           |                |           |