

SAFETY HARNESS USE TOOLBOX TALK

Prevent falls through correct selection, inspection, connection and rescue.

PURPOSE AND SCOPE

Ensure that full-body harnesses, lanyards, energy absorbers and connectors are correctly selected, inspected and used, and prevent unsafe anchorage, disconnection and suspension-related risks.

KEY HAZARDS

1  Cut, burned, chemically damaged or worn	2  Missing, loose or incorrectly fastened	3  Connection to an unsuitable anchor point.	4  Complete disconnection while moving or
5  Connecting a snap hook back onto its own	6  Insufficient fall clearance above a lower level.	7  Swing-fall exposure caused by poor	8  Prolonged suspension and delayed rescue after

CRITICAL POINTS TO VERIFY IN THE FIELD

01 Cut, burned, chemically damaged or worn webbing.	02 Missing, loose or incorrectly fastened buckles.	03 Connection to an unsuitable anchor point.
--	---	---



REMEMBER — SERNEM

S

Stop and think

E

Evaluate the risk

R

Remove or reduce

N

Never assume

E

Ensure protection

M

Monitor and communicate

SAFETY HARNESS USE TOOLBOX TALK

Prevent falls through correct selection, inspection, connection and rescue.

FIELD REQUIREMENTS AND VERIFICATION

Ensure that full-body harnesses, lanyards, energy absorbers and connectors are correctly selected, inspected and used, and prevent unsafe anchorage, disconnection and suspension-related risks.

SERNEM FIELD 01 FIELD VERIFICATION 1

Harness inspected

SERNEM FIELD 02 FIELD VERIFICATION 2

Label readable

SERNEM FIELD 03 FIELD VERIFICATION 3

Buckles secure

SERNEM FIELD 04 FIELD VERIFICATION 4

Stitching intact

VERIFICATION BEFORE START

- | | |
|--|---|
| ☐ Harness inspected | ☐ Label readable |
| ☐ Buckles secure | ☐ Stitching intact |
| ☐ Lanyard suitable | ☐ Energy absorber intact |

SUPERVISOR DISCUSSION POINTS

- Is there any damage, cutting or burning on the harness or lanyard?
- Who approved the anchor point to be used today?
- How will continuous attachment be maintained while moving?

FIELD APPLICATION



Prevent falls through correct selection, inspection, connection and rescue.

SAFETY HARNESS USE TOOLBOX TALK

Prevent falls through correct selection, inspection, connection and rescue.

CRITICAL CONTROL MEASURES

1. ELIMINATE / REDUCE THE RISK

Use only an approved full-body harness. • Connect only to approved and adequately rated anchor points.
• Protect equipment from sharp-edge contact.

2. ENGINEERING & PHYSICAL CONTROLS

Inspect webbing, stitching, buckles, D-rings and labels before every use. • Select an anchor as high as reasonably practicable. • Confirm the rescue plan, rescue team and equipment before starting.

3. WORK METHOD & FIELD CONTROLS

Verify periodic inspection status and records. • Maintain continuous attachment with a twin-leg lanyard where required.

4. PPE, VERIFICATION & SUPERVISION

Adjust the harness correctly and evenly to the body. • Check available fall clearance and swing-fall exposure.

CRITICAL WARNING



Team, today we will not wear a harness simply to meet a rule. We will inspect the webbing, buckles, D-rings, lanyard and hooks together. Connection will be made only to an approved anchor and continuous attachment will be maintained while moving. We will not start if fall clearance is inadequate, an edge is unprotected or the anchor is unsuitable. Everyone must understand the rescue arrangement.

SITE CHECKLIST — BEFORE STARTING WORK

- | | |
|--|---|
| ☐ Harness inspected | ☐ Label readable |
| ☐ Buckles secure | ☐ Stitching intact |
| ☐ Lanyard suitable | ☐ Energy absorber intact |
| ☐ Anchor approved | ☐ Continuous attachment possible |
| ☐ Fall clearance adequate | ☐ Rescue plan ready |



SAFETY HARNESS USE TOOLBOX TALK

Prevent falls through correct selection, inspection, connection and rescue.

ATTENDANCE AND APPROVAL

Project / Site:

Date:

Presented by:

Work area:

No	Full Name	Company / Role	Signature
1			
2			
3			
4			
5			
6			
7			
8			
9			
10			
11			
12			