

HSE TOOLBOX TALK

STEAM AND HOT SURFACES TOOLBOX TALK

PURPOSE AND SCOPE

Prevent thermal burns and pressurised releases from steam, condensate, hot piping and process equipment.

KEY HAZARDS

1  Direct contact with high-temperature steam.	2  Fine and difficult-to-see steam jets.	3  Discharge of hot condensate.	4  Uninsulated piping and equipment.
5  Trapped pressure inside steam lines.	6  Incorrect or premature valve operation.	7  Slip hazards from wet surfaces.	8  Inadequate gloves or clothing for thermal

CRITICAL POINTS TO VERIFY IN THE FIELD

01

Direct contact with high-temperature steam.

02

Fine and difficult-to-see steam jets.

03

Discharge of hot condensate.



REMEMBER — SERNEM

S

Stop and think

E

Evaluate the risk

R

Remove or reduce

N

Never assume

E

Ensure protection

M

Monitor and communicate

HSE TOOLBOX TALK

STEAM AND HOT SURFACES TOOLBOX TALK

FIELD REQUIREMENTS AND VERIFICATION

Prevent thermal burns and pressurised releases from steam, condensate, hot piping and process equipment.

SERNEM FIELD 01**FIELD VERIFICATION 1**

Hot lines identified

SERNEM FIELD 02**FIELD VERIFICATION 2**

Insulation checked

SERNEM FIELD 03**FIELD VERIFICATION 3**

Leak method suitable

SERNEM FIELD 04**FIELD VERIFICATION 4**

Pressure verified

VERIFICATION BEFORE START

- | | |
|---|---|
| ☐ Hot lines identified | ☐ Insulation checked |
| ☐ Leak method suitable | ☐ Pressure verified |
| ☐ Temperature verified | ☐ Drainage safe |

SUPERVISOR DISCUSSION POINTS

- Where are the hot surfaces?
- Is any insulation missing?
- How will steam leaks be checked?

FIELD APPLICATION



Steam can be difficult to see, and even a small leak can cause severe burns.

HSE TOOLBOX TALK

STEAM AND HOT SURFACES TOOLBOX TALK

CRITICAL CONTROL MEASURES

1. ELIMINATE / REDUCE THE RISK

Identify hot piping and equipment before work. • Route condensate drains to a safe location. • Remove slip hazards created by condensate.

2. ENGINEERING & PHYSICAL CONTROLS

Barricade or guard areas with missing insulation. • Open steam valves slowly and under control. • Restore insulation and protective coverings after maintenance.

3. WORK METHOD & FIELD CONTROLS

Use an approved method rather than hands to detect steam leaks. • Wear suitable thermal gloves, face protection and clothing.

4. PPE, VERIFICATION & SUPERVISION

Verify pressure and temperature before opening systems. • Immediately isolate areas containing steam leaks.

CRITICAL WARNING



Team, a small steam leak can still cause a major injury. We will not use our hands to locate leaks, and we will verify pressure, temperature and insulation before starting work.

SITE CHECKLIST — BEFORE STARTING WORK

- | | |
|--|---|
| ☐ Hot lines identified | ☐ Insulation checked |
| ☐ Leak method suitable | ☐ Pressure verified |
| ☐ Temperature verified | ☐ Drainage safe |
| ☐ Valve method understood | ☐ PPE suitable |
| ☐ Area barricaded | ☐ Crew briefed |

HSE TOOLBOX TALK

STEAM AND HOT SURFACES TOOLBOX TALK

ATTENDANCE AND APPROVAL

Project / Site:

Date:

Presented by:

Work area:

No	Full Name	Company / Role	Signature
1			
2			
3			
4			
5			
6			
7			
8			
9			
10			
11			
12			