

HSE TOOLBOX TALK

TAG LINE SAFETY TOOLBOX TALK

PURPOSE AND SCOPE

Prevent entanglement, pulling and line-of-fire exposure while controlling suspended loads with tag lines.

KEY HAZARDS

1  Rope wrapped around hand or wrist.	2  Load pulling the worker.	3  Crushing between load and structure.	4  Standing beneath suspended loads.
5  Tag line too short.	6  Wind effects.	7  Tag line snagging on equipment.	8  Communication loss.

CRITICAL POINTS TO VERIFY IN THE FIELD

01 Rope wrapped around hand or wrist.	02 Load pulling the worker.	03 Crushing between load and structure.
---	---	---



REMEMBER — SERNEM

S

Stop and think

E

Evaluate the risk

R

Remove or reduce

N

Never assume

E

Ensure protection

M

Monitor and communicate

HSE TOOLBOX TALK

TAG LINE SAFETY TOOLBOX TALK

FIELD REQUIREMENTS AND VERIFICATION

Prevent entanglement, pulling and line-of-fire exposure while controlling suspended loads with tag lines.

SERNEM FIELD 01
FIELD VERIFICATION 1
Tag line suitable

SERNEM FIELD 02
FIELD VERIFICATION 2
Length adequate

SERNEM FIELD 03
FIELD VERIFICATION 3
Position safe

SERNEM FIELD 04
FIELD VERIFICATION 4
Outside line of fire

VERIFICATION BEFORE START

- | | |
|--|---|
| ☐ Tag line suitable | ☐ Length adequate |
| ☐ Position safe | ☐ Outside line of fire |
| ☐ Pinch points understood | ☐ No access under load |

SUPERVISOR DISCUSSION POINTS

- Is a tag line required?
- Is the length suitable?
- Where will we stand?

FIELD APPLICATION



A tag line controls the load; it should never pull the worker into danger.

HSE TOOLBOX TALK

TAG LINE SAFETY TOOLBOX TALK

CRITICAL CONTROL MEASURES

1. ELIMINATE / REDUCE THE RISK

Use a tag line of suitable length. • Stay clear of pinch points. • Release the tag line if the load becomes uncontrolled.

2. ENGINEERING & PHYSICAL CONTROLS

Never wrap the line around the body. • Ensure the line cannot snag on equipment. • Do not use tag lines where they are not required.

3. WORK METHOD & FIELD CONTROLS

Stand outside the load movement path. • Reassess lifting during strong wind.

4. PPE, VERIFICATION & SUPERVISION

Never stand beneath suspended loads. • Follow banksman instructions.

CRITICAL WARNING



Team, tag lines are designed to keep us away from the load. We will not wrap them around ourselves and we will release them if load control is lost.

SITE CHECKLIST — BEFORE STARTING WORK

- | | |
|--|---|
| ☐ Tag line suitable | ☐ Length adequate |
| ☐ Position safe | ☐ Outside line of fire |
| ☐ Pinch points understood | ☐ No access under load |
| ☐ Wind acceptable | ☐ Banksman ready |
| ☐ Communication clear | ☐ Crew briefed |

HSE TOOLBOX TALK

TAG LINE SAFETY TOOLBOX TALK

ATTENDANCE AND APPROVAL

Project / Site:

Date:

Presented by:

Work area:

No	Full Name	Company / Role	Signature
1			
2			
3			
4			
5			
6			
7			
8			
9			
10			
11			
12			