

HSE TOOLBOX TALK

MOBILE EQUIPMENT SAFETY

PURPOSE AND SCOPE

Review collision, crushing, entrapment, overturning, blind-spot and reversing hazards associated with excavators, loaders, telehandlers, forklifts, mobile elevating work platforms, dumpers and similar equipment, and verify operator, equipment, area and pedestrian controls. Mobile equipment has large blind spots that cannot be seen directly by the operator. Pedestrians must not approach until eye contact is established and safe passage has been confirmed.

KEY HAZARDS

1



BLIND SPOT

2



REVERSING

3



PEDESTRIAN STRIKE

4



ROLLOVER

5



SPEED

6



DROPPED LOAD

7



WEAK GROUND

8



UNAUTHORIZED USE

CRITICAL VALUES TO VERIFY IN THE FIELD

100%

Pre-shift equipment inspection

0 pedestrians

Inside the active maneuvering zone

Seat belt

Fastened whenever moving



REMEMBER - SERNEM

S

Stop and think

E

Evaluate the risk

R

Remove or reduce

N

Never assume

E

Ensure protection

M

Monitor and communicate

HSE TOOLBOX TALK

MOBILE EQUIPMENT SAFETY

STANDARDS AND FIELD REQUIREMENTS

OSHA 1926.601-602 and manufacturer instructions cover seat belts, visibility, reverse alarms, spotters, inspections and safe parking.

OSHA 1926.601(b)(4)

REVERSING

Where rear view is obstructed, do not reverse without an audible alarm or a signal person directing the movement safely.

OSHA 1926.601(b)(9)

DAILY INSPECTION

Inspect vehicles and safety devices at the start of each shift and correct unsafe defects before use.

OSHA 1926.602(a)

SEAT BELT AND BRAKES

Use the manufacturer-provided seat belt and maintain brakes, parking brake and warning systems.

ÜRETİCİ TALİMATI

CAPACITY AND ATTACHMENTS

Control loads, attachments, visibility, slopes and work-area limits to manufacturer instructions.

MINIMUM EVIDENCE BEFORE START

- | | |
|--|--|
| ☐ Traffic-management plan | ☐ Pedestrian and vehicle route layout |
| ☐ Pre-shift inspection record | ☐ Operator qualification record |
| ☐ Spotter briefing | ☐ Equipment capacity data |

SUPERVISOR DISCUSSION POINTS

- Are pedestrian and vehicle routes separated today?
- Who will act as the reversing spotter?
- Which signals will the operator and spotter use?

PEDESTRIAN-EQUIPMENT SEPARATION AND SPOTTER CONTROL



Separated route - Safe spotter - Visibility - Low speed - Seat belt

HSE TOOLBOX TALK

MOBILE EQUIPMENT SAFETY

CRITICAL CONTROL MEASURES (HIERARCHY OF CONTROLS)

1. SEPARATE PEOPLE AND PLANT

Allow only authorised and competent operators to use equipment. Complete a daily pre-use inspection before every shift.

2. PLAN ROUTE AND VISIBILITY

Physically separate pedestrian and vehicle routes. Use a spotter or banksman during reversing and restricted visibility. Agree standard signals between the operator and spotter.

3. INSPECT THE EQUIPMENT

Follow site speed limits and traffic-management controls. Require the operator to wear the seat belt at all times. Check ground condition, slope, edge distance and bearing capacity.

4. USE A SPOTTER AND PARK SAFELY

Park safely, lower attachments and isolate power. Remove defective equipment from service and report it.

CRITICAL WARNING



If the operator cannot see you, you are not safe. Establish eye contact, obtain confirmation and never approach until the equipment has fully stopped.

SITE CHECKLIST (BEFORE STARTING WORK)

- ☐ Operator authorised

☐ Brakes and steering serviceable

☐ Cameras and mirrors suitable

☐ Spotter ready

☐ Ground suitable
- ☐ Daily inspection complete

☐ Alarms and lights working

☐ Seat belt serviceable

☐ Pedestrian routes separated

HSE TOOLBOX TALK

MOBILE EQUIPMENT SAFETY

ATTENDANCE AND APPROVAL

Project / Site:

Date:

Presented by:

Work area:

No	Full Name	Company / Role	Signature
1			
2			
3			
4			
5			
6			
7			
8			
9			
10			
11			
12			