

HSE TOOLBOX TALK

VEHICLE REVERSING AND SPOTTER

PURPOSE AND SCOPE

Control blind spots and reversing through one-way routes, physical pedestrian segregation, cameras/alarms and one trained spotter; require the driver to stop when visual contact is lost.

KEY HAZARDS

1



BLIND SPOT

2



REVERSING

3



PEDESTRIAN STRIKE

4



CRUSHING

5



MULTIPLE SIGNALS

6



LOST SIGHT

7



NOISE

8



TIGHT ROUTE

CRITICAL VALUES TO VERIFY IN THE FIELD

1

Spotter controlling the maneuver

0

Movement without driver-spotter visual contact

100%

Reverse alarm/camera and route check



REMEMBER - SERNEM

S

Stop and think

E

Evaluate the risk

R

Remove or reduce

N

Never assume

E

Ensure protection

M

Monitor and communicate

HSE TOOLBOX TALK

VEHICLE REVERSING AND SPOTTER

STANDARDS AND FIELD REQUIREMENTS

OSHA 1926.601(b)(4), 1926.602(a)(9) and the site traffic plan integrate rear visibility, alarms or spotters, operator line of sight and pedestrian segregation.

OSHA 1926.601(b)(4)

REAR VIEW / ALARM

For obstructed rear views, use an audible reverse alarm or a spotter verifying safe movement.

OSHA 1926.602(a)(9)

SPOTTER VISIBILITY

The operator must not move unless the spotter is clearly visible and the signal understood.

OSHA 1926.200(g)

TRAFFIC SIGNS

Mark hazardous routes, exits and speed controls using visible signs, barriers and direction.

SAHA TRAFİK PLANI

PEDESTRIAN-VEHICLE SEGREGATION

Define one-way flow, parking, turning areas, speed and spotter position in the site plan.

MINIMUM EVIDENCE BEFORE START

- | | |
|--|--|
| ☐ Site traffic plan | ☐ Vehicle daily inspection |
| ☐ Alarm/camera check | ☐ Spotter competency record |
| ☐ Maneuvering-area inspection | ☐ Shift briefing |

SUPERVISOR DISCUSSION POINTS

- Where is the driver's blind area?
- What does the driver do if the spotter disappears?
- How are pedestrians segregated from this route?

ONE SPOTTER, CLEAR CONTACT AND BARRICADED ROUTE



Route check - Pedestrian separation - Camera - Alarm - One spotter - Stop

HSE TOOLBOX TALK

VEHICLE REVERSING AND SPOTTER

CRITICAL CONTROL MEASURES (HIERARCHY OF CONTROLS)

1. ELIMINATE REVERSING

Reduce reversing with one-way traffic and drive-through parking.

2. SEGREGATE PEOPLE AND VEHICLES

Barrier pedestrian routes and clear the maneuvering zone of unauthorized entry.

3. USE CAMERA, ALARM AND ROUTE

Check camera, mirrors, lights and alarm; walk the route for ground and overhead obstructions.

4. ONE SPOTTER AND STOP RULE

One spotter stands safely on the driver's side; the driver brakes immediately if contact is lost.

CRITICAL WARNING



If the driver cannot see the spotter, the vehicle must not move. The spotter must never enter a blind spot, stand behind the vehicle or between it and a fixed object.

SITE CHECKLIST (BEFORE STARTING WORK)

- | | |
|---|---|
| ☐ Reversing necessary | ☐ Route walk-down complete |
| ☐ Pedestrian area segregated | ☐ Alarm/camera working |
| ☐ One spotter assigned | ☐ Signals agreed |
| ☐ Spotter in driver's view | ☐ No crush point |
| ☐ Stop-on-lost-contact rule | |

HSE TOOLBOX TALK

VEHICLE REVERSING AND SPOTTER

ATTENDANCE AND APPROVAL

Project / Site:

Date:

Presented by:

Work area:

No	Full Name	Company / Role	Signature
1			
2			
3			
4			
5			
6			
7			
8			
9			
10			
11			
12			