

Paddle Motor Level Switch

[DATASHEET](#)

NT-LSW-P — PADDLE MOTOR LEVEL SWITCH

Rotating-paddle level switch for reliable full/empty detection in bulk solid silos. When material covers the rotating paddle, resistance torque stops the shaft; an optical sensor detects this and triggers the relay output. Eight selectable torque levels suit any bulk density.

KEY FEATURES

- 8 selectable torque levels
- 24VDC or 220VAC versions
- IP67 standard / IP68 optional
- Max. response time: 1.6 s
- Relay output NO/NC
- Suitable for powders & granules
- Digital gearbox-free design
- Compact ORION series

APPLICATIONS

Grain & Feed Silos

Cement Plants

Plaster & Lime Production

Plastic Granule Storage

Coal & Coke Bunkers

Flour & Sugar Mills

TECHNICAL SPECIFICATIONS

PARAMETER	VALUE
Supply (DC)	12 – 24 VDC $\pm 30\%$, max 2.7 W
Supply (AC)	85 – 250 VAC, max 3.1 W
Output	1 relay, NO/NC, max 250VAC / 1A
Response Time	≤ 1.6 seconds
Torque Selection	8 digital levels
Protection	IP67 (std) / IP68 (opt.)
Cable Entry	PG9, max 2 mm ² (AWG14)
Ambient Temperature	-20 °C ~ +70 °C
Process Temperature	max +80 °C
Paddle Length	Standard 150 mm
Applications	Powder · Grain · Granules · Cement
Certifications	CE