

Magnetic Bypass Level Indicator

DATASHEET

NT-MBL — MAGNETIC BYPASS LEVEL INDICATOR

No-power magnetic bypass level indicator with rotating flag elements. Level change in the tank proportionally changes liquid level in the bypass tube; the internal magnetic float actuates 180° colour-flip flaps visible from 15 m. Up to 5800 mm single-piece construction.

KEY FEATURES

- No power required
- Visible from 15 m distance
- Pressure: 10/16/25/40 bar
- Temperature: up to 350 °C
- Single-piece up to 5800 mm
- SS316 tube as standard
- Limit switches optional
- Bureau Veritas & Türk Loydu approved

APPLICATIONS

Storage Tanks

Boiler Drums

Fuel & LPG Tanks

Chemical Tanks

Ship Ballast Tanks

Refineries

TECHNICAL SPECIFICATIONS

PARAMETER	VALUE
Nominal Pressure	10 / 16 / 25 / 40 bar
Max. Temperature	200 °C (std) / 350 °C (HT)
Min. Liquid Density	> 0.7 kg/L
Level Tube Material	AISI 304 / AISI 316
Flange Material	St 37.2 / AISI 304 / AISI 316
Max. Single Length	5800 mm
Connection Type	Flanged · Threaded · Special
Flag Element	Glass-fibre reinforced
Limit Switches	Reed / magnetic (optional)
Approvals	Bureau Veritas · Türk Loydu · TSEK
Analog Transmitter	4-20 mA add-on (optional)