

Zero Straight-Run Flow Meter

[DATASHEET](#)

NT-VMF-0D — ZERO STRAIGHT-RUN FLOW METER

Reduced-bore electromagnetic flow meter requiring zero upstream or downstream straight pipe. Installs directly after elbows, valves or pumps in space-constrained environments. Increases velocity for low-flow accuracy.

KEY FEATURES

- OD upstream & downstream
- Installs after elbows/valves/pumps
- Increases low-flow velocity
- DN50 – DN300
- $\pm 0.5\%$ accuracy
- No flow conditioner needed
- 4-20 mA + Pulse + RS485
- Compact installation footprint

APPLICATIONS

Post-Valve Metering

Post-Pump Metering

Space-Constrained Plants

Low-Flow Enhancement

Chemical Dosing

Compact Skid Systems

TECHNICAL SPECIFICATIONS

PARAMETER	VALUE
Nominal Size	DN50 – DN300 (2" – 12")
Upstream / Downstream	ØD required
Accuracy	$\pm 0.5\%$ of reading
Bore	Reduced (convergent)
Body Material	Carbon Steel / SS304 / SS316
Liner	PTFE · Neoprene · PU
Electrodes	SS316L · Hastelloy C · Ti
Medium Temperature	-10 °C ~ +150 °C
Nominal Pressure	≤ 1.6 MPa
Supply Voltage	AC 85–250 V / DC 20–36 V
Output	4–20 mA + Pulse + RS485
Protection	IP65 / IP67