

Battery-Powered Flow Meter

DATASHEET

NT-VMF-BT — BATTERY-POWERED FLOW METER

Lithium-battery powered electromagnetic flow meter for remote sites with no mains power. Up to 6-year battery life with GPRS/CDMA wireless data transmission. IP68 rated for underground and submerged installations.

KEY FEATURES

- ▶ 3.6 V lithium battery — 3-6 year life
- ▶ IP68 waterproof — underground safe
- ▶ GPRS / CDMA wireless optional
- ▶ RS485 Modbus communication
- ▶ LCD display with backlight
- ▶ Power-failure data logging
- ▶ Infrared remote configuration
- ▶ No mains power required

APPLICATIONS

Remote Water Mains

DMA & NRW Metering

Irrigation Schemes

Groundwater Monitoring

Mining Sites

Agricultural Water

TECHNICAL SPECIFICATIONS

PARAMETER	VALUE
Nominal Size	DN3 — DN600
Accuracy	±0.5% of reading
Battery	3.6 V Lithium, 3-6 years
Body Material	SS304
Liner	PTFE · Neoprene · PU
Electrodes	SS316L · Hastelloy C · Ti
Min. Conductivity	≥ 5 µS/cm
Medium Temperature	-10 °C ~ +80 °C
Protection	IP68
Communication	RS485 Modbus · GPRS (opt.)
Display	LCD, flow rate & total
Output	Pulse + RS485