

Insertion Flow Meter

DATASHEET

NT-VMF-I — INSERTION FLOW METER

Single-point insertion electromagnetic flow meter for large-diameter pipelines. Retrofit onto existing lines without cutting the pipe. ABS or polypropylene body for chemical resistance. Hot-tap installation available.

KEY FEATURES

- DN100–DN3000 pipe size
- No pipe cutting — easy retrofit
- ABS / Polypropylene body
- Hot-tap installation optional
- $\pm 0.5\%$ accuracy
- Bi-directional measurement
- 4-20 mA + Pulse + RS485
- Suitable for large water mains

APPLICATIONS

Large Water Mains

Irrigation Canals

Industrial Pipelines

Mining Water Supply

District Heating

Wastewater Networks

TECHNICAL SPECIFICATIONS

PARAMETER	VALUE
Pipe Size	DN100 – DN3000
Accuracy	$\pm 0.5\%$ of reading
Body Material	ABS / Polypropylene
Electrode Material	SS316L
Min. Conductivity	$\geq 5 \mu\text{S}/\text{cm}$
Flow Velocity	0.3 – 15 m/s
Medium Temperature	0 °C ~ +60 °C
Nominal Pressure	$\leq 0.6 \text{ MPa}$
Supply Voltage	AC 85–250 V / DC 20–36 V
Output	4–20 mA + Pulse + RS485
Protection	IP65
Installation	Insertion · Hot-tap (opt.)