

Miniature Flow Meter

DATASHEET

NT-VMF-M — MINIATURE FLOW METER

Compact electromagnetic flow meter for DN3–DN15 micro-flow applications. Polyimide composite body for chemical resistance. Measures strong acids, alkalis, slurries and liquid-solid suspensions from 0.1 m/s minimum velocity.

KEY FEATURES

- DN3 / DN6 / DN10 / DN15
- Polyimide composite body
- Min. velocity: 0.1 m/s
- $\pm 0.5\%$ accuracy
- RS232 / RS485 Modbus
- Empty-pipe detection
- Power-failure data logging
- 30-day measurement records

APPLICATIONS

Chemical Micro-Dosing

Pharmaceutical Lab

Reagent Injection

Ink & Dye Industry

Acid / Alkali Transfer

Slurry & Pulp Metering

TECHNICAL SPECIFICATIONS

PARAMETER	VALUE
Nominal Size	DN3 · DN6 · DN10 · DN15 (thread)
Flow Velocity	0.1 – 15 m/s
Accuracy	$\pm 0.5\%$ of reading
Body Material	PIC (Polyimide Composite)
Electrode Material	SS316L · Hastelloy C · Titanium
Min. Conductivity	$\geq 5 \mu\text{S/cm}$
Ambient Temperature	$-10\text{ }^{\circ}\text{C} \sim +55\text{ }^{\circ}\text{C}$
Medium Temperature	$-10\text{ }^{\circ}\text{C} \sim +60\text{ }^{\circ}\text{C}$
Nominal Pressure	$\leq 1.0\text{ MPa}$
Supply Voltage	AC 85–250 V / DC 20–36 V
Output	4–20 mA + Pulse + RS485
Communication	RS232 / RS485 Modbus
Protection	IP65