

Partially-Filled Flow Meter

DATASHEET

NT-VMF-P — PARTIALLY-FILLED FLOW METER

Measures both velocity and level simultaneously in non-full pipes using electromagnetic induction. Ideal for gravity-flow sewerage, stormwater and industrial drainage channels. DN200–DN3000 range.

KEY FEATURES

- Simultaneous velocity + level measurement
- DN200 – DN3000
- $\pm 2.5\%$ accuracy for partial fill
- No upstream straight pipe needed
- RS485 / RS232 communication
- Built-in data logger
- Self-cleaning electrodes
- Gravity-flow applications

APPLICATIONS

Sewerage Systems

Stormwater Drainage

Industrial Effluent

Open Channel Flow

Municipal Drainage

Culverts & Tunnels

TECHNICAL SPECIFICATIONS

PARAMETER	VALUE
Nominal Size	DN200 – DN3000
Accuracy	$\pm 2.5\%$ (partial fill)
Measurement	Velocity + Level simultaneous
Min. Fill Level	10% of diameter
Electrode Material	SS316L / Hastelloy C
Body Material	SS304 / SS316
Medium Temperature	0 °C ~ +80 °C
Supply Voltage	AC 85–250 V / DC 20–36 V
Output	4–20 mA + Pulse + RS485 + RS232
Protection	IP68
Data Logger	Built-in (optional)