

Slurry Flow Meter

DATASHEET

NT-VMF-S — SLURRY FLOW METER

Heavy-duty electromagnetic flow meter for abrasive slurries, mining pulp and drilling mud. High-frequency 25/30 Hz excitation suppresses particle noise. Platinum-iridium electrodes for maximum abrasion resistance and repeatability $\leq 0.17\%$.

KEY FEATURES

- ▶ Pt-Ir electrodes — abrasion resistant
- ▶ 25 / 30 Hz high-frequency excitation
- ▶ Repeatability $\leq 0.17\%$
- ▶ DN3 – DN3000
- ▶ Hard rubber or PU liner
- ▶ $\pm 0.5\%$ accuracy
- ▶ 4-20 mA + Pulse + RS485
- ▶ Compact & remote versions

APPLICATIONS

Mining & Ore Processing

Cement & Concrete

Drilling Mud

Paper & Pulp

Wastewater Sludge

Chemical Slurries

TECHNICAL SPECIFICATIONS

PARAMETER	VALUE
Nominal Size	DN3 – DN3000
Accuracy	$\pm 0.5\%$ / $\pm 0.3\%$ (opt.)
Repeatability	$\leq 0.17\%$
Excitation Frequency	25 Hz / 30 Hz
Electrode Material	Platinum-Iridium (Pt-Ir)
Liner Material	Hard Rubber · Polyurethane · PTFE
Body Material	Carbon Steel / SS304 / SS316
Min. Conductivity	$\geq 5 \mu\text{S/cm}$
Medium Temperature	$-10^\circ\text{C} \sim +80^\circ\text{C}$
Nominal Pressure	$\leq 1.6 \text{ MPa}$
Supply Voltage	AC 85–250 V / DC 20–36 V
Output	4–20 mA + Pulse + RS485
Protection	IP65 / IP67