

Food-Grade Flow Meter

DATASHEET

NT-VMF-W — FOOD-GRADE FLOW METER

Hygienic electromagnetic flow meter with tri-clamp connection for dairy, beverage, pharma and CIP lines. PTFE/PFA lined with SS316L electrodes. Fully drainable design meets FDA and EHEDG requirements.

KEY FEATURES

- Tri-Clamp / DIN hygienic connection
- PTFE or PFA liner
- SS316L wetted parts
- CIP & SIP compatible
- Surface finish $Ra \leq 0.8 \mu m$
- FDA-compliant materials
- Zero dead-leg design
- $\pm 0.5\%$ accuracy

APPLICATIONS

Dairy & Milk Processing

Juice & Beverage

Brewing & Winery

Pharmaceutical

CIP / SIP Cleaning

Food Ingredient Dosing

TECHNICAL SPECIFICATIONS

PARAMETER	VALUE
Nominal Size	DN10 — DN200
Connection	Tri-Clamp · DIN 11851 · Flange
Accuracy	$\pm 0.5\%$ of reading
Liner Material	PTFE / PFA
Electrode Material	SS316L
Body Material	SS304 / SS316L
Surface Finish	$Ra \leq 0.8 \mu m$ (interior)
Medium Temperature	$0 \text{ }^{\circ}\text{C} \sim +130 \text{ }^{\circ}\text{C}$
Nominal Pressure	$\leq 1.6 \text{ MPa}$
Supply Voltage	AC 85–250 V / DC 20–36 V
Output	4–20 mA + Pulse + RS485
Protection	IP67