

NET FLOW

Industrial Instrumentation

PRODUCT CATALOG

19 Instruments

Flow Meters · Level Instruments · Process Transmitters

netflw.com · info@netflw.com · +90 541 373 79 53
Made in Türkiye · TÜRKAK AB-0354-K · ISO/IEC 17025:2017

NT-VMF

Electromagnetic Flow Meter

FLOW METER

No moving parts, zero pressure drop. For any conductive liquid, six liners, six electrode alloys.

DN3-DN3000 DIAMETER	±0.2% ACCURACY	IP68 PROTECTION	4-20mA / HART OUTPUT
------------------------	-------------------	--------------------	-------------------------

NT-VMF-W

Food-Grade Flow Meter

FLOW METER

Hygienic tri-clamp for dairy, beverage and pharma lines.

DN10-DN200 DIAMETER	Tri-Clamp CONNECTION	PTFE / PFA LINER	316L ELECTRODE
------------------------	-------------------------	---------------------	-------------------

NT-VMF-BT

Battery-Powered Flow Meter

FLOW METER

Five-year lithium battery for remote sites, irrigation and DMA stations.

DN3-DN600 DIAMETER	3.6V Li POWER	5 years BATTERY LIFE	IP68 PROTECTION
-----------------------	------------------	-------------------------	--------------------

NT-VMF-I

Insertion Flow Meter

FLOW METER

Single-point insertion for large mains, retrofit without cutting the pipe.

DN100-DN3000 DIAMETER	±0.5% ACCURACY	ABS / PP BODY	Hot-tap INSTALL
--------------------------	-------------------	------------------	--------------------

Level and velocity measurement in non-full pipes, sewerage and drainage.

DN200–DN3000 DIAMETER	±2.5% ACCURACY	Level + velocity METHOD	IP68 PROTECTION
--------------------------	-------------------	----------------------------	--------------------

No straight pipe required, mount after elbows, valves or pumps.

DN3–DN3000 DIAMETER	±0.5% ACCURACY	0D STRAIGHT RUN	4–20mA OUTPUT
------------------------	-------------------	--------------------	------------------

Precision micro-dosing from 0.2 L/min, chemical and pharma applications.

DN3–DN15 DIAMETER	PIC body MATERIAL	0.2 L/min FROM	316L ELECTRODE
----------------------	----------------------	-------------------	-------------------

Abrasion-resistant for mining, cement and drilling mud.

Pt-Ir ELECTRODE	≤0.17% REPEATABILITY	25/30 Hz EXCITATION	IP68 PROTECTION
--------------------	-------------------------	------------------------	--------------------

NT-MLI

Magnetic Bypass Level Indicator

LEVEL INSTRUMENT

Sealed magnetic flag indication, no power, zero maintenance.

200°C MAX TEMP	PN10 PRESSURE	No power SUPPLY	Flag display READOUT
--------------------------	-------------------------	---------------------------	--------------------------------

NT-MLI-EX

Ex-Proof Bypass Indicator

LEVEL INSTRUMENT

For hazardous atmospheres, refineries, LPG/LNG terminals.

150°C MAX TEMP	PN10 PRESSURE	Ex-proof DESIGN	Flag display READOUT
--------------------------	-------------------------	---------------------------	--------------------------------

NT-MLI-BR

Boiler-Type Bypass Indicator

LEVEL INSTRUMENT

High-pressure steam systems, boiler drums, power-plant feed tanks.

300°C MAX TEMP	PN40 PRESSURE	Steam SERVICE	Flag display READOUT
--------------------------	-------------------------	-------------------------	--------------------------------

NT-FLT

Float Level Transmitter

LEVEL INSTRUMENT

Continuous level with float + magnetic coupling for water and process tanks.

0-6000mm RANGE	4-20mA OUTPUT	Magnetic COUPLING	IP67 PROTECTION
--------------------------	-------------------------	-----------------------------	---------------------------

NT-MLS

Motorized Level Sensor

LEVEL INSTRUMENT

Rotary-paddle detection for grain silos, cement and powder storage.

Relay OUTPUT	IP65 PROTECTION	Rotary paddle METHOD	Bulk solids MEDIA
------------------------	---------------------------	--------------------------------	-----------------------------

NT-MLP

Side-Mount Level Switch

LEVEL SWITCH

Lever-arm float switch for tank high/low alarms and pump control.

Side mount TYPE	IP67 PROTECTION	NO/NC RELAY	Liquids MEDIA
---------------------------	---------------------------	-----------------------	-------------------------

NT-LSW-M

Mini Stainless Level Switch

LEVEL SWITCH

Compact stainless switch for tight spaces, machine tanks and compressors.

IP67 PROTECTION	316L BODY	NO/NC RELAY	Compact SIZE
---------------------------	---------------------	-----------------------	------------------------

NT-LSW-F

Float Level Switch

LEVEL SWITCH

Simple, economical level detection for pump control and condensate tanks.

120°C MAX TEMP	PP / SS BODY	Float METHOD	NO/NC RELAY
--------------------------	------------------------	------------------------	-----------------------

Rotating-paddle detection for grain, cement and plastic-granule silos.

220VAC

SUPPLY

IP65

PROTECTION

Rotary paddle

METHOD

Silos

MEDIA

Contactless Hall-effect angle sensing for valve feedback and machinery.

0-360°

RANGE

12-bit

RESOLUTION

Hall-effect

SENSING

Unlimited

ROTATION LIFE

Two measurements from one tapping: pressure and temperature together.

0-600 bar

PRESSURE

PT100

TEMP

2-in-1

MEASUREMENT

4-20mA

OUTPUT