

EXAMPLE MAKEFILES

Shared Library

```
SAGA_SRC      = $(wildcard *.cpp)
SAGA_ADD_LIB_OBJ = $(SAGA_SRC:%.cpp=%.o)
SAGA_LIB      = my_saga_based_library

include $(SAGA_LOCATION)/share/saga/make/saga.application.mk

## Other (optional) compiler and linker flags
SAGA_CPPFLAGS += -I/opt/super/include
SAGA_LDFLAGS  += -L/opt/super/lib -lsuper
```

Executable

```
SAGA_SRC      = $(wildcard *.cpp)
SAGA_ADD_BIN_OBJ = $(SAGA_SRC:%.cpp=%.o)
SAGA_BIN      = my_saga_based_executable

include $(SAGA_LOCATION)/share/saga/make/saga.application.mk

## Other (optional) compiler and linker flags
SAGA_CPPFLAGS += -I/opt/super/include
SAGA_LDFLAGS  += -L/opt/super/lib -lsuper
```

ADAPTOR URL SCHEMES

File Adaptors

```
file://      Local (default) adaptor
griftp://    GridFTP adaptor (also accepts gsiftp://)
```

Job Adaptors

```
condor://    Condor adaptor
fork://      Local (default) adaptor
gram://      Globus GRAM adaptor
gridsam://   OMII GridSAM adaptor
lsf://       Platform LSF adaptor
ssh://       SSH Job Adaptor
```

Replica Adaptors

```
replica://   PostgreSQL/SQLite-based (default) adaptor
rls://       Globus Replica Location Service (RLS) adaptor
```

Advert Adaptors

```
advert://    PostgreSQL/SQLite-based (default) adaptor
```