

Projektaufgaben Block 2

Carlo Michaelis, 573479; David Hinrichs, 572347; Lukas Ruff, 572521

06 Dezember 2016

1 Nichtparametrisches Testen

1.1 Zwillingsstudie

Um zu testen, ob der Kindergartenbesuch einen signifikanten Einfluss auf die sozialen Fähigkeiten eines Kindes hat, führen wir einen zweiseitigen t -Test und einen zweiseitigen Wilcoxon-Vorzeichen-Test, jeweils zum Signifikanzniveau $\alpha = 0.05$, durch:

```
# Enter data
x <- c(82,69,73,43,58,56,76,65)
y <- c(63,42,74,37,51,43,80,62)

# Two-sided t-test
t.test(x, y, alternative = "two.sided", mu = 0, conf.level = 0.95, paired = TRUE)

##
## Paired t-test
##
## data:  x and y
## t = 2.3791, df = 7, p-value = 0.04895
## alternative hypothesis: true difference in means is not equal to 0
## 95 percent confidence interval:
##  0.05320077 17.44679923
## sample estimates:
## mean of the differences
##                8.75

# t.test(x-y, alternative = "two.sided", mu = 0, conf.level = 0.95) # alternative

# Two-sided Wilcoxon signed rank test
wilcox.test(x, y, alternative = "two.sided", mu = 0, conf.level = 0.95,
            paired = TRUE, conf.int = TRUE)

##
## Wilcoxon signed rank test
##
## data:  x and y
## V = 32, p-value = 0.05469
## alternative hypothesis: true location shift is not equal to 0
## 95 percent confidence interval:
##  -0.5 19.0
## sample estimates:
## (pseudo)median
##                7.75

# wilcox.test(x-y, alternative = "two.sided", mu = 0, conf.level = 0.95,
#             conf.int = TRUE) # alternative
```

Wir können sehen, dass der t -Test die Nullhypothese ablehnt und somit einen signifikanten Einfluss feststellt. Der Wilcoxon-Vorzeichen-Test verwirft die Nullhypothese dagegen nicht. Durch die Normalverteilungsannahme $X_i - Y_i \sim N(0, \sigma^2)$, die für gegebenes Sample in Frage gestellt werden kann, besitzt der t -Test eine größere Power. Der nichtparametrische Wilcoxon-Vorzeichen-Test benötigt hingegen keine Verteilungsannahme, besitzt jedoch eine kleinere Power.

1.2 t -Test vs. Wilcoxon-Vorzeichen-Test

```
fnTestPowerMC <- function(fnError, n = 30, theta = 0, alpha = 0.05, nSim = 10^4,
  ...) {
  # This function estimates the probability of rejecting the null hypothesis of a
  # t-test and a Wilcoxon signed rank test using Monte Carlo simulations of iid
  # random variables  $X_i = \theta + \epsilon_i$ .
  #
  # Args:
  # fnError: Function which generates random samples from a symmetric error
  #           distribution  $\epsilon$ 
  # n:       Number of random samples used in tests
  # theta:   True parameter
  # alpha:   Significance level used in tests
  # nSim:    Number of MC simulations of size n
  # ...:     Further arguments to be passed to fnError
  #
  # Returns:
  # A list containing the following elements:
  #   $TProb: MC estimation of rejection probability for the t-test
  #   $WilcoxProb: MC estimation of rejection probability for the Wilcoxon
  #               signed rank test

  # Perform MC simulation
  matX <- matrix(theta + fnError(n*nSim, ...), ncol = n)

  # Define sub-functions which only return p-values from the two tests
  fnPvalT <- function(x, theta) {
    return(t.test(x, mu = theta)$p.value)
  }
  fnPvalWilcox <- function(x, theta) {
    return(wilcox.test(x, mu = theta)$p.value)
  }

  # Perform nSim number of tests with sample size n for each of the two tests
  vecPvalT <- apply(matX, 1, fnPvalT, theta = theta)
  vecPvalWilcox <- apply(matX, 1, fnPvalWilcox, theta = theta)

  # Compute and return estimations of rejection probabilities
  result <- list()
  result$TProb <- mean(vecPvalT < alpha)
  result$WilcoxProb <- mean(vecPvalWilcox < alpha)
  return(result)
}

# Set seed
set.seed(42)
```

```

# Normal errors
fnTestPowerMC(fnError = rnorm, nSim = 10^5, theta = 0)

## $TProb
## [1] 0.04999
##
## $WilcoxProb
## [1] 0.04981

# Cauchy errors (t-distribution with df = 1)
fnTestPowerMC(fnError = rt, nSim = 10^5, df = 1)

## $TProb
## [1] 0.02034
##
## $WilcoxProb
## [1] 0.04947

# Uniform errors
fnTestPowerMC(fnError = runif, nSim = 10^5, min = -1, max = 1)

## $TProb
## [1] 0.05177
##
## $WilcoxProb
## [1] 0.05073

```

2 Dichteschätzung

3 Bildentrauschen