

Status	Finished
Started	Sunday, 2 November 2025, 1:45 PM
Completed	Sunday, 2 November 2025, 2:40 PM
Duration	55 mins

Question **1**

Correct

A single line L with a set of space separated values indicating distance travelled and time taken is passed as the input. The program must calculate the average speed S (with precision upto 2 decimal places) and print S as the output.

Note: The distance and time taken will follow the format DISTANCE@TIMETAKEN. DISTANCE will be in kilometers and TIMETAKEN will be in hours.

Input Format:

The first line contains L.

Output Format:

The first line contains the average speed S.

Boundary Conditions:

Length of L will be from 3 to 100.

Example Input/Output 1:

Input:

60@2 120@3

Output:

36.00 kmph

Explanation:

Total distance = $60+120 = 180$ km.

Total time taken = $2+3 = 5$ hours.

Hence average speed = $180/5 = 36.00$ kmph

For example:

Input	Result
60@2 120@3	36.00 kmph

Answer: (penalty regime: 0 %)

```

1  #include<stdio.h>
2
3
4  int main()
5  {
6      float d,t,td=0,tt=0;
7      while(scanf("%f%*[^0-9.]%f",&d,&t)==2){
8          td+=d;
9          tt+= t;
10     }
11
12
13
14
15
16     printf("%.2f kmph\n",td/tt);
17 }
```



	Input	Expected	Got	
✓	60@2 120@3	36.00 kmph	36.00 kmph	✓

Passed all tests! ✓

Question **2**

Correct

The program must accept two numbers X and Y and then print their HCF/GCD.

Input Format:

The first line denotes the value of X.

The second line denotes the value of Y.

Output Format:

The first line contains the HCF of X and Y.

Boundary Conditions:

$1 \leq X \leq 999999$

$1 \leq Y \leq 999999$

Example Input/Output 1:

Input:

30

40

Output:

10

Example Input/Output 2:

Input:

15

10

Output:

5

For example:

Input	Result
30	10
40	

Answer: (penalty regime: 0 %)

```
1  #include<stdio.h>
2  int main()
3  {
4      int x,y;
5      scanf("%d",&x);
6      scanf("%d",&y);
7
8      while(y!=0){
9          int temp=y;
10         y=x%y;
11         x=temp;
12     }
13     printf("%d\n",x);
14 }
```



	Input	Expected	Got	
✓	30 40	10	10	✓

Passed all tests! ✓

Question **3**

Correct

A string S is passed as input. S will contain two integer values separated by one of these alphabets - A, S, M, D where

- A or a is for addition
- S or s is for subtraction
- M or m is for multiplication
- D or d is for division

The program must perform the necessary operation and print the result as the output. (Ignore any floating point values just print the integer result.)

Input Format:

The first line contains S .

Output Format:

The first line contains the resulting integer value.

Boundary Conditions:

Length of S is from 3 to 100.

Example Input/Output 1:

Input:

5A11

Output:

16

Explanation:

As the alphabet is A, 5 and 11 are added giving 16.

Example Input/Output 2:

Input:

120D6

Output:

20

Example Input/Output 3:

Input:

1405d10

Output:

140

For example:

Input	Result
5A11	16
120D6	20
1405d10	140

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 #include<ctype.h>
3 int main(){
4     int a=0,b=0;
5     char s[100],op;
6     scanf("%s",s);
7
8     int i=0;
9     while(s[i]>='0'&& s[i]<='9')
10         a=a*10+(s[i++]-'0');
11     op=s[i++];
12     while(s[i])
13         b=b*10+(s[i++] - '0');
14
15     switch (toupper(op)){
16         case 'A':printf("%d\n",a+b);break;
17         case 'S':printf("%d\n",a-b);break;
```

```
18 |         case 'M':printf("%d\n",a*b);break;
19 |         case 'D':printf("%d\n",a/b);break;}
20 |
21 |
22 |
23 | }
```



	Input	Expected	Got	
✓	5A11	16	16	✓
✓	120D6	20	20	✓
✓	1405d10	140	140	✓

Passed all tests! ✓

