

Status	Finished
Started	Sunday, 2 November 2025, 2:44 PM
Completed	Sunday, 2 November 2025, 3:22 PM
Duration	37 mins 50 secs

Question **1**

Correct

The name and mileage of certain cars is passed as the input. The format is CARNAME@MILEAGE and the input is as a single line, with each car information separated by a space. The program must print the car with the lowest mileage. (Assume no two cars will have the lowest mileage)

Input Format:

The first line contains the CARNAME@MILEAGE separated by a space.

Output Format:

The first line contains the name of the car with the lowest mileage.

Boundary Conditions:

The length of the input string is between 4 to 10000.

The length of the car name is from 1 to 50.

Example Input/Output 1:

Input:

Zantro@16.15 Zity@12.5 Gamry@9.8

Output:

Gamry

For example:

Input	Result
Zantro@16.15 Zity@12.5 Gamry@9.8	Gamry

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 #include<string.h>
3
4 int main(){
5     char name[100],best[100];
6     float mileage,min=1e9;
```

```

7
8  while(scanf("%[^@]@%f",name,&mileage)==2){
9      if(mileage<min){
10         min=mileage;
11         strcpy(best,name);
12     }
13     getchar();
14 }
15 printf("%s",best);
16 }
17

```

	Input	Expected	Got	
✓	Zantro@16.15 Zity@12.5 Gamry@9.8	Gamry	Gamry	✓

Passed all tests! ✓

Question **2**

Correct

A certain number of people attended a meeting which was to begin at 10:00 am on a given day. The arrival time in HH:MM format of those who attended the meeting is passed as the input in a single line, with each arrival time by a space. The program must print the count of people who came late (after 10:00 am) to the meeting.

Input Format:

The first line contains the arrival time separated by a space.

Output Format:

The first line contains the count of late comers.

Boundary Conditions:

The length of the input string is between 4 to 10000.

The time HH:MM will be in 24 hour format (HH is hours and MM is minutes).

Example Input/Output 1:

Input:

10:00 9:55 10:02 9:45 11:00

Output:

2

Explanation:

The 2 people were those who came at 10:02 and 11:00

For example:

Input	Result
10:00 9:55 10:02 9:45 11:00	2

Answer: (penalty regime: 0 %)

```

1  #include<stdio.h>
2  int main(){
3      char input[10000];
4      int hour,minute,count=0;
5      char*p=input;
6      fgets(input,sizeof(input),stdin);
7      while(*p){
8          if(sscanf(p, "%d:%d", &hour, &minute) ==2){
9              if(hour > 10|| (hour == 10 && minute > 0))
10                 count++;
11             }
12             while(*p && *p !=' ')
13                 p++;
14             if(*p == ' ')p++;
15         }
16         printf("%d\n",count);
17     }
18 }

```



	Input	Expected	Got	
✓	10:00 9:55 10:02 9:45 11:00	2	2	✓

Passed all tests! ✓

Question **3**

Correct

A single line consisting of a set of integers, each separated by space is passed as input to the program. The program must print the sum of all the integers present.

Input Format:

The first line contains the integer values (Each separated by a space)

Output Format:

The first line contains the sum of all the integers.

Boundary Conditions:

The length of the input string is between 3 to 10000

The value of the integer values will be from -99999 to 99999

Example Input/Output 1:

Input:

100 -99 98 5

Output:

104

Example Input/Output 2:

Input:

100 200 -300 500 -450 -50

Output:

0

For example:

Input	Result
100 -99 98 5	104
100 200 -300 500 -450 -50	0

Answer: (penalty regime: 0 %)

```

1  #include<stdio.h>
2  int main(){
3
4      int num,sum=0;
5
6
7
8  while(scanf("%d",&num)==1){
9      sum+=num;
10
11
12 }
13 printf("%d\n",sum);
14 }
15
16

```



	Input	Expected	Got	
✓	100 -99 98 5	104	104	✓
✓	100 200 -300 500 -450 -50	0	0	✓

Passed all tests! ✓