

# 5-Class Sentiments Analysis using Random Forest

May 16, 2020

## Data Exploration

```
[1]: # importing require libraries
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
%matplotlib inline
```

```
[2]: # Reading dataset of train and test
train_df = pd.read_csv('data/sentiment_5_class_train.csv')
test_df = pd.read_csv('data/sentiment_5_class_test.csv')
```

```
[3]: train_df.head()
```

```
[3]:
```

|   | Phrase  | Sentiment |
|---|---|-----------|
| 0 | the prisoner                                      | 2         |
| 1 | The sheer joy and pride they took in their wor... | 3         |
| 2 | has never made a more sheerly beautiful film t... | 3         |
| 3 | the story has the sizzle of old news that has ... | 3         |
| 4 | far superior                                      | 4         |

```
[4]: test_df.head()
```

```
[4]:
```

|   | Phrase  | Sentiment |
|---|---|-----------|
| 0 | makes for a touching love story , mainly becau... | 3         |
| 1 | a truly magical movie                             | 4         |
| 2 | check   | 3         |
| 3 | is a remarkably accessible and haunting film .    | 4         |
| 4 | are too cute                                      | 3         |

```
[5]: # checking the shape of dataset
print('train_df shape: ', train_df.shape)
print('test_df shape: ', test_df.shape)
```

```
train_df shape: (14711, 2)
test_df shape: (3678, 2)
```

```
[6]: # checking the null values
train_df.isnull().sum()
```

```
[6]: Phrase      0
      Sentiment   0
      dtype: int64
```

```
[7]: test_df.isnull().sum()
```

```
[7]: Phrase      0
      Sentiment   0
      dtype: int64
```

```
[8]: # checking the number of sentiments
train_df.Sentiment.unique()
```

```
[8]: array([2, 3, 4, 0, 1])
```

Here, above sentiments represents:

0 : Very Bad  
1 : Bad  
2 : Normal  
3 : Good  
4 : Very Good

```
[9]: # checking if there is empty phrase or not
empty_train = train_df[train_df.Phrase.apply(lambda x: len(x.split()) == 0)]
empty_test = test_df[test_df.Phrase.apply(lambda x: len(x.split()) == 0)]

print('Empty train Phrase: \n', empty_train)
print('Empty test Phrase: \n', empty_test)
```

```
Empty train Phrase:
  Phrase  Sentiment
6189      1
Empty test Phrase:
Empty DataFrame
Columns: [Phrase, Sentiment]
Index: []
```

Here, we have empty Phrase at training set but not in test set.

```
[10]: # removing empty Phrase index
train_df.drop(empty_train.index, inplace=True)
```

```
[11]: # Total number of Phrase with sentiments in train set
sentiments_collection_train = train_df.groupby('Sentiment').size()
sentiments_collection_test = test_df.groupby('Sentiment').size()
```

```
print('In train set: \n', sentiments_collection_train)
print('\n In test set: \n', sentiments_collection_test)
```

In train set:

```
Sentiment
0      988
1     1164
2     1876
3     7033
4     3649
dtype: int64
```


In test set:

```
Sentiment
0      247
1      291
2      469
3     1759
4      912
dtype: int64
```

```
[12]: # barplot of no. of phrase with sentiments in train set
sentiments_collection_train.plot(kind='bar', color=['r', 'y', 'g', 'b', 'c'])

plt.title('No. of Phrase with Sentiments in train set', fontsize=14)
plt.xlabel('Sentiments', fontsize=12)
plt.ylabel('No. of Phrase')


plt.show()
```



```
[13]: # barplot of no. of phrase with sentiments in test set
sentiments_collection_test.plot(kind='bar', color=['r', 'y', 'g', 'b', 'c'])

plt.title('No. of Phrase with Sentiments in test set', fontsize=14)
plt.xlabel('Sentiments', fontsize=12)
plt.ylabel('No. of Phrase')

plt.show()
```




This diagram shows that, we have more number of positive phrase than the negative phrase. We can also observe that the data is imbalanced because label 3 is higher than other. so, to make a balanced dataset we can use SMOOTEING method.

```
[14]: # lets check the distribution of train and test set
train_len = len(train_df)
test_len = len(test_df)

plt.pie(x=[train_len, test_len], labels=['Train dataset', 'Test dataset'],
        autopct='%1.0f%%', radius=1.4)
plt.legend()

plt.show()
```



## Feature Extraction and Preprocessing

Splitting train and test set.

```
[15]: X_train = train_df['Phrase'].tolist()
      y_train = train_df['Sentiment']

      X_test = test_df['Phrase'].tolist()
      y_test = test_df['Sentiment']

      print('X_train length: ', len(X_train))
      print('X_test length: ', len(X_test))
      print('\n')

      print('y_train length: ', len(y_train))
      print('y_test length: ', len(y_test))
```

```
X_train length:  14710
X_test length:   3678
```

```
y_train length:  14710
y_test length:   3678
```

Using Term Frequency - Inverse Dense Frequency (TF-IDF) for vectorization.

```
[16]: from sklearn.feature_extraction.text import TfidfVectorizer

vectorizer = TfidfVectorizer()
vectorizer.fit(X_train)
```

```
[16]: TfidfVectorizer()
```

```
[17]: X_train_v = vectorizer.transform(X_train)
X_test_v = vectorizer.transform(X_test)

print('X_train_v shape: ', X_train_v.shape)
print('X_test_v shape: ', X_test_v.shape)
```

```
X_train_v shape: (14710, 7115)
```

```
X_test_v shape: (3678, 7115)
```

We, know that the data is imbalanced. So, we are using SMOTE Oversampling to make the data balanced.

```
[18]: from collections import Counter
from imblearn.over_sampling import SMOTE

smote = SMOTE(random_state=42, sampling_strategy='auto')
X_train_smote, y_train_smote = smote.fit_resample(X_train_v, y_train)
```

```
/home/code_monkey/anaconda3/lib/python3.7/site-
packages/sklearn/utils/deprecation.py:143: FutureWarning: The
sklearn.neighbors.base module is deprecated in version 0.22 and will be removed
in version 0.24. The corresponding classes / functions should instead be
imported from sklearn.neighbors. Anything that cannot be imported from
sklearn.neighbors is now part of the private API.
```

```
warnings.warn(message, FutureWarning)
```

```
/home/code_monkey/anaconda3/lib/python3.7/site-
packages/sklearn/utils/deprecation.py:143: FutureWarning: The
sklearn.ensemble.bagging module is deprecated in version 0.22 and will be
removed in version 0.24. The corresponding classes / functions should instead be
imported from sklearn.ensemble. Anything that cannot be imported from
sklearn.ensemble is now part of the private API.
```

```
warnings.warn(message, FutureWarning)
```

```
/home/code_monkey/anaconda3/lib/python3.7/site-
packages/sklearn/utils/deprecation.py:143: FutureWarning: The
sklearn.ensemble.base module is deprecated in version 0.22 and will be removed
in version 0.24. The corresponding classes / functions should instead be
imported from sklearn.ensemble. Anything that cannot be imported from
sklearn.ensemble is now part of the private API.
```

```
warnings.warn(message, FutureWarning)
```

```
/home/code_monkey/anaconda3/lib/python3.7/site-
packages/sklearn/utils/deprecation.py:143: FutureWarning: The
```

sklearn.ensemble.forest module is deprecated in version 0.22 and will be removed in version 0.24. The corresponding classes / functions should instead be imported from sklearn.ensemble. Anything that cannot be imported from sklearn.ensemble is now part of the private API.

```
warnings.warn(message, FutureWarning)
/home/code_monkey/anaconda3/lib/python3.7/site-
packages/sklearn/utils/deprecation.py:143: FutureWarning: The
sklearn.utils.testing module is deprecated in version 0.22 and will be removed
in version 0.24. The corresponding classes / functions should instead be
imported from sklearn.utils. Anything that cannot be imported from sklearn.utils
is now part of the private API.
```

```
warnings.warn(message, FutureWarning)
/home/code_monkey/anaconda3/lib/python3.7/site-
packages/sklearn/utils/deprecation.py:143: FutureWarning: The
sklearn.metrics.classification module is deprecated in version 0.22 and will be
removed in version 0.24. The corresponding classes / functions should instead be
imported from sklearn.metrics. Anything that cannot be imported from
sklearn.metrics is now part of the private API.
```

```
warnings.warn(message, FutureWarning)
/home/code_monkey/anaconda3/lib/python3.7/site-
packages/sklearn/utils/deprecation.py:86: FutureWarning: Function safe_indexing
is deprecated; safe_indexing is deprecated in version 0.22 and will be removed
in version 0.24.
```

```
warnings.warn(msg, category=FutureWarning)
```

```
[19]: Counter(y_train_smote)
```

```
[19]: Counter({2: 7033, 3: 7033, 4: 7033, 0: 7033, 1: 7033})
```

Now, our dataset is balanced.

## Grid Search

```
[20]: grid_params={
        'n_estimators': (5, 8, 11, 13),
        'max_depth': (3, 5, 7, 9, 11, 13),
        'min_samples_split': (2, 4, 6, 8, 10),
        'random_state': (1, 42),
    }
```

```
[21]: from sklearn.svm import SVC
        from sklearn.metrics import make_scorer, f1_score
        from sklearn.ensemble import RandomForestClassifier
        from sklearn.model_selection import GridSearchCV

        scorer = make_scorer(f1_score, average='micro')
        clf = GridSearchCV(RandomForestClassifier(), grid_params, scoring=scorer)
        clf.fit(X_train_smote, y_train_smote)
```



```
[21]: GridSearchCV(estimator=RandomForestClassifier(),
                  param_grid={'max_depth': (3, 5, 7, 9, 11, 13),
                              'min_samples_split': (2, 4, 6, 8, 10),
                              'n_estimators': (5, 8, 11, 13),
                              'random_state': (1, 42)},
                  scoring=make_scorer(f1_score, average=micro))
```

```
[22]: best_score = clf.best_score_

print(best_score)
```

0.5197781885397412

```
[23]: best_params = clf.best_params_

print(best_params)
```

```
{'max_depth': 13, 'min_samples_split': 8, 'n_estimators': 13, 'random_state': 42}
```

```
[24]: print('The best score is: {} with params {}'.format(best_score, best_params))
```

The best score is: 0.5197781885397412 with params {'max\_depth': 13, 'min\_samples\_split': 8, 'n\_estimators': 13, 'random\_state': 42}

## Model Evaluation

```
[25]: from sklearn import metrics

model=RandomForestClassifier(random_state=1,n_estimators=13,max_depth=13,min_samples_split=6)
model.fit(X_train_smote, y_train_smote)

y_pred = model.predict(X_test_v)
print(metrics.classification_report(y_test,y_pred))
```

|              | precision | recall | f1-score | support |
|--------------|-----------|--------|----------|---------|
| 0            | 0.29      | 0.34   | 0.32     | 247     |
| 1            | 0.30      | 0.21   | 0.25     | 291     |
| 2            | 0.20      | 0.84   | 0.32     | 469     |
| 3            | 0.60      | 0.12   | 0.21     | 1759    |
| 4            | 0.48      | 0.42   | 0.45     | 912     |
| accuracy     |           |        | 0.31     | 3678    |
| macro avg    | 0.37      | 0.39   | 0.31     | 3678    |
| weighted avg | 0.47      | 0.31   | 0.29     | 3678    |

[ ]: