



# Linux Academy

## Study Guide

# Learning Python Development

# Contents

---

Installing Python.....	3
Python Variable Basics.....	3
Strings.....	5
Standard Modules.....	7
Conditionals.....	8
Loops.....	8
Lists.....	10
Dictionaries.....	12
Tuples and Sets.....	13
Tuples.....	13
Sets.....	14
Functions.....	15
Exceptions.....	16
File Processing.....	16
Class.....	17
Decorators.....	18
Generators.....	19
Regular Expressions (regex).....	20
JSON.....	21
List Comprehension.....	22
System Automation with Fabric.....	23
Web Scraping.....	23

# Installing Python

---

Installation on CentOS:

```
sudo yum install epel-release  
sudo yum install python python-pip
```

Starting Python in interactive mode:

```
python
```

Zen of Python:

```
import this
```

First "Hello World":

```
print "Hello World"
```

## Python Variable Basics

---

Variable assignment:

```
my_variable = "Hello World"
```

Numeric variable:

```
number_of_items = 1247
```

String variable:

```
number_of_items = "1247"
```

Force a string variable to be used as a integer:

```
int(number_of_items)
```

Force a string variable to be used as a float:

```
float(number_of_items)
```

Determine the type of a variable:

```
type(number_of_items)
```

Basic example:

```
number_of_items = 1247

total_price = 31

price_of_one_item = total_price / number_of_items

print price_of_one_item
```

Floor division: Returns the value as an integer and throws away the decimals.

```
841.1//4
```

Modulus: Returns just the remainder.

```
841 % 4
```

Exponent:

```
2**4
```

Number precision, using round:

```
price_of_one_item = round(total_price / number_of_items, 4)
```

Comparisons:

```
# greater than
1 > 2
```

```
# less than
600 < 5
```

```
# less than or equal to
600 ≤ 5

# equal to
2 == 2

# complex
1 ≤ 2 ≤ 4
```

Minimum number from a list of numbers:

```
min(1, 5, 2, 5, 300, .03)
```

Maximum number from a list of numbers:

```
max(1, 5, 2, 5, 300, .03)
```

## Strings

---

Can be quoted in single, double or even triple quotes. The triple quotes allow for multi-line strings.

```
server_type = 'centos'
server_name = "alpha_01"
server_desc = """ My test server
                at Linux Academy
            """
```

Variables can be printed as part of another string using the `%`'s placeholder and passing in the variables:

```
print "Server name: %s" % (server_name)
```

Length of a string variable:

```
len(server_desc)
```

Concatenate strings together:

```
server_desc = "Server " + server_name + " is running " + server_type
server_desc = " ".join(("Server", server_name, "is running", server_
type))
```

Searching a string (is case-sensitive):

```
"centos" in server_desc  
"CentOS" in server_desc
```

Location of a substring:

```
server_desc.find("centos")
```

Splicing or creating a substring:

```
# characters 7 to 15  
server_desc[7:15]  
  
# all characters up to the 6th one  
server_desc[0:6]  
server_desc[:6]  
  
# last 6 characters  
server_desc[-6:]  
  
# from the 7th to the end  
server_desc[7:]
```

Search and replace:

```
server_desc = server_desc.replace('centos', 'CentOS')
```

Removing characters:

```
# remove all white spaces around a string plus any carriage return  
my_str.strip()  
  
# remove all white spaces from the left of the string  
my_str.lstrip()  
  
# remove white spaces and carriage from the right of a string  
my_str.rstrip()  
  
# remove the characters 'abc' from the end of a my_str  
my_str.rstrip('abc')
```

# Standard Modules

---

Online documentation:

- <https://docs.python.org/2/library/>
- <https://docs.python.org/2/search.html>

Import a module for use:

```
import subprocess
```

Functions available in a module:

```
dir(subprocess)
```

Using a module:

```
import subprocess
host_name = subprocess.check_output("hostname")
host_name
```

Installing new modules:

```
pip install boto3
```

List of useful modules:

```
collections
datetime
glob
logging
os
pexpect
re
requests
string
subprocess
sys
timeit
urllib
```

Public Python module repository:

- <https://pypi.python.org/pypi>

# Conditionals

---

Example IF statement:

```
# this module has a function called linux distro which returns the linux
distro the server is running
import platform
platform.linux_distribution()
sys_info = ' '.join(platform.linux_distribution())
sys_info
if "CentOS" in sys_info:
    print "CentOS"
elif "Ubuntu" in sys_info:
    print "Debian OS"
else:
    print "Unknown OS"
```

Another example:

```
""" Generate a random number between 0 and 100 and grade it
    A if > 90, B ≥ 80-89 """

# module for generating random number
import random

# and generate a random integer between 1 and 100
test_score = random.randint(0,100)

# evaluate using if
if test_score ≥ 90:
    print "A"
elif test_score ≥ 80:
    print "B"
elif test_score ≥ 70:
    print "C"
elif test_score ≥ 60:
    print "D"
else:
    print "F"
```

# Loops

---

FOR loop using `range()`:

```
""" Loop to print the odd numbers between 1 and 10 """

for number in range(1, 11):
    if number % 2 > 0:
```



```
print number
```

Break out of a loop using **break**:

```
for number in range(1, 10):
    if number == 5:
        print "I have counted to %s" % number
        break
```

ELSE statement with a FOR loop:

```
# ELSE statement will execute
for number in range(1, 10):
    if number == 5:
        print "I have counted to %s" % number
else:
    # will print out since we did not exit the loop
    print "I counted from 1 to 10 "
# ELSE statement will not execute
for number in range(1, 10):
    if number == 5:
        print "I have counted to %s" % number
        break
else:
    # will not print out since we did not exit the loop
    print "I counted from 1 to 10 "
```

Loops to iterate over strings:

```
notes = "And a 1 and a 2 and a 3"
for x in notes:
    if x.isdigit():
        # only print char if numeric
        print x
```

WHILE loops:

```
""" Coin toss using while loop and count the number of tosses before we
get 10 heads in a row """

import random

heads_in_a_row_needed = 10
heads_in_a_row = 0
total_tries = 0
while heads_in_a_row_needed != heads_in_a_row:
    # mimic a coin toss by generating 0 and 1 randomly
    toss = random.randint(0,1)
    if toss == 1:
        heads_in_a_row +=1
```

```
    else:
        heads_in_a_row = 0
        total_tries +=1
    print "It took %s tries to get %s heads in a row" % (total_tries, heads_
in_a_row)
```

WHILE loops with a break:

```
heads_in_a_row_needed = 10
heads_in_a_row = 0
total_tries = 0
while True:
    toss = random.randint(0,1)
    if toss == 1:
        heads_in_a_row +=1
    else:
        heads_in_a_row = 0
    total_tries +=1
    if heads_in_a_row_needed == heads_in_a_row:
        break

print "It took %s tries to get %s heads in a row" % (total_tries, heads_
in_a_row)
```

## Lists

---

Creating lists:

```
list1 = [1,2,3,4]
list2 = ['a','b','c']
list3 = ['1','62','q',"I am also a member"]

# other variables in a list
str1 = "string var"
list4 = ["4", str1, list3]

people = ["jet", "donny", "jerome", "paul"]
```

Accessing list item (positions are zero-relative):

```
# Single item
people[2]

# First 2 item
people[:2]
```

Appending to a list:

```
people.append("george")
```

Position of an item in a list:

```
people.index("jerome")
people.index("mark")
```

Length:

```
len(people)
```

Removing items:

```
people.remove("donny")
```

Example script:

```
""" Monitors the partitions on a linux server
    and notifies if the partition usage is beyond the set threshold """

import subprocess

# threshold at which we should raise the alarm
partition_usage_threshold = 5

# run the linux command using the subprocess module
df_cmd = subprocess.check_output(['df', '-k'])
print df_cmd

# split the output into a list called lines
lines = df_cmd.splitlines()
print lines

# for each line except the first once, since that has the column names
for line in lines[1:]:
    # split the line into columns
    columns = line.split()
    # get the used percentage val from column 4
    used_percentage = columns[4]
    # remove the % sign
    used_percentage = used_percentage.replace('%', '')
    # check for threshold breach
    if int(used_percentage) ≥ partition_usage_threshold:
        print "partition %s usage is beyond threshold at %s " %
(colums[0], columns[4])
        # you can have an email function here that alerts you about this
```

# Dictionaries

---

Creating a dictionary:

```
# empty dictionary
traffic_signal = {}
```

Adding elements:

```
# one at a time
traffic_signal['red']='stop'
traffic_signal['yellow']='about to be red'
traffic_signal['green']='go'

# multiple keys at a time
traffic_signal = {'red' : 'stop', 'yellow' : 'about to be red',
'green':'go'}
```

Retrieving elements:

```
# if you know the key exists
traffic_signal['red']

# if unsure if key exists
traffic_signal.get('xyw')

# if unsure if key exists with return value if not found
traffic_signal.get('xyw', 'that key is not in there')
```

Example script 1:

```
""" script that does 1000 coin tosses and counts how many were heads and
tails """
import random
# dict to keep track of heads and tails
results = {'heads':0, 'tails':0}
for i in range(0,1000)
    toss = random.randint(0,2)
    if toss == 1:
        results['heads']+=1
    else:
        results['tails']+=1

for toss in results.keys():
    print "Coinface %s showed up %s times " % (toss, results['toss'])
```

Example script 2:

```
""" Count the number of processes being run by each user on CentOS """

import subprocess
users = {}
ps_cmd = subprocess.check_output(['ps', '-ef'])
for line in ps_cmd.splitlines()[1:]:
    user = line.split()[0]
    if users.get(user):
        users[user] += 1
    else:
        users[user] = 1

print "Active users on the system are " + ','.join(users.keys())
for user, process_count in users.items():
    print "%s is running %s processes" % (user, process_count)

print users
del users['root']
print users
```

Example 3:

```
""" Count the number of processes being run by each user on CentOS """

import subprocess
users = {}
ps_cmd = subprocess.check_output(['ps', '-ef'])
for line in ps_cmd.splitlines()[1:]:
    user = line.split()[0]
    users[user] = users.get(user, 0) + 1
```

## Tuples and Sets

A tuple consists of a number of values separated by commas. They are useful for ordered pairs and returning several values from a function.

They cannot be modified like lists thus they are much faster than a list to iterate over.

## Tuples

Creating a tuple:

```
constant_vals = ()
constant_vals = ("Jack", "Arizona", 9, "Atlanta", 9, 14, 6)

# a tuple can contain other data structures
```

```
tuples = ( [1,2,3], "a", 9 )  
  
# when crating a tuple with one value only you have to use a comma at  
the end  
constant_vals = (39,)
```

Length of a tuple:

```
len(constant_vals)
```

Counting the occurrence of a string/number within a tuple:

```
constant_vals.count(9)
```

Locating a string/number within a tuple:

```
constant_vals.index("Atlanta")  
"Texas" in constant_vals
```

Iterating:

```
# and you can iterate over tuples just like lists  
for val in constant_vals:  
    print val
```

## Sets

One of the most useful data structures when dealing with data analysis. A set can extract the unique values from a list, which then can be used for unions, intersections, etc.

Create a set:

```
linux_essentials =  
set(["John", "Kevin", "Anthony", "James", "Sara", "Marge", "John"])  
lpic_level1 = set(["Kevin", "James", "Marge", "Lewis", "Nancy"])
```

Set intersections:

```
# people who watch both the linux_essentials_certification and lpic  
videos  
both_courses = linux_essentials & lpic_level1  
print both_courses
```

Set subtraction:

```
# people who should watch the linux essential video but skipped it
need_to_watch_le = lpic_level1 - linux_essentials
print(need_to_watch_le)

# people who should watch the lpic video
need_to_watch_lpic = linux_essentials - lpic_level1
print(need_to_watch_lpic)
```

## Functions

Create a function:

```
def functionname(variables_passed_in):
    # do something here
    return some_value
```

Example script 1:

```
def activeProcesses(lookup_user):
    """ Look up how many processes a user is running """
    processes_running = 0
    for line in subprocess.check_output("ps -ef", shell=True).
splitlines()[1:]:
        user = line.split()[0]
        if lookup_user == user:
            processes_running+=1
    return "User %s has %s processes running" % (lookup_user, processes_
running)
print activeProcesses('root')
print activeProcesses('postfix')

def activeProcesses(lookup_user, lookup_cmd):
    """ Look up how many command of a particular type a user is running
    """
    processes_running_all = 0
    processes_running_searched = 0
    for line in subprocess.check_output("ps -ef", shell=True).
splitlines()[1:]:
        user = line.split()[0]
        if lookup_user == user:
            processes_running_all+=1
            if lookup_cmd in line:
                processes_running_searched+=1
    return processes_running_all, processes_running_searched
procs_total, procs_searched = activeProcesses('root', 'aws')
print procs_total, procs_searched
```

# Exceptions

---

Catch bad code:

```
# division by zero
try:
    print 1/0
except ZeroDivisionError:
    print "Cannot divide by a zero"
else:
    print "All good"

# bad command
try:
    import subprocess
    subprocess.check_output(['k'])
except Exception as ex:
    print "A %s exception happened because %s" % (type(ex).__name__,
ex.args)
else:
    print "all good"
```

Catch importing a module that is not installed:

```
try:
    import some_module
except Exception as ex:
    print "A %s exception happened because %s" % (type(ex).__name__,
ex.args)
else:
    print "all good"
```

# File Processing

---

Open a file and read the lines one at a time:

```
filename = '/var/log/secure'
# one line at a time
for line in open(filename):
    print line
```

Slurp the file whole:

```
with open(filename) as file_handle:
    lines = file_handle.readlines()
    for line in lines:
        print(line)
```



Write to a file:

```
filename = 'textfile.txt'
with open(filename, 'w') as file_handle:
    file_handle.write("here is some text\n")
```

Append to a file:

```
with open(filename, 'a') as file_handle:
    file_handle.write("here is more text")
```

Reading a CSV:

```
import csv
file_handle = open('servers.csv')
reader = csv.reader(file_handle)
os_counts = {}
for row in reader:
    os_counts[row[2]] = os_counts.get(row[2],0)+1

print os_counts
```

Open a file safely:

```
try:
    filename = '/var/log/notthere'
    for line in open(filename):
        print line
        # do any processing here
except IOError:
    print "File does not exist"
except:
    print "Can't open file for other reason"
else:
    print "Done processing file"
```

## Class

---

Create a class:

```
class Car():
    def __init__(self):
        self.color = ''
        print "car started"
    def accel(self, speed):
        print "speeding up to %s mph" % speed
    def turn(self, direction):
```

```
        print "turning " + direction
    def stop(self):
        print "stop"
```

Inherit from another class:

```
class RaceCar(Car):
    def __init__(self, color):
        self.color = color
        self.top_speed = 200
        print "%s race car started with a top speed of %s" % (self.
color, self.top_speed)
    def accel(self, speed):
        print "speeding up to %s mph very very fast" % speed
```

Instantiate:

```
car1 = Car()
car2 = RaceCar('blue')
```

Change variables within a class:

```
car1.color='red'
car2.color='red'
```

Call functions within a class:

```
car1.accel(10)
car1.turn('right')
car1.stop()
car2.accel(10)
car2.turn('left')
car2.stop()
```

Available functions in a class:

```
vars(car1)
vars(car2)
```

## Decorators

---

Think of decorators like wrappers. They essentially allow one function to be passed into another function.

```
""" Decorater elapsed_time to time how long it takes to download a
webpage"""

# module for timing
import time

# module to open web pages
import urllib2

def elapsed_time(function_to_time):
    def wrapper():
        t0 = time.time()
        function_to_time()
        t1 = time.time()
        print "Elapsed time: %s\n" % (t1 - t0)
    return wrapper

@elapsed_time
def download_webpage():
    url = 'http://linuxacademy-static-blogpost.s3-website-us-east-1.
amazonaws.com/'
    response = urllib2.urlopen(url, timeout = 60)
    return response.read()

webpage = download_webpage()

@elapsed_time
def another_function():
    print "Doing something else"
    for i in range(1,1000000):
        pass
```

## Generators

---

Generators iterate without creating all values at ones:

```
def counter():
    i=0
    while True:
        i+=1
        return i
a = counter()
print a
type(a)

### Instead of returning a value, you generate a series of values (using
the yield statement)
def counter():
    i=0
    while True:
        i+=1
        yield i
```

```
a = counter()
type(a)
print next(a)
print next(a)
print next(a)
```

## Regular Expressions (regex)

Cheat sheet available in the course downloads.

Example script 1:

```
line = "Oct  7 17:28:59 shirazk2141 sshd[2877]: Failed password for root
from 31.220.3.180 port 50388 ssh2"

import re
match = re.search('sshd', line)
print match

match = re.search('hello', line)
print match

#Bad way to do it
match = re.search('[A-Z][a-z]{2}\s{1,2}\d{1,2}\s\d{2}:\d{2}:\d{2}\s\w*\ssshd\[\\d*\]: Failed password for \w+ from \\d{1,3}\\.\d{1,3}\\.\d{1,3}\\.\d{1,3} port \\d* ssh2', line)
print match

#A little simpler
match = re.search('^(.*)\s(\\w+)\ssshd.*?Failed\spasswd.*?from\s(.*)\sport.*$', line)
print match
print match.groups()

#With named groups
match = re.search('^(?P<date>.*?)\s(\\w+)\ssshd.*?Failed\spasswd.*?from\s(.*)\sport', line)
print match.group('date')
```

Example script 2:

```
""" Script to parse the '/var/log/secure' to find all the hacking
attempts and the originating IP addresses using regex """

import re
filename = '/var/log/secure'
ips = []
for line in open(filename):
```

```
# Failed password attempts
match = re.search('^(*?)\s(\w+)\ssshd.*?Failed\s
spassw.*?from\s(*?)\sport.*$', line)
if match:
    if match.group()

# Bad user attempts
match = re.search('^(*?)\s\w+\sssh.*?Invalid\suser\s(\w+)\s
sfrom\s(*?)', line);
```

## JSON

```
# module for json parsing
import json

# module for opening webpages
import urllib

# open a url
url = "https://labfiles.linuxacademy.com/python/ec2-response.json"
response = urllib.urlopen(url)
# get the json data into json_string
json_string = response.read()
print json_string

# safe JSON parsing using exception catching
data = None
try:
    # parse the JSON
    data = json.loads(str(json_string))
except:
    data = None

# if valid JSON
if ( data ):
    # access the data just like a dictionary/list
    print "InstanceID %s is %s" % (data['InstanceStatuses'][0]
['InstanceId'], data['InstanceStatuses'][0]['InstanceState']['Name'])

# create a JSON string using a dictionary variable
data = {
    'course_name' : 'python',
    'videos' : ['strings', 'classes', 'json'],
    'id' : 5
}

# pass the variable to the JSON module for serializing.
# the indent=4 gets it nicely formatted for viewing
json_string = json.dumps(data, indent=4)
print json_string
json_string = json.dumps(data)
print json_string
```

# List Comprehension

---

```
# create a list var with values 1 thru 49
numbers = range(0,50)
print numbers

# list of even numbers
even_numbers = [i for i in range(0,50) if i % 2 == 0 and i >=2 ]
print even_numbers

even_numbers = [i for i in numbers if i % 2 == 0 and i >=2 ]
print even_numbers

# squared numbers
squares = [i*i for i in numbers if i % 2 == 0 and i >=2]
print squares

# generate a list of random 50 numbers
import random
random_numbers = [ random.randint(1,100) for x in range(50) ]
print random_numbers

# let's get the unique numbers from random_numbers
unique_random_numbers = list(set(random_numbers))
print unique_random_numbers

# list comprehension using strings
names = ['adam', 'Justin', 'joe', 'tony', 'zoe']
names_formatted = [ x.title() for x in names]
print names_formatted

#using map
names_formatted = map(lambda x: x.title(), names)
print names_formatted

#names that start with a j, case-insensitive
names_starting_with_j = [name for name in names_formatted if name[0].lower() == 'j']
print names_starting_with_j
```

Example script 1:

```
""" Create a random encoding system that only encodes letters and
nothing else using random letters """

# module for string functions
import string

# module to randomize lists
from random import shuffle
raw_text = "Hello and welcome to Linux Academy!!"
```

```
# get letters a to z in both upper and lower case
letters = list(string.ascii_letters)
print letters

# create a copy of the letters list
encoded_letters = letters[: ]

# randomize it
shuffle(encoded_letters)
print encoded_letters

# initialize the keys
encoding_key = {}
decoding_key = {}
# zip will iterate over two lists at the same time
for k, v in zip(letters, encoded_letters):
    encoding_key[k]=v
    decoding_key[v]=k

print encoding_key

encoded_text = ''
# for each letter in the raw_text
for letter in raw_text:
    # lookup the encoding and append it to the encoded text
    encoded_text += encoding_key.get(letter, letter)
print encoded_text

# a better way to do the encoding and decoding
encoding_key = dict(zip(letters,encoded_letters))
decoding_key = dict(zip(encoding_key.values(),encoding_key.keys()))
encoded_text = ''.join([ encoding_key.get(w, w) for w in raw_text])
print encoded_text

decoded_text = ''.join([ decoding_key.get(w, w) for w in encoded_text])
print decoded_text
```

## System Automation with Fabric

Source file with comments available at:

- <http://labfiles.linuxacademy.com/python/fabric/scripts/fabfile.py>

## Web Scraping

Source file with comments available at:

- <http://labfiles.linuxacademy.com/python/scraping/scripts/web scraping.py>